

**PROJECT TEAM**

ARCHITECT OF RECORD

**TREANORHL**

1811 BALTIMORE AVE.  
KANSAS CITY, MO 64108  
OFFICE: 816.221.0900  
FAX: 816.221.4992  
WWW.TREANORHL.COM

STRUCTURAL ENGINEER

**KH**  
ENGINEERING GROUP, P.A.

15377 WEST 95 ST.  
LENEXA, KS 66219  
OFFICE: 913.825.9381  
WWW.KHEGROUP.COM

MECHANICAL, ELECTRICAL,  
PLUMBING ENGINEER

**McCLURE ENGINEERING**

1000 CLARK AVE.  
SAINT LOUIS, MO 631102  
OFFICE: 314.645.6232  
FAX: 314.745.0145  
WWW.MCCLUREENG.COM

INTERIOR DESIGNER

**spellman  
brady &  
company**

8251 MARYLAND AVE., SUITE 300  
SAINT LOUIS, MO 63105  
OFFICE: 314.862.0070  
FAX: 314.745.0145  
WWW.SPELLMANBRADY.COM

OWNER



UNIVERSITY OF MISSOURI  
COLUMBIA, MISSOURI

**CERTIFICATIONS**

ARCHITECTURAL STATEMENT:  
I hereby certify that Sheets G000 - A751, have been prepared by me, or under my supervision. I further certify that to the best of my knowledge these Drawings and/or Specifications are as required by and in compliance with Building Codes of the University of Missouri.  
SIGNATURE: \_\_\_\_\_

STRUCTURAL STATEMENT:  
I hereby certify that Sheets S101-S301, have been prepared by me, or under my supervision. I further certify that to the best of my knowledge these Drawings and/or Specifications are as required by and in compliance with Building Codes of the University of Missouri.  
SIGNATURE: \_\_\_\_\_

MECHANICAL & PLUMBING STATEMENT:  
I hereby certify that Sheets M000 - M800, have been prepared by me, or under my supervision. I further certify that to the best of my knowledge these Drawings and/or Specifications are as required by and in compliance with Building Codes of the University of Missouri.  
SIGNATURE: \_\_\_\_\_

ELECTRICAL STATEMENT:  
I hereby certify that Sheets E000-E701, have been prepared by me, or under my supervision. I further certify that to the best of my knowledge these Drawings and/or Specifications are as required by and in compliance with Building Codes of the University of Missouri.  
SIGNATURE: \_\_\_\_\_

**DEFERRED SUBMITTALS:**


AS DEFINED BY IBC SECTION 107.3.4.1, THE FOLLOWING DEFERRED SUBMITTALS ARE REQUIRED AS PART OF THIS PROJECT:  
- FIRE ALARM  
- FIRE SPRINKLER

**SPECIAL INSPECTIONS:**

AS DEFINED BY IBC SECTION 1704.2.3, THE FOLLOWING SPECIAL INSPECTIONS ARE REQUIRED AS PART OF THIS PROJECT:  
- PLUMBING, MECHANICAL & ELECTRICAL COMPONENTS


UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
UNIVERSITY OF MISSOURI, COLUMBIA, MISSOURI  
MU PROJECT #: CP210701  
FOR THE CURATORS OF THE UNIVERSITY OF MISSOURI  
**BID DOCUMENTS**

ISSUE DATE: AUGUST 10, 2021  
RE-ISSUED IN ENTIRETY



**KEY PLAN, 2ND FLOOR**


NOT TO SCALE



**PROJECT LOCATION**

**VICINITY MAP**

NOT TO SCALE



**PROJECT LOCATION**

**AREA MAP**

NOT TO SCALE

**SHEET LIST**

GENERAL	COVER SHEET
G000	ADA TYP. & GENERAL SCHEDULES
G002	TYPICAL MOUNTING HEIGHTS
G003	PARTITION DETAILS AND NOTES
G101	LIFE SAFETY PLAN
G102	CONSTRUCTION ACCESS
G103	FIRST FLOOR INFECTION CONTROL
G104	SECOND FLOOR INFECTION CONTROL
ARCHITECTURAL	FIRST FLOOR DEMOLITION PLAN
AD101	SECOND FLOOR DEMOLITION PLAN
A101	FIRST FLOOR PLAN
A102	SECOND FLOOR PLAN
A151	REFLECTED CEILING PLAN
A401	ENLARGED PLANS
A402	ENLARGED PLANS
A420	INTERIOR ELEVATIONS
A421	INTERIOR ELEVATIONS
A501	SECTIONS & DETAILS
A520	CASEWORK DETAILS
A601	DOORS AND FRAMES
A701	INTERIORS
A712	INTERIOR FINISH PLAN
A720	FURNITURE & EQUIPMENT PLAN
STRUCTURAL	STRUCTURAL GENERAL NOTES & DETAILS
S001	STRUCTURAL GENERAL NOTES & DETAILS
MECHANICAL & PLUMBING	SYMBOLS, ABBREVIATIONS, AND SCHEDULE
M001	FIRST FLOOR DEMOLITION PLUMBING PLAN
PD201	SECOND FLOOR DEMOLITION PLUMBING PLAN
PD202	SECOND FLOOR DEMOLITION PLUMBING PLAN
MD302	SECOND FLOOR DEMOLITION HVAC PLAN
P201	FIRST FLOOR PLUMBING PLAN
P202	SECOND FLOOR PLUMBING PLAN
M302	SECOND FLOOR HVAC PLAN
M501	AIRFLOW DIAGRAM
M502	MECHANICAL WATER FLOW DIAGRAM
M601	SCHEDULES, DETAILS, AND SEQUENCE OF OPERATIONS
M602	CONTROLS DETAILS
FIRE PROTECTION	SECOND FLOOR FIRE PROTECTION PLAN
FP102	SECOND FLOOR FIRE PROTECTION PLAN
ELECTRICAL	PARTIAL SECOND FLOOR PLAN - DEMOLITION
ED201	PARTIAL SECOND FLOOR PLAN - DEMOLITION
E001	ELECTRICAL SYMBOLS AND ABBREVIATIONS
E002	LIGHTING FIXTURE SCHEDULE AND DETAILS
E003	PARTIAL SECOND FLOOR PLAN - LIFE SAFETY
E004	PARTIAL SECOND FLOOR PLAN - LIFE SAFETY
E005	ELECTRICAL PANEL SCHEDULES
E201	PARTIAL SECOND FLOOR PLAN - LIGHTING
E202	PARTIAL SECOND FLOOR PLAN - POWER
E203	PARTIAL SECOND FLOOR PLAN - SYSTEMS



**TREANORHL**  
1811 Baltimore Ave.  
Kansas City, Missouri 64108  
Office: 816.221.0900  
www.treanorhl.com

**McCLURE ENGINEERING**  
1000 Clark Avenue  
Saint Louis, Missouri 63102  
T 314-645-6232  
www.mcclureeng.com  
McClure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY	08/10/21	

**G000**

COVER SHEET

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00

MU Project Number: CP210701

**KEY PLAN**

### ABBREVIATIONS

AA	AUTOMATICALLY ACTUATED	FL	FLOW LINE	PLWD	PLYWOOD
ABV	ABOVE	FLUOR	FLUORESCENT	PNL	PANEL
AC	ACROSS COUNTER	FND	FOUNDATION	PR	PAIR
ACMU	ARCHITECTURAL CEMENTITIOUS MASONRY UNIT	FOC	FACE OF CONCRETE	PSF	POUNDS PER SQUARE FOOT
ACOUS	ACOUSTICAL	FOF	FACE OF FINISH	PSI	POUNDS PER SQUARE INCH
AD	AREA DRAIN	FOM	FACE OF MASONRY	PT	PAINT, PAINTED
ADJ	ADJUSTABLE	FOS	FACE OF STUCCO	PTR	PAPER TOWEL RECEPTOR
ADA	AMERICANS WITH DISABILITIES ACT	PVC	POLYVINYL CHLORIDE	PVC	PAVEMENT
AG	ABOVE FINISHED FLOOR	FR	FIRE RATED	QTY	QUANTITY
AGF	ACRYLIC GLAZING	FRP	FIBERGLASS REINFORCED PLASTIC	QT	QUANTITY
AHJ	APPLICABLE AUTHORITY	FS	FLOOR SINK	Q	QUANTITY
ALT	ALTERNATE	FTG	FEET	R	RADIUS OR RISER
ALUM	ALUMINUM	FTG	FOOTING	RA	RADIUS
ANCH	ANCHOR	FUR	FURRING	RB	RUBBER BASE
APC	ACCESS PANEL	FUT	FUTURE	RBT	RABBIT
APC	ACCESS PANEL CEILING	GA	GAUGE	RCP	REFLECTED CEILING PLAN
APX	APPROXIMATE	GALV	GALVANIZED	RD	ROOF DRAIN
ARCH	ARCHITECT(URAL)	GC	GENERAL CONTRACTOR	RE	REFERENCE
AUTO	AUTOMATIC	GD	GRADE/GRADING	RECEP	RECEPTACLE
BD	BOARD	GF	GROUND FACE	REF	REFER TO REFERENCE
BLDG	BUILDING	GFRCC	GLASS FIBER REINFORCED CONCRETE	REFR	REFRIGERATOR
BLK	BLOCK	GR	GRADE, GRADING	REG	REGISTER
BM	BENCH MARK	GYP	GYPSON	REINF	REINFORCED(ING)
BO	BOTTOM OF	GYP BD	GYPSON WALL BOARD	REM	REMOVE
BT	BOTTOM	H	HIGH/HEIGHT	REQ	REQUIRED
BS	BRICK	HB	HOSE BIB	RES	RESILIENT
BSG	BEARING	HM	HOLLOW METAL, (CUSTOM STEEL)	RET	RETURN
BS	BOTH SIDES	HO	HOLD OPEN	REV	REVISION
BSMT	BASEMENT	HORIZ	HORIZONTAL	RFG	ROOFING
BUR	BUILT UP ROOFING	HR	HOUR	RFL	REFLECT(ED), (IVE), (OR)
CA	CARD ACTUATED	HT	HEIGHT	RFS	ROOM FINISH SCHEDULE
CAB	CABINET	HVAC	HEATING/VENTILATING/AIR CONDITIONING	RH	RIGHT HAND
CB	CHALKBOARD	HW	HOT WATER	RM	ROOM
CCTV	CLOSED CIRCUIT TELEVISION	HWD	HARD WOOD	RO	ROUGH OPENING
CF	CORR FLOORING	ID	INSIDE DIAMETER	RTU	ROOF TOP UNIT
CFCI	CONTRACTOR FURNISHED CONTRACTOR INSTALLED	IN	INCHES	RVRS	REVERSE
CG	CORNER GUARD	INCL	INCLUDE(D), (ING)	SA	SOUTH
CH	CONDUCTOR HEAD	INSUL	INSULATION, INSULATING	SA	SUPPLY AIR
CIP	CAST IRON	INT	INTERIOR	SAM	SELF-ADHERED MEMBRANE
CIP	CAST IN PLACE	INTM	INTERMEDIATE	SAN	SANITARY
CJ	CONTROL JOINT	JB	JUNCTION BOX	SCHD	SCHEDULE
CL	CLEAR	JF	JOINT FILLER	SD	STORM DRAIN
CL OF CLR	CLEAR LINE	JST	JOIST	SEC	SECTION
CLG	CEILING	JT	JOINT	SF	SQUARE FEET
CMU	CONCRETE MASONRY UNIT	K	KEYHOLE	SHT	SHEATHING
COL	COLUMN	KO	KNOCK OUT	SHWR	SHOWER
CONC	CONCRETE	KS	KNEE SPACE	SIM	SIMILAR
COND	CONDITION	L	LONG LENGTH	SLNT	SEALANT
CONST	CONSTRUCTION	LAM	LAMINATE	SNM	SANITARY NAPKIN DISPENSER
CONT	CONTINUOUS, CONTINUE	LAV	LAVATORY	SNR	SANITARY NAPKIN RECEPTACLE
COR	CORRIDOR	LH	LEFT HAND	SPC	SPACE
COT	CARPET	LIN	LINOLEUM	SPCR	SPACER
CR	CARD READER	LLH	LONG LEG HORIZONTAL	SPEC	SPECIFICATION(S)
CRF	CORK/RUBBER FLOORING	LV	LONG LEG VERTICAL	SPKR	SPEAKER
CS	CUSTOM STEEL (HOLLOW METAL)	LMS	LIMESTONE	SQR	SQUARE
CT	CERAMIC TILE	LT	LIGHT	SS	SOLID SURFACE
CTR	COUNTER	LTL	LINTEL	SSK	SERVICE SINK
CTSK	COUNTERSINK	LW	LIGHT WEIGHT	SST	STAINLESS STEEL
CW	COLD WATER	LWC	LIGHT WEIGHT CONCRETE	STA	STATION
D	DEEP/DEPTH/DRAIN	LWCMU	LIGHT WEIGHT CONCRETE MASONRY UNIT	STD	STANDARD
DBL	DOUBLE	M	METERS	STL	STEEL
DF	DRINKING FOUNTAIN	MAS	MASONRY	STN	STONE
DFS	DOOR AND FRAME SCHEDULE	MAT	MATERIAL(S)	STR	STORAGE
DIA	DIAMETER	MAX	MAXIMUM	STP	STANDPIPE
DIM	DIMENSION	MB	MARKERBOARD	STRUC	STRUCTURAL
DIW	DOWN	MDF	MEDIUM DENSITY FIBER	SUSP	SUSPENDED
DN	DOWN	MECH	MECHANICAL	SY	SQUARE YARD
DPR	DISPENSER	MEMB	MEMBRANE	SYM	SYMMETRICAL
DR	DOOR	MET	METAL ROOF DECK	SYS	SYSTEM
DS	DOWNSPOUT	MFR	MANUFACTURE/MANUFACTURER	T	TREAD
DWG	DRAWING	MH	MANHOLE	T&G	TONGUE AND GROOVE
E	EAST	MNO	MACHINE HOLD OPEN	TB	TACKBOARD
EA	EXPANSION BOLT	MIN	MINIMUM	TBD	TO BE DETERMINED
ECLH	ELECTRIC CLOSET UNIT HEATER	MIR	MIRROR	TD	TRENCH DRAIN
EF	EACH FACE	MISC	MISCELLANEOUS	TEL	TELEPHONE
EIFS	EXTERIOR INSUL. FINISH SYSTEM	MLD	MOLDING, MOLDING	THK	THICKNESS
EJ	EXPANSION JOINT	MO	MASONRY OPENING	THRU	THROUGH
ELEV	ELEVATION	MOD	MODULAR	TLT	TOILET
ELEC	ELECTRICAL	MRO	METAL ROOF DECK	TOP	TOP OF
ELEV	ELEVATION/ELEVATOR	MS	METAL STUDS	TOC	TOP OF CONCRETE
EMER	EMERGENCY	MT	MOUNTED, (ING)	TOS	TOP OF STEEL, TOP OF SLAB
ENC	ENCLOSURE	MTRF	METAL FURRING	TOP	TOP OF WALL
EOS	EDGE OF SLAB	MTL	METAL	TPD	TOILET PAPER DISPENSER
EP	ELECTRICAL PANEL	MULL	MULLION	TPN	TOILET PARTITION
EPS	EXPANDED POLYSTYRENE	N	NORTH	TS	TUBE STEEL
EQ	EQUAL	NIC	NOT IN CONTRACT	TYP	TYPICAL
EQUIP	EQUIPMENT	NTS	NOT TO SCALE	TZ	TERRAZZO
EST	ESTIMATE	NOM	NOMINAL	UC	UNDER CONTRACT
ETR	EXISTING TO REMAIN	NR	NOISE REDUCTION	UNF	UNFINISHED
EWC	ELECTRIC WATER COOLER	NRC	NOISE REDUCTION COEFFICIENT	UNO	UNLESS NOTED OTHERWISE
EXIST	EXISTING	NTS	NOT TO SCALE	UR	URINAL
EXP	EXPANSION	OC	ON CENTER	US	URINAL SCREEN
EXT	EXTERIOR	OD	OUTSIDE DIAMETER (or) OVERFLOW DRAIN	VB	VAPOR BARRIER
FA	FRESH AIR	OFCI	OWNER FURNISHED CONTRACTOR INSTALLED	VCT	VINYL COMPOSITE TILE
FAAP	FIRE ALARM ANNUNCIATOR PANEL	OFV	OWNER FURNISHED VENDOR INSTALLED	VERT	VERTICAL
FACP	FIRE ALARM CONTROL PANEL	OH	OVERHEAD	VFCI	VENDOR FURNISHED CONTRACTOR INSTALLED
FAS	FASTENER	OPNG	OPENING	VFOI	VENDOR FURNISHED OWNER INSTALLED
FB	FACE BRICK	OPP	OPPOSITE	VFVI	VENDOR FURNISHED VENDOR INSTALLED
FBO	FURNISHED BY OTHERS	OPPH	OPPOSITE HAND	VIF	VERIFY IN FIELD
FBD	FLOOR DRAIN	PAR	PARAPET	W	WIDE/WIDTH
FDC	FIRE DEPARTMENT CONNECTION	PAV	PAVING	W	WITH
FE	FIRE EXTINGUISHER	PB	PUSH BUTTON	WO	WITHOUT
FE	FIRE EXTINGUISHER BRACKET	PCC	PRECAST CONCRETE	W/C	WATER CLOSET
FEC	FIRE EXTINGUISHER CABINET	PER	PERMETER	WD	WOOD
FF	FINISH FLOOR	PERP	PERPENDICULAR	WDB	WOOD BASE
FFCO	FLUSH FLOOR CLEANOUT	PFB	PREFABRICATE(D)	WDO	WINDOW
FFE	FINISHED FLOOR ELEVATION	PIC	POLYISOCYANURATE	WGS	WIRE GLASS
FFL	FINISHED FLOOR LINE	PK	PARKING	WGO	WHERE OCCURS
FH	FLAT HEAD	PL	PLATE	WPG	WATERPROOFING
FHC	FIRE HOSE CABINET	PL	PROPERTY LINE	WS	WRITABLE SURFACE
FHMS	FLAT HEAD MACHINE SCREW	PLAM	PLASTIC LAMINATE	WS	WATERS/TO
FHWS	FLAT HEAD WOOD SCREW	PLAS	PLASTER	W/SC	WAINSCOT
FIN	FINISH	PLBG	PLUMBING	WT	WEIGHT
				WTV	WALL TO WALL
				WWF	WELDED WIRE FABRIC


### MATERIAL LEGEND

	FACE BRICK (PLAN/SECTION)
	CAST STONE (ELEVATION)
	RIGID INSULATION
	SPRAYED INSULATION
	CONCRETE MASONRY
	ASPHALT SHINGLES
	CONCRETE
	UNDISTURBED EARTH
	DISTURBED EARTH
	METAL STUD/STEEL
	GYPSON BOARD
	DRAINAGE FILL
	PLYWOOD
	BLANKET OR LOOSE FILL INSULATION
	WOOD FINISH
	WOOD ROUGH
	DEMOLITION
	EXISTING
	NEW PARTITION


### SYMBOLS

	DETAIL SECTION		ELEVATION LEVEL
	BUILDING SECTION		CEILING TAG W/ HEIGHT/MATERIAL
	WALL SECTION		DOOR DESIGNATION
	EXTERIOR ELEVATION		WINDOW TAGS
	INTERIOR ELEVATION		GRAPHIC SCALE
	PLAN DETAIL		NORTH ARROW
	NEW COLUMN CENTER LINE		REVISION TAG
	EXISTING COLUMN CENTER LINE		ROOM DESIGNATION
	PARTITION TYPE INDICATOR		ROOM DESIGNATION W/ AREA
	FINISH TAG		OCCUPANCY TAG
	PLAN NOTE & DEMO NOTE		EXIT WIDTH TAG
			CASEWORK TAG


### LEVEL CHANGES




### ADA LAVATORY-PLAN



### ADA W.C.-PLAN




### ADA STALL-PLAN




### GENERAL NOTES

- GENERAL NOTES SHALL APPLY EQUALLY TO THE FULL SET OF DOCUMENTS INCLUDING CHANGES APPROVED BY THE OWNER DURING THE COURSE OF THE WORK.
- DRAWINGS ARE INTENDED TO SHOW END RESULT OF DESIGN. MINOR MODIFICATIONS NECESSARY TO SUIT JOB CONDITIONS SHALL BE INCLUDED AS PART OF THE WORK.
- ARCHITECTURAL FLOOR PLAN DIMENSIONS ARE TO FACE OF CONCRETE, FACE OF MASONRY, FACE OF STUD OR COLUMN LINE, UNO, MASONRY DIMENSIONS ARE NOMINAL UNLESS NOTED OTHERWISE. MINIMUM FINISH TO FINISH DIMENSION.
- DO NOT SCALE DRAWINGS; DIMENSIONS SHALL GOVERN.
- CONTRACTOR TO FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO BEGINNING WORK. REPORT ANY DISCREPANCIES TO ARCHITECT IN WRITING PRIOR TO BEGINNING WORK IN AFFECTED AREAS.
- CONTRACTOR TO VERIFY ALL EXISTING SYSTEMS CURRENTLY INSTALLED IN THE CONSTRUCTION AREA. ALL DEVICES TO REMAIN SHALL BE CHECKED AND IN WORKING CONDITION WHEN PROJECT IS COMPLETE.
- CONTRACTOR SHALL EMPLOY ANY REASONABLE MEANS TO CONTAIN DUST, DEBRIS, AND NOISE DUE TO DEMOLITION AND NEW CONSTRUCTION. CONTRACTOR TO MAINTAIN NEGATIVE PRESSURE WITH HEPA FILTERS PER INFECTION CONTROL CRITERIA. PROVIDE BALL-IN-WALL FOR NEGATIVE TRACKING. REFER TO DIVISION 01 IN PROJECT MANUAL.
- CONTRACTOR SHALL COMPLY WITH OWNER'S INFECTION CONTROL RISK ASSESSMENT (ICRA) AND REQUIREMENTS FOR MITIGATION. INFECTION CONTROL BARRIER (HARD BARRIER) SURROUNDING AREAS OF WORK, SUBJECT TO APPROVAL BY OIG OR ASSE BY CASE.
- "ALIGN" AS USED THROUGHOUT THESE DOCUMENTS IS UNDERSTOOD TO MEAN FINISH SURFACE OF NEW CONSTRUCTION SHALL MEET FINISH SURFACE OF EXISTING CONSTRUCTION IN A NEAT AND SMOOTH MANNER, PROVIDING A FLUSH, FINISHABLE SURFACE.
- REFER TO MEP, STRUCTURAL, & VENDOR DRAWINGS FOR ADDITIONAL INFORMATION AND WORK.
- ALL WALLS SHOWN AS INFILL IN EXISTING WALLS OR SHOWN FLUSH WITH EXISTING WALL SURFACES ARE TO BE THE SAME WIDTH AS EXISTING WALL AND ALIGN FLUSH WITH BOTH FACES OF SAID WALL. NOTIFY ARCHITECT OF ANY POTENTIAL DISCREPANCIES PRIOR TO BEGINNING OF WORK.
- NO SMOKING OR CHEWING TOBACCO USE WILL BE PERMITTED ANYWHERE IN THE CONSTRUCTION SITE ON THE HOSPITAL CAMPUS.
- FINISH EXPOSED STUD INTERIOR FACES OF EXISTING EXTERIOR WALLS WHERE FINISH HAS BEEN DEMOLISHED WITH 6/8\"/>
- THE NOTES AND SYMBOLS SET DOWN ON THESE DRAWINGS ARE FOR THE GUIDANCE OF ALL TRADES INVOLVED IN THE PROJECT AND MUST BE FOLLOWED TO EXECUTE THE WORK AS INTENDED.
- THE CONTRACTOR SHALL REFER TO ARCHITECTURAL, STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL, AND VENDOR DRAWINGS FOR DETAILS OF BUILDING CONSTRUCTION TO INSURE SPACE AND SATISFACTORY ARRANGEMENT FOR THEIR WORK. THE VARIOUS DRAWINGS COMPRISING THE SET ARE INTERDEPENDENT AND MUST BE USED JOINTLY AT ALL TIMES. EACH CONTRACTOR SHOULD REFER TO THE GENERAL REQUIREMENTS OF THE CONTRACT. IF DISCREPANCIES OCCUR, CONTACT THE ARCHITECT THROUGH THE GENERAL CONTRACTOR FOR CLARIFICATION BEFORE PROCEEDING.
- IN ACCORDANCE WITH GENERALLY ACCEPTED CONSTRUCTION PRACTICES, THE CONTRACTOR WILL BE SOLELY AND COMPLETELY RESPONSIBLE FOR THE CONDITIONS ON THE JOB SITE, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY DURING PERFORMANCE OF THE WORK. THIS WILL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS.
- ALL WORK MUST BE COORDINATED WITH THE OWNER TO MAINTAIN OPERATION OF THE EXISTING HOSPITAL & OTHER TENANT SUITES.
- TITLES, CAPIONS, HEADINGS, ETC. ARE INTENDED FOR GENERAL REFERENCE AND SHALL NOT LIMIT THE WORK REQUIRED IN ANY WAY.
- EACH CONTRACTOR SHALL COORDINATE THEIR WORK WITH THE WORK OF OTHERS. THEY SHALL KEEP THEMSELVES INFORMED OF THE PROGRESS AND DETAIL DEVELOPMENT OF THE WORK OF OTHERS AND SHALL BE RESPONSIBLE FOR COORDINATING AND EXPEDITING THEIR WORK WITH THAT OF OTHERS SO THAT THE PROGRESS OF THE TOTAL WORK SHALL BE KEPT ON SCHEDULE.
- EXISTING CONDITIONS SHOWN HAVE BEEN BASED UPON AVAILABLE DRAWING INFORMATION AND MAY BE AT VARIANCE WITH ACTUAL WORK IN PLACE. THE CONTRACTOR SHALL TAKE ALL NECESSARY FIELD MEASUREMENTS AND FIELD VERIFY ALL CONDITIONS AFFECTING THE EXECUTION OF THE WORK. ANY DISCREPANCIES BETWEEN EXISTING CONDITIONS AND THE WORK SHOWN ON THE CONTRACT DOCUMENTS WHICH MAY IMPACT THE PROGRESS OF THE WORK SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT IN WRITING FOR RESOLUTION BEFORE PROCEEDING WITH THE WORK.
- EACH CONTRACTOR AND/OR TRADE FITTING OR OTHERS COMPLETES WORK WITH THE UNDERSTANDING THAT THE INSTALLATION OF THE WORK CONSTITUTES THEIR ACCEPTANCE OF THE SUITABILITY OF THE WORK IN PLACE. IF THE WORK OF OTHERS IS NOT ACCEPTABLE, THEY SHALL NOTIFY THE GENERAL CONTRACTOR AND SUCH WORK SHALL BE CORRECTED. ANY NEW WORK INSTALLED IN/OVER UNSUITABLE EXISTING WORK SHALL BE APPROVED.
- ANY STRUCTURAL, MECHANICAL, ELECTRICAL, FIRE PROTECTION, PLUMBING, OR VENDOR INFORMATION INDICATED ON ARCHITECTURAL DRAWINGS IS FOR REFERENCE PURPOSES ONLY UNLESS OTHERWISE INDICATED.
- IN THE EVENT THAT HAZARDOUS MATERIAL(S), INCLUDING BUT NOT LIMITED TO ASBESTOS, ARE DISCOVERED OR ARE SUSPECTED OF BEING PRESENT, THE CONTRACTOR SHALL NOTIFY THE ARCHITECT IN WRITING PRIOR TO BEGINNING WORK IN THE AFFECTED AREA.
- ALL TEMPORARY PARTITIONS CONSTRUCTED DURING THE PROJECT SHALL BE FULL HEIGHT WALLS EXTENDING FROM FLOOR TO UNDERSIDE OF DECK ABOVE, APPROPRIATELY SEALED TO PREVENT THE SPREADING OF DUST, NOISE AND CONTAMINANTS. REFER TO DIVISION 01 SPECIFICATIONS FOR ADDITIONAL INFORMATION. REFER TO DIVISION 01 IN PROJECT MANUAL.
- CONTRACTOR TO PICK UP AND DROP OFF PRE-APPROVED WORK PERMIT FROM HOSPITAL ON A DAILY BASIS AS DESCRIBED IN THE TERMS AND CONDITIONS. REFER TO DIVISION 01 IN PROJECT MANUAL.
- CONTRACTOR SHALL MAINTAIN A CLEAN AND CONTROLLED WORK AREA TO THE BUILDING AND SUITE. DEBRIS SHALL BE REMOVED VIA COVERED CART. STICKY MATS OR WETTED WALK OFF MATS SHALL BE USED AT ENTRY DOORS - CHANGE REGULARLY. REFER TO DIVISION 01 IN PROJECT MANUAL.
- CONTRACTOR SHALL MAINTAIN A NEGATIVE AIR PRESSURE RELATIONSHIP TO ALL ADJACENT SPACES/TENANTS. USE HEPA FILTERED AIR DEVICES TO EXHAUST AIR TO THE OUTSIDE OF THE BUILDING. REFER TO DIVISION 01 IN PROJECT MANUAL.
- 1 1/2\"/>
- PROVIDE AND INSTALL ONE GROMMET IN EACH COUNTERTOP WHEN AN OUTLET IS LOCATED BELOW THE COUNTER. EXACT GROMMET LOCATION TO BE SPECIFIED BY THE OWNER IN THE FIELD.


### LAVATORY-ELEVATION




### ADA W.C.-ELEVATIONS




### ADA STALL-ELEVATIONS



### DRINKING FOUNTAIN



### DOOR CLEARANCES



**TREANORHL**  
 1811 Bluffview Ave.  
 Saint Louis, Missouri 63102  
 Office: 816.227.0900  
 Fax: 816.227.1699  
 www.treanorhl.com

**MCCLURE ENGINEERING**  
 1000 Clair Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-6522  
 www.mcclureeng.com  
 McClure Engineering Corporation  
 Missouri State Certificate of Authority #00087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS  
 RE-ISSUED IN ENTIRETY 08/10/21  
 NO DESCRIPTION DATE

**ACCESSIBILITY GENERAL NOTES**  
 A. REFERENCED STANDARD(S) PROJECT SHALL COMPLY WITH ADA 2010 AND ANS I 117.  
 B. DIMENSIONS ON THIS SHEET ARE TO FINISH FACE OF WALLS AND CEILINGS.


**NOTE:**  
 NO WOOD BLOCKING WILL BE PERMITTED IN CONSTRUCTION. PROVIDE 16 GA. STRAP OR CHANNELS WITHIN ALL WALLS.

**G001**  
 ADA TYP. & GENERAL SCHEDULES  
 BID DOCUMENTS


Date: 08/10/2021  
 TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701




**DRINKING FOUNTAIN**  
1/2" = 1'-0"




**DISPENSERS/DISPOSALS**  
1/2" = 1'-0"




**TOILET PAPER DISPENSERS**  
1/2" = 1'-0"




**URINAL**  
1/2" = 1'-0"




**GRAB BARS AT WATER CLOSETS**  
1/2" = 1'-0"




**TOILET PARTITION**  
1/2" = 1'-0"




**ADULT WATER CLOSET**  
1/2" = 1'-0"




**LAVATORY**  
1/2" = 1'-0"




**TOWEL BAR**  
1/2" = 1'-0"




**CHANGING STATION**  
1/2" = 1'-0"




**MIRRORS**  
1/2" = 1'-0"




**LIGHT SWITCH/THERMOSTAT CONTROLS**  
1/2" = 1'-0"




**MOP SINK BASIN**  
1/2" = 1'-0"




**MOP/BROOM HOLDER**  
1/2" = 1'-0"




**FIRE EXTINGUISHER CABINET**  
1/2" = 1'-0"




**COAT/ROBE HOOKS**  
1/2" = 1'-0"




**CLOSET SHELF AND ROD**  
1/2" = 1'-0"




**UTILITY SHELF**  
1/2" = 1'-0"




**PERSONAL EMERGENCY PULL SWITCH**  
1/2" = 1'-0"




**DOOR ACCESSORIES**  
1/2" = 1'-0"




**ELEVATOR HALL CALL BUTTONS**  
1/2" = 1'-0"



**ELEVATOR BUTTONS**  
1/2" = 1'-0"



**ELEC/DATAPORTS/PHONE JACK**  
1/2" = 1'-0"



**TREANORHL**  
1511 E. Bellevue Ave.  
Kansas City, MO 64108  
Office: 816.221.0900  
Fax: 816.221.1692  
www.treanorhl.com

**MCCLURE ENGINEERING**  
1000 Chest Avenue  
Saint Louis, Missouri 63102  
T 314-645-5232  
www.mcclureeng.com  
McClure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000687

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS  
RE-ISSUED IN ENTIRETY 08/10/21

NO	DESCRIPTION	DATE


**G002**

TYPICAL MOUNTING HEIGHTS


BID DOCUMENTS

Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701


BIM 360: RH-20728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
 8/6/2021 12:12:03 PM



WALL SCHEDULE						
TYPE	DIM.	GYP. BD.	FIRE RATING	SOUND BATT	UL NO	STC(SOUND)
A3	4 7/8"	5/8"				
A3A	4 7/8"	5/8"		Y	465	46
A3F	4 7/8"	5/8"	1 HOUR	Y	465	46
A3S	4 7/8"	5/8"	SMOKE	Y	494	46
E3	4 1/4"	5/8"		Y		34
F0	1 1/2"	5/8"				
F2	3 1/8"					
F3	4 1/4"	5/8"				
H2	3 1/8"	5/8"	1 HOUR		499	34



BACKING PLATE SCHEDULE				
CONDITION	H	A	B	C
		MAX LOADS IN LBS	100	100
MINIMUM STUD GAUGE	V	20	20	16
BACKING DESCRIPTION		6" HIGH SHT MTL X 16 GA	6" MTL STUD X 16 GA	6" MTL STUD X 14 GA
SHT MTL SCREW SIZE		#10	#10	#10



FOUR-HOUR FIRE WALL	PRIORITY 1	HIGHEST	
THREE-HOUR FIRE WALL	PRIORITY 2		
TWO-HOUR FIRE WALL	PRIORITY 3		
FOUR-HOUR FIRE & SMOKE BARRIER	PRIORITY 4		
FOUR-HOUR FIRE BARRIER	PRIORITY 5		
THREE-HOUR FIRE & SMOKE BARRIER	PRIORITY 6		
THREE-HOUR FIRE BARRIER	PRIORITY 7		
TWO-HOUR FIRE & SMOKE BARRIER	PRIORITY 8		
TWO-HOUR FIRE BARRIER	PRIORITY 9		
ONE-HOUR FIRE & SMOKE BARRIER	PRIORITY 10		
ONE-HOUR FIRE BARRIER	PRIORITY 11		
NON-RATED SMOKE PARTITION	PRIORITY 12		
NON-RATED PARTITION	PRIORITY 13		LOWEST

**PARTITION NOTES:**

A. STUD SPACING IS 16 INCHES ON CENTER MAX. REFER TO THE ARCHITECTURAL FLOOR PLANS (A100 SHEETS)

B. REFER TO THE ARCHITECTURAL FLOOR PLANS (A100 SHEETS)

C. REFER TO THE DASHED LINES ON THE LIFE SAFETY PLANS (G101) FOR THE FIRE RATING LOCATIONS. PARTITIONS MUST CONFORM TO TESTED, RATED ASSEMBLIES WHEN THEY ARE INDICATED TO BE RATED ON THE ARCHITECTURAL LIFE SAFETY PLANS. WHEN NO RATING IS INDICATED, CONSTRUCT THE PARTITION PER THE INDICATED TYPE AS A NON-RATED ASSEMBLY.

D. LABEL FIRE AND SMOKE WALLS AS FOLLOWS: LABEL BOTH SIDES. LABEL ALL SECTIONS. USE 4" HIGH STENCILS. USE FLUORESCENT ORANGE PAINT; LOCATE ABOUT 12" ABOVE THE FINISHED CEILING. SPACE STENCILS 10 FEET ON MAX. SPECIFIC LABELS TO READ "1HR", "2HR", "1HR SMOKE", "2HR SMOKE", "SMOKE", ETC AS IDENTIFIED IN THE LIFE SAFETY PLANS.

E. PROVIDE STENCIL WITH THE LABEL "SOUND" AS DESCRIBED IN NOTE 3 ON ALL SOUND RATED WALLS IDENTIFIED BY A "F" SUFFIX AND THAT GO TO STRUCTURE.

F. PROVIDE FIRE STOP & SMOKE STOP SYSTEMS PER SPECIFICATION AT ALL PENETRATIONS & OPENINGS (INCLUDING THE PERIMETER) THROUGH FIRE RATED WALLS.

G. SEAL ALL PENETRATIONS & OPENINGS (INCLUDING THE PERIMETER) PER SPECIFICATIONS IN ALL SOUND RATED WALLS INDICATED BY A "F" SUFFIX.

H. THE PARTITION TYPES INDICATE THE BASIC WALL CONSTRUCTION ONLY. REFER TO ALL OF THE CONSTRUCTION DOCUMENTS FOR OTHER REQUIREMENTS INCLUDING: MECHANICAL, ELECTRICAL, PLUMBING, BLOCKING & BACKING, WALL BASE, WALL FINISH, AND RECESSED & SURFACE MOUNTED EQUIPMENT.

I. PROVIDE TESTED, RATED ASSEMBLIES AT THE TOP OF ALL PARTITIONS INDICATED TO BE FIRE OR SMOKE RATED THAT EXTEND TO THE BOTTOM OF STRUCTURE OR DECK ABOVE. ALL ASSEMBLIES SHALL BE TESTED BY UNDERWRITERS LABORATORY OR OTHER TESTING FACILITY ACCEPTABLE TO THE AUTHORITY HAVING JURISDICTION. PROVIDE A FIRE AND SMOKE RATING CONSISTENT WITH THE PARTITION. THE ASSEMBLY SHALL ALLOW VERTICAL MOVEMENT PER THE SLIP SPACE SCHEDULE.

J. WHEN WALLS CONTINUE PAST INTERMEDIATE STRUCTURE, FOR EXAMPLE IN MULTI-STORY STAIR ENCLOSURES, ATTACHMENT TO INTERMEDIATE STRUCTURE SHALL BE WITH A SLOTTED CONNECTION OR OTHER MEANS SO THAT STRUCTURAL DEFLECTION WILL NOT TRANSFER LOADS TO WALL FRAMING.

K. WHERE METAL DECK ASSEMBLIES AND FIRE RATED WALLS MEET, THE CONTRACTOR MAY INSTALL FIRE RATED MINERAL BATT INSULATION WITH FIRE CALLING OR USE THE HEAD OF DETAIL SHOWN BELOW THE SLIP SPACE SCHEDULE ON THIS SHEET TO COMPLETE THE UL LISTED ASSEMBLY.

**PARTITION TYPE**

A. MTL STUD, SGL LAYER OF GYP BD, BS - TO ROOF OR BOTTOM OF DECK

B. MTL STUD, SGL LAYER OF GYP BD, BS - 4" ABV CLG

C. MTL STUD, SGL LAYER OF GYP BD, BS - PARTIAL HEIGHT

D. MTL STUD, DBL LAYER OF GYP BD, BS

E. MTL STUD, SGL LAYER OF GYP BD, SGL SIDE - TO ROOF OR BOTTOM OF DECK

F. MTL STUD, SGL LAYER OF GYP BD, SGL SIDE - 6" ABOVE CLG

G. MTL FURRING, SGL LAYER OF GYP BD

H. SHAFT WALL

J. CMU

**DIMENSIONAL MODIFIER**

MTL STUD

0 - 7/8"

1 - 1 5/8"

2 - 2 1/2"

3 - 3 5/8"

4 - 4"

5 - 5"

6 - 6"

SHAFT WALL

2 - 2 1/2" SHAFT WALL FRAMING

4 - 4" SHAFT WALL FRAMING

6 - 6" SHAFT WALL FRAMING

CMU

1 - 9 5/8"

2 - 11 5/8"

3 - 9 5/8"

6 - 5 5/8"

8 - 7 5/8"

WOOD

4 - 2x4

6 - 2x6

8 - 2x8

**TYPE MODIFIER:**

A. ACOUSTIC

F. FIRE BARRIER

L. LEAD

M. BARRIER MESH

P. SMOKE PARTITION

R. FIRE PARTITION

S. SMOKE BARRIER

W. FIRE WALL

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**

**FITOUT SPACE 2W**

1 HOSPITAL DRIVE, COLUMBIA, MO 65212

REVISIONS

NO	DESCRIPTION	DATE

**G003**


PARTITION DETAILS AND NOTES

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00

MU Project Number: CP210701



**CODE PLAN LEGEND**

SYMBOL	DESCRIPTION	PROTECTIVE ELEMENTS
[Symbol]	EXIT - EXTERIOR	
[Symbol]	EXIT - INTERIOR (Assembly occ. over 50 and exits from floor.)	
[Symbol]	FIRE EXTINGUISHER	
[Symbol]	HOSE CABINET	
[Symbol]	HOSE CABINET WITH EXTINGUISHER	
[Symbol]	FIRE EXTINGUISHER SPACING (Show rates)	
[Symbol]	HAZARDOUS AREA	
[Symbol]	DISTANCE TO SMOKE BARRIER DOOR	
[Symbol]	DISTANCE TO EXIT	
[Symbol]	SUITE ID	
[Symbol]	2.1 COMPARTMENT ID	
[Symbol]	3 HR FIRE BARRIER	3 hour Fire Barrier wall construction, 3-hour rated door assembly, Fire Damper.
[Symbol]	2 HR FIRE BARRIER	2 hour Fire Barrier wall construction, 1 1/2 hour rated door assembly, Fire Damper.
[Symbol]	1 HR FIRE BARRIER	1 hour Fire Barrier wall construction, 3/4-hour rated door assembly, Fire Damper.
[Symbol]	2 HR FIRE SMOKE BARRIER	2 hour Fire Barrier wall construction, 2-hour rated door assembly, Fire Damper.
[Symbol]	HOSPITAL CORRIDOR WALL (OR SMOKE PARTITION)	Partition built to resist the passage of smoke. Smoke damper is not required.
[Symbol]	SMOKE BARRIERS (1-2 and S-3 occupancies)	1 hour resistive rated wall, 20-minute rated door assembly. Smoke Damper. All perimeter of smoke compartments.
[Symbol]	EXIT STAIRWELL	2 hour Fire Barrier wall construction. No openings other than rated exit doors. 1 1/2-hour door assembly.
[Symbol]	SUITES	
[Symbol]	EXIT DISCHARGE PASSAGEWAY	
[Symbol]	AREA UNDER CONSTRUCTION	
[Symbol]	SPRINKLERED INCIDENTAL USE AREAS	Wall construction to resist the passage of smoke from floor to floor to F.R. Non-load bearing assembly. Self-closing doors with no transfer glazing.
[Symbol]	ACCUMULATED EXIT WIDTH AT REQUIRED EXIT (Show width)	Occupants / Required width
[Symbol]	SHOW ACCUMULATED OCCUPANT LOADS FOR COMPLEX EXIT PATHS	Provided with

**LIFE SAFETY GENERAL NOTES**

- A. ALL PENETRATIONS (NEW OR EXISTING) SHALL BE SEALED AT ALL TIMES, EXCEPT WHEN ACTIVELY WORKING WITH THE PENETRATION. EXISTING UNSEALED PENETRATIONS, ONCE ENCOUNTERED, SHALL BE SEALED IMMEDIATELY WITH THE APPROPRIATE FIRE/SMOKE STOPPING MATERIAL. COORDINATE THE SEALING METHOD, WHETHER TEMPORARY OR PERMANENT, WITH THE OWNER'S REPRESENTATIVE.
- B. EXISTING EXITS MUST REMAIN ACCESSIBLE. CLEAR PATHS OF TRAVEL TO EXITS MUST BE MAINTAINED WITHIN THE CONSTRUCTION LIMITS. CONTRACTOR IS TO COORDINATE WITH OWNER'S REPRESENTATIVE TO MAINTAIN PROPER EXIT SIGNAGE THROUGHOUT CONSTRUCTION.
- C. FIREWALLS, FIRE BARRIERS, FIRE PARTITIONS, SMOKE BARRIERS AND SMOKE PARTITIONS SHALL BE EFFECTIVELY IDENTIFIED WITH SIPS OR STENCILING IN CONCEALED SPACES. SUCH IDENTIFICATION SHALL:
  - 1) BE LOCATED WITHIN 15' OF THE END OF EACH WALL AND AT INTERVALS NOT EXCEEDING 30' MEASURED HORIZONTAL ALONG THE WALL PARTITION.
  - 2) INCLUDE LETTERING NOT LESS THAN 3" IN HEIGHT WITH A MINIMUM 3/8" STROKE IN A CONTRASTING COLOR INCORPORATING WORDING IDENTIFYING THE BARRIER DESIGNATION AND FIRE RESISTANCE RATING.

**CODE PLAN ANALYSIS**

**GENERAL INFORMATION**  
**LOCATION:** Teaching Hospital, University Hospital Complex, One Hospital Drive, Columbia, Missouri 65212  
**AGENCY INFORMATION:** University of Missouri, Columbia, Missouri  
**REASON FOR SUBMITTAL:** Infill/New Construction  
**AUTHORITIES HAVING JURISDICTION:** LM Director of Facilities Planning & Development, University of Missouri System

**PROJECT DESCRIPTION**  
 The renovation of a space on the second floor of the University of Missouri Teaching Hospital, approximately 4,450 SF. Physicians workrooms consisting of three conference study rooms, a large conference room and a break room. The connecting corridor, bathrooms and support spaces are included.

**APPLICABLE CODES - UNIVERSITY OF MISSOURI - HEALTH CARE PROJECTS**

2018 - International Building Code	2012 & 2018 - NFPA 90A Installation of AC & Ventilation Systems
2018 - International Plumbing Code	2010 & 2018 - NFPA 72 National Fire Alarm Code
2018 - International Mechanical Code	2014 - NFPA 518 Fire Prevention During Welding, Cutting and Other Hot Work
2018 - International Existing Building Code (Level 1 & Level 2 Alterations only with pre-approval of AHJ)	2011 & 2015 - NFPA 45 Fire Protection for Laboratories Using Chemicals
2018 - International Fire Code	2018 - NFPA 20 Installation of Stationary Fire Pumps for Fire Protection
2018 - International Fuel Gas Code	2018 & 2016 - NFPA 14 Standpipe, Private Hydrants and Hose Systems
2011 & 2017 - National Electric Code/NFPA 70	2010 & 2016 - NFPA 13 Installation of Fire Sprinkler Systems
2010 & 2016 - NFPA 110 Emergency & Standby Power Systems	2018 - ASHRAE 90.1 Energy Standard for Buildings
2012 - NFPA 101 Life Safety Code	2017 - ASHRAE 170 Ventilation of Health Care Facilities
2012 - NFPA 99 Standard for Health Care Facilities	2010 - Americans with Disabilities Act, Standards for Accessible Design
	2018 - Facility Guidelines Institute

**BUILDING DESCRIPTION**  
 The existing Teaching Hospital is nine stories (with a basement), and is part of the University Hospital Complex.

**BUILDING HEIGHTS AND AREAS**  
 Section 503, Table 504.3, Table 504.4, Table 506.2  
 Height Allowable: Unlimited  
 Stories Allowable: Unlimited  
 Floor Area Allowable: Unlimited

**Actual Gross Square Footage (TH-W):**

Ground Floor	15,859 SF
First Floor	10,458 SF
Second Floor	16,376 SF
Third Floor	15,944 SF
Fourth Floor	13,058 SF
Fifth Floor	13,041 SF
Sixth Floor	13,304 SF
Seventh Floor	13,329 SF
Eighth Floor	13,431 SF
Ninth Floor	11,192 SF
<b>Total Building</b>	<b>135,990 SF</b>

**OCCUPANCY TYPE** Section 302, 508.3.2  
 I-2 Institutional

**CONSTRUCTION TYPE:**  
 Construction Type I-A  
 Seismic Design Category: C

**STRUCTURAL FIRE RATINGS**

IBC	Table 601, Table 602
Exterior Non Bearing Wall:	
Fire Separation <30 feet:	1
Fire Separation >30 feet:	0
Interior Bearing Walls and Structural Frame:	
Supporting > 1 Floor:	3
Supporting only 1 Floor:	3
Supporting Roof only:	2
Floor construction including supporting beams & joists:	
Supporting > 1 Floor:	3
Supporting only 1 Floor:	3
Supporting Roof only:	2
Roof construction including supporting beams & joists:	1 1/2

**ACTIVE LIFE SAFETY SYSTEMS:**

Fire Alarm:	Required/Provided	Backup Power:	Required/Provided
Remote Annunciator Panel:	Required/Provided	Suppression-Standpipes:	Required/Provided
Smoke Barriers:	Required/Provided: (709 & LSC 18.3.7)	Suppression-Automatic:	Required/Provided
Exit Signs:	Required/Provided	Fire Extinguishers:	Required/Provided
Emergency Lights:	Required/Provided		Per NFPA 10 (max 75)


**CODE LIFE SAFETY ANALYSIS**

- 18.2.3.4 Minimum corridor width required for exit access: 4'  
 Exception 1: In adjunct areas not intended for the housing, treatment, or use of inpatient shall be not less than 44".
- 18.2.3.6 Minimum clear width of doors for means of egress from sleeping rooms, surgery etc., 41.5" minimum.
- 18.2.5.7.3.3 Maximum size of suite - Non sleeping less than or equal to 10,000 S.F.
- 18.2.5.7.3.4 (A) Travel distance within a non-sleeping suite to an exit access door shall not exceed 100 ft.  
 (B) Travel distance between any point in a non-sleeping suite and an exit shall not exceed 200 ft.
- 18.2.5.2 Maximum dead end = 30'
- 18.2.6.2.2.3 Maximum travel distance between any point in sleeping room and exit access door shall not exceed 50 ft.
- 18.3.6.1 Corridors shall be separated from all other areas by partitions.  
 Exception 1 Spaces open to corridor shall be unlimited in area, provided that the following criteria are met.  
 a) The spaces are not used for patient sleeping rooms, treatment rooms, or hazardous areas.  
 b) The corridors onto which the spaces open in the same smoke compartment are protected by an electrically supervised automatic smoke detection system in accordance with 18.3.4, or the smoke compartment is protected throughout with quick response sprinklers.  
 c) The space is directly supervised by staff, such as a nurses station.  
 d) The space does not obstruct access to required exits.
- 18.3.6.3 Corridor Doors  
 Per 18.3.6.3.1 Resist the passage of smoke (refer to CMS - ref. S&C-07-18 Door Gaps)  
 18.3.6.3.1 Gaskets not required. Clearance between the bottom of door and floor may not exceed 1"  
 18.3.6.3.2 Positive latching required.  
 18.3.6.3.11 Door closing devices not required, other than those serving required exits, smoke barriers, or enclosures of vertical openings and hazardous areas.
- 18.3.7.1 (3) Maximum size of each smoke compartment not to exceed 22,500 S.F.
- 18.3.7.1 (4) Travel distance within compartment not exceeding 200' to smoke barrier.
- 18.3.7.3 Smoke barrier minimum 1 hour construction.
- 18.3.7.6 Doors in smoke barrier minimum 20min. rating.  
 Minimum door width within corridor 41.5"  
 Doors in cross corridor shall swing in opposite directions.  
 18.3.7.8 (2) Positive latching not required.
- 18.3.7.8 Rabbits, Bevels, or astragals shall be required at the meeting edges, and stops shall be required at the head and sides of door frames in smoke barriers. Center mullions are prohibited.


**MEANS OF EGRESS**

- 1. Occupancy load per Table 1004.1.2
- 2. Egress width per occupant per Table 1005.3.2 (with sprinkler system)  
 Vertical travel: 0.3 inches per person  
 Horizontal travel: 0.2 inches per person
- 3. Minimum number of Exits per Table 1006.3.1  
 Minimum stair clear width: 44 inches per 1011.2
- 4. Length of exit access travel, (with sprinkler system) per Table 1017.2  
 Max. common path of egress travel 75 ft  
 Distance between any point in a sleeping room to an exit access door < 50 ft. (407.4.2)  
 Movement from habitable rooms shall not require passage through more than three doors and 100 ft. maximum within the suite (125 ft w/ automatic smoke detection) (407.4.4.3)  
 200 feet to a Smoke Barrier per 407.5
- 5. Dead ends: (NFPA 101 LSC- Table A.7.6.1 fully sprinklered building)  
 Healthcare = 20 feet  
 Ambulatory HC = 50 feet  
 Assembly = 20 feet  
 Business = 50 feet  
 Mercantile = 20 feet  
 Storage = 100 feet

**NOTE:**  
 THIS SHEET IS ONLY VALID IF PRINTED IN COLOR.



**2ND FLOOR LIFE SAFETY PLAN A1**  
 1/8" = 1'-0"



**TREANORHL**  
 1811 Baltimore Ave.  
 Kansas City, Missouri 64108  
 Office: 816.221.0900  
 Fax: 816.221.1899  
 www.treanorhl.com

**MCGUIRE ENGINEERING**  
 1000 Clay Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-5232  
 www.mcguiire.com

McGuire Engineering Corporation  
 Professional Engineering Corporation  
 Missouri State Certificate of Authority #00087


UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY		08/10/21

**G101**  
 LIFE SAFETY PLAN  
 BID DOCUMENTS  
 Date: 08/10/2021  
 TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701




**2ND FLOOR C4**  
1/16" = 1'-0"




**1ST FLOOR C1**  
1/16" = 1'-0"

**ACCESS PLAN KEY NOTES**


#	DESCRIPTION
1	THIS PLAN IS ISSUED FOR THE PURPOSE OF DEFINING THE CONTRACTOR'S LABOR PATH TO THE JOBSITE.
2	FOOT TRAFFIC TO PROCEED THROUGH DESIGNATED AREA. KEEP ALL TRAFFIC WITHIN BOUNDARY. ENSURE THAT DEBRIS IS NOT TRACKED THROUGH SPACE.
3	ELEVATOR TO ACCESS GROUND, 1ST, 2ND FLOOR ONLY.
5	LOADING AND UNLOADING THROUGH DOCK COORDINATED THROUGH OWNER'S REPRESENTATIVE. NO MATERIALS ALLOWED THROUGH THESE SPACES WITHOUT EXPLICIT PERMISSION OF THE MU PROJECT MANAGER.
6	HOSPITAL PROVIDED DUMPSTER.
7	JUST IN TIME DELIVERIES, MATERIAL STORAGE WITHIN PROJECT SITE.




**GROUND FLOOR A3**  
1/16" = 1'-0"



**SITE ACCESS PLAN A1**  
NOT TO SCALE



**KEY PLAN**



**TREANORHL**  
1811 E. Babcock Ave.  
St. Louis, Missouri 63102  
Office: 314-646-5232  
Fax: 314-221-1690  
www.treanorhl.com

**MCCLURE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T: 314-646-5232  
www.mcclureeng.com

McClure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #00087


UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS	NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY	08/10/21		

**G102**  
CONSTRUCTION ACCESS  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701

8/6/2021 12:12:05 PM BIM 360:RH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt



### INFECTION CONTROL NOTES

- CONFINE DUST AND DEBRIS TO WITHIN DUST PARTITION ENCLOSURE. THERE SHALL BE NO VISIBLE DUST OR DEBRIS OUTSIDE OF DUST PARTITIONED AREA. INF. UNABLE TO MAINTAIN A DUST AND DEBRIS FREE AREA OUTSIDE OF DUST PARTITION ENCLOSURE, MORE EXTENSIVE MEASURES WILL BE REQUIRED AT CONTRACTOR'S EXPENSE. THE FOLLOWING GENERAL NOTES FURTHER INDICATE REQUIRED MEASURES.
- NO WORK TO BEGIN UNTIL INFECTION CONTROL MEASURES ARE IN PLACE AND APPROVED BY OWNER'S REPRESENTATIVE.
- THE INFECTION CONTROL DEPARTMENT SHALL EXAMINE THE PRIMARY INFECTION CONTROL BARRIER ASSEMBLY AND VERIFY THE NEGATIVE-AIR ENVIRONMENT.
- WORKERS WEARING APPROPRIATE SURGICAL ATTIRE SHALL INSTALL THE INFECTION CONTROL BARRIERS THAT ARE EXPOSED TO THE ACTIVE HOSPITAL ZONES, INCLUDING THOSE LOCATED IN CORRIDORS CC3015 & 3E59.
- ESTABLISH A NEGATIVE AIR ENVIRONMENT INSIDE THE DESIGNATED PROJECT AREA UTILIZING HEPA-FILTERED AIR FILTRATION EQUIPMENT. A PRESSURE DIFFERENCE OF AT LEAST 0.1" OF WATER COLUMN SHALL BE MAINTAINED WITH THE ADJACENT PATIENT CARE AREAS AT ALL TIMES. A MANOMETER SHALL BE INSTALLED FOR MONITORING THE PRESSURE DIFFERENTIAL.
- ISOLATE THE HVAC SYSTEM IN THE WORK AREA TO PREVENT CONTAMINATION OF THE EXISTING DUCT SYSTEM.
- SEAL HOLES, PIPES, CONDUITS, AND PUNCTURES AS REQUIRED.
- HVAC REQUIRED IN THE CONSTRUCTION ZONE MUST BE PROVIDED BY THE CONTRACTOR. THE UNIT SHOULD RECIRCULATE AIR IN THE CONSTRUCTION ZONE WITH NO ADDITIONAL OUTSIDE AIR OR EXHAUST.
- PROVIDE ADHESIVE WALK-OFF MATS AT ENTRANCE TO WORK AREA. REPLACE USED MATS WITH NEW MATS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- CONSTRUCTION WASTE SHALL BE REMOVED FROM THE AREA IN APPROVED CONTAINERS.
- DO NOT REMOVE BARRIERS FROM THE WORK AREA UNTIL THE PROJECT IS COMPLETED. AT THE COMPLETION OF THE PROJECT CAREFULLY REMOVE BARRIERS TO MINIMIZE SPREADING OF DUST AND DEBRIS ASSOCIATED WITH CONSTRUCTION.
- WORKERS WEARING APPROPRIATE SURGICAL ATTIRE SHALL REMOVE ANY BARRIERS NO LONGER NEEDED THAT ARE EXPOSED TO ACTIVE HOSPITAL AREAS, INCLUDING THOSE LOCATED IN CORRIDORS CC3015 & 3E59. THE DIRTY SIDE OF THE BARRIER SHOULD BE FOLDED TO THE INSIDE IN A MANNER THAT LIMITS THE SPREAD OF DUST.
- REMOVE ISOLATION OF HVAC, IN AREA WHERE WORK IS BEING PERFORMED, AT THE COMPLETION OF THE JOB.
- WORKERS SHALL CONDUCT A CONSTRUCTION CLEAN BOTH SIDES OF THE INFECTION CONTROL BARRIER PRIOR TO COMPLETION OF WORK. HOSPITAL WILL PROVIDE A SECONDARY ADDITIONAL CLEANING PRIOR TO OCCUPATION. COORDINATE TIMING TO ALLOW BOTH CLEANINGS TO OCCUR.
- INFECTION CONTROL WILL RE-INSPECT THE AREA PRIOR TO RE-ENTRY BY EMPLOYEES OR PATIENTS.
- REFERENCE SPECIFICATIONS DIVISION 01 FOR ADDITIONAL COMMENTARY.

**RDB - Rigid Drywall Barrier**  
 The barrier shall extend from floor to ceiling and constructed utilizing 3-5/8" metal studs and 1/2" or 5/8" gypsum board on clean side of studs. Metal studs shall be placed at no less than 16" and no more than 24" O.C. Gypsum boards seams and joints must be sealed with an approved tape or with joint compound/tape. The barrier shall be adequately sealed and maintained at floor and ceiling connections throughout to prevent migration of dust from area of Work into adjacent occupied areas. There shall be no penetrations in the barrier.

Air filtration equipment exhaust/vent hose may pass through upper portion of the barrier. Penetration/opening for exhaust/vent hoses shall be adequately sealed and maintained throughout.

The barrier shall be equipped with a door/frame assembly. The assembly is not required to be fire-rated, however, must be hinged swing type, minimum width of 36", and be solid wood or metal clad with a metal frame. The door shall be equipped with commercial grade lever handle with removable key core. The hardware must be positive latching and accept a Best 7-pin core, OFOL. A door sweep may be required. The barrier door shall remain closed and locked during the work period.

Above ceiling requirement:  
 The barrier shall also include 6 or 10-mil fire-resistant polyethylene barrier extending from ceiling to deck directly above rigid barrier. If necessary, non-combustible components shall be utilized to support polyethylene. The barrier shall be adequately sealed at deck and ceiling connections and at penetrations in the barrier to prevent migration of dust from area of Work into adjacent areas.

**MC - Modular Containment**  
 The barrier shall be achieved utilizing an approved modular system. The system shall be composed of floor-to-ceiling partitions of not less than nominal 1 1/2" thickness aluminum framing. System joints shall be interlocking and/or sealed. Ceiling, floor, and wall connections shall be sealed to prevent migration of dust and contaminants from area of Work into adjacent occupied areas. The partitions should have sound isolation properties to reduce transfer of sound to occupied adjacent areas. The barrier shall be equipped with integrated door panel. The door shall be equipped with commercial grade lever handle with removable key core. The hardware must be positive latching and accept Best 7-pin core, OFOL. The barrier shall be equipped with integrated air management panel to accept negative air exhaust discharge hose and be equipped with magnetic negative air indicator.

Above ceiling requirement:  
 The barrier shall also include 6 or 10-mil fire-resistant polyethylene barrier extending from ceiling to deck directly above rigid barrier. If necessary, non-combustible components shall be utilized to support the polyethylene. The barrier shall be adequately sealed at the deck and ceiling connections and at penetrations in the barrier to prevent the migration of dust from the work area into adjacent areas.

**Infection control barrier at west door for negative air discharge**  
 The barrier shall be constructed of 1/2" or 5/8" gypsum board and installed in door frame assembly, completely filling opening. The door may be removed or held in open position. The barrier shall be adequately sealed around perimeter of gypsum board and be maintained to prevent migration of dust from area of Work into adjacent occupied areas. Air filtration equipment exhaust/vent hose may pass through upper portion of the barrier. Penetration/opening for exhaust/vent hoses shall be adequately sealed and maintained. There shall be no additional penetrations in the barrier.

**EWB - Existing Wall as Barrier**  
 The barrier shall be achieved utilizing existing wall assembly as infection control barrier. If the assembly does not extend to deck above, a barrier constructed of 6-mil fire resistant polyethylene shall be installed extending from ceiling/top of wall assembly to deck above. If necessary, non-combustible components may be utilized to support polyethylene. The barrier shall be adequately sealed at deck, ceiling, top of wall assembly connections, and penetrations in the barrier. The polyethylene barrier shall be maintained to prevent the migration of dust from area of Work into adjacent occupied spaces.



### I.C. PLAN KEY NOTES

#	DESCRIPTION

### INFECTION CONTROL LEGEND

- INFECTION CONTROL BARRIER - EWB
- INFECTION CONTROL BARRIER - RDB
- INFECTION CONTROL BARRIER - RB smoke rated
- NEGATIVE AIR EXHAUST - HEPA FILTERED
- TEMP DUCT

**NOTE:**  
 THIS SHEET IS ONLY VALID  
 IF PRINTED IN COLOR.



**TREANORHL**  
 1511 Fairview Ave.  
 Kansas City, Missouri 64108  
 Office: 816.221.0900  
 Fax: 816.221.1892  
 www.treanorhl.com

**MCGUIRE ENGINEERING**  
 1000 Clair Avenue  
 Saint Louis, Missouri 63102  
 T: 314-646-5232  
 www.mcguiire.com  
 McGuiire Engineering Corporation  
 Missouri State Certificate of Authority #00087


UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS

NO	DESCRIPTION	DATE

**G103**  
 FIRST FLOOR INFECTION CONTROL  
 BID DOCUMENTS  
 Date: 08/10/2021  
 TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701



2ND FLOOR INFECTION CONTROL PLAN  
PHASE I A2  
1/8" = 1'-0"



2ND FLOOR INFECTION CONTROL PLAN  
PHASE II - CORRIDOR FINISHES A1  
1/8" = 1'-0"

**INFECTION CONTROL NOTES**

- CONFINE DUST AND DEBRIS TO WITHIN DUST PARTITION ENCLOSURE. THERE SHALL BE NO VISIBLE DUST OR DEBRIS OUTSIDE OF DUST PARTITIONED AREA. UNABLE TO MAINTAIN A DUST AND DEBRIS FREE AREA OUTSIDE OF DUST PARTITIONED ENCLOSURE. MORE EXTENSIVE MEASURES WILL BE REQUIRED AT CONTRACTOR'S EXPENSE. THE FOLLOWING GENERAL NOTES FURTHER INDICATE REQUIRED MEASURES:
- NO WORK TO BEGIN UNTIL INFECTION CONTROL MEASURES ARE IN PLACE AND APPROVED BY OWNER'S REPRESENTATIVE.
  - THE INFECTION CONTROL DEPARTMENT SHALL EXAMINE THE PRIMARY INFECTION CONTROL BARRIER ASSEMBLY AND VERIFY THE NEGATIVE-AIR ENVIRONMENT.
  - WORKERS WEARING APPROPRIATE SURGICAL ATTIRE SHALL INSTALL THE INFECTION CONTROL BARRIERS THAT ARE EXPOSED TO THE ACTIVE HOSPITAL ZONES, INCLUDING THOSE LOCATED IN CORRIDORS CC3015 & 3E59.
  - ESTABLISH A NEGATIVE AIR ENVIRONMENT INSIDE THE DESIGNATED PROJECT AREA UTILIZING HEPA-FILTERED AIR FILTRATION EQUIPMENT. A PRESSURE DIFFERENCE OF AT LEAST 0.1" OF WATER COLUMN SHALL BE MAINTAINED WITH THE ADJACENT PATIENT CARE AREAS AT ALL TIMES. A MANOMETER SHALL BE INSTALLED FOR MONITORING THE PRESSURE DIFFERENTIAL.
  - ISOLATE THE HVAC SYSTEM IN THE WORK AREA TO PREVENT CONTAMINATION OF THE EXISTING DUCT SYSTEM.
  - SEAL HOLES, PIPES, CONDUITS, AND PUNCTURES AS REQUIRED.
  - HVAC REQUIRED IN THE CONSTRUCTION ZONE MUST BE PROVIDED BY THE CONTRACTOR. THE UNIT SHOULD RECIRCULATE AIR IN THE CONSTRUCTION ZONE WITH NO ADDITIONAL OUTSIDE AIR OR EXHAUST.
  - PROVIDE ADHESIVE WALK-OFF MATS AT ENTRANCE TO WORK AREA. REPLACE USED MATS WITH NEW MATS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
  - CONSTRUCTION WASTE SHALL BE REMOVED FROM THE AREA IN APPROVED CONTAINERS.
  - DO NOT REMOVE BARRIERS FROM THE WORK AREA UNTIL THE PROJECT IS COMPLETED. AT THE COMPLETION OF THE PROJECT CAREFULLY REMOVE BARRIERS TO MINIMIZE SPREADING OF DUST AND DEBRIS ASSOCIATED WITH CONSTRUCTION.
  - WORKERS WEARING APPROPRIATE SURGICAL ATTIRE SHALL REMOVE ANY BARRIERS NO LONGER NEEDED THAT ARE EXPOSED TO ACTIVE HOSPITAL AREAS, INCLUDING THOSE LOCATED IN CORRIDORS CC3015 & 3E59. THE DIRTY SIDE OF THE BARRIER SHOULD BE FOLDED TO THE INSIDE IN A MANNER THAT LIMITS THE SPREAD OF DUST.
  - REMOVE ISOLATION OF HVAC, IN AREA WHERE WORK IS BEING PERFORMED, AT THE COMPLETION OF THE JOB.
  - WORKERS SHALL CONDUCT A CONSTRUCTION CLEAN BOTH SIDES OF THE INFECTION CONTROL BARRIER PRIOR TO COMPLETION OF WORK. HOSPITAL WILL PROVIDE A SECONDARY ADDITIONAL CLEANING PRIOR TO OCCUPATION. COORDINATE TIMING TO ALLOW BOTH CLEANINGS TO OCCUR.
  - INFECTION CONTROL WILL RE-INSPECT THE AREA PRIOR TO RE-ENTRY BY EMPLOYEES OR PATIENTS.
  - REFERENCE SPECIFICATIONS DIVISION 01 FOR ADDITIONAL COMMENTARY.

**RDB - Rigid Drivall Barrier**  
The barrier shall extend from floor to ceiling and constructed utilizing 3/8" metal studs and 1/2" or 5/8" gypsum boards on clean side of studs. Metal studs shall be placed at no less than 16" and no more than 24" O.C. Gypsum boards seams and joints must be sealed with an approved tape or with joint compound. The barrier shall be adequately sealed and maintained at floor and ceiling connections throughout to prevent migration of dust from area of Work into adjacent occupied areas. There shall be no penetrations in the barrier.

Air filtration equipment exhaust/vent hose may pass through upper portion of the barrier. Penetration/opening for exhaust/vent hose shall be adequately sealed and maintained throughout.

The barrier shall be equipped with a door/frame assembly. The assembly is not required to be fire-rated, however, must be hinged swing-type, minimum width of 36", and be solid wood or metal clad with a metal frame. The door shall be equipped with commercial grade lever handle with removable key core. The hardware must be positive latching and accept a Best 7-pin core, OFOI. A door sweep may be required. The barrier door shall remain closed and locked during the work period.

**Above ceiling requirement**  
The barrier shall also include 6 or 10-mil fire-resistant polyethylene barrier extending from ceiling to deck directly above rigid barrier. If necessary, non-combustible components shall be utilized to support polyethylene. The barrier shall be adequately sealed at deck and ceiling connections and at penetrations in the barrier to prevent migration of dust from area of Work into adjacent areas.

**MC - Modular Containment**  
The barrier shall be achieved utilizing an approved modular system. The system shall be composed of floor-to-ceiling partitions of not less than nominal 1 1/2" thickness aluminum framing. System joints shall be interlocking and/or sealed. Ceiling, floor, and wall connections shall be sealed to prevent migration of dust and contaminants from area of Work into adjacent occupied areas(s). The partitions should have sound isolation properties to reduce transfer of sound to occupied adjacent areas. The barrier shall be equipped with integrated door panel. The door shall be equipped with commercial grade lever handle with removable key core. The hardware must be positive latching and accept Best 7-pin core, OFOI. The barrier shall be equipped with integrated air management panel to accept negative air exhaust discharge hose and be equipped with magnahelic negative air indicator.

**Above ceiling requirement**  
The barrier shall also include 6 or 10-mil fire-resistant polyethylene barrier extending from ceiling to deck directly above rigid barrier. If necessary, non-combustible components shall be utilized to support the polyethylene. The barrier shall be adequately sealed at the deck and ceiling connections and at all penetrations in the barrier to prevent the migration of dust from the work area into adjacent areas.

**Infection control barrier at west door for negative air discharge**  
The barrier shall be constructed of 1/2" or 5/8" gypsum board and installed in door frame assembly, completely filling opening. The door may be removed or be held in open position. The barrier shall be adequately sealed around perimeter of gypsum board and be maintained to prevent migration of dust from area of Work into adjacent occupied areas. Air filtration equipment exhaust/vent hose may pass through upper portion of the barrier. Penetration/opening for exhaust/vent hose shall be adequately sealed and maintained. There shall be no additional penetrations in the barrier.

**EWB - Existing Wall as Barrier**  
The barrier shall be achieved utilizing existing wall assembly as infection control barrier. If the assembly does not extend to deck above, a barrier constructed of 6-mil fire resistant polyethylene shall be installed extending from ceiling/top of wall assembly to deck above. If necessary, non-combustible components may be utilized to support polyethylene. The barrier shall be adequately sealed at deck, ceiling, top of wall assembly connections, and penetrations in the barrier. The polyethylene barrier shall be maintained to prevent the migration of dust from area of Work into adjacent occupied spaces.



**I.C. PLAN KEY NOTES**

#	DESCRIPTION

**INFECTION CONTROL LEGEND**

- INFECTION CONTROL BARRIER - EWB
- INFECTION CONTROL BARRIER - RDB
- INFECTION CONTROL BARRIER - RDB smoke rated
- NEGATIVE AIR EXHAUST - HEPA FILTERED
- TEMP DUCT

**NOTE:**  
THIS SHEET IS ONLY VALID  
IF PRINTED IN COLOR.



**TREANORHL**  
1811 Eastmore Ave.  
St. Louis, Missouri 63102  
Office: 314-645-5232  
Fax: 314-627-1692  
www.treanorhl.com

**MCGUIRE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T 314-645-5232  
www.mcguireeng.com

McGuire Engineering  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE

**G104**

SECOND FLOOR  
INFECTION CONTROL

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number:  
HC0728.2101.00

MU Project Number:  
CP210701

BIM 360:PH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
8/6/2021 12:12:06 PM




BIM 360:RH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
8/6/2021 12:11:57 PM



### DEMO NOTES - GENERAL

- A CONTRACTOR TO FIELD VERIFY ALL WORK AND REPORT ANY DISCREPANCIES TO ARCHITECT IN WRITING PRIOR TO BEGINNING WORK IN AFFECTED AREAS.
- B CONTRACTOR TO VERIFY ALL EXISTING HOSPITAL SYSTEMS CURRENTLY INSTALLED IN THE CONSTRUCTION AREA. ALL DEVICES TO REMAIN SHALL BE CHECKED AND IN WORKING CONDITION WHEN PROJECT IS COMPLETE.
- C CONTRACTOR SHALL PATCH TO MATCH SURROUNDING FINISHES ANY AREAS DAMAGED AS A RESULT OF, OR CAUSED BY THE WORK INDICATED THROUGHOUT THE CONTRACT DOCUMENTS.
- D WHERE REMOVAL OF EXISTING WALL PARTITIONS, EQUIPMENT, ETC DISRUPTS OR DISTURBS EXISTING ELECTRICAL, MECHANICAL, OR PLUMBING SERVICES TO AREAS NOT DESIGNATED AS THE CONSTRUCTION AREAS, CONTRACTOR SHALL PROVIDE TEMPORARY CONNECTIONS AS REQUIRED TO ENSURE UNINTERRUPTED SERVICE TO SAID AREAS. NOTE: NO SERVICE IS TO BE SHUT DOWN WITHOUT PRIOR APPROVAL BY OWNER.
- E REFER TO MEP DEMOLITION DRAWINGS FOR ADDITIONAL INFORMATION.
- F WORK IN THE CEILING AREAS ON THE 1ST FLOOR IS AFTER-HOURS WORK. COORDINATION AND SCHEDULING WITH THE OWNER IS REQUIRED.
- G UTILIZE ESTABLISHED HOSPITAL ICRA TEMPORARY STANDARDS FOR ALL WORK OUTSIDE OF THE ESTABLISHED WORK ZONE. WORK PLAN SUBMITTAL, REVIEW AND APPROVAL IS REQUIRED FOR EACH CONDITION AND LOCATION.
- H CLEAN AND RESTORE SPACES TO ORIGINAL CONDITION PRIOR TO HOURS OF OPERATION.
- I USE ELEVATOR TO REMOVE DEMOLISHED ELEMENTS AND DEBRIS FROM SITE. USE OF WINDOW OPENINGS FOR REMOVAL IS NOT PERMITTED.



**TREANORHL**  
1811 Babine Ave.  
St. Louis, Missouri 63103  
Office: 816.221.0900  
Fax: 816.221.1692  
www.treanorhl.com

**MCCLEURE ENGINEERING**  
1000 Clay Avenue  
St. Louis, Missouri 63102  
T 314-646-5232  
www.mccleure.com

MCCleure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #00087

### DEMOLITION KEY NOTES

#	DESCRIPTION
D1	REMOVE PORTION OF CEILING AS NEEDED TO ACCOMMODATE ABOVE CEILING MEP WORK. PROTECT EXISTING CONDITIONS INCLUDING FINISHES & FEE
D2	DESIGN TEAM WAS UNABLE TO FIELD VERIFY DUE TO COVID RESTRICTIONS.
D3	EXISTING SUSPENDED CEILING. SALVAGE PANELS FOR REINSTALLATION.
D4	EXISTING GYP BD CEILING.

### DEMOLITION PLAN LEGEND

- REMOVE EXISTING WALL, FLOOR TO CEILING
- EXISTING WALL TO REMAIN
- EXISTING DOOR & FRAME TO REMAIN
- REMOVE EXISTING DOOR, FRAME, AND HARDWARE

### F# W# C# FLOOR/WALL/CEILING NOTES

- F1 - REMOVE EXISTING FLOOR, BASE, GLUE, ETC. TO SLAB. PATCH, PRIME, AND PREPARE SUB-FLOOR TO RECEIVE NEW FLOORING AS SCHEDULED.
- F2 - EXISTING FLOOR TO REMAIN.
- F3 - SPECIAL CONDITION - REFER TO KEYNOTE.
- W1 - REMOVE EXISTING WALL COVERINGS, PAINT, ETC. PATCH, PREP, AND PRIME WALL TO RECEIVE NEW FINISHES AS SCHEDULED.
- W2 - EXISTING WALL TO REMAIN.
- W3 - SPECIAL CONDITION - REFER TO KEYNOTE.
- C1 - REMOVE EXISTING CEILING, HANGERS, ETC. TO BTM OF STRUCTURE. EXERCISE EXTREME CAUTION AS TO NOT DISTURB SYSTEMS INTENDED TO REMAIN.
- C2 - EXISTING CEILING TO REMAIN.
- C3 - SPECIAL CONDITION - REFER TO KEYNOTE.

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY	08/10/21	

**AD101**

FIRST FLOOR DEMOLITION PLAN


BID DOCUMENTS

Date: 08/10/2021


TreanorHL Project Number: HC0728.2101.00

MU Project Number: CP210701

**1ST FLOOR DEMO PLAN A1**  
1/8" = 1'-0"



BIM 360:RHC0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
8/6/2021 12:11:57 PM



2ND FLOOR DEMO PLAN A1  
1/8" = 1'-0"

**DEMO NOTES - GENERAL**

- A CONTRACTOR TO FIELD VERIFY ALL WORK AND REPORT ANY DISCREPANCIES TO ARCHITECT IN WRITING PRIOR TO BEGINNING WORK IN AFFECTED AREAS.
- B CONTRACTOR TO VERIFY ALL EXISTING HOSPITAL SYSTEMS CURRENTLY INSTALLED IN THE CONSTRUCTION AREA. ALL DEVICES TO REMAIN SHALL BE CHECKED AND IN WORKING CONDITION WHEN PROJECT IS COMPLETE.
- C CONTRACTOR SHALL PATCH TO MATCH SURROUNDING FINISHES ANY AREAS DAMAGED AS A RESULT OF, OR CAUSED BY THE WORK INDICATED THROUGHOUT THE CONTRACT DOCUMENTS.
- D WHERE REMOVAL OF EXISTING WALL PARTITIONS, EQUIPMENT, ETC. DISRUPTS OR DISTURBS EXISTING ELECTRICAL, MECHANICAL, OR PLUMBING SERVICES TO AREAS NOT DESIGNATED AS THE CONSTRUCTION AREAS, CONTRACTOR SHALL PROVIDE TEMPORARY CONNECTIONS AS REQUIRED TO ENSURE UNINTERRUPTED SERVICE TO SAID AREAS. NOTE: NO SERVICE IS TO BE SHUT DOWN WITHOUT PRIOR APPROVAL BY OWNER.
- E REFER TO MEP DEMOLITION DRAWINGS FOR ADDITIONAL INFORMATION.
- F WORK IN THE CEILING AREAS ON THE 1ST FLOOR IS AFTER-HOURS WORK. COORDINATION AND SCHEDULING WITH THE OWNER IS REQUIRED.
- G UTILIZE ESTABLISHED HOSPITAL IGRA TEMPORARY STANDARDS FOR ALL WORK OUTSIDE OF THE ESTABLISHED WORK ZONE. WORK PLAN SUBMITTAL, REVIEW AND APPROVAL IS REQUIRED FOR EACH CONDITION AND LOCATION.
- H CLEAN AND RESTORE SPACES TO ORIGINAL CONDITION PRIOR TO HOURS OF OPERATION.
- I USE ELEVATOR TO REMOVE DEMOLISHED ELEMENTS AND DEBRIS FROM SITE. USE OF WINDOW OPENINGS FOR DEBRIS REMOVAL IS NOT PERMITTED.

**DEMOLITION KEY NOTES**


#	DESCRIPTION
D01	REMOVE ABANDONED PLUMBING STUB-UPS AND ELECTRICAL CONDUIT. CAP AT FLOOR BELOW. RE. M.E.P. DRAWINGS.
D02	GRIND FLOOR TO LEVEL AND PREP FOR NEW FINISH.
D03	REMOVE WINDOW FRAME AND GLAZING.
D04	REMOVE TILE WALL FROM FLOOR TO DECK.
D05	REMOVE TILE WALL FROM FLOOR TO BOTTOM OF BEAM / HEAD OF EXISTING WINDOW OPENING.
D06	REMOVE WALL FOR NEW DOOR. RE. DOOR SCHEDULE.
D09	REMOVE WOOD CLEAT. PREP SURFACE FOR NEW FINISH.
D10	REMOVE TACKBOARD. PREP SURFACE FOR NEW FINISH.
D11	REMOVE ACCESS PANEL.
D12	REMOVE SHELVING. PREP SURFACE FOR NEW FINISH.
D13	REMOVE DOOR AND HARDWARE. SALVAGE CARD READER AND ELECTRIC STRIKE WHERE OCCURS. FRAME TO REMAIN. PREP. FRAME FOR NEW FINISH.
D14	REMOVE PLUMBING FIXTURES. RE. PLUMBING DRAWINGS.
D16	REMOVE WINDOW SILL. PREP LEDGE FOR NEW SILL.
D17	REMOVE PLASTER AND LATHE CEILING.
D18	REMOVE DOOR, FRAME, AND HARDWARE. SALVAGE FOR RELOCATION. RE. DOOR SCHEDULE.

**DEMOLITION PLAN LEGEND**

- REMOVE EXISTING WALL, FLOOR TO CEILING
- EXISTING WALL TO REMAIN
- EXISTING DOOR & FRAME TO REMAIN
- REMOVE EXISTING DOOR, FRAME, AND HARDWARE

**F/W/W/C/W FLOOR/WALL/CEILING NOTES**

- F1 - REMOVE EXISTING FLOOR, BASE, GULCH, ETC. TO SLAB. PATCH, PRIME, AND PREPARE SUB-FLOOR TO RECEIVE NEW FLOORING AS SCHEDULED.
- F2 - EXISTING FLOOR TO REMAIN.
- F3 - SPECIAL CONDITION - REFER TO KEYNOTE.
- W1 - REMOVE EXISTING WALL COVERINGS, PAINT, ETC. PATCH, PREP, AND PRIME WALL TO RECEIVE NEW FINISHES AS SCHEDULED.
- W2 - EXISTING WALL TO REMAIN.
- W3 - SPECIAL CONDITION - REFER TO KEYNOTE.
- C1 - REMOVE EXISTING CEILING, HANGERS, ETC. TO BTM OF STRUCTURE. EXERCISE EXTREME CAUTION AS TO NOT DISTURB SYSTEMS INTENDED TO REMAIN.
- C2 - EXISTING CEILING TO REMAIN.
- C3 - SPECIAL CONDITION - REFER TO KEYNOTE.



**TREANORHL**  
 1511 Babine Ave.  
 Kansas City, Missouri 64108  
 Office: 816.221.0900  
 Fax: 816.221.1692  
 www.treanorhl.com

**MCCLEURE ENGINEERING**  
 1000 Chest Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-5232  
 www.mccleure.com

MCCleure Engineering Corporation  
 Missouri State Certificate of Authority #00087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY	08/10/21	

**AD102**

SECOND FLOOR DEMOLITION PLAN

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00

MU Project Number: CP210701

BIM 360: RH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
8/6/2021 12:11:47 PM



**FLOOR PLAN NOTES**

- A. ALL DIMENSIONS ARE TO GRID LINE, FACE OF CONCRETE OR MASONRY, OR FACE OF STRUCTURE, UNLESS OTHERWISE NOTED.
- B. ALL FLOOR PLAN DIMENSIONS TO MASONRY ARE NOMINAL DIMENSIONS, UNLESS NOTED AS ACTUAL.
- C. ALL ANGLES SHOWN ON THE FLOOR PLANS ARE 90 DEGREES UNLESS OTHERWISE NOTED.
- D. ALL SPOT ELEVATIONS SHOWN ON THE FLOOR PLANS OUTSIDE THE BUILDING RELATE TO USGS ELEVATIONS. ALL SPOT ELEVATIONS INSIDE THE BUILDING REFER TO BUILDING REFERENCE ELEVATIONS. NOTIFY ARCHITECT IMMEDIATELY SHOULD CONDITIONS BE FOUND CONTRADICTORY TO THESE DRAWINGS. 100'-0" = 5280.0'
- E. FURNISHINGS (SHOWN DASHED) ARE SHOWN FOR GENERAL COORDINATION. REFER TO 'F' SERIES FOR COMPLETE SCOPE OF WORK.
- F. EQUIPMENT (SHOWN DASHED) SHOWN FOR COORDINATION ONLY. REFER TO EQUIPMENT DRAWINGS FOR DIMENSIONS. VERIFY EQUIPMENT ROUGH-IN DIMENSIONS WITH MANUFACTURER AND/OR WITH REUSED OR EXISTING EQUIPMENT.
- G. IN ROOMS WITH FLOOR DRAINS, SLOPE CONCRETE SURFACE WITHIN 18" RADIUS AT 1/4" PER FOOT TOWARD FLOOR DRAIN, UNLESS OTHERWISE INDICATED.
- H. DO NOT SCALE DRAWINGS.
- I. COORDINATE ALL FLOOR CORE DRILLING WITH EXISTING STRUCTURE.
- J. PATCH AND LEVEL FLOOR SUBSTRATES TO RECEIVE NEW WORK AS SCHEDULED.
- K. PATCH AND REPAIR CEILING AS REQUIRED FOR NEW LAYOUT. CONTRACTOR TO REPAIR ALL CEILINGS TO MATCH EXISTING WHERE PARTITIONS HAVE BEEN DEMOLISHED AND EXISTING CEILING IS TO REMAIN.
- L. PATCH WALLS AT REMOVED RECEPTACLE OPENINGS SO AS TO RECEIVE SUBSEQUENT WORK.
- M. PATCH EXISTING FIRE-RATED WALLS, FLOORS, CEILINGS, ETC. SO AS TO MAINTAIN THE FIRE-RATING. ADD FIRE-SMOKE DAMPERS WHERE NEW DUCTS CROSS. ADD FIRE STOP AT ALL PENETRATIONS.
- N. PATCH EXISTING CONSTRUCTION SCHEDULED TO REMAIN. REPAIR SURFACES TO BE FLUSH WITH ADJACENT FINISH SURFACES. PATCH, SAND, AND TEXTURE EXISTING SURFACES TO SAME QUALITY AS NEW CONSTRUCTION PRIOR TO INSTALLING NEW FINISHES. REFER TO THE FINISH MANUFACTURER'S GUIDELINES FOR INSTALLATION.
- O. PATCH AND REPAIR OPENINGS FROM DEMOLISHED PIPING, CONDUIT, AND DUCTWORK PER S01.

**FLOOR PLAN KEY NOTES**

#	DESCRIPTION
P1	REPLACE OR PATCH & REPAIR CEILING TO MATCH EXISTING CONDITIONS WHERE DEMOLITION HAS OCCURRED FOR ABOVE CEILING WORK.



**TREANORHL**  
1811 E. Main Ave.  
St. Louis, MO 63103  
Office: 314-646-5532  
Fax: 314-227-1692  
www.treanorhl.com

**MCCLEURE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T 314-646-5532  
www.mccleure.com  
McCleure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #00087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS  
RE-ISSUED IN ENTIRETY 08/10/21


NO	DESCRIPTION	DATE

**A101**  
FIRST FLOOR PLAN  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701

**1ST FLOOR PLAN A1**  
0 4' 8' 16' 1/8" = 1'-0"



BIM 360: RH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
8/6/2021 12:11:47 PM



**FLOOR PLAN NOTES**

- A. ALL DIMENSIONS ARE TO GRID LINE, FACE OF CONCRETE OR MASONRY, OR FACE OF STRUCTURE, UNLESS OTHERWISE NOTED.
- B. ALL FLOOR PLAN DIMENSIONS TO MASONRY ARE NOMINAL DIMENSIONS, UNLESS NOTED AS ACTUAL.
- C. ALL ANGLES SHOWN ON THE FLOOR PLANS ARE 90 DEGREES UNLESS OTHERWISE NOTED.
- D. ALL SPOT ELEVATIONS SHOWN ON THE FLOOR PLANS OUTSIDE THE BUILDING RELATE TO USGS ELEVATIONS. ALL SPOT ELEVATIONS INSIDE THE BUILDING REFER TO BUILDING REFERENCE ELEVATIONS. NOTIFY ARCHITECT IMMEDIATELY SHOULD CONDITIONS BE FOUND CONTRADICTORY TO THESE DRAWINGS. 100'-0" = 5280.0'
- E. FURNISHINGS (SHOWN DASHED) ARE SHOWN FOR GENERAL COORDINATION. REFER TO 'F' SERIES FOR COMPLETE SCOPE OF WORK.
- F. EQUIPMENT (SHOWN DASHED) SHOWN FOR COORDINATION ONLY. REFER TO EQUIPMENT DRAWINGS FOR DIMENSIONS. VERIFY EQUIPMENT ROUGH-IN DIMENSIONS WITH MANUFACTURER AND/OR WITH REUSED OR EXISTING EQUIPMENT.
- G. IN ROOMS WITH FLOOR DRAINS, SLOPE CONCRETE SURFACE WITHIN 18" RADIUS AT 1/4" PER FOOT TOWARD FLOOR DRAIN, UNLESS OTHERWISE INDICATED.
- H. DO NOT SCALE DRAWINGS.
- I. COORDINATE ALL FLOOR CORE DRILLING WITH EXISTING STRUCTURE.
- J. PATCH AND LEVEL FLOOR SUBSTRATES TO RECEIVE NEW WORK AS SCHEDULED.
- K. PATCH AND REPAIR CEILING AS REQUIRED FOR NEW LAYOUT. CONTRACTOR TO REPAIR ALL CEILINGS TO MATCH EXISTING WHERE PARTITIONS HAVE BEEN DEMOLISHED AND EXISTING CEILING IS TO REMAIN.
- L. PATCH WALLS AT REMOVED RECEPTACLE OPENINGS SO AS TO RECEIVE SUBSEQUENT WORK.
- M. PATCH EXISTING FIRE-RATED WALLS, FLOORS, CEILINGS, ETC. SO AS TO MAINTAIN THE FIRE-RATING. ADD FIRE-SMOKE DAMPERS WHERE NEW DUCTS CROSS. ADD FIRE STOP AT ALL PENETRATIONS.
- N. PATCH EXISTING CONSTRUCTION SCHEDULED TO REMAIN. REPAIRED SURFACES TO BE FLUSH WITH ADJACENT FINISH SURFACES. PATCH, SAND, AND TEXTURE EXISTING SURFACES TO SAME QUALITY AS NEW CONSTRUCTION PRIOR TO INSTALLING NEW FINISHES. REFER TO THE FINISH MANUFACTURER'S GUIDELINES FOR INSTALLATION.
- O. PATCH AND REPAIR OPENINGS FROM DEMOLISHED PIPING, CONDUIT, AND DUCTWORK PER S01.

**FLOOR PLAN KEY NOTES**

#	DESCRIPTION
P01	EXISTING ACCESS PANEL
P03	UPGRADE PARTITION TO ACHIEVE RATING PER NEW PARTITION TYPE, RE. PARTITION TAG AND SCHEDULE
P05	CONFIRM WITH A.H.J. FOR PUSH CLEARANCE VARIANCE FOR EXISTING DOOR OPENING.
P06	INFILL FLOOR AFTER DUCT DEMOLITION
P07	PROVIDE 20 GA. SHEET METAL UP TO 8'-0" ENTIRE LENGTH OF WALL FOR IN-WALL BLOCKING. COORDINATE HEIGHT WITH SUPPLY STORAGE VENDORS.
P08	INFILL FLOOR AFTER DUCT DEMOLITION. REFERENCE A1/S01
P09	SEAL HEAD AND SILL OF PERIMETER WALL FOR PRESSURIZATION
P10	MAINTAIN OWNER ACCESS TO 2W06 AND 2W07 THROUGHOUT CONSTRUCTION

--- SCOPE DEMARCATION

**TREANORHL**  
1811 E. Highway Ave.  
Hollister, MO 64408  
Office: 816.221.0500  
Fax: 816.221.1692  
www.treanorhl.com

**MCGUIRE ENGINEERING**  
1000 Clark Avenue  
Saint Louis, Missouri 63102  
T 314-646-5522  
www.mcguireeng.com

McGuire Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS


NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY	08/10/21	

**A102**  
SECOND FLOOR PLAN

BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701

**2ND FLOOR PLAN A1**  
1/8" = 1'-0"





RCP NOTES-GENERAL

- GEN NOTES - REFLECTED CEILING PLANS
- A CONTRACTOR TO FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO BEGINNING WORK. REPORT ANY DISCREPANCIES TO ARCHITECT IN WRITING BEFORE BEGINNING WORK IN AFFECTED AREA(S)
  - B CONTRACTOR SHALL VERIFY ALL EXISTING HOSPITAL SYSTEMS CURRENTLY INSTALLED IN THE CONSTRUCTION AREA. ALL DEVICES SHALL BE CHECKED AND IN WORKING CONDITION UPON COMPLETION OF THE PROJECT.
  - C REFER TO MEP DRAWINGS FOR ADDITIONAL INFORMATION AND WORK.
  - D PATCH EXISTING WALLS AND CEILINGS SHOWN TO REMAIN THAT ARE DAMAGED BY WORK PERFORMED IN WALL OR ABOVE CEILING, INCLUDING WORK PERFORMED BY OTHER TRADES SUCH AS, BUT NOT LIMITED TO, INSTALLATION AND DEMOLITION OF UTILITIES. RETURN WALL OR CEILING SURFACE TO ITS ORIGINAL CONDITION. FINISH TO MATCH ORIGINAL OR PROVIDE NEW FINISH WHERE SCHEDULED.
  - E PROVIDE TAPING AND SANDING OF EXISTING GYP. BD. THAT WILL BE EXPOSED BELOW CEILING AND RECEIVE NEW FINISHES.
  - F CENTER ALL LIGHTING WITHIN CEILING TILE UNLESS NOTED OTHERWISE.
  - G NEW CEILING WORK TO MATCH AND ALIGN WITH EXISTING CEILINGS.
  - H CEILINGS SHALL BE APC AT 9' - 0" A.F.F. UNLESS NOTED OTHERWISE.
  - J PATCH AND REPLACE BROKEN, DAMAGED, STAINED, OR OTHERWISE COMPROMISED EXISTING CEILINGS AS NECESSARY.
  - K REFER TO FIRE PROTECTION DRAWINGS FOR LOCATIONS OF FIRE SPRINKLER HEADS. CENTER FIRE SPRINKLER HEADS BOTH DIRECTIONS IN CEILING TILES.
  - L SUBMIT LAYOUT OF ALL GYPSUM BOARD CEILING CONTROL JOINTS FOR REVIEW.
  - M CENTER ALL CEILING GRIDS IN EACH ROOM OR SPACE UNLESS OTHERWISE INDICATED WITH A GRID ORIGIN OR DIMENSION.
  - N LIGHTS, DIFFUSERS, EXIT SIGNS, SMOKE DETECTORS, AND FIREALARM SPEAKER/STROBES SHALL BE CENTERED IN THE CEILING TILES IN WHICH THEY OCCUR, UNLESS NOTED OTHERWISE.
  - P SEE MECHANICAL AND ELECTRICAL DRAWINGS FOR MOUNTING LOCATIONS OF ITEMS WHERE NO CEILING IS REQUIRED OR INDICATED.

**TREANORHL**  
 1511 Babine Ave  
 Kansas City, MO 64108  
 Office: 816.221.0900  
 Fax: 816.221.1692  
 www.treanorhl.com

**MCCLURE ENGINEERING**  
 1000 Clark Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-5522  
 www.mcclureeng.com


McClure Engineering Corporation  
 Missouri State Certificate of Authority #00087

RCP KEY NOTES

#	DESCRIPTION
---	-------------

RCP LEGEND

- APC 2' X 2'
- APC 2' X 4'
- GYP CEILING
- CEILING GRID ORIGIN LOCATION
- RECESSED CAN LIGHT
- SUPPLY DIFFUSER  
PROVIDE HEPA FILTER WHEN "H" IS SHOWN
- RETURN DIFFUSER
- SPEAKER
- EXIT LIGHT - SINGLE
- EXIT LIGHT - DOUBLE
- WALL SCONCE
- RADIANT HEATING PANEL
- CEILING ACCESS PANEL
- RECESSED INDIRECT LIGHT
- RECESSED TROFFER LIGHT
- SURFACE MOUNTED STRIP LIGHT
- LINEAR WALL LIGHT
- LINEAR PENDANT
- DECORATIVE PENDANT LIGHT
- PLAM FASCIA
- CUBICLE CURTAIN TRACK (CCT)



2ND FLOOR RCP A1  
1/8" = 1'-0"

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
FITOUT SPACE 2W  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY	08/10/21	

**A151**

REFLECTED CEILING PLAN


BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00

MU Project Number: CP210701

BIM 360: RH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
8/6/2021 12:11:48 PM




ACCESSORY SCHEDULE					
Type	Description	Manufacturer	Model	Procurement	Procure
E01	60"x84" GLASS MARKERBOARD MTD 4'-0" CTR. A.F.E.	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E02	42" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E03	60" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E04	MICROWAVE	PER OWNER		OFCI	
E05	COPIER	PER OWNER		OFCI	
E06	PRINTER	PER OWNER		OFCI	
E07	SHREDDER	PER OWNER		OFCI	
E08	W.D.W.	PER OWNER		OFCI	
E09	FRIDGE	PER OWNER		OFCI	
TA01	TOILET SEAT COVER DISPENSER	BOBRICK	B-221	CFCI	
TA03	TOILET TISSUE DISPENSER LARGE	BOBRICK	B-27460	CFCI	
TA04	SANITARY NAPKIN DISPOSAL	BOBRICK	B-353 (Recessed)	CFCI	
TA05	GRAB BARS - 12" VERTICAL 36" REAR 42" SIDE	BOBRICK	B-8606	CFCI	
TA05A	GRAB BAR - REAR WALL	BOBRICK	B-6806-36	CFCI	
TA05B	GRAB BAR - VERTICAL	BOBRICK	B-6806-18	CFCI	
TA05C	GRAB BAR - SIDE WALL	BOBRICK	B-6806-42	CFCI	
TA06	SOAP DISPENSER	PER OWNER		OFCI	
TA07	PAPER TOWEL DISPENSER	PER OWNER		OFCI	
TA08	RECESSED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE	BOBRICK	B-39747	CFCI	
TA10	FRAMED MIRROR 24"x36"	BOBRICK	B-165	CFCI	
TA11	TOILET COMPARTMENT	BOBRICK	B-1082	CFCI	
TA12	TOILET COMPARTMENT ADA	BOBRICK	B-1082	CFCI	
TA13	5 HOOK COAT RACK	PER OWNER		OFCI	
TA14	MOP HOLDER	BOBRICK	B-223-36	CFCI	
TA15	SHelf STANDARD	METRO	24"x14"	CFCI	POWDERCOAT

**FLOOR PLAN NOTES**

- A. ALL DIMENSIONS ARE TO GRID LINE, FACE OF CONCRETE OR MASONRY, OR FACE OF STRUCTURE, UNLESS OTHERWISE NOTED.
- B. ALL FLOOR PLAN DIMENSIONS TO MASONRY ARE NOMINAL DIMENSIONS, UNLESS NOTED AS ACTUAL.
- C. ALL ANGLES SHOWN ON THE FLOOR PLANS ARE 90 DEGREES UNLESS OTHERWISE NOTED.
- D. ALL SPOT ELEVATIONS SHOWN ON THE FLOOR PLANS OUTSIDE THE BUILDING RELATE TO USGS ELEVATIONS. ALL SPOT ELEVATIONS INSIDE THE BUILDING REFER TO BUILDING REFERENCE ELEVATIONS. NOTIFY ARCHITECT IMMEDIATELY SHOULD CONDITIONS BE FOUND CONTRADICTORY TO THESE DRAWINGS. 100'-0" = 5280.0'
- E. FURNISHINGS (SHOWN DASHED) ARE SHOWN FOR GENERAL COORDINATION, REFER TO 'I' SERIES FOR COMPLETE SCOPE OF WORK.
- F. EQUIPMENT (SHOWN DASHED) SHOWN FOR COORDINATION ONLY. REFER TO EQUIPMENT DRAWINGS FOR DIMENSIONS. VERIFY EQUIPMENT ROUGH-IN DIMENSIONS WITH MANUFACTURER AND/OR WITH REUSED OR EXISTING EQUIPMENT.
- G. IN ROOMS WITH FLOOR DRAINS, SLOPE CONCRETE SURFACE WITHIN 18" RADIUS AT 1/4" PER FOOT TOWARD FLOOR DRAIN, UNLESS OTHERWISE INDICATED.
- H. DO NOT SCALE DRAWINGS.
- I. COORDINATE ALL FLOOR CORE DRILLING WITH EXISTING STRUCTURE.
- J. PATCH AND LEVEL FLOOR SUBSTRATES TO RECEIVE NEW WORK AS SCHEDULED.
- K. PATCH AND REPAIR CEILING AS REQUIRED FOR NEW LAYOUT. CONTRACTOR TO REPAIR ALL CEILINGS TO MATCH EXISTING WHERE PARTITIONS HAVE BEEN DEMOLISHED AND EXISTING CEILING IS TO REMAIN.
- L. PATCH EXISTING FIRE-RATED WALLS, FLOORS, CEILINGS, ETC. SO AS TO MAINTAIN THE FIRE-RATING. ADD FIRE-SMOKE DAMPERS WHERE NEW DUCTS CROSS. ADD FIRE STOP AT ALL PENETRATIONS.
- N. PATCH EXISTING CONSTRUCTION SCHEDULED TO REMAIN. REPAIRED SURFACES TO BE FLUSH WITH ADJACENT FINISH SURFACES. PATCH, SAND, AND TEXTURE EXISTING SURFACES TO SAME QUALITY AS NEW CONSTRUCTION PRIOR TO INSTALLING NEW FINISHES. REFER TO THE FINISH MANUFACTURER'S GUIDELINES FOR INSTALLATION.
- O. PATCH AND REPAIR OPENINGS FROM DEMOLISHED PIPING, CONDUIT, AND DUCTWORK PER S01.

**FLOOR PLAN KEY NOTES**

- | #   | DESCRIPTION  |
|-----|--|
| P01 | EXISTING ACCESS PANEL  |
| P03 | UPGRADE PARTITION TO ACHIEVE RATING PER NEW PARTITION TYPE. RE. PARTITION TAG AND SCHEDULE                                       |
| P05 | CONFIRM WITH A. H. J. FOR PUSH CLEARANCE VARIANCE FOR EXISTING DOOR OPENING.   |
| P06 | INFILL FLOOR AFTER DUCT DEMOLITION   |
| P07 | PROVIDE 20 GA. SHEET METAL UP TO 8'-0" ENTIRE LENGTH OF WALL FOR IN-WALL BLOCKING. COORDINATE HEIGHT WITH SUPPLY STORAGE VENDOR. |
| P08 | INFILL FLOOR AFTER DUCT DEMOLITION. REFERENCE A1/S001  |
| P09 | SEAL HEAD AND SILL OF PERIMETER WALL FOR PRESSURIZATION  |
| P10 | MAINTAIN OWNER ACCESS TO 2W06 AND 2W07 THROUGHOUT CONSTRUCTION   |



**TREANORHL**  
1811 Babine Ave.  
Holt, MO 64108  
Office: 816.221.0900  
Fax: 816.221.1892  
www.treanorhl.com

**MCCURE ENGINEERING**  
1000 Clark Avenue  
Saint Louis, Missouri 63102  
T 314-646-6522  
www.mccureeng.com  
McClure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #00087


UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS	NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY			08/10/21

**A401**  
ENLARGED PLANS  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701

**PHYSICIANS' WORKROOM A1**  
1/4" = 1'-0"



BIM 360:RH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
8/6/2021 12:11:48 PM




ACCESSORY SCHEDULE					
Type	Description	Manufacturer	Model	Procurement	Procure
E01	60"x84" GLASS MARKERBOARD MTD 4'-0" CTR. A.F.F.	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E02	42" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E03	60" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E04	MICROWAVE	PER OWNER		OFCI	
E05	COPIER	PER OWNER		OFCI	
E06	PRINTER	PER OWNER		OFCI	
E07	SHREDDER	PER OWNER		OFCI	
E08	W.D.W.	PER OWNER		OFCI	
E09	FRIDGE	PER OWNER		OFCI	
TA01	TOILET SEAT COVER DISPENSER	BOBRICK	B-221	CFCI	
TA03	TOILET TISSUE DISPENSER LARGE	BOBRICK	B-27460	CFCI	
TA04	SANITARY NAPKIN DISPOSAL	BOBRICK	B-353 (Recessed)	CFCI	
TA05	GRAB BARS - 12" VERTICAL 36" REAR 42" SIDE	BOBRICK	B-8606	CFCI	
TA05A	GRAB BAR - REAR WALL	BOBRICK	B-6806-36	CFCI	
TA05B	GRAB BAR - VERTICAL	BOBRICK	B-6806-18	CFCI	
TA05C	GRAB BAR - SIDE WALL	BOBRICK	B-6806-42	CFCI	
TA06	SOAP DISPENSER	PER OWNER		OFCI	
TA07	PAPER TOWEL DISPENSER	PER OWNER		OFCI	
TA08	RECESSED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE	BOBRICK	B-39747	CFCI	
TA10	FRAMED MIRROR 24"x36"	BOBRICK	B-165	CFCI	
TA11	TOILET COMPARTMENT	BOBRICK	B-1062	CFCI	
TA12	TOILET COMPARTMENT ADA	BOBRICK	B-1062	CFCI	
TA13	5 HOOK COAT RACK	PER OWNER		OFCI	
TA14	MOP HOLDER	BOBRICK	B-223-36	CFCI	
TA15	SHelf STANDARD	METRO	24"x14"	CFCI	POWDERCOAT

**FLOOR PLAN NOTES**

- A. ALL DIMENSIONS ARE TO GRID LINE, FACE OF CONCRETE OR MASONRY, OR FACE OF STRUCTURE, UNLESS OTHERWISE NOTED.
- B. ALL FLOOR PLAN DIMENSIONS TO MASONRY ARE NOMINAL DIMENSIONS, UNLESS NOTED AS ACTUAL.
- C. ALL ANGLES SHOWN ON THE FLOOR PLANS ARE 90 DEGREES UNLESS OTHERWISE NOTED.
- D. ALL SPOT ELEVATIONS SHOWN ON THE FLOOR PLANS OUTSIDE THE BUILDING RELATE TO USGS ELEVATIONS. ALL SPOT ELEVATIONS INSIDE THE BUILDING REFER TO BUILDING REFERENCE ELEVATIONS. NOTIFY ARCHITECT IMMEDIATELY SHOULD CONDITIONS BE FOUND CONTRADICTORY TO THESE DRAWINGS. 100'-0" = 5280.0'
- E. FURNISHINGS (SHOWN DASHED) ARE SHOWN FOR GENERAL COORDINATION, REFER TO 'I' SERIES FOR COMPLETE SCOPE OF WORK.
- F. EQUIPMENT (SHOWN DASHED) SHOWN FOR COORDINATION ONLY. REFER TO EQUIPMENT DRAWINGS FOR DIMENSIONS. VERIFY EQUIPMENT ROUGH-IN DIMENSIONS WITH MANUFACTURER AND/OR WITH REUSED OR EXISTING EQUIPMENT.
- G. IN ROOMS WITH FLOOR DRAINS, SLOPE CONCRETE SURFACE WITHIN 18" RADIUS AT 1/4" PER FOOT TOWARD FLOOR DRAIN, UNLESS OTHERWISE INDICATED.
- H. DO NOT SCALE DRAWINGS.
- I. COORDINATE ALL FLOOR CORE DRILLING WITH EXISTING STRUCTURE.
- J. PATCH AND LEVEL FLOOR SUBSTRATES TO RECEIVE NEW WORK AS SCHEDULED.
- K. PATCH AND REPAIR CEILING AS REQUIRED FOR NEW LAYOUT. CONTRACTOR TO REPAIR ALL CEILINGS TO MATCH EXISTING WHERE PARTITIONS HAVE BEEN DEMOLISHED AND EXISTING CEILING IS TO REMAIN.
- L. PATCH WALLS AT REMOVED RECEPTACLE OPENINGS SO AS TO RECEIVE SUBSEQUENT WORK.
- M. PATCH EXISTING FIRE-RATED WALLS, FLOORS, CEILINGS, ETC. SO AS TO MAINTAIN THE FIRE-RATING. ADD FIRE-SMOKE DAMPERS WHERE NEW DUCTS CROSS. ADD FIRE STOP AT ALL PENETRATIONS.
- N. PATCH EXISTING CONSTRUCTION SCHEDULED TO REMAIN. REPAIRED SURFACES TO BE FLUSH WITH ADJACENT FINISH SURFACES. PATCH, SAND, AND TEXTURE EXISTING SURFACES TO SAME QUALITY AS NEW CONSTRUCTION PRIOR TO INSTALLING NEW FINISHES. REFER TO THE FINISH MANUFACTURER'S GUIDELINES FOR INSTALLATION.
- O. PATCH AND REPAIR OPENINGS FROM DEMOLISHED PIPING, CONDUIT, AND DUCTWORK PER S01.

**FLOOR PLAN KEY NOTES**

#	DESCRIPTION
P01	EXISTING ACCESS PANEL
P03	UPGRADE PARTITION TO ACHIEVE RATING PER NEW PARTITION TYPE, RE. PARTITION TAG AND SCHEDULE
P05	CONFIRM WITH A.H.J. FOR PUSH CLEARANCE VARIANCE FOR EXISTING DOOR OPENINGS.
P06	INFILL FLOOR AFTER DUCT DEMOLITION
P07	PROVIDE 20 GA. SHEET METAL UP TO 8'-0" ENTIRE LENGTH OF WALL FOR IN-WALL BLOCKING. COORDINATE HEIGHT WITH SUPPLY STORAGE VENDOR.
P08	INFILL FLOOR AFTER DUCT DEMOLITION. REFERENCE A1/901
P09	SEAL HEAD AND SILL OF PERIMETER WALL FOR PRESSURIZATION
P10	MAINTAIN OWNER ACCESS TO 2W06 AND 2W07 THROUGHOUT CONSTRUCTION



**TREANORHL**  
1811 Babine Ave.  
St. Louis, MO 63102  
Office: 313.221.0900  
Fax: 313.221.1699  
www.treanorhl.com

**MCGUIRE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T 314-646-5522  
www.mcguireeng.com  
McGuire Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE


**A402**  
ENLARGED PLANS  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701

**CORRIDOR & TOILETS A1**  
1/4" = 1'-0"




BIM 360:RH-C0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
 8/6/2021 12:11:51 PM


ACCESSORY SCHEDULE					
Type	Description	Manufacturer	Model	Procurement	Procure
E01	60"x84" GLASS MARKERBOARD MTD 4'-0" CTR. A.F.F.	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E02	42" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E03	60" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E04	MICROWAVE	PER OWNER		OFCI	
E05	COPIER	PER OWNER		OFCI	
E06	PRINTER	PER OWNER		OFCI	
E07	SHREDDER	PER OWNER		OFCI	
E08	W.O.V.	PER OWNER		OFCI	
E09	FRIDGE	PER OWNER		OFCI	
TA01	TOILET SEAT COVER DISPENSER	BOBRICK	B-221	CFCI	
TA03	TOILET TISSUE DISPENSER LARGE	BOBRICK	B-27460	CFCI	
TA04	SANITARY NAPKIN DISPOSAL (Recessed)	BOBRICK	B-353	CFCI	
TA05	GRAB BARS - 12" VERTICAL 36" REAR 42" SIDE	BOBRICK	B-8606	CFCI	
TA05A	GRAB BAR - REAR WALL	BOBRICK	B-6806-36	CFCI	
TA05B	GRAB BAR - VERTICAL	BOBRICK	B-6806-18	CFCI	
TA05C	GRAB BAR - SIDE WALL	BOBRICK	B-6806-42	CFCI	
TA06	SOAP DISPENSER	PER OWNER		OFCI	
TA07	PAPER TOWEL DISPENSER	PER OWNER		OFCI	
TA08	RECESSED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE	BOBRICK	B-39747	CFCI	
TA10	FRAMED MIRROR 24"x36"	BOBRICK	B-165	CFCI	
TA11	TOILET COMPARTMENT	BOBRICK	B-1062	CFCI	
TA12	TOILET COMPARTMENT ADA	BOBRICK	B-1062	CFCI	
TA13	5 HOOK COAT RACK	PER OWNER		OFCI	
TA14	MOP HOLDER	BOBRICK	B-223-36	CFCI	
TA15	SHELF STANDARD	METRO	24"x14"	CFCI	POWDERCOAT




**IM TEAM D CASEWORK D4**  
1/4" = 1'-0"




**IM TEAM D COUNTER D2**  
1/4" = 1'-0"




**IM TEAM D MARKERBOARD D1**  
1/4" = 1'-0"




**IM TEAM C MONITOR C5**  
1/4" = 1'-0"




**IM TEAM C MARKERBOARD C4**  
1/4" = 1'-0"




**IM TEAM C CASEWORK C2**  
1/4" = 1'-0"




**IM TEAM C COUNTER C1**  
1/4" = 1'-0"




**IM TEAM B MARKERBOARD B5**  
1/4" = 1'-0"




**IM TEAM B NORTH B4**  
1/4" = 1'-0"




**IM TEAM B CASEWORK B2**  
1/4" = 1'-0"




**IM TEAM B MONITOR B1**  
1/4" = 1'-0"




**IM TEAM A CASEWORK A5**  
1/4" = 1'-0"



**IM TEAM A COUNTER A4**  
1/4" = 1'-0"



**IM TEAM A MARKERBOARD A2**  
1/4" = 1'-0"




**IM TEAM A MONITOR A1**  
1/4" = 1'-0"


**EQUIPMENT KEY**

- N POWER DUPLEX OUTLET
- E EMERGENCY POWER OUTLET
- AN POWER A-FLEX OUTLET
- T TELEPHONE JACK
- D DATA JACK
- S LIGHT SWITCH(ES)
- T THERMOSTAT
- NC NURSE CALL
- L CASEWORK LOCK
- ◀ FINISH FACE OF CASEWORK
- BLANK PLATED PULL BOX

REFERENCE SHEET A701 - MATERIAL FINISH LEGEND - FOR FINISHES CALLED OUT ON ELEVATIONS



**KEY PLAN**



**TREANORHL**  
 1511 Babine Ave.  
 Kansas City, Missouri 64108  
 Office: 816.221.0900  
 www.treanorhl.com

**MCGUIRE ENGINEERING**  
 1000 Clay Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-5522  
 www.mcguire.com  
 McGuire Engineering Corporation  
 Professional Engineering Corporation  
 Missouri State Certificate of Authority #00087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE

**A420**

INTERIOR ELEVATIONS


BID DOCUMENTS

Date: 08/10/2021


TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701




ACCESSORY SCHEDULE					
Type	Description	Manufacturer	Model	Procurement	Procure
E01	60"x84" GLASS MARKERBOARD MTD 4'-0" CTR. A.F.F.	PER OWNER		OF CI	PROVIDE IN-WALL BLOCKING
E02	42" MONITOR	PER OWNER		OF OI	PROVIDE IN-WALL BLOCKING
E03	60" MONITOR	PER OWNER		OF OI	PROVIDE IN-WALL BLOCKING
E04	MICROWAVE	PER OWNER		OF OI	
E05	COPIER	PER OWNER		OF OI	
E06	PRINTER	PER OWNER		OF OI	
E07	SHREDDER	PER OWNER		OF OI	
E08	W.O.W.	PER OWNER		OF OI	
E09	FRIDGE	PER OWNER		OF OI	
TA01	TOILET SEAT COVER DISPENSER	BOBRICK	B-221	CFCI	
TA03	TOILET TISSUE DISPENSER LARGE	BOBRICK	B-27480	CFCI	
TA04	SANITARY NAPKIN DISPOSAL	BOBRICK	B-353 (Recessed)	CFCI	
TA05	GRAB BARS - 12" VERTICAL 36" REAR 42" SIDE	BOBRICK	B-8606	CFCI	
TA05A	GRAB BAR - REAR WALL	BOBRICK	B-6806-36	CFCI	
TA05B	GRAB BAR - VERTICAL	BOBRICK	B-6806-18	CFCI	
TA05C	GRAB BAR - SIDE WALL	BOBRICK	B-6806-42	CFCI	
TA06	SOAP DISPENSER	PER OWNER		OF CI	
TA07	PAPER TOWEL DISPENSER	PER OWNER		OF CI	
TA08	RECESSED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE	BOBRICK	B-39747	CFCI	
TA10	FRAMED MIRROR 24"x36"	BOBRICK	B-165	CFCI	
TA11	TOILET COMPARTMENT	BOBRICK	B-1082	CFCI	
TA12	TOILET COMPARTMENT ADA	BOBRICK	B-1082	CFCI	
TA13	5 HOOK COAT RACK	PER OWNER		OF CI	
TA14	MOP HOLDER	BOBRICK	B-223-36	CFCI	
TA15	SHelf STANDARD	METRO	24"x14"	CFCI	POWDERCOAT




**BREAK ROOM - WEST C5**  
1/4" = 1'-0"




**BREAK ROOM - EAST C4**  
1/4" = 1'-0"




**MEN'S RESTROOM - EAST B5**  
1/4" = 1'-0"




**MEN'S RESTROOM - WEST B4**  
1/4" = 1'-0"




**WOMEN'S RESTROOM - EAST B2**  
1/4" = 1'-0"




**WOMEN'S RESTROOM - WEST B1**  
1/4" = 1'-0"



**CONFERENCE MARKERBOARD A4**  
1/4" = 1'-0"



**CONFERENCE MONITOR A2**  
1/4" = 1'-0"




**CONFERENCE ROOM - WEST A1**  
1/4" = 1'-0"


**EQUIPMENT KEY**  
1/4" = 1'-0"

- N POWER DUPLEX OUTLET
- E EMERGENCY POWER OUTLET
- 4N POWER 4-FLEX OUTLET
- T TELEPHONE JACK
- D DATA JACK
- S LIGHT SWITCH(ES)
- T THERMOSTAT
- NC NURSE CALL
- L CASEWORK LOCK
- ◄ FINISH FACE OF CASEWORK
- ◻ BLANK PLATED PULL BOX

REFERENCE SHEET A701 - MATERIAL FINISH LEGEND - FOR FINISHES CALLED OUT ON ELEVATIONS



**KEY PLAN**



**TREANORHL**  
1811 Eastmore Ave.  
Kansas City, Missouri 64108  
Office: 816.221.0900  
Fax: 816.221.1892  
www.treanorhl.com

**MCGUIRE ENGINEERING**  
1000 Clay Avenue  
Saint Louis, Missouri 63102  
T 314-645-5232  
www.mcguireeng.com  
McGuire Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #00087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE

**A421**  
INTERIOR ELEVATIONS  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701


















BIM 360:RH:0728 MU Teaching Hospital/UMTH Fitout Space 2W.rvt  
 8/6/2021 12:11:56 PM

**INTERIOR SYMBOLS LEGEND**

- SHADED AREAS ARE NOT INCLUDED IN SCOPE OF WORK FOR INTERIOR RENOVATION
- KEYED NOTE
- INSTALLATION DIRECTION. INSTALL PARALLEL WITH DIRECTION OF SYMBOL
- LOCATION OF FLOORING MATERIAL TRANSITION
- SPECIFIED FINISH, REFERENCE FINISH SCHEDULE IF NOT NOTED.
- EXTENTS OF WALL FINISH
- CORNER GUARD LOCATION



**FINISH PLAN KEY NOTE LEGEND:**  
 1 PATCH EXISTING VCT FLOORING TO CENTER OF DOOR.



**TREANORHL**  
 1511 Eastmore Ave.  
 Kansas City, Missouri 64108  
 Office: 816.221.0900  
 Fax: 816.221.1899  
 www.treanorhl.com

**MCGUIRE ENGINEERING**  
 1000 Clair Avenue  
 Saint Louis, Missouri 63102  
 T 314-645-5232  
 www.mcguires.com  
 McGuire Engineering Corporation  
 Professional Engineering Corporation  
 Missouri State Certificate of Authority #000087




UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS	NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY	08/10/21		


**A712**  
 INTERIOR FINISH PLAN  
 BID DOCUMENTS  
 Date: 08/10/2021  
 TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701



**PHYSICIANS' WORKROOM PLAN A4**  
1/4" = 1'-0"

ACCESSORY SCHEDULE					
Type	Description	Manufacturer	Model	Procurement	Procure
E01	60"x84" GLASS MARKERBOARD MTD 4'-0" CTR. A.F.F.	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E02	42" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E03	60" MONITOR	PER OWNER		OFCI	PROVIDE IN-WALL BLOCKING
E04	MICROWAVE	PER OWNER		OFCI	
E05	COPIER	PER OWNER		OFCI	
E06	PRINTER	PER OWNER		OFCI	
E07	SHREDDER	PER OWNER		OFCI	
E08	I.W.O.W.	PER OWNER		OFCI	
E09	FRIDGE	PER OWNER		OFCI	
TA01	TOILET SEAT COVER DISPENSER	BOBRICK	B-221	CFCI	
TA03	TOILET TISSUE DISPENSER LARGE	BOBRICK	B-27460	CFCI	
TA04	SANITARY NAPKIN DISPOSAL	BOBRICK	B-353 (Processed)	CFCI	
TA05	GRAB BARS - 12" VERTICAL 36" REAR 42" SIDE	BOBRICK	B-8606	CFCI	
TA05A	GRAB BAR - REAR WALL	BOBRICK	B-6806-36	CFCI	
TA05B	GRAB BAR - VERTICAL	BOBRICK	B-6806-18	CFCI	
TA05C	GRAB BAR - SIDE WALL	BOBRICK	B-6806-42	CFCI	
TA06	SOAP DISPENSER	PER OWNER		OFCI	
TA07	PAPER TOWEL DISPENSER	PER OWNER		OFCI	
TA08	RECESSED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE	BOBRICK	B-39747	CFCI	
TA10	FRAMED MIRROR 24"x36"	BOBRICK	B-165	CFCI	
TA11	TOILET COMPARTMENT	BOBRICK	B-1082	CFCI	
TA12	TOILET COMPARTMENT ADA	BOBRICK	B-1082	CFCI	
TA13	5 HOOK COAT RACK	PER OWNER		OFCI	
TA14	MOP HOLDER	BOBRICK	B-223-36	CFCI	
TA15	SHELF STANDARD	METRO	24"x14"	CFCI	POWDERCOAT

8/6/2021 12:11:57 PM BIM 360://R:\C0728 MU Teaching Hospital\UMTH Fitout Space 2W.rvt



**TREANORHL**  
1811 Babine Ave.  
Kansas City, MO 64108  
Office: 816.221.0900  
Fax: 816.221.1892  
www.treanorhl.com

**MCGUIRE ENGINEERING**  
1000 Chest Avenue  
Saint Louis, Missouri 63102  
T 314-645-5232  
www.mcguiire.com  
McGuire Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #00087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS		
NO	DESCRIPTION	DATE

**A720**

FURNITURE & EQUIPMENT PLAN

BID DOCUMENTS

Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701



KEY PLAN

BIM 360/2/11/2024 AM 5/27/2021 11:32:24 AM


E 28" 27" 26" 25" 24" 23" 22" 21" 20" 19" 18" 17" 16" 15" 14" 13" 12" 11" 10" 9" 8" 7" 6" 5" 4" 3" 2" 1"

1. GENERAL REQUIREMENTS:
- A. BUILDING CODE: 2018 INTERNATIONAL BUILDING CODE
  - B. FLOOR LIVE LOADS:
    - a. HOSPITAL – CORRIDORS ABOVE FIRST FLOOR 80 PSF
    - b. PATIENT ROOMS 40 PSF
    - c. MECHANICAL ROOMS 150 PSF
  - C. WIND LOADS
    - a. INTERIOR 5 PSF
  - D. SEISMIC LOADS
    - a. RISK CATEGORY IV
    - b. SPECTRAL RESPONSE ACCELERATION: S<sub>s</sub> 0.163g  
S<sub>1</sub> 0.094g
    - c. SEISMIC IMPORTANCE FACTOR: I 1.5
    - d. SPECTRAL RESPONSE COEFFICIENTS: SDS 0.141  
SD1 0.094
    - e. SITE CLASS C
    - f. SEISMIC DESIGN CATEGORY C
  - E. DEAD LOADS
    - a. STRUCTURE ACTUAL WEIGHT
    - b. MISC. UNDERHUNG MECHANICAL 10 PSF
  - F. CONTRACTOR SHALL REVIEW AND COMPARE THE STRUCTURAL DRAWINGS WITH ALL OTHER CONTRACT DOCUMENTS, VERIFYING ALL DIMENSIONS AND ELEVATIONS, AND REPORT ANY INCONSISTENCIES TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.
  - G. THE EXISTING CONDITIONS INDICATED ON THE DRAWINGS ARE BASED ON SURVEYS MADE BY THE CONSULTANT(S) AS WELL AS ON MATERIAL PROVIDED BY THE OWNER AND NO CLAIM IS MADE AS TO ITS ABSOLUTE COMPLETENESS AND/OR ACCURACY. PRIOR TO THE START OF CONSTRUCTION OPERATIONS, FIELD-VERIFY EXISTING CONDITIONS AND DIMENSIONS PERTAINING TO THIS CONTRACT. NOTIFY THE ARCHITECT IMMEDIATELY OF ANY DISCREPANCIES FOUND AT THE SITE IN RELATION TO THE INFORMATION PROVIDED ON THE DRAWINGS.
  - H. HANDRAILS AND GUARDS SHALL BE DESIGNED TO RESIST A CONCENTRATED LOAD OF 200 LBS AND A UNIFORM LOAD OF 50 PLF, IN ANY DIRECTION, AT ANY POINT ALONG THE HANDRAIL. THE CONCENTRATED LOAD AND UNIFORM LOAD ARE NOT ASSUMED TO ACT CONCURRENTLY.
2. CONCRETE:
- A. CAST-IN-PLACE CONCRETE CONSTRUCTION SHALL CONFORM TO THE LATEST AMERICAN CONCRETE INSTITUTE DOCUMENTS, ACI-301, 305, 306, 315, 318 AND 347 AND CONCRETE REINFORCING STEEL INSTITUTE MANUAL OF STANDARD PRACTICE UNLESS OTHERWISE NOTED IN THESE CONTRACT DOCUMENTS.
  - B. ALL CONCRETE, UNLESS OTHERWISE NOTED, SHALL DEVELOP A 28 DAY COMPRESSIVE STRENGTH AND HAVE MAXIMUM WATER/CEMENT RATIOS AS FOLLOWS:
    - SLABS, JOISTS, BEAMS: 4000 PSI (w/c ≤ 0.44)
  - C. IT IS THE INTENT OF THESE CONCRETE SPECIFICATIONS THAT THE CONTRACTOR SUPPLY CONCRETE MIXES WITH A MINIMUM AMOUNT OF WATER IN ORDER TO LIMIT PLASTIC SHRINKAGE CRACKING IN FRESHLY PLACED CONCRETE. IT IS EXPECTED THAT WORKABILITY FOR CONCRETE MIXES WILL REQUIRE THE ADDITION OF WATER-REDUCING AND/OR SUPER-PLASTICIZING CHEMICAL ADMIXTURES. WATER SHALL NOT BE ADDED TO THE CONCRETE MIX ON SITE.
  - D. CONCRETE SLUMP SHALL BE A MAXIMUM OF 4" +/- 1" (ASTM C-143) AS DELIVERED IN THE FIELD. CONTRACTOR MAY USE CHEMICAL ADMIXTURES TO ATTAIN A MAXIMUM SLUMP OF 8" FOR WORKABILITY.
  - E. NO ALUMINUM ITEMS SHALL BE EMBEDDED IN CONCRETE.
  - F. UNLESS NOTED OTHERWISE, TYPICAL HOUSEKEEPING PAD SHALL BE 6" THICK REINFORCED WITH #4 at 12" o.c. AND PAD SHALL EXTEND 6" BEYOND EQUIPMENT EACH DIRECTION.
3. REINFORCING STEEL
- A. REINFORCING SHALL BE DETAILED, FABRICATED, PLACED, AND SUPPORTED IN ACCORDANCE WITH ACI 315, LATEST EDITION.
  - B. ALL REINFORCING STEEL SHALL BE ASTM A615 GRADE 60.
  - C. ALL WELDED WIRE FABRIC SHALL BE ASTM A185.
  - D. ALL ACCESSORIES FOR SUPPORTING REINFORCING SHALL BE GALVANIZED OR HAVE PLASTIC-COATED FEET.


- E. STANDARD COVERAGE OF REINFORCING, UNLESS OTHERWISE SHOWN, SHALL BE AS FOLLOWS:
    - NOT EXPOSED TO EARTH OR WEATHER: SLABS, WALLS.....3/4"
  - F. REINFORCE ALL CONCRETE NOT OTHERWISE SHOWN WITH SAME STEEL AS IN SIMILAR SECTIONS OR AREAS. CLEARANCES BETWEEN BARS SHALL MEET ACI 318 REQUIREMENTS.
  - G. WELDED WIRE FABRIC SHALL BE LAPPED ONE FULL MESH SPACING.
  - H. ALL SPLICES SHALL BE CLASS "B" TENSION LAP SPLICE, UNLESS NOTED.
4. MODULAR SUPPORT FRAMING:
- A. ALL MODULAR SUPPORT FRAMING (UNISTRUT) SHALL BE MANUFACTURED BY:
    - a. UNISTRUT CORPORATION
    - b. HILTI, INC
  - B. MATERIALS
    - a. ALL COLD-FORMED CHANNEL MEMBERS SHALL BE FABRICATED FROM STRUCTURAL GRADE STEEL CONFORMING TO ASTM A1011C SS GR 33 OR ASTM A653 GR 33.
    - b. CHANNEL SHALL BE 1 5/8" 12 GAUGE, MINIMUM YIELD 33,0000 PSI
    - c. ALL COLD-FORMED FITTINGS, CHANNEL NUTS AND OTHER SYSTEM COMPONENTS SHALL BE FABRICATED FROM STRUCTURAL GRADE STEEL, MINIMUM YIELD 33,000 PSI.
    - d. ALL BOLTS AND FASTENERS SHALL BE MINIMUM SAE GRADE 5.
    - e. ALL COMPONENTS SHALL BE PRE-GALVANIZED (PG), ELECTRO GALVANIZED (EG), OR HOT DIPPED GALVANIZED (HDG).
5. ANCHORS:
- A. CONCRETE:
    - a. ALL POST-INSTALLED ANCHORS SHALL MEET THE REQUIREMENTS OF ACI 318, APPENDIX D AND SHALL BE ACCEPTABLE FOR CRACKED CONCRETE.
    - b. MECHANICAL ANCHORS FOR CRACKED CONCRETE SHALL BE HILTI KWIK HUS EZ SCREW ANCHORS PER ICC ESR-3027 UNLESS NOTED OTHERWISE.
    - c. ADHESIVE ANCHORS FOR CRACKED CONCRETE SHALL BE HILTI HIT-HY 200 SAFE SET SYSTEM W/ HILTI HAS-E THREADED ROD OR CONTINUOUSLY DEFORMED STEEL REINFORCING PER ICC ESR-3187, UNLESS NOTED OTHERWISE.
  - B. EMBEDMENT DEPTH SHALL BE DEFINED AS THE DISTANCE FROM THE SURFACE OF THE LOAD BEARING BASE MATERIAL TO THE DEEPEST PART OF THE ANCHOR AFTER THE ANCHOR HAS BEEN DRIVEN INTO THE HOLE BUT NOT YET EXPANDED.
  - C. EQUIVALENT ANCHORS MAY BE SUBSTITUTED WITH THE ENGINEER'S APPROVAL. SUBMITTAL IS THE CONTRACTOR'S RESPONSIBILITY AND MUST INCLUDE EVALUATION REPORTS FROM THE INTERNATIONAL CONFERENCE OF BUILDING OFFICIALS.
  - D. INSTALL ANCHORS TO MEET THE REQUIREMENTS INDICATED IN THE CONTRACT DOCUMENTS, THE MANUFACTURER'S RECOMMENDATIONS AND ICC CODE REPORTS.
  - E. ANCHOR CAPACITY IS DEPENDANT UPON THE SPACING BETWEEN ADJACENT ANCHORS AND PROXIMITY OF ANCHORS TO EDGE OF CONCRETE OR MASONRY. INSTALL ANCHORS IN ACCORDANCE WITH SPACING AND EDGE CLEARANCES INDICATED ON THE DRAWINGS.
  - F. EXISTING REINFORCING BARS IN THE CONCRETE STRUCTURE SHALL NOT BE CUT DURING ANCHOR INSTALLATION UNLESS NOTED OTHERWISE. LOCATE THE POSITION OF THE EXISTING REINFORCING BARS AT THE LOCATIONS OF THE CONCRETE ANCHORS BY FERROSCAN, GPR, X-RAY OR OTHER APPROVED MEANS.
6. SUBMITTALS:
- A. ALL SHOP DRAWINGS AND SUBMITTALS MUST BE REVIEWED AND APPROVED BY THE CONTRACTOR PRIOR TO SUBMITTAL. ENGINEER'S REVIEW OF SHOP DRAWINGS IS LIMITED TO CHECKING FOR GENERAL CONFORMANCE WITH DESIGN DRAWINGS AND STRENGTH OF COMPONENTS AND MATERIALS. CONTRACTOR IS RESPONSIBLE FOR ANY CHANGES FROM THE DESIGN DRAWINGS, QUANTITIES, DIMENSIONAL ERRORS OR OMISSIONS ON THE SHOP DRAWINGS.
  - B. ALL SHOP DRAWINGS MUST BE ORIGINAL DOCUMENTS AND SHALL NOT BE REPRODUCTIONS OF THESE CONTRACT DOCUMENTS.
  - C. CONTRACTOR SHALL SUBMIT THE FOLLOWING:
    - a. MODULAR SUPPORT FRAMING PRODUCT INFORMATION

STRUCTURAL GENERAL NOTES C1

1. GENERAL:
- 1.1. THE REPAIRS SHOWN IN THESE CONSTRUCTION DOCUMENTS SHALL BE APPLIED BY THE CONTRACTOR AS NEEDED TO ALL AREAS OF THE CONCRETE FRAMING AS NEEDED AND DIRECTED BY THE ARCHITECT. ALL ABANDONED PENETRATIONS REQUIRE REPAIR.
  - 1.2. CONDITIONS OBSERVED DURING PRE-BID WALK THROUGH AND CONSTRUCTION SIMILAR TO THOSE SHOWN BUT NOT SPECIFICALLY NOTED IN THE CONSTRUCTION DOCUMENTS SHALL BE INCLUDED IN THE CONTRACTOR'S PRICE.
2. GENERAL REPAIR PREPARATION REQUIREMENTS:
- 2.1. ALL AREAS WITH REQUIRED WORK SHALL BE CLEANED TO SOUND CONCRETE WITH A 1/8" MINIMUM SURFACE PROFILE. CONCRETE SHALL BE REMOVED BEYOND SOUND CONCRETE AS REQUIRED FOR MINIMUM PATCH THICKNESS.
  - 2.2. ACCESS TO SOUND CONCRETE SHALL INCLUDE THE REMOVAL OF ALL DEBRIS AND ABANDONED EQUIPMENT, FORMS, INSULATION, PIPING, ETC.
  - 2.3. ALL EXPOSED AND DAMAGED REINFORCING SHALL BE CLEANED WITH A WIRE BRUSH, SAND-BLASTING, OR OTHER APPROVED METHOD UNTIL ONLY NON-DAMAGED MATERIAL REMAINS. NOTIFY THE ARCHITECT IF LESS THAN 90 PERCENT OF THE ORIGINAL BAR AREA REMAINS. THIS MAY REQUIRE NEW REINFORCING TO BE SPLICED WITH NON-DAMAGED REINFORCING.
  - 2.4. ALL REPAIR MATERIALS SHALL BE APPLIED PER MANUFACTURER'S WRITTEN SPECIFICATIONS.
  - 2.5. REPAIRED STRUCTURE SHALL MATCH PROFILE OF EXISTING UNDAMAGED STRUCTURE.
3. PARTIAL-DEPTH CONCRETE SLAB REPAIR:
- 3.1. IF SLAB REINFORCING IS EXPOSED USE FULL DEPTH REPAIR BELOW.
  - 3.2. INFILL CRACKS AND HOLES (MAX DIA = 3/8") AT TOP OF SLAB ABOVE DAMAGED AREAS WITH MULTI-PURPOSE, TWO-COMPONENT, SOLVENT-FREE, MOISTURE INSENSITIVE, STRUCTURAL EPOXY ADHESIVE AND PROTECTIVE COATING.
  - 3.3. SCRUB COAT CONCRETE SUBSTRATE AS REQUIRED PRIOR TO REPAIR PER MANUFACTURER'S RECOMMENDATIONS.
  - 3.4. HAND PATCH WITH FAST SETTING, ONE COMPONENT, READY-TO-USE REPAIR MORTAR PER MANUFACTURER'S RECOMMENDATIONS. MAXIMUM LIFT THICKNESS = 1 INCH.
4. FULL-DEPTH REPAIR OR SLAB INFILL:
- 4.1. SAWCUT EXISTING CONCRETE SLAB FULL WIDTH BETWEEN EXISTING CONCRETE JOISTS + 2" BEYOND EXTENTS OF ANY DAMAGE EACH SIDE.
  - 4.2. ROUGHEN EXISTING CONCRETE SLAB EDGE PERPENDICULAR TO JOIST SIMILAR TO SMALL HOLE REPAIR DETAIL.
  - 4.3. PROVIDE DOWELS AT 8" ON CENTER ON ALL FOUR SIDES OF OPENING USING HILTI HIT-HY 200 ADHESIVE OR EQUAL. REINFORCE SLAB AS SHOWN.
  - 4.4. SCRUB COAT CONCRETE SUBSTRATE AS REQUIRED PRIOR TO REPAIR WITH CEMENT-SAND SLURRY.
  - 4.5. PLACE FULL DEPTH 4000 PSI CONCRETE SLAB.



STRUCTURAL REPAIRS A1



**TREANORHL**  
 1811 Bellmore Ave  
 Kansas City, MO 64118  
 Office: 816.221.0900  
 Fax: 816.221.4692  
 www.treanorhl.com  
 TreanorHL, P.A. - Architect  
 Missouri Certificate of Authority # A2009030447

**KH ENGINEERING GROUP**  
 13426 West 96th St., Lenexa, KS 66215  
 www.KHEGroup.com  
 KH Engineering Group P.A. - Engineer  
 Missouri Certificate of Authority #2004020065

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE
1	Re-issued in Entirety	8/10/21

**S001**

STRUCTURAL GENERAL NOTES AND DETAILS

BID DOCUMENTS

Date: August 10, 2021

TreanorHL Project Number: HC0728-2101.00

MU Project Number: CP210701




# PLUMBING

AD	AREA DRAIN
AP	ACCESS PANEL
AW	ACID WASTE
AV	ACID VENT
BV	BALANCE VALVE
CB	CATCH BASIN
CFS	CUBIC FEET PER SECOND
CO	CLEANOUT
CHV	CHECK VALVE
CW	COLD WATER
DN	DOWN
DV	DRAIN VALVE
EX	EXISTING PIPING OR EQUIPMENT
F	FLANGE CONNECTION
FCO	FLOOR CLEANOUT
FD	FLOOR DRAIN
GA	GAUGE
GC	GAUGE COCK
HW	HOT WATER
HWC	HOT WATER CIRCULATING
L	LAVATORY
MSB	MOP SERVICE BASIN
RD	ROOF DRAIN
RI	ROUGH-IN (ONLY)
RI & C	ROUGH-IN AND CONNECT
SAN	SANITARY SEWER
SS	SERVICE SINK
ST	STORM SEWER
SV	SERVICE VALVE
TD	TRENCH DRAIN
TH	THERMOMETER
U	UNION
UR	URNAL
V	VENT
VTR	VENT THROUGH ROOF
W	WASTE
WC	WATER CLOSET

SAN	SANITARY SEWER (SOIL, WASTE) BELOW GRADE
SAN	SANITARY SEWER (SOIL, WASTE) ABOVE GRADE
ST	STORM SEWER BELOW GRADE
ST	STORM SEWER ABOVE GRADE
	SLOPE IN DIRECTION OF ARROW (SEE PLANS FOR % OF SLOPE)
V	VENT
SSD	SUBSOIL DRAIN
CW	COLD WATER
ICW	ICE COLD WATER
SCW	SOFT COLD WATER
HW	HOT WATER
HWC	HOT WATER CIRCULATING
WM	WATER MAIN (OUTSIDE OF BUILDING)
RV	RELIEF VALVE
TPV	TEMPERATURE & PRESSURE RELIEF VALVE
UP	PIPE LINE, TURN UP
DN	PIPE LINE, TURN DOWN
BV	BALANCE VALVE
CHV	CHECK VALVE
DV	DRAIN VALVE
GA	GAUGE AND GAUGE COCK
PR	PRESSURE REGULATOR
PRV	PRESSURE REDUCING VALVE
RPBP	REDUCED PRESSURE BACKFLOW PREVENTER
SV	SERVICE VALVE
TH	THERMOMETER
U	UNION
1	CONNECT TO EXISTING EQUIPMENT, SYMBOL
1	PLUMBING RISER DESIGNATION
3	DOWNSPOUT DESIGNATION
3	KEYED NOTE DESIGNATION

# MECHANICAL

AD	ACCESS DOOR
AHU	AIR HANDLING UNIT
AP	ACCESS PANEL
AV	AIR VENT
BV	BALANCE VALVE
COM	COMMON
CHWS	CHILLED WATER SUPPLY
CHWR	CHILLED WATER RETURN
CHV	CHECK VALVE
CT	COOLING TOWER
CU	CONTROL VALVE
CV	CONTROL VALVE
D	DAMPER
DN	DOWN
DP	DIFFERENTIAL PRESSURE
DR	DRAIN LINE
DV	DRAIN VALVE
EF	EXHAUST FAN
EX	EXISTING
EXH	EXHAUST
F	FLANGE CONNECTION
FC	FLEXIBLE CONNECTION
FCU	FAN COIL UNIT
FRD	FIRE RATED DAMPER
T	STEAM TRAP
G	GAS
GA	GAUGE
GC	GAUGE COCK
H	HUMIDIFIER
HWS	HEATING WATER SUPPLY
HWR	HEATING WATER RETURN
LPS	LOW PRESSURE STEAM
LPC	LOW PRESSURE CONDENSATE
MA	MAKE-UP AIR
MA	1000 BTU/HR
MC	MECHANICAL COUPLING
MXA	MIXED AIR
NC	NORMALLY CLOSED
NO	NORMALLY OPEN
OA	OUTSIDE AIR
P	PETE'S PLUG
RA	RETURN AIR
RLA	RELIEF AIR
RV	RELIEF VALVE
SA	SUPPLY AIR
SD	SMOKE DAMPER
SF	SUPPLY FAN
STR	STRAINER
SV	SERVICE VALVE
TH	THERMOMETER
TW	THERMOMETER WELL
U	UNION
UH	UNIT HEATER
UV	UNIT VENTILATOR
V	VENT
VAV	VARIABLE AIR VOLUME UNIT
CHWS	CHILLED WATER SUPPLY
CHWR	CHILLED WATER RETURN
HWS	HEATING WATER SUPPLY
HWR	HEATING WATER RETURN
LPS	LOW PRESSURE STEAM
LPC	LOW PRESSURE CONDENSATE
D	DAMPER
UP	PIPE LINE, TURNED UP
DN	PIPE LINE, TURNED DOWN
BV	BALANCE VALVE
CV	2 WAY CONTROL VALVE
CHV	CHECK VALVE
DV	DRAIN VALVE
F	FLANGE CONNECTION
GA	GAUGE AND GAUGE COCK
MC	MECHANICAL COUPLING
P	PETE'S PLUG
PFC	PIPE FLEXIBLE CONNECTOR
PR	PRESSURE REGULATOR
PRV	PRESSURE REDUCING VALVE
RV	RELIEF VALVE
SV	SERVICE VALVE
STR	STRAINER
T	STEAM TRAP
TH	THERMOMETER
TW	THERMOMETER WELL
U	UNION
U	METER
	CAP
	CONCENTRIC REDUCER
	ECCENTRIC REDUCER (BOTTOM & TOP LEVEL)
PA	PIPE ANCHOR
PG	PIPE GUIDE



# FIRE PROTECTION

F	FIRE LINE
SPR	SPRINKLER MAIN
SIV	SUPERVISED INDICATING VALVE
WFI	WATER FLOW INDICATOR
URH	UPRIGHT HEAD
PH	PENDENT HEAD
CH	CONCEALED HEAD
SWH	SIDEWALL HEAD
FEC	FIRE EXTINGUISHER CABINET
FVC	FIRE VALVE CABINET
FHC	FIRE HOSE CABINET

BIM 360/Revit/2021 MU Teaching Hospital/UMTH-2-West\_Materials\_Swamp.rvt 5/27/2021 11:32:04 AM



**TREANORHL**  
 1511 Bellvue Ave  
 Saint Louis, Missouri 63102  
 Office: 616.221.0900  
 Fax: 616.221.4692  
 www.treanorhl.com  
 TreanorHL, P.A. - Architect  
 Missouri Certificate of Authority # A2009030447


**MCCLURE ENGINEERING**  
 1000 Chestnut Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-6232  
 www.mcclureeng.com  
 McClure Engineering Corporation  
 Professional Engineering Corporation  
 Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY		08/10/2021



**M001**  
 SYMBOLS, ABBREVIATIONS, AND SCHEDULE  
 BID DOCUMENTS  
 Date: 08/10/2021  
 TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701




S:\1071625.000 UMC UMTH Renovate 2W\03 Mechanical\SWAMP\PD201.dwg 04/15/21 09:03 SUJ

BIM 360:RUC02728 MU Teaching Hospital\UMTH\2-West\_Materials\Swamp.rvt

5/27/2021 11:32:04 AM



- GENERAL NOTES**
1. ABANDONED PIPING STUBBED INTO SECOND FLOOR SHALL BE DEMOLISHED DOWN TO BELOW FLOOR AND CARPED. PATCH FLOOR TO MATCH EXISTING.
  2. ALL ABANDONED PIPING SHALL BE LABELED AS "ABANDONED IN PLACE".
- KEYED NOTES**
1. COULD NOT VERIFY EXISTING CONDITIONS. CONTRACTOR TO FIELD VERIFY CONDITIONS FOR DEMOLITION WORK.
  2. DEMOLISH EXISTING PIPING AND CAP BACK AT MAINRISERS AS INDICATED. PATCH REMAINING OPENINGS IN CHASE WALL TO MATCH EXISTING.



**TREANORHL**  
 1811 Bellvue Ave  
 Saint Louis, Missouri 63102  
 Office: 616.221.0900  
 Fax: 616.221.4692  
 www.treanorhl.com

**MCCLURE ENGINEERING**  
 1000 Chestnut Avenue  
 Saint Louis, Missouri 63102  
 T 314-645-6232  
 www.mcclureeng.com

McClure Engineering  
 Professional Engineering Corporation  
 Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE
1	RE-ISSUED IN ENTIRETY	08/10/21

**PD201**


FIRST FLOOR  
 DEMOLITION PLUMBING  
 PLAN

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number:  
 HC0728.2101.00


MU Project Number:  
 CP210701



**PARTIAL FIRST FLOOR DEMOLITION PLUMBING PLAN**  
 SCALE: 1/8"=1'-0"

S:\1071625.000 UMC UMTH Renovate 2W03 Mechanical\SWAMP\PD202.dwg 04/15/21 09:10 SJF

BIM 360:R:\C20728 MU Teaching Hospital\UMTH-2\West\_Materials\_Swamp.rvt 5/27/2021 11:32:04 AM




**PARTIAL SECOND FLOOR DEMOLITION PLUMBING PLAN**  
 SCALE: 1/8"=1'-0"

**GENERAL NOTES**

- CONTRACTOR IS RESPONSIBLE FOR MAINTAINING SERVICE ACCESS. ANY CHANGES THAT NEGATIVELY AFFECT SERVICE ACCESS SHALL BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
- CONTRACTOR SHALL COORDINATE SYSTEM SHUT DOWN WITH OWNER AND PROVIDE DRAINING AND FILLING OF ALL WATER SYSTEMS AS REQUIRED TO PERFORM WORK NOTED HEREIN.
- ALL SCOPE SHOWN IS TO BE PHASED TO MINIMIZE OUTAGE OF SERVICE TO LESS THAN 24 HOURS.
- ALL ABANDONED PIPING SHALL BE LABELED AS "ABANDONED IN PLACE".

**KEYED NOTES**

- DEMOLISH AND CAP ABANDONED PIPING STUBBED UP THROUGH FLOOR BACK TO MAIN.
- DEMOLISH AND CAP ABANDONED WASTE AND VENT PIPING BACK TO MAIN.
- DEMOLISH AND CAP ABANDONED DOMESTIC WATER SUPPLY LINES BACK TO MAIN.
- DEMOLISH AND CAP ABANDONED SANITARY PIPING BACK TO MAIN IN 1ST FLOOR CEILING SPACE BELOW.



**TREANORHL**  
 ERIC A. REUTHER  
 PROFESSIONAL ENGINEER  
 NUMBER: PE-2011015792  
 EXPIRES: 12/31/2024  
 ERIC A. REUTHER  
 STATE LIC. 2011015792

**MCCLEURE ENGINEERING**  
 1000 Clark Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-6232  
 www.mccleure.com

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**  
 FITOUT SPACE 2W  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212

REVISIONS

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY		08/10/21


**PD202**

SECOND FLOOR DEMOLITION PLUMBING PLAN  
 BID DOCUMENTS


Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701


S:\071625.000 UMC UMTH Renovate 2W\03 Mechanical\SWAMP\MD201.dwg 04/15/21 09:08 SJF



**PARTIAL FIRST FLOOR HVAC DEMOLITION PLAN**  
SCALE: 1/8"=1'-0"




**PARTIAL SECOND FLOOR TEMPORARY HVAC PLAN**  
SCALE: 1/8"=1'-0"



**PARTIAL SECOND FLOOR DEMOLITION HVAC PLAN**  
SCALE: 1/8"=1'-0"

- GENERAL NOTES**
- CONTRACTOR IS RESPONSIBLE FOR MAINTAINING SERVICE ACCESS. ANY CHANGES THAT NEGATIVELY AFFECT SERVICE ACCESS SHALL BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
  - CONTRACTOR SHALL COORDINATE SYSTEM SHUT DOWN WITH OWNER AND PROVIDE DRAINING AND FILLING OF ALL HYDRONIC SYSTEMS AS REQUIRED TO PERFORM WORK NOTED HEREIN.
  - ALL SCOPE SHOWN IS TO BE PHASED TO MINIMIZE OUTAGE OF SERVICE TO LESS THAN 24 HOURS.
  - PRIOR TO BEGINNING DEMOLITION, CONTACT THE OWNER REPRESENTATIVE CONCERNING REMOVAL OF EXISTING CONTROLLERS AND ZONE TEMPERATURE SENSORS SO THEY ARE NOT DAMAGED. RETURN CONTROLLER AND SENSOR TO OWNER IN NOT BEING REUSED. RECONNECT THE EXISTING NETWORK BUS WIRING SO COMMUNICATIONS IS MAINTAINED DURING DEMOLITION AND CONSTRUCTION. CONTACT THE OWNER REPRESENTATIVE CONCERNING THE BUS ROUTING. SPLICING OF WIRES IS NOT ALLOWED. PULL NEW WIRES IF EXISTING WIRES ARE TOO SHORT.
- KEY NOTES**
- DEMOLISH ABANDONED PNEUMATIC TUBE.
  - DEMOLISH EXISTING DUCTWORK AS INDICATED.
  - DEMOLISH EXISTING VAV, ASSOCIATED AIR DEVICES, AND DUCTWORK, HEATING WATER PIPING, AND DRAIN PIPING AND CAP AT SERVICE VALVES.
  - DEMOLISH EXISTING AIR DEVICES AS INDICATED.
  - PROVIDE TEMPORARY FLEX CONNECTIONS AND CAPS ON SUPPLY AND RETURN DUCT TO KEEP AHU-28 LIVE DOWN TO 1ST FLOOR DURING CONSTRUCTION. SUPPORT FLEX DUCT OVERHEAD.
  - DEMOLISH AIR DEVICES AND FLEX DUCTWORK SERVING FORMER OFFICE AREAS ASSOCIATED WITH V2-212. CAP AT SUPPLY DUCTWORK AND SEAL AND INSULATE SUPPLY DUCT.
  - DEMOLISH ABANDONED SUPPLY AIR DUCTWORK AND ASSOCIATED AIR DEVICE. CAP AT RISER.
  - DEMOLISH AND ABANDONED DUCTWORK WHILE LEAVING HORIZONTAL STUBS AND TO ALLOW TEMPORARY FLEX DUCT CONNECTION. RELOCATE EXISTING SMOKE DETECTOR TO REMAINING SECTION OF DUCT.
  - DEMOLISH AND PROTECT EXISTING LIFE SAFETY DAMPERS FOR RE-INSTALLATION.
  - DEMOLISH EXISTING DUCTWORK BELOW ASSOCIATED FLOOR/CEILING PENETRATION. CAP IN 1ST FLOOR CEILING SPACE. PATCH REMAINING HOLE TO MATCH EXISTING OR NEW CONSTRUCTION AS NEEDED.
  - REMOVE THERMOSTAT AND RE-INSTALL IN NEW LOCATION SHOWN ON M-302 BEFORE DEMOLITION WORK IS PERFORMED.
  - DEMOLISH EXHAUST DUCT TO ALLOW FOR NEW SUPPLY AIR DUCT TO BE ROUTED. CAP AND SEAL EXHAUST DUCT AT CEILING LEVEL.
  - DEMOLISH AND CAP EXISTING DUCTWORK FROM RISER IN CHASE TO EXISTING CONTROL DAMPERS AS INDICATED. LABEL REMAINING HORIZONTAL DUCTWORK AS "ABANDONED". PATCH CHASE WALL TO MATCH EXISTING.
  - PRE-READ AIRFLOW IN EXISTING EXHAUST DUCTWORK BEFORE ANY DEMOLITION TO THE SYSTEM IS PERFORMED. REPORT PRE-READ VALUES TO ENGINEER.
  - DEMOLISH THROUGH WALL. PATCH WALL TO MATCH EXISTING.
  - DEMOLISH AND CAP AT MAINS.
  - PROVIDE TEMPORARY FLEX CONNECTIONS AND CAPS ON SUPPLY DUCT TO KEEP PHARMACY AREA LIVE DURING CONSTRUCTION. SUPPORT FLEX DUCT OVERHEAD.
  - PROVIDE TEMPORARY FLEX CONNECTIONS AND CAPS ON EXHAUST DUCT TO KEEP EXISTING EF-18 LIVE UP TO ROOF DURING CONSTRUCTION. SUPPORT FLEX DUCT OVERHEAD.
  - LABEL EQUIPMENT AS ABANDONED IN PLACE. SHUT CLOSE ALL VALVES, CONNECTING TO THE DEVICES.
  - DEMOLISH AND TEMPORARILY CAP SECTION OF EXISTING HEATING WATER PIPING SHOWN IN ORDER TO ACCOMMODATE NEW RETURN AIR MAIN DUCT. SEE NEW WORK PLAN FOR NEW HEATING WATER PIPE ROUTING.



**TREANORHL**  
1811 Bellvue Ave.  
Saint Louis, Missouri 63102  
Office: 616.221.0900  
Fax: 616.221.4692  
www.treanorhl.com

Eric A. Reuther  
Architect  
TreanorHL, P.A.  
Missouri State Certificate of Authority # A200903047

---

**MCCLURE ENGINEERING**  
1000 Clair Avenue  
Saint Louis, Missouri 63102  
T 314-646-6522  
www.mcclureeng.com

McClure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000897

---

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212

---

REVISIONS		
NO	DESCRIPTION	DATE

---

**MD302**

SECOND FLOOR  
DEMOLITION HVAC PLAN


BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728-2101.00  
MU Project Number: CP210701

S:\1071625.000 UMC UMTH Renovate 2W-03 Mechanical\SWAMP\IP201.dwg 04/15/21 09:07 SJF

BIM 360:RVT0728 MU Teaching Hospital\UMTH-2\West\_Materials\_Swamp.rvt



**PARTIAL FIRST FLOOR PLUMBING PLAN**  
 SCALE: 1/8"=1'-0"

- GENERAL NOTES**
- FIELD VERIFICATION NEEDED FOR FIRST FLOOR PLUMBING NEW WORK SCOPE. ABANDONED PIPING STUBBED INTO SECOND FLOOR SHALL BE DEMOLISHED BACK TO MAINS.
  - CONTRACTOR IS RESPONSIBLE FOR MAINTAINING SERVICE ACCESS. ANY CHANGES THAT NEGATIVELY AFFECT SERVICE ACCESS SHALL BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
  - CONTRACTOR SHALL COORDINATE SYSTEM SHUT DOWN WITH OWNER AND PROVIDE DRAINING AND FILLING OF ALL WATER SYSTEMS AS REQUIRED TO PERFORM WORK NOTED HEREIN.
  - ALL SCOPE SHOWN IS TO BE PHASED TO MINIMIZE OUTAGE OF SERVICE TO LESS THAN 24 HOURS.
- KEYED NOTES**
- CONNECT NEW 4" WASTE INTO EXISTING WASTE RISER AS INDICATED.
  - CONNECT NEW 2" WASTE AND 2" VENT INTO EXISTING RISERS AS INDICATED.
  - FIELD VERIFY EXISTING HORIZONTAL WASTE AND VENT PIPING SIZES. CONNECT NEW 3" WASTE AND 2" VENT INTO EXISTING HORIZONTAL PIPING OR NEAREST VERTICAL RISERS IF HORIZONTAL PIPING ISN'T SUITABLE.



**KEY PLAN**

**TREANORHL**  
 ERIC A. REUTHER  
 PROFESSIONAL ENGINEER  
 NUMBER: PE-2011015792  
 EXPIRES: 12/31/2024  
 ERIC A. REUTHER  
 STATE LIC. 2011015792

**MCCLURE ENGINEERING**  
 1000 Clark Avenue  
 Saint Louis, Missouri 63102  
 T 314-646-6232  
 www.mcclureeng.com

**PROGRESS PRINT**  
 05/27/2021

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**RENOVATE 2W - DIALYSIS UNIT**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS

NO	DESCRIPTION	DATE
1	ADDENDUM #1	06/24/21

**P201**  
 FIRST FLOOR PLUMBING PLAN  
 SCHEMATIC DESIGN  
 Date: 05/27/2021  
 TreanorHL Project Number: HC0728.2102.00  
 MU Project Number: CP210702


S:\071625.000 UMC UMTH Renovate 2W\03 Mechanical\SWAMP\IP202.dwg 04/15/21 09:15 SJF

BIM 360:R:\C\0728 MU Teaching Hospital\UMTH\2 West\_Materials\_Swamp.rvt 5/27/2021 11:32:04 AM



**PARTIAL SECOND FLOOR PLUMBING PLAN**  
SCALE: 1/8"=1'-0"

- GENERAL NOTES**
- CONTRACTOR IS RESPONSIBLE FOR MAINTAINING SERVICE ACCESS. ANY CHANGES THAT NEGATIVELY AFFECT SERVICE ACCESS SHALL BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
  - CONTRACTOR SHALL COORDINATE SYSTEM SHUT DOWN WITH OWNER AND PROVIDE DRAINING AND FILLING OF ALL WATER SYSTEMS AS REQUIRED TO PERFORM WORK NOTED HEREIN.
  - ALL SCOPE SHOWN IS TO BE PHASED TO MINIMIZE OUTAGE OF SERVICE TO LESS THAN 24 HOURS.
- KEYED NOTES**
- TAP EXISTING DOMESTIC 1-1/2" COLD AND 1" HOT WATER RISERS WITH VALVES AND ROUTE NEW 1" COLD AND 3/4" HOT WATER PIPING AS INDICATED.
  - FURNISH AND INSTALL NEW PLUMBING FIXTURES AND ROUTE VENT AND DOMESTIC COLD AND HOT WATER AS INDICATED.
  - CONNECT NEW 2" VENT PIPING INTO EXISTING VENT RISER AS INDICATED.
  - PROVIDE WATER HAMMER ARRESTORS AT HOT AND COLD CONNECTIONS TO FAUCETS AND FLUSH VALVES. REFER TO SPECIFICATION SECTION 22 80 01.
  - ROUTE HARD PIPED COLD WATER CONNECTION UNDER THE COUNTER AND PROVIDE WITH CHROME VALVE AND A FILTER BEFORE CONNECTING TO THE ICE MAKER. PROVIDE HUB DRAIN FOR ICE MAKER AND ROUTE DRAIN TO THE INTO SINK WASTE. REFER TO COUNTER/ICE MAKER DRAIN DETAIL ON M601.
  - CONTINUE EXISTING COLD WATER PIPING AS INDICATED.



ERIC A. REUTHER  
STATE LIC. 2011015792

**TREANORHL**

1811 Bellflower Ave.  
Saint Louis, Missouri 63102  
T 314-645-6522  
www.treanorhl.com

Eric A. Reuther  
Professional Engineer  
Missouri State Certificate of Authority # AZ00903047

**MCCURE ENGINEERING**

1000 Clair Avenue  
Saint Louis, Missouri 63102  
T 314-645-6522  
www.mccureeng.com

McClure Engineering  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000897

UNIVERSITY OF MISSOURI TEACHING HOSPITAL

**FITOUT SPACE 2W**

1 HOSPITAL DRIVE, COLUMBIA, MO 65212

REVISIONS		
NO	DESCRIPTION	DATE
RE-1	ISSUED IN ENTIRETY	08/10/21

**P202**

SECOND FLOOR PLUMBING PLAN

BID DOCUMENTS


Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00

MU Project Number: CP210701

S:\1071625.000 UMC UMTH Renovate 2W\03 Mechanical\Sheets - Phase 1 - SWAMP\M302 - 071625.000.dwg 05/27/21 22:50 Dschreier

BIM 360:R-C-0728 MU Teaching Hospital\UMTH\2-West\_Materials\Swamp.rvt  
5/27/2021 11:32:04 AM



- GENERAL NOTES**
- CONTRACTOR IS RESPONSIBLE FOR MAINTAINING SERVICE ACCESS. ANY CHANGES THAT NEGATIVELY AFFECT SERVICE ACCESS SHALL BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
  - CONTRACTOR SHALL COORDINATE SYSTEM SHUT DOWN WITH OWNER AND PROVIDE DRAINING AND FILLING OF ALL HYDRONIC SYSTEMS AS REQUIRED TO PERFORM WORK NOTED HEREIN.
  - ALL SCOPE SHOWN IS TO BE PHASED TO MINIMIZE OUTAGE OF SERVICE TO LESS THAN 24 HOURS.
  - TEST AND BALANCE CONTRACTOR SHALL PERFORM A BLOWER DOOR TEST AFTER WALLS ARE CONSTRUCTED AND SEALED. WORK SHALL BE PERFORMED PRIOR TO INSTALLATION OF CEILING.
  - BALANCE DAMPER TO BE INSTALLED AT ALL DIFFUSER AND GRILLE TAKE-OFFS.
- KEYED NOTES**
- TRANSITION TO RETURN, ROUTE UP INTO BEAM POCKET AT 45 ANGLE. ROUTE ABOVE EXISTING UTILITIES, DROP DOWN AND TRANSITION TO RECONNECT TO EXISTING EXHAUST DUCT.
  - TRANSITION V2-212 DUCTWORK TO ROUND FOR CORRIDOR AIR DEVICE CONNECTION.
  - ROUTE 18x18 RETURN DUCT IN BEAM POCKET ABOVE SUPPLY AIR DUCTWORK.
  - SLOPE RETURN DUCTWORK OVERDERS SUPPLY DUCTWORK.
  - SET V2-212 TO 350 CFM CONSTANT VOLUME IN BAS.
  - RE-LABEL EXISTING VAV 28-204 TO VAV 28-209. CHANGE NAME TO V-28-209 IN BAS.
  - INSTALL NEW BUILT-UP RETURN AIR VAV UNIT FOR FIRST FLOOR RETURN AIR SERVICE. INSTALL NEW FLOW STATION IN VERTICAL RETURN AIR DUCTWORK FROM 1ST FLOOR. INSTALL AT ACCESSIBLE HEIGHT. PROVIDE AND INSTALL ACCESS DOORS TO ALLOW COMPLETE SERVICE AND REMOVAL OF FLOW STATION AND CONTROL DAMPER. COORDINATE WITH CARPENTRY AND DRYWALL CONTRACTORS.
  - INSTALL NEW CONTROL DAMPER IN VERTICAL SECTION OF 36x16 DUCTWORK AT ACCESSIBLE HEIGHT WITH ACCESS DOORS. COORDINATE ACCESS DOORS WITH OTHER TRADES. INSTALL CONTROL DAMPER DOWNSTREAM OF AIRFLOW MEASURING STATION.
  - INSTALL NEW THERMOSTAT FOR EXISTING TERMINAL BOX V2-212.
  - PROVIDE VAV BOX (SUPPLY AND RETURN) AND DUCTS AS ILLUSTRATED ON PLANS TO BACKFEED EXISTING DUCTWORK. CONNECT RETURN VAV IN TO RETURN MAIN AND ROUTE BACK TO NEW SYSTEMS. CONNECT SUPPLY MAIN INTO EXISTING MAIN AND ROUTE BACK TO NEW SYSTEM.
  - ADD BALANCE DAMPER TO EXISTING EXHAUST DUCTWORK.
  - RE-INSTALL LIFE SAFETY DAMPERS IN RAISED DUCT LOCATION.
  - INSTALL NEW BALANCE DAMPER IN EXISTING RETURN DUCTWORK.
  - RE-LABEL EXISTING VAV 28-202 TO VAV 28-205. CHANGE NAME TO V-28-205 IN BAS.
  - NEW STRAIGHT 4" CHILLED WATER SUPPLY AND RETURN PIPING INSTALLED TO REPLACE DEMOLISHED TAPS.
  - ROUTE NEW 2" HEATING WATER SUPPLY AND RETURN PIPING TO AVOID NEW RETURN AIR DUCT OFFSET. CONNECT TO EXISTING 2" HEATING WATER PIPING MAINS.
  - ROUTE NEW 3/4" HEATING WATER SUPPLY AND RETURN PIPING WITH VALVES TO EXISTING HEATING WATER PIPING SERVING EXISTING VAV 28-205. ENSURE NEW VALVES ARE AS CLOSE TO MAINS AS POSSIBLE WHILE MAINTAINING ACCESS.

ERIC A. REUTHER  
STATE LIC. 2011015792

**TREANORHL**

151 Bellmore Ave.  
St. Louis, MO 63102  
Office: 616.221.0900  
Fax: 616.221.4692  
www.treanorhl.com

TreanorHL, P.A. - Architect  
Missouri Certificate of Authority # A2009030447

**MCCLURE ENGINEERING**

1000 Clair Avenue  
St. Louis, Missouri 63102  
T 314-646-6232  
www.mcclureeng.com

McClure Engineering  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL

**FITOUT SPACE 2W**

1 HOSPITAL DRIVE, COLUMBIA, MO 65212

REVISIONS		
NO	DESCRIPTION	DATE
1	RE-ISSUED IN ENTIRETY	08/10/21

**M302**


SECOND FLOOR  
HVAC PLAN


BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number:  
HC0728.2101.00

MU Project Number:  
CP210701





**KEYED NOTES**

- 1 RENAME EXISTING VAV.



ERIC A. REUTHER  
STATE LIC. 2011015792

**TREANORHL**

1511 S. Brentwood Ave.  
St. Louis, MO 63108  
Office: 616.221.0900  
Fax: 616.221.4692  
www.treanorhl.com

**MCCURE ENGINEERING**

1000 Chestnut Avenue  
St. Louis, Missouri 63102  
T 314-645-6232  
www.mccureeng.com

UNIVERSITY OF MISSOURI TEACHING HOSPITAL

**FITOUT SPACE 2W**

1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY		08/10/2021

**M501**


AIRFLOW DIAGRAM

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00


MU Project Number: CP210701



**KEY PLAN**

5/27/2021 11:32:04 AM BIM\_360\_RHC0728 MU Teaching Hospital/UMTH-2-West\_Materials\_Swamp.rvt





BIM 360-PC-0728 MU Teaching Hospital/UMH-2-West\_Materials\_Swamp.rvt  
5/27/2021 11:32:04 AM



**TREANORHL**  
1511 S. Brentwood Ave.  
St. Louis, MO 63104  
Office: 616.221.0900  
Fax: 616.221.4692  
www.treanorhl.com  
Eric A. Reuther, P.E., Architect  
Missouri Certificate of Authority # A2009030447

**MCCLURE ENGINEERING**  
1000 Clark Avenue  
Saint Louis, Missouri 63102  
T 314-645-6232  
www.mcclureeng.com  
McClure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #00087


UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS

NO	DESCRIPTION	DATE
RE-1	ISSUED IN ENTIRETY	08/10/2021


**M502**  
MECHANICAL WATER FLOW DIAGRAM  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728-2101-00  
MU Project Number: CP210701




BIM 360/2021 11:52:04 AM




FILE NAME: M-0022A  
SCALE: NONE  
**PIPE HANGER SUPPORT WITH INSERT**




FILE NAME: M-0009A  
SCALE: NONE  
**LAY-IN DIFFUSER/GRILLE INSTALLATION**




FILE NAME: M-0006B  
SCALE: NONE  
**DUCTWORK BRANCH RECTANGULAR 90° ELBOWS**




FILE NAME: -  
SCALE: NONE  
**COUNTERTOP ICE MAKER DRAIN DETAIL**



FILE NAME: M-0025A  
SCALE: NONE  
**45 DEGREE TAKE-OFF (RECTANGULAR DUCT MAIN)**



FILE NAME: M-0025B  
SCALE: NONE  
**SADDLE TAKE-OFF (ROUND DUCT MAIN)**



**VARIABLE AIR VOLUME UNIT SCHEDULE**

UNIT DESIG.	AHU NO.	AREA SERVED	MANUFACTURER & MODEL NO.	INLET SIZE (IN.)	DESIGN FLOW CONDITIONS			MAX. APD (N. W.C.)	MIN. CAPACITY (MBH)	EAT (°F)	LAT (°F)	EWT (°F)	MAX. FLOW (GPM)	MAX. WPD (FT.)	MIN. ROWS	ROOM TEMP. SENSOR TYPE	NOTES
					COOLING MAX. FLOW (CFM)	HEATING MAX. FLOW (CFM)	VAV MIN. FLOW (CFM)										
VAV-28-201	28	2W22 IM TEAM D	TITUS DESV	6	300	250	250	0.5	8	55	80	140/180	0.8	5	2	T1	1, 2
VAV-28-202	28	2W23 CONFERENCE	TITUS DESV	6	350	250	250	0.5	8	55	80	140/180	0.8	5	2	T1	1, 2
VAV-28-203	28	2W24 IM TEAM C & 2W25 IM TEAM B	TITUS DESV	10	800	500	500	0.5	14	55	80	140/180	1.3	5	2	T1	1, 2
VAV-28-204	28	2W26 IM TEAM A & 2W27 BREAK	TITUS DESV	10	875	500	500	0.5	14	55	80	140/180	1.3	5	2	T1	1, 2
VAV-28-205	28	SHELL SPACE 2W34	EXISTING	-	2600	2600	2000	-	-	-	-	-	-	-	-	-	4
VAV-28-206	28	MICROBIOLOGY 2W39	TITUS DESV	14	1800	1800	350	0.5	49	55	80	140/180	4.2	5	2	T1	1, 2
VAV-28-209	28	FUTURE DIALYSIS AREA 2W09	EXISTING	-	1200	600	600	-	-	-	-	-	-	-	-	-	4
V2-212	2	2W06 BIO-HAZARD STORAGE & BREAK	EXISTING	-	500	500	500	-	-	-	-	-	-	-	-	-	4
RVAV-28-201	28	IM TEAMS, BREAK	ACCUTROL ACCUVALVE AVT4000	12x18	1625	1050	1050	0.2	-	-	-	-	-	-	-	-	-
RVAV-28-202	28	CONFERENCE	ACCUTROL ACCUVALVE AVT4000	8	250	150	150	0.2	-	-	-	-	-	-	-	-	-
RVAV-28-205	28	SHELL SPACE 2W34	ACCUTROL ACCUVALVE AVT4000	24x12	2600	2600	2000	0.2	-	-	-	-	-	-	-	-	-
RVAV-28-206	28	MICROBIOLOGY 2W39	ACCUTROL ACCUVALVE AVT4000	14	1400	1400	350	0.2	-	-	-	-	-	-	-	-	-
RVAV-28-209	28	FUTURE DIALYSIS AREA 2W09	ACCUTROL ACCUVALVE AVT4000	12	1200	600	600	0.2	-	-	-	-	-	-	-	-	-
RVAV-28-199	28	1ST FLOOR PLENUM RETURN	BUILT-UP - SEE CD/AFMS SCHEDULES	-	3500	N/A	N/A	-	-	-	-	-	-	-	-	-	6

GENERAL NOTES:  
1. SEE SPECIFICATION FOR ROOM TEMPERATURE SENSOR TYPE.  
2. MAXIMUM AIR PRESSURE DROP IS FOR THE ENTIRE ASSEMBLY.  
3. VAV USED ONLY IF AHU-28 IS OUT OF SERVICE.  
4. UPDATE EXISTING BOX NAME AND AIRFLOWS IN BAS. UPDATE BOX TAG TO NEW NAME.  
5. INSTALL COMBINATION TEMPERATURE/HUMIDITY SENSOR  
6. SHOWN FOR REFERENCE ONLY. BUILT UP RETURN SHALL TRACK EXISTING VAV SETPOINTS.

**CONTROL DAMPER SCHEDULE**

UNIT DESIGNATION	LOCATION	SERVICE	MANUFACTURER & MODEL NO.	NOMINAL SIZE (W X H) (IN.)	AIRFLOW (CFM)	TYPE	BLADE TYPE	MOUNTING	ACTUATOR		POWER (24V/120V)	NOTES
									TYPE	ACTION		
CD-28-199	AHU-2 RETURN DUCT	1ST FLOOR PLENUM RETURN	GREENHECK VCD-33	36X14	3,500	OPPOSED	AIRFOIL	DUCT	PROPORTIONAL	NONE	24	1,2

NOTES:  
1. BUILT UP RVAV-28-199  
2. NOTE ON BAS "LOCATED ON 2ND FLOOR"

BLADE TYPE: AIRFOIL, NON-AIRFOIL  
DAMPER TYPE: PARALLEL, OPPOSED  
ACTUATOR TYPE: PROPORTIONAL, TWO-POSITION  
ACTION: NO - NORMALLY OPEN, NC - NORMALLY CLOSED, NONE

**AIR DEVICE SCHEDULE**

UNIT DESIGNATION	SERVICE	MANUFACTURER & MODEL NO.	TYPE	NECK SIZE (IN.)	CFM RANGE	FACE SIZE (IN.)	THROW	FINISH	NOTES
A	SUPPLY	TITUS TDC	LAY-IN	8"	100-200	24"x24"	4-WAY	WHITE	3
B	SUPPLY	TITUS TDC	LAY-IN	10"	210-400	24"x24"	4-WAY	WHITE	3
C	SUPPLY	TITUS 33RL	SURFACE	16"x12"	0-1100	18"x14"	-	SEE PLANS	WHITE
D	RETURN	TITUS PAS	LAY-IN	10"	210-400	24"x24"	-	WHITE	3
E	RETURN	TITUS PAS	LAY-IN	12"	410-500	24"x24"	-	WHITE	3
F	EXHAUST	TITUS PAS	LAY-IN	8"	0-250	24"x24"	-	WHITE	3
G	EXHAUST	TITUS 33RL	SURFACE	6"x6"	0-100	6"x6"	-	SEE PLANS	WHITE
H	TRANSFER	TITUS TDC	LAY-IN	8"	-	24"x24"	-	WHITE	4
J	SUPPLY	TITUS 33RL	SURFACE	12"x12"	0-500	14"x14"	-	SEE PLANS	WHITE
K	SUPPLY	TITUS 33RL	SURFACE	36"x12"	0-1300	36"x14"	-	SEE PLANS	WHITE

NOTES:  
1. DIFFUSER IN E.V.S. 2W32 SHALL BE ALUMINUM  
2. PROVIDE BORDER FOR DRYWALL INSTALLATION  
3. PROVIDE BORDER FOR LAY-IN INSTALLATION  
4. INSTALL ON BOTH SIDES OF WALL FOR TRANSFER OPENING

**AIRFLOW MEASURING STATION SCHEDULE**

UNIT DESIG.	AHU NO.	AREA SERVED	MANUFACTURER & MODEL NO.	DUCT SIZE (IN x IN)	AIRFLOW	# PROBES	SENSORS PER PROBE	NOTES
AFS-28-199	28	1ST FLOOR RETURN PLENUM	ACCUTROL VTD21-23-36-00 BD	36 x 14	3500	2	3	1,2

NOTES:  
1. BUILT UP RVAV-28-199  
2. NOTE ON BAS "LOCATED ON 2ND FLOOR"

ERIC A. REUTHER  
STATE LIC. 2011015792

**TREANORHL**  
1511 Bellvue Ave.  
St. Louis, MO 63104  
Office: 616.221.0900  
Fax: 616.221.4692  
www.treanorhl.com

TreanorHL, P.A. - Architect  
Missouri Certificate of Authority # AZ009030447

**MCCLURE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T 314-646-6322  
www.mcclureeng.com

McClure Engineering Corporation  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000697

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212

**M601**

SCHEDULES, DETAILS, AND SEQUENCE OF OPERATIONS

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701

**KEY PLAN**

**SUPPLY AIR VARIABLE VOLUME TERMINAL UNIT SEQUENCE OF OPERATION**

- A. **DAMPER OPERATION:** THE SUPPLY TERMINAL UNITS SHALL DELIVER AIRFLOW AS REQUIRED BY VARYING DAMPER POSITION TO MEET A FLOW SETPOINT OUTLINED IN THE MECHANICAL SCHEDULE.
- B. **REHEAT VALVE OPERATION:** IF ZONE TEMPERATURE IS BELOW SETPOINT, THE REHEAT COIL VALVE SHALL MODULATE OPEN. THE REVERSE SHALL OCCUR AS ZONE TEMPERATURE INCREASES ABOVE SETPOINT.
- C. **ZONE TEMPERATURE CONTROL:** EACH INDIVIDUAL ZONE SHALL HAVE A BASE TEMPERATURE SETPOINT OF 72°F (USER ADJUSTABLE), UNLESS OTHERWISE SPECIFIED. FOR ZONE DETERMINED TO HAVE ADJUSTABLE CONTROL, AN OCCUPANT-CONTROLLED PUSH BUTTON SHALL ADJUST THE BASE TEMPERATURE SETPOINT BY NO MORE THAN ±3°F.
- D. **ZONE HUMIDITY SAFETY:** ANY SPACE WITH A ZONE HUMIDITY SENSOR SHALL BE PROGRAMMED WITH A SAFETY WHICH PREVENTS THE SPACE FROM GOING ABOVE 60% RH. IF THE SPACE RELATIVE HUMIDITY RISES ABOVE 58%, THE SPACE TEMPERATURE SETPOINT SHALL BE INCREMENTALLY RESET UP TO 75°F IN ORDER TO PREVENT THE HUMIDITY FROM GOING TOO HIGH. AN ALARM SHALL BE TRIGGERED IN THIS EVENT TO THE BAS WORKSTATION. THE ALARM WILL REQUIRE AN OPERATOR OVERRIDE TO CLEAR AND ALLOW THE SPACE TO CONTROL TO USER-SELECTED SETPOINT.

**RETURN AIR VARIABLE VOLUME TERMINAL UNIT (TRACKING) SEQUENCE OF OPERATION**


- A. **DAMPER OPERATION:** THE RETURN TERMINAL UNITS SHALL RETURN AIRFLOW AS REQUIRED MATCH THE ACTUAL SUPPLY AIRFLOW OF THE TERMINAL UNITS THAT THEY ARE TRACKING (AS SHOWN ON THE FLOW DIAGRAM). EXHAUST OR OTHER NON-RETURNED AIRFLOW SHALL BE OFFSET TO THE CALCULATION TO MAINTAIN THE PRESSURIZATION REQUIREMENTS OF THE ZONES. THE UNITS SHALL TRACK AS FOLLOWS:

- RVAV-28-201 = VAV-28-201 + VAV-28-203 + VAV-28-204 - 300
- RVAV-28-202 = VAV-28-202 - 100
- RVAV-28-205 = VAV-28-205
- RVAV-28-206 = VAV-28-206 - 400 CFM
- RVAV-28-209 = VAV-28-209

**AIRFLOW STATION UNIT (TRACKING) SEQUENCE OF OPERATION**

- B. **DAMPER OPERATION:** THE AIRFLOW STATION SHALL MONITOR RETURN AIRFLOW AND CONTROL THE ASSOCIATED DAMPER REQUIRED TO MATCH THE ACTUAL SUPPLY AIRFLOW OF THE TERMINAL UNITS THAT THEY ARE TRACKING (AS SHOWN ON THE FLOW DIAGRAM). EXHAUST OR OTHER NON-RETURNED AIRFLOW SHALL BE OFFSET TO THE CALCULATION TO MAINTAIN THE PRESSURIZATION REQUIREMENTS OF THE ZONES. THE UNITS SHALL TRACK AS FOLLOWS:


- CD-28-1 = VAV-28-101 + VAV-28-103 + VAV-28-105 + VAV-28-107 + VAV-28-108 + VAV-28-110 + VAV-28-113 + VAV-28-114 + VAV-28-115 - 1675 CFM



**NOTES:**

1. FC BUS TO BE CONTINUOUS DAISY CHAIN WITHOUT SPLICES. CONNECTIONS CAN ONLY BE MADE AT CONTROLLERS. SEE PLANS FOR QUANTITY AND LOCATIONS OF VMA CONTROLLERS.
2. BREAK BUS BETWEEN TWO EXISTING CONNECTED VAV CONTROLLERS AND REROUTE AS SHOWN. BUS CAN BE REROUTED IN MULTIPLE LOCATIONS TO KEEP OVERALL BUS LENGTH SHORT. COORDINATE FC BUS ROUTING AND OUTAGES WITH OWNERS REP.
3. FC COMMUNICATION BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 3 CONDUCTOR, WITH BLUE OUTER CASING, DESCRIBED AS 22-03 OAS STR PLNM NEON BLU JK DISTRIBUTED BY WINDY CITY WIRE, CONSTRUCTED BY CABLE-TEK, OR APPROVED EQUIVALENT.

**FC BUS SCHEMATIC DIAGRAM**  
NO SCALE




**VAV BOX CONTROL DIAGRAM WITH REHEAT AND EXHAUST**  
NO SCALE

**NOTES:**

1. VMA TERMINAL INCLUDES CONSTANT VOLUME (CV) UNITS & VARIABLE AIR VOLUME (VAV) UNITS. UNLESS OTHERWISE NOTED, ALL CONTROL WORK SHALL BE BY CONTRACTOR.
2. CAPS FOR VAV DP TEST PORTS MUST BE 1/4" BRASS PLUGS.

**KEYED NOTES:**

1. CONTROLLER WILL BE FURNISHED BY OWNER. CONTROLLER WILL BE JCI MODEL MS-VMA-16XX SERIES. PROGRAMMING WILL BE DONE BY OWNER.
2. NETWORK SENSOR WILL BE FURNISHED BY OWNER & INSTALLED BY CONTRACTOR. NETWORK SENSOR WILL BE JCI NS SERIES.
3. FC COMMUNICATION BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 3 CONDUCTOR, WITH BLUE OUTER CASING, DESCRIBED AS 22-03 OAS STR PLNM NEON BLU JK DISTRIBUTED BY WINDY CITY WIRE CONSTRUCTED BY CABLE-TEK, OR APPROVED EQUIVALENT.
4. INSTALLATION OF OCC SENSOR IS WORK OF DIVISION 26. SEE E-SERIES SHEETS FOR FINAL LOCATIONS. A CONTROL CIRCUIT SHALL BE CONNECTED TO ALL OCC SENSORS AS WORK OF DIVISION 23. A CONTROL SIGNAL SHALL BE RELAYED TO THE VAV TERMINAL UNIT THAT SERVES THAT SPACE. IN LOCATIONS WHERE MULTIPLE OCC SENSORS ARE PRESENT, ALL SENSORS SHALL BE MONITORED AND TRANSMIT A SIGNAL TO THE VAV TERMINAL UNIT WITHIN THAT SPACE. ALL SENSORS SHALL BE WIRED IN PARALLEL.
5. CONTROLLER MUST HAVE A MINIMUM OF 18 INCHES OF ACCESSIBLE CLEARANCE.
6. VAV SUPPLY TEMP SENSOR 1000 OHM PLATINUM RTD LOCATED APPROX. 8 FT. FROM VAV BOX DISCHARGE. PROVIDED, INSTALLED, & WIRED TO CONTROLLER BY CONTRACTOR.
7. FUSE LOCATED WITHIN 2 FEET OF VMA CONTROLLER.
8. LOW VOLTAGE WIRE BY DIVISION 23. SEE ELECTRICAL DRAWINGS FOR SOURCE.
9. VALVE WITH PROPORTIONAL 0-10 VOLT ACTUATOR OR EQUIVALENT.
10. SA BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 4 CONDUCTOR.
11. FACTORY SUPPLIED ELECTRIC ACTUATOR. CONNECT DIRECTLY TO VMA CONTROLLER.
12. FACTORY SUPPLIED FLOW CONTROLLER. CONNECT FLOW AO TO VMA CONTROLLER




**CUSTOM BUILT-UP VAV (AFMS/CD)**  
NO SCALE

**NOTES:**

1. VMA TERMINAL INCLUDES CONSTANT VOLUME (CV) UNITS & VARIABLE AIR VOLUME (VAV) UNITS. UNLESS OTHERWISE NOTED, ALL CONTROL WORK SHALL BE BY CONTRACTOR.
2. CAPS FOR VAV DP TEST PORTS MUST BE 1/4" BRASS PLUGS.

**KEYED NOTES:**

1. CONTROLLER WILL BE FURNISHED BY OWNER. CONTROLLER WILL BE JCI MODEL MS-VMA-16XX SERIES. PROGRAMMING WILL BE DONE BY OWNER.
2. FC COMMUNICATION BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 3 CONDUCTOR, WITH BLUE OUTER CASING, DESCRIBED AS 22-03 OAS STR PLNM NEON BLU JK DISTRIBUTED BY WINDY CITY WIRE CONSTRUCTED BY CABLE-TEK, OR APPROVED EQUIVALENT.
3. CONTROLLER MUST HAVE A MINIMUM OF 18 INCHES OF ACCESSIBLE CLEARANCE.
4. FUSE LOCATED WITHIN 2 FEET OF VMA CONTROLLER.
5. LOW VOLTAGE WIRE BY DIVISION 23. SEE ELECTRICAL DRAWINGS FOR SOURCE.



**RTN/EXH VALVE CONTROL DIAGRAM**  
NO SCALE

**KEYED NOTES:**

1. CONTROLLER WILL BE FURNISHED BY OWNER. CONTROLLER WILL BE JCI MODEL MS-VMA-16XX SERIES. PROGRAMMING WILL BE DONE BY OWNER.
2. FC COMMUNICATION BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 3 CONDUCTOR, WITH BLUE OUTER CASING, DESCRIBED AS 22-03 OAS STR PLNM NEON BLU JK DISTRIBUTED BY WINDY CITY WIRE CONSTRUCTED BY CABLE-TEK, OR APPROVED EQUIVALENT.
3. CONTROLLER MUST HAVE A MINIMUM OF 18 INCHES OF ACCESSIBLE CLEARANCE.
4. FUSE LOCATED WITHIN 2 FEET OF VMA CONTROLLER.
5. LOW VOLTAGE WIRE BY DIVISION 23. SEE ELECTRICAL DRAWINGS FOR SOURCE.
6. FACTORY SUPPLIED ELECTRIC ACTUATOR. CONNECT DIRECTLY TO VMA CONTROLLER.
7. FACTORY SUPPLIED FLOW CONTROLLER. CONNECT FLOW AO TO VMA CONTROLLER



ERIC A. REUTHER  
STATE LIC. 2011015792

**TREANORHL**  
1811 Bellvue Ave  
St. Louis, MO 63104  
Office: 616.221.0900  
Fax: 616.221.4692  
www.treanorhl.com

**MCCLURE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T 314-646-6232  
www.mcclureeng.com

McClure Engineering  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE
1	RE-ISSUED IN ENTIRETY	08/10/21

**M602**


CONTROLS DETAILS

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00


MU Project Number: CP210701



**KEY PLAN**


S:\071625.000 UMC UMTH Renovate 2W\03 Mechanical\SWAMP\IP208.dwg 04/15/21 09:04 SJF

BIM 360:RHC02728 MU Teaching Hospital\UMTH\2-West\_Materials\_Swamp.rvt 5/27/2021 11:32:04 AM



**PARTIAL SECOND FLOOR FIRE PROTECTION PLAN**  
SCALE: 1/8"=1'-0"

**NFPA 13 OCCUPANCY CLASSIFICATION**





**FIRE PROTECTION GENERAL NOTES**

- EXISTING FIRE PROTECTION PIPING SHOWN FOR REFERENCE ONLY. CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFICATION OF ALL EXISTING CONDITIONS.

**KEYED NOTES**

- DEMOLISH EXISTING SPRINKLER HEADS AND BRANCH PIPING WITHIN SCOPE AREA. PROVIDE NEW BRANCH PIPING AND SPRINKLER HEAD LAYOUT CORRESPONDING TO NEW CEILING PLAN. REFER TO ARCHITECTURAL DRAWINGS FOR NEW CEILING PLAN. COORDINATE NEW PIPING LAYOUT WITH NEW HVAC AND OTHER TRADES WITHIN SCOPE AREA.
- PROVIDE TEMPORARY FIRE PROTECTION FOR ALL AREAS THAT ARE AFFECTED BY DEMOLITION FOR ZONE WORK. PROVIDE AND INSTALL PERIMETER CPVC PIPING FOR AFFECTED AREAS.



**TREANORHL**  
 151 Bellvue Ave  
 Saint Louis, Missouri 63102  
 T 314-645-6232  
 www.treanorhl.com

**MCCLURE ENGINEERING**  
 1000 Chest Avenue  
 Saint Louis, Missouri 63102  
 T 314-645-6232  
 www.mcclureeng.com

McClure Engineering  
 Professional Engineering Corporation  
 Missouri State Certificate of Authority #000087

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY		08/10/21

**FP102**

SECOND FLOOR  
FIRE PROTECTION  
PLAN

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number:  
HC0728.2101.00

MU Project Number:  
CP210701

S:\071625.000 UMC UMTH Renovate 2W03 Electrical\SWAMP\ED201-071625.000.dwg 08/05/21 14:29 SFreund

BIM 360:R:\0728 MU Teaching Hospital\UMTH\2-West\_Materials\_Swamp.rvt 5/27/2021 11:32:04 AM




**PARTIAL SECOND FLOOR PLAN - DEMOLITION**  
SCALE: 1/8" = 1'-0"

**GENERAL DEMOLITION NOTES:**

- ALL SYMBOLS SHOWN DASHED ARE EXISTING ELECTRICAL DEVICES TO BE REMOVED OR AS NOTED. ALL SYMBOLS SHOWN SOLID LIGHT LINE ARE EXISTING ELECTRICAL DEVICES TO REMAIN. EXISTING ELECTRICAL DEVICES WHICH ARE TO REMAIN SHALL BE EXTENDED TO BE FLUSH WITH NEW FINISH ON EXISTING WALLS WHERE REQUIRED.
- ALL EXISTING ELECTRICAL DEVICES IN A WALL THAT IS TO BE REMOVED, ELECTRICAL CONTRACTOR SHALL DISCONNECT POWER, CUT OFF CONDUCTORS AND CAP CONDUIT IN FLOOR OR CEILING AS REQUIRED. DEVICES ARE TO BE REMOVED ALONG WITH WALL BY GENERAL CONTRACTOR UNLESS OTHERWISE NOTED.
- ALL EXISTING ELECTRICAL DEVICES TO BE REMOVED FROM WALLS WHICH ARE TO REMAIN, ELECTRICAL CONTRACTOR SHALL DISCONNECT POWER, REMOVE CONDUCTORS, REMOVE DEVICE AND PROVIDE BLANK COVERPLATES AS REQUIRED, UNLESS OTHERWISE NOTED.
- FOR A PORTION OF A CIRCUIT WHICH IS REMOVED OR ABANDONED, RE-ESTABLISH CIRCUIT CONTINUITY FOR THE PORTION OF THE CIRCUIT WHICH IS TO REMAIN.
- ALL EXISTING CONDUITS, RACEWAYS AND WIRING ROUTED IN EXISTING WALLS AND CEILING SPACES (WHICH ARE TO BE DEMOLISHED) WHICH SERVE OTHER AREAS SHALL BE REROUTED AS REQUIRED.
- ALL EXISTING LIGHTING FIXTURES THAT ARE TO BE REINSTALLED SHALL BE REPAIRED, (AS REQUIRED) CLEANED AND RELAMPED BEFORE REINSTALLATION.
- ALL EXISTING LIGHTING FIXTURES THAT ARE NOTED TO BE REINSTALLED WHICH ARE NOT REINSTALLED SHALL BE RETURNED TO THE OWNER.
- PROVIDE AND INSTALL SUPPORTS FOR EXISTING CABLES AND CONDUITS ABOVE CEILING THAT ARE CURRENTLY UNSUPPORTED IN ALL AREAS WHERE CEILING IS BEING REMOVED.

**KEYED NOTES**

- DISCONNECT AND REMOVE ALL CLOTH WIRE, ABANDONED AND OR EMPTY CONDUITS AND JUNCTION BOXES IN THIS AREA.
- EXISTING FLAMMABLE ALARM BEACON TO REMAIN.
- EXISTING FIRE ALARM DUCT DETECTORS ONE AT CEILING AND ONE AT FLOOR AND 120 VOLT BRANCH CIRCUIT TO REMAIN.
- EXISTING 3" CONDUIT SHALL BE INTERCEPTED AND BE RE-ROUTED, EXISTING CONDUIT SHALL REMAIN AS INDICATED.
- DISCONNECT AND REMOVE EXISTING PANEL, CONDUIT AND CONDUCTORS BACK TO SOURCE. COORDINATE WITH OWNER TO TRACE AND IDENTIFY EXISTING ENERGIZED BRANCH CIRCUITS, EXISTING BRANCH CIRCUITS THAT ARE DETERMINED TO NEED TO BE RE-CIRCUITED WILL BE HANDLED BY CHANGE ORDER AFTER IDENTIFICATION.
- EXISTING SMOKE DAMPER FIRE ALARM DEVICE, DEVICE AND POWER TO REMAIN.
- DISCONNECT REMOVE AND RELOCATE EXISTING 'VAV' POWER SUPPLY.
- EXISTING SPEAKER IS TO BE TEMPORARILY SUPPORTED DURING DEMOLITION, SPEAKER TO BE RELOCATED IN NEW CEILING.
- DISCONNECT AND REMOVE ALL ELECTRICAL DEVICES IN THIS AREA, VERIFY EXISTING CONDITIONS AT JOB SITE.



**TREANORHL**  
181 Bellmore Ave  
St. Louis, MO 63108  
Office: 616.221.0900  
Fax: 616.221.4692  
www.treanorhl.com  
TreanorHL, P.A. - Architect  
Missouri Certificate of Authority # A2009030447


**MCCLURE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T 314-646-6232  
www.mcclureeng.com  
McClure Engineering  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY		08/10/21

**ED201**  
PARTIAL SECOND FLOOR PLAN - DEMOLITION  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701



**KEY PLAN**

S:\071625.000 UMC UJTH Renovate 2W03 Electrical\SWAMP\00-071625.000.dwg 08/04/21 11:18 SFreund

BIM 360:R:\020728 MU Teaching Hospital\UMTH\2\West\_Materials\_Swamp.rvt 5/27/2021 11:52:04 AM

**LIGHTING FIXTURES**

NOTE: EMERGENCY FIXTURE DESIGNATIONS:

- STRIP FIXTURE
- 1x4' WALL MOUNTED
- 1x4' SURFACE MOUNTED
- 1x4' RECESS MOUNTED
- 2x2' SURFACE MOUNTED
- 2x2' RECESS MOUNTED
- 2x4' SURFACE MOUNTED
- 2x4' RECESS MOUNTED
- WALL MOUNTED LIGHT FIXTURE
- DOWN LIGHT SURFACE MOUNTED
- DOWN LIGHT RECESS MOUNTED
- WALL WASH DOWN LIGHT RECESS MOUNTED
- EXIT SIGN DOUBLE FACE CEILING MOUNTED
- EXIT SIGN SINGLE FACE WALL MOUNTED (BACK)
- EXIT SIGN SINGLE FACE WALL MOUNTED (END)
- EXIT SIGN NOTE: SHADING INDICATES FACE SEE FLOOR PLANS FOR ARROW DIRECTIONS
- BATTERY PACK LIGHTING FIXTURE

**MISCELLANEOUS CONTROL DEVICES**

- PUSH-BUTTON/PUSH PAD RECESS MOUNTED +48" AFF
- MUSHROOM HEAD/EMERGENCY PUSH BUTTON RECESS MOUNTED +48" AFF

**MISCELLANEOUS COMMUNICATION DEVICES**

- SPEAKER RECESS CEILING MOUNTED
- SPEAKER SURFACE CEILING MOUNTED
- TWO WAY SPEAKER ENCLOSURE MOUNT WITH MANUFACTURE'S WIDER HORIZONTAL BEAM WIDTH INDICATED BY SYMBOL ORIENTATION UNLESS OTHERWISE INDICATED ON DRAWINGS
- SPEAKER WALL MOUNTED +90" AFF
- INTERCOM SPEAKER CEILING MOUNTED
- INTERCOM SPEAKER WALL MOUNTED +90" AFF
- SPEAKER VOLUME CONTROL RECESS WALL MOUNTED +54" AFF
- PROGRAM BELL WALL MOUNTED +90" AFF
- CLOCK WALL MOUNTED +90" AFF
- CLOCK OUTLET WALL MOUNTED +90" AFF
- DOOR OPERATOR
- POWER POLE WITH RECEPTACLE AND DATA OUTLET AS INDICATED ON FLOOR PLAN

**SWITCHES**

WALL SWITCH +48" AFF

**LIGHTING CONTROL SUBSCRIPT TAGS**

- BLANK SINGLE POLE TOGGLE SWITCH
- 3 3-WAY TOGGLE SWITCH
- 4 4-WAY TOGGLE SWITCH
- CP ROOM CONTROL PANEL
- D DIMMER SWITCH
- 3D 3-WAY DIMMER SWITCH
- DT DIGITAL TIMER
- K KEY OPERATED TOGGLE SWITCH
- LV LOW VOLTAGE MOMENTARY SWITCH
- LVD LOW VOLTAGE WITH DIMMING
- OS OCCUPANCY SENSOR
- OSD OCCUPANCY SENSOR WITH DIMMING
- PL PILOT LIGHTED TOGGLE SWITCH
- R SINGLE POLE DOUBLE THROW CENTER OFF MOMENTARY SWITCH
- SC SHADE CONTROLLER
- T MANUAL TIMER SWITCH
- V VACANCY SENSOR
- VSD VACANCY SENSOR WITH DIMMER
- CS# DIGITAL LIGHTING CONTROL STATION # = NUMBER OF BUTTONS UP TO 8
- OS OCCUPANCY SENSOR CEILING MOUNTED
- PIR - PASSIVE INFRARED
- CL DAY LIGHT SENSOR CEILING MOUNTED
- P PHOTOCELL
- LS1 LIGHTING TRANSFER SWITCH FOR SINGLE FIXTURE ACCESSIBLE CEILING SPACE
- LS2 LIGHTING TRANSFER SWITCH FOR MULTI FIXTURE MOUNTED IN ACCESSIBLE CEILING SPACE
- LC LIGHTING CONTACTOR
- LC1 1 ZONE 0-10V LIGHTING CONTROLLER
- LC2 2 ZONE 0-10V LIGHTING CONTROLLER
- LC3 3 ZONE 0-10V LIGHTING CONTROLLER
- LC4 1 ZONE FORWARD PHASE LIGHTING CONTROLLER
- LC5 2 ZONE FORWARD PHASE LIGHTING CONTROLLER
- LC6 1 ZONE REVERSE PHASE LIGHTING CONTROLLER
- LC7 1 ZONE ON/OFF LIGHTING CONTROLLER
- LC8 2 ZONE ON/OFF LIGHTING CONTROLLER
- FL PLUG LOAD LIGHTING CONTROLLER
- TC TIME CLOCK

**SECURITY**

- CAMERA CEILING MOUNTED
- CAMERA WALL MOUNTED
- CARD READER
- DOOR CONTACT/DOOR POSITION
- DELAY EGRESS
- EXIT ALARM
- ELECTRIC EXIT
- ELECTRIC LATCH
- ELECTRIC LATCH RETRACTION
- EXIT REQUEST
- ELECTRIC STRIKE
- GLASS BREAK
- NUMERIC KEYPAD
- KEY SWITCH
- MOTION DETECTOR MOUNTED +7' AFF
- MAGNETIC LOCK
- PANIC BUTTON
- DOOR POWER SUPPLY
- POWER TRANSFER
- SECURITY VIDEO MONITOR

**ELECTRICAL SYMBOLS**

**COMMUNICATION DEVICES**

- 'COMMUNICATIONS' OUTLET, RECESSED WALL MOUNTED +18" AFF, 'UNO' ON FLOOR PLANS SEE FLOOR PLANS FOR DEVICE TYPE AND NUMBER
- 'COMMUNICATIONS' OUTLET, RECESSED WALL MOUNTED +44" AFF (ABOVE COUNTER), 'UNO' ON FLOOR PLANS SEE FLOOR PLANS FOR DEVICE TYPE AND NUMBER
- 'COMMUNICATIONS' OUTLET, RECESSED FLOOR MOUNTED SEE FLOOR PLANS FOR DEVICE TYPE AND NUMBER
- 'COMMUNICATIONS' RECESSED IN CEILING SEE FLOOR PLANS FOR DEVICE TYPE AND NUMBER

**COMMUNICATION DEVICE TYPE**

- \* = D DATA
- I INTERCOM
- ICS INTERCOM CALL-IN STATION
- M MICROPHONE
- P PRINTER
- T TELEPHONE
- TV TELEVISION / MONITOR
- WAP WIRELESS ACCESS POINT

NOTE: FUTURE WIRELESS ACCESS POINT (WAP) PROVIDE 15'-0" SERVICE LOOP AT OUTLET. SERVICE LOOP SHALL BE COILED IN ACCESSIBLE CEILING SPACE. WHEN OUTLET IS LOCATED IN AREAS THAT ARE OPEN TO STRUCTURE, OUTLET SHALL BE MOUNTED TO STRUCTURE PROVIDE 15'-0" SERVICE LOOP AT OUTLET. SERVICE LOOP SHALL BE COILED AND TIED TO STRUCTURE.

**RECEPTACLES**

- SINGLE CONVENIENCE OUTLET, RECESSED WALL MOUNTED +18" AFF, 'UNO' ON FLOOR PLANS
- DUPLEX CONVENIENCE OUTLET, RECESSED WALL MOUNTED +18" AFF, 'UNO' ON FLOOR PLANS
- DUPLEX CONVENIENCE OUTLET, RECESSED WALL MOUNTED ABOVE COUNTER +44" AFF 'UNO' ON FLOOR PLANS
- DOUBLE DUPLEX CONVENIENCE OUTLET, RECESSED WALL MOUNTED +18" AFF, 'UNO' ON FLOOR PLANS
- DOUBLE DUPLEX CONVENIENCE OUTLET, RECESSED WALL MOUNTED ABOVE COUNTER +44" AFF, 'UNO' ON FLOOR PLANS
- CEILING MOUNTED
- SPECIAL PURPOSE OUTLET, RECESSED WALL MOUNTED +18", 'UNO' ON FLOOR PLANS SEE FLOOR PLANS FOR SIZE
- DUPLEX RECEPTACLE, RECESSED FLOOR MOUNTED
- DOUBLE DUPLEX RECEPTACLE, RECESSED FLOOR MOUNTED
- DEAD FRONT / FACELESS 'GFCI' DEVICE RECESSED WALL MOUNTED +48" AFF WITH ENGRAVED COVERPLATE AS NOTED ON FLOOR PLAN
- RECESSED FLOOR BOX
- ? = FLOOR BOX TYPE ('A', ETC) SEE FLOOR BOX SCHEDULE
- 4"x4"x2" JUNCTION BOX WITH FINISHED BLANK COVER RECESSED WALL MOUNTED +18" AFF 'UNO' ON FLOOR PLANS
- 4"x4"x2" JUNCTION BOX WITH FINISHED BLANK COVER MOUNTED ABOVE ACCESSIBLE CEILING UNO
- PULL BOX WITH FINISHED BLANK COVER MOUNTING AND SIZE AS NOTED ON FLOOR PLAN

**RECEPTACLE SUB SCRIPT**

- HG HOSPITAL GRADE
- TR TAMPER RESISTANCE
- IG ISOLATED GROUND
- G GROUND FAULT CIRCUIT INTERRUPTER
- WR WEATHER RESISTANCE
- WP WEATHERPROOF COVER
- WPI WEATHERPROOF IN-USE COVER
- U USB PORT

**POWER EQUIPMENT**

- LIGHTING PANELBOARD
- DISTRIBUTION PANEL
- MOTOR CONTROL CENTER
- SWITCHBOARD
- TRANSFORMER, SEE PLAN FOR TYPE AND SIZE
- WEATHER HEAD
- AUTOMATIC TRANSFER SWITCH
- FACTORY WIRED CONTROL PANEL
- VARIABLE FREQUENCY DRIVE

**MOTORS**

- SINGLE PHASE MANUAL MOTOR STARTER WITH PILOT LIGHT
- RELAY IN BOX
- DISCONNECT SWITCH
- MAGNETIC STARTER 1 PHASE
- MAGNETIC STARTER 3 PHASE
- COMBINATION MAGNETIC STARTER/ DISCONNECT SWITCH 1 PHASE
- COMBINATION MAGNETIC STARTER/ DISCONNECT SWITCH 3 PHASE
- LINE VOLTAGE THERMOSTAT
- VAV JUNCTION BOX WITH TOGGLE SWITCH
- 208V, 3 PHASE MOTOR
- 480V, 3 PHASE MOTOR
- 120V, 1 PHASE MOTOR
- 208V, 1 PHASE MOTOR
- DC MOTOR

**MOUNTING HEIGHTS**

ALL MOUNTING HEIGHTS ARE AS GIVEN UNLESS OTHERWISE NOTED ON PLANS. ALL MOUNTING HEIGHTS ARE TO CENTER OF DEVICE/ LIGHT FIXTURE, UNLESS OTHERWISE NOTED

**FIRE ALARM**

- PULL STATION WALL MOUNTED +48" AFF (C = INDICATES ALARM COVER)
- ALARM BELL WALL MOUNTED +80" AFF TO BOTTOM
- ALARM SPEAKER HORN WALL MOUNTED +80" AFF TO BOTTOM
- ALARM HORN WALL MOUNTED +80" AFF TO BOTTOM
- FIRE ALARM HORN CEILING MOUNTED
- COMBINATION ALARM SPEAKER AND VISUAL DEVICE # INTENSITY OF STROBE (15/75 UNLESS OTHERWISE SPECIFIED) CEILING MOUNTED
- COMBINATION ALARM HORN AND VISUAL DEVICE # INTENSITY OF STROBE (15/75 UNLESS OTHERWISE SPECIFIED) WALL MOUNTED +80" AFF TO BOTTOM
- COMBINATION ALARM SPEAKER AND VISUAL DEVICE # INTENSITY OF STROBE (15/75 UNLESS OTHERWISE SPECIFIED) CEILING MOUNTED
- VISUAL DEVICE # INTENSITY OF STROBE (15/75 UNLESS OTHERWISE SPECIFIED) WALL MOUNTED +80" AFF TO BOTTOM
- ALARM SPEAKER CEILING MOUNTED
- FIREMANS PHONE
- FIRE ALARM RELAY
- CARBON MONOXIDE DETECTOR
- MAGNETIC DOOR HOLD-OPEN
- MAGNETIC DOOR HOLD-OPEN WITH BUILT IN SMOKE DETECTOR
- HEAT DETECTOR FIXED TEMPERATURE
- HEAT DETECTOR RATE OF RISE
- WATER FLOW SWITCH
- TAMPER SWITCH
- SMOKE DETECTOR CEILING MOUNTED
- SMOKE DETECTOR OTHER THAN CEILING MOUNTED
- SMOKE DETECTOR WITH RELAY BASE CEILING MOUNTED
- SMOKE DETECTOR WITH RELAY BASE CEILING MOUNTED OTHER THAN CEILING MOUNTED
- SMOKE DETECTOR WITH SOUNDER BASE CEILING MOUNTED
- SMOKE DETECTOR WITH SOUNDER BASE OTHER THAN CEILING MOUNTED
- SMOKE DETECTOR DUCT MOUNTED
- SMOKE DETECTOR DUCT MOUNTED WITH RELAY BASE
- REMOTE TEST SWITCH CEILING MOUNTED
- REMOTE TEST SWITCH OTHER THAN CEILING MOUNTED
- MOTORIZED SMOKE DAMPER
- FIRE ALARM CONTROL MODULE
- FIRE ALARM MONITOR MODULE
- FIRE ALARM DUAL MONITOR MODULE
- POST INDICATOR VALVE
- POWER SUPERVISION RELAY
- FIRE ALARM CONTROL PANEL
- FIRE ALARM ANNUNCIATOR
- FIRE ALARM SIGNAL EXTENDER
- END OF LINE RESISTOR


**ABBREVIATIONS**

- AFF ABOVE FINISHED FLOOR
- AFG ABOVE FINISHED GRADE
- AL ALUMINUM
- ARC ALUMINUM RIGID CONDUIT
- AUX AUXILIARY
- BOF BOTTOM OF FIXTURE
- C CONDUIT
- CB CIRCUIT BREAKER
- CKT CIRCUIT
- COF CENTER OF FIXTURE
- EC ELECTRICAL CONTRACTOR
- EMT ELECTRICAL METALLIC TUBING
- EWC ELECTRIC WATER COOLER
- GRC GALVANIZED RIGID CONDUIT
- GFI GROUND FAULT CIRCUIT INTERRUPTER
- G GROUND
- IMC INTERMEDIATE METAL CONDUIT
- MCB MAIN CIRCUIT BREAKER
- MLO MAIN LUG ONLY
- NC NORMALLY CLOSED
- NF NON FUSED
- NO NORMALLY OPEN
- NTS NOT TO SCALE
- PVC PVC CONDUIT
- TOF TOP OF FIXTURE
- U USB PORT
- UCR UNDER CABINET REFRIGERATOR
- UNO UNLESS NOTED OTHERWISE
- WP WEATHERPROOF COVER
- WPI WEATHERPROOF IN-USE COVER

**WIRING SYMBOLS**


- CONDUIT DOWN
- CONDUIT UP
- CONDUIT CAPPED
- EXISTING
- DEMOLITION WORK
- NEW WORK
- CONDUIT CONCEALED IN SLAB OR IN ACCESSIBLE SPACE BELOW
- CONDUIT EXPOSED
- CONDUIT CONCEALED IN WALL OR ABOVE CEILING
- WIREWAY / WIREMOLD
- WIRE MOLD WITH DUPLEX RECEPTACLE (DUPLEX RECEPTACLE SYMBOL INDICATES MOUNTING HEIGHT, +18" AFF SHOWN) 'UNO' ON FLOOR PLANS
- DIVIDED WIRE MOLD WITH DATA/TELEPHONE (TOP CELL) AND DUPLEX RECEPTACLE (BOTTOM CELL) OUTLETS AS INDICATED (DEVICE SYMBOLS INDICATE MOUNTING HEIGHT, +44" AFF SHOWN) 'UNO' ON FLOOR PLANS
- PLUG MOLD WITH SINGLE RECEPTACLE
- VERTICAL WIREWAY
- CABLE TRAY
- CONDUIT SLEEVE (SIZED TO 40% FILL, 2" MINIMUM) UNLESS NOTED OTHERWISE

**BRANCH CIRCUITING LEGEND**



**ELECTRICAL SYSTEMS COMPONENTS EARTHQUAKE LOAD RESISTANCE**

LISTING OF EQUIPMENT & SYSTEMS COMPONENTS	COMPONENTS IMPORTANCE FACTOR	ANCHORAGE TO FLOORS, ROOFS, ETC				SWAY BRACING			LOCATION OF PROFESSIONALLY SEALED ANCHORAGE AND SWAY BRACING DETAIL			COMMENTS
		NOT PROVIDED		PROVIDED		NOT PROVIDED	PROVIDED	ON CONSTRUCTION DOCUMENTS				
		NOT PROVIDED	PROVIDED	NOT PROVIDED	PROVIDED	DRAWING NUMBER OR SPECIFICATION SECTION	SHOP DRAWING	SEPARATE PERMIT & PLANS				
FIRE ALARM CONDUIT & PANELS	1.5		X		X				X			WHERE NOT DIRECTLY ATTACHED TO STRUCTURE
FIRE ALARM CONDUIT & PANELS	1.5	X			X							WHERE DIRECTLY ATTACHED TO STRUCTURE
LIFE SAFETY POWER CONDUIT, PANELS, GENERATORS, INVERTERS	1.5		X		X				X			WHERE NOT DIRECTLY ATTACHED TO STRUCTURE
LIFE SAFETY POWER CONDUIT, PANELS, GENERATORS, INVERTERS	1.5	X			X							WHERE DIRECTLY ATTACHED TO STRUCTURE
POWER CONDUIT	1.5		X		X				X			WHERE NOT DIRECTLY ATTACHED TO STRUCTURE
POWER CONDUIT	1.5	X			X							WHERE DIRECTLY ATTACHED TO STRUCTURE
COMMUNICATION CONDUIT	1.5		X		X				X			WHERE NOT DIRECTLY ATTACHED TO STRUCTURE
COMMUNICATION CONDUIT	1.5	X			X							WHERE DIRECTLY ATTACHED TO STRUCTURE
FREE STANDING EQUIPMENT	1.5		X		X				X			WHERE NOT DIRECTLY ATTACHED TO STRUCTURE



**TREANORHL**  
1811 Bellflower Ave.  
Saint Louis, Missouri 63102  
Office: 616.221.0990  
Fax: 616.221.4692  
www.treanorhl.com

**MCCLURE ENGINEERING**  
1000 Clay Avenue  
Saint Louis, Missouri 63102  
T 314-646-6232  
www.mcclureeng.com

McClure Engineering  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000087

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS

NO	DESCRIPTION	DATE
RE-1	ISSUED IN ENTIRETY	08/10/21

**E000**

ELECTRICAL SYMBOLS AND ABBREVIATIONS

BID DOCUMENTS

Date: 08/10/2021

Treanorhl Project Number: HC0728.2101.00

MU Project Number: CP210701



S:\071625.000 UMC UIMTH Renovate 2W\03 Electrical\SWAMP\E002-071625.000.dwg 08/04/21 11:19 SFreund



BIM 360:RHC020728 MU Teaching Hospital\UMTH\2-West\_Materials\_Swamp.rvt 5/27/2021 11:52:04 AM



SYMBOL	DESCRIPTION	PROTECTIVE ELEMENTS
	2HR	2 HOUR FIRE BARRIER
	1HR	1 HOUR FIRE BARRIER
	2HR SM	2 HOUR FIRE SMOKE BARRIER
	SM	HOSPITAL CORRIDOR WALL OR SMOKE PARTITION

**NOTE:**  
THIS SHEET IS ONLY VALID  
IF PRINTED IN COLOR.

**PARTIAL SECOND FLOOR PLAN - LIFE SAFETY**  
SCALE: 1/8" = 1'-0"



**TREANORHL**  
1511 Bellvue Ave  
St. Louis, MO 63102  
Office: 616.221.0900  
www.treanorhl.com  
Austin P. Strieker  
Professional Engineer  
Missouri State Certificate of Authority # A2009030447

**MCCLURE ENGINEERING**  
1000 Chest. Avenue  
St. Louis, Missouri 63102  
T 314-645-6232  
www.mcclureeng.com  
McClure Engineering  
Professional Engineering Corporation  
Missouri State Certificate of Authority #000897

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



REVISIONS		
NO	DESCRIPTION	DATE
RE-1	ISSUED IN ENTIRETY	08/10/21

**E002**  
PARTIAL SECOND FLOOR PLAN - LIFE SAFETY  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701



PANELBOARD: W2NH VOLTAGE: 480 /277V MAIN: 125 A POWER NORMAL BRANCH													
CONNECTED KVA			LOAD		POLES		CKT BKR		CKT		LOAD		
LTG	RECP	OTHER											
1.40			EXISTING		1P	20	1	A	2	20	1P	EXISTING	
			LIGHTING		1P	20	3	B	4	20	1P	SPARE	
			SPARE		1P	20	5	C	6	20	1P	SPARE	
			SPARE		1P	20	7	A	8	20	1P	SPARE	
			SPARE		1P	20	9	B	10	20	1P	SPARE	
			SPARE		1P	20	11	C	12	20	1P	SPARE	
			SPARE		1P	20	13	A	14	20	1P	SPARE	
			SPARE		1P	20	15	B	16	20	1P	SPARE	
			SPARE		1P	20	17	C	18	20	1P	SPARE	
			SPARE		1P	20	19	A	20	20	1P	SPARE	
			SPARE		1P	20	21	B	22	20	1P	SPARE	
			SPARE		1P	20	23	C	24	20	1P	SPARE	
			SPARE		1P	20	25	A	26	20	1P	SPARE	
			SPARE		1P	20	27	B	28	20	1P	SPARE	
			SPARE		1P	20	29	C	30	20	1P	SPARE	
			SPARE		1P	20	31	A	32	20	1P	SPARE	
			SPARE		1P	20	33	B	34	20	1P	SPARE	
			SPARE		1P	20	35	C	36	20	1P	SPARE	
			SPARE		1P	20	37	A	38	20	1P	SPARE	
			SPARE		1P	20	39	B	40	20	1P	SPARE	
			SPARE		1P	20	41	C	42	20	1P	SPARE	
1.40	0.00	0.00	SUBTOTALS										SUBTOTALS

PANELBOARD: W2CRH VOLTAGE: 480 /277V MAIN: 125 A POWER CRITICAL BRANCH													
CONNECTED KVA			LOAD		POLES		CKT BKR		CKT		LOAD		
LTG	RECP	OTHER											
			EXISTING		1P	20	1	A	2	20	1P	LIGHTING	
			SPARE		1P	20	3	B	4	20	1P	SPARE	
			SPARE		1P	20	5	C	6	20	1P	SPARE	
			SPARE		1P	20	7	A	8	20	1P	SPARE	
			SPARE		1P	20	9	B	10	20	1P	SPARE	
			SPARE		1P	20	11	C	12	20	1P	SPARE	
			SPARE		1P	20	13	A	14	20	1P	SPARE	
			SPARE		1P	20	15	B	16	20	1P	SPARE	
			SPARE		1P	20	17	C	18	20	1P	SPARE	
			SPARE		1P	20	19	A	20	20	1P	SPARE	
			SPARE		1P	20	21	B	22	20	1P	SPARE	
			SPARE		1P	20	23	C	24	20	1P	SPARE	
			SPARE		1P	20	25	A	26	20	1P	SPARE	
			SPARE		1P	20	27	B	28	20	1P	SPARE	
			SPARE		1P	20	29	C	30	20	1P	SPARE	
			SPARE		1P	20	31	A	32	20	1P	SPARE	
			SPARE		1P	20	33	B	34	20	1P	SPARE	
			SPARE		1P	20	35	C	36	20	1P	SPARE	
			SPARE		1P	20	37	A	38	20	1P	SPARE	
			SPARE		1P	20	39	B	40	20	1P	SPARE	
			SPARE		1P	20	41	C	42	20	1P	SPARE	
			SUBTOTALS										SUBTOTALS

**GENERAL NOTES**  
1. DIVISION 26 CONTRACTOR SHALL VERIFY EXISTING LOADS, SPARE, AND BREAKER SPACE IN FIELD AND PROVIDE UPDATED PANEL DIRECTORIES PER SPECIFICATION. NEW DIRECTORIES SHALL INCLUDE EXISTING LOAD INFORMATION AND NOT INCLUDE "EXISTING LOAD, ETC" RETURN EXISTING PANEL DIRECTORIES TO OWNER.

PANELBOARD: W2NL VOLTAGE: 208 /120V MAIN: 225 A POWER NORMAL BRANCH													
CONNECTED KVA			LOAD		POLES		CKT BKR		CKT		LOAD		
LTG	RECP	OTHER											
			EXISTING		1P	20	1	A	2	20	1P	EXISTING	
			EXISTING		1P	20	3	B	4	20	1P	EXISTING	
			3 DD RECPT RN 2W24		1P	20	5	C	6	20	1P	PRINTER 2W20	
			3 DD RECPT RN 2W24		1P	20	7	A	8	20	1P	6 GP RECPT	
			PRINTER RN 2W24		1P	20	9	B	10	20	1P	3 DD RECPT	
			3 DD RECPT RN 2W25		1P	20	11	C	12	20	1P	4 RECPT GP	
			3 DD RECPT RN 2W25		1P	20	13	A	14	20	1P	4 RECPT GP	
			PRINTER RN 2W25		1P	20	15	B	16	20	1P	4 RECPT GP	
			3 DD RECPT RN 2W26		1P	20	17	C	18	20	1P	GFCE 1 FL RECPT	
			3 DD RECPT RN 2W26		1P	20	19	A	20	20	1P	GFCE 1 FL RECPT	
			PRINTER RN 2W26		1P	20	21	B	22	20	1P	GFCE 1 FL RECPT	
			3 DD RECPT RN 2W22		1P	20	23	C	24	20	1P	GFCE 1 FL RECPT	
			3 DD RECPT RN 2W22		1P	20	25	A	26	20	1P	GFCE 1 FL RECPT	
			PRINTER RN 2W22		1P	20	27	B	28	20	1P	ICE MACHINE	
			SPARE		1P	20	29	C	30	20	1P	SPARE	
			SPARE		1P	20	31	A	32	20	1P	SPARE	
			1 RECPT 2W27		1P	20	33	B	34	20	1P	SPARE	
			1 RECPT 2W27		1P	20	35	C	36	20	1P	6 GP RECPT	
			1 RECPT 2W27		1P	20	37	A	38	20	1P	SPARE	
			1 RECPT 2W27		1P	20	39	B	40	20	1P	SPARE	
			6 GP RECPT		1P	20	41	C	42	20	1P	SPARE	
			SPARE		1P	30	43	A	44	20	1P	SPARE	
			SPARE		1P	30	45	B	46	20	1P	SPARE	
			SPARE		1P	30	47	C	48	20	1P	SPARE	
			SPARE		1P	30	49	A	50	20	1P	SPARE	
			SPARE		1P	30	51	B	52	20	1P	SPARE	
			SPARE		1P	20	53	C	54	20	1P	SPARE	
			SPARE		1P	20	55	A	56	20	1P	SPARE	
			SPARE		1P	20	57	B	58	20	1P	SPARE	
			SPARE		1P	20	59	C	60	20	1P	SPARE	
			SPARE		1P	20	61	A	62	20	1P	SPARE	
			SPARE		1P	20	63	B	64	20	1P	SPARE	
			SPARE		1P	20	65	C	66	20	1P	SPARE	
			SPARE		1P	20	67	A	68	20	1P	SPARE	
			SPARE		1P	20	69	B	70	20	1P	SPARE	
			SPARE		1P	20	71	C	72	20	1P	SPARE	
			SPARE		1P	20	73	A	74	20	1P	SPARE	
			SPARE		1P	20	75	B	76	20	1P	SPARE	
			SPARE		1P	20	77	C	78	20	1P	SPARE	
			SPARE		1P	20	79	A	80	20	1P	SPARE	
			SPARE		1P	20	81	B	82	20	1P	SPARE	
			SPARE		1P	20	83	C	84	20	1P	SPARE	
			SUBTOTALS										SUBTOTALS

PANELBOARD: W2LSH VOLTAGE: 480 /277V MAIN: 125 A POWER LIFE SAFETY BRANCH													
CONNECTED KVA			LOAD		POLES		CKT BKR		CKT		LOAD		
LTG	RECP	OTHER											
			LIGHTING		1P	20	1	A	2	20	1P	EXISTING	
			SPARE		1P	20	3	B	4	20	1P	SPARE	
			SPARE		1P	20	5	C	6	20	1P	SPARE	
			SPARE		1P	20	7	A	8	20	1P	SPARE	
			SPARE		1P	20	9	B	10	20	1P	SPARE	
			SPARE		1P	20	11	C	12	20	1P	SPARE	
			SPARE		1P	20	13	A	14	20	1P	SPARE	
			SPARE		1P	20	15	B	16	20	1P	SPARE	
			SPARE		1P	20	17	C	18	20	1P	SPARE	
			SPARE		1P	20	19	A	20	20	1P	SPARE	
			SPARE		1P	20	21	B	22	20	1P	SPARE	
			SPARE		1P	20	23	C	24	20	1P	SPARE	
			SPARE		1P	20	25	A	26	20	1P	SPARE	
			SPARE		1P	20	27	B	28	20	1P	SPARE	
			SPARE		1P	20	29	C	30	20	1P	SPARE	
			SPARE		1P	20	31	A	32	20	1P	SPARE	
			SPARE		1P	20	33	B	34	20	1P	SPARE	
			SPARE		1P	20	35	C	36	20	1P	SPARE	
			SPARE		1P	20	37	A	38	20	1P	SPARE	
			SPARE		1P	20	39	B	40	20	1P	SPARE	
			SPARE		1P	20	41	C	42	20	1P	SPARE	
			SUBTOTALS										SUBTOTALS



PANELBOARD: W2LSL VOLTAGE: 208 /120V MAIN: 125 A POWER LIFE SAFETY BRANCH													
CONNECTED KVA			LOAD		POLES		CKT BKR		CKT		LOAD		
LTG	RECP	OTHER											
			EXISTING		1P	20	1	A	2	20	1P	EXISTING	
			EXISTING		1P	20	3	B	4	20	1P	SPARE	
			SMOKE SHUTTER CKT		1P	20	5	C	6	20	1P	SPARE	
			AUTO DOOR		1P	20	7	A	8	20	1P	SPARE	
			SPARE		1P	20	9	B	10	20	1P	SPARE	
			SPARE		1P	20	11	C	12	20	1P	SPARE	
			SPARE		1P	20	13	A	14	20	1P	SPARE	
			SPARE		1P	20	15	B	16	20	1P	SPARE	
			SPARE		1P	20	17	C	18	20	1P	SPARE	
			SPARE		1P	20	19	A	20	20	1P	SPARE	
			SPARE		1P	20	21	B	22	20	1P	SPARE	
			SPARE		1P	20	23	C	24	20	1P	SPARE	
			3P		20	25	A	26	20	1P	NO SPACE		
			3P		20	27	B	28	20	1P	NO SPACE		
			3P		20	29	C	30	20	1P	NO SPACE		
			SUBTOTALS										SUBTOTALS

PANELBOARD: W2EQL VOLTAGE: 208 /120V MAIN: 225 A POWER EQUIPMENT BRANCH												
CONNECTED KVA			LOAD		POLES		CKT BKR		CKT		LOAD	
LTG	RECP	OTHER										
			EXISTING		1P	20	1	A	2	20	1P	EXISTING
			EXISTING		1P	20	3	B	4	20	1P	EXISTING
			EXISTING		1P	20	5	C	6	20	1P	EXISTING
	</											

S:\071625.000 UMC UIMH Renovate 2W\03 Electrical\SWAMP\E201-071625.000.dwg 08/05/21 11:13 SFreund

BIM 360:R:\0728 MU Teaching Hospital\UMH\2-West\_Materials\_Swamp.rvt 5/27/2021 11:52:04 AM

**TEMPORARY EGRESS CORRIDOR - LIGHTING**  
SCALE: 1/8" = 1'-0"




**PARTIAL SECOND FLOOR PLAN - LIGHTING**  
SCALE: 1/8" = 1'-0"

**GENERAL LIGHTING NOTES:**

- REFER TO SYMBOL LEGEND ON SHEET E000 FOR INFORMATION ON COMMUNICATION DEVICES.
- TYPE MC CABLE IS PERMITTED FOR WIRING FROM LOCAL DISTRIBUTION JUNCTION BOXES TO DEVICES OR EQUIPMENT IN NEARBY WALLS OR CEILING SPACE. THE LOCAL DISTRIBUTION JUNCTION BOXES SHOULD BE LOCATED WITHIN 20 FEET OF THE DEVICE OR EQUIPMENT SERVED. CONDUIT AND WIRING SHALL BE USED FOR BRANCH CIRCUITING BETWEEN THE LOCAL DISTRIBUTION JUNCTION BOXES AND FOR THE "HOMERUNS" FROM THE PANELS. THE MC CABLE IS PERMITTED TO ROUTE FROM RECEPTACLE TO RECEPTACLE THROUGH WALLS AND THROUGH THE CEILING SPACE FOR THE FINAL PORTION OF BRANCH CIRCUIT WIRING BETWEEN RECEPTACLES IN ADJACENT WALLS OF THE SAME ROOM OR AREA. TYPE MC CABLE SHALL NOT BE INSTALLED WHERE EXPOSED.
- ELECTRICAL PANELBOARD DIRECTORIES SHALL BE LABELED WITH FINAL ROOM NUMBERS.
- SEE SCHEDULE E200 FOR LUMINAIRE SCHEDULE, LIGHTING WIRING DIAGRAMS AND DETAILS.
- FURNISH AND INSTALL EXPANSION FITTINGS FOR ALL CONDUIT CROSSING BUILDING EXPANSION JOINT.

**KEYED NOTES:**

- CONNECT TO SPARE 20 AMP SINGLE POLE CIRCUIT BREAKER IN EXISTING PANEL AS INDICATED.



**TREANORHL**  
1811 Bellvue Ave  
St. Louis, MO 63102  
Office: 616.221.0900  
www.treanorhl.com


**MCCLURE ENGINEERING**  
1000 Clark Avenue  
St. Louis, Missouri 63102  
T 314-645-6232  
www.mcclureeng.com

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS		
NO	DESCRIPTION	DATE
RE-1	ISSUED IN ENTIRETY	08/10/21


**E201**  
PARTIAL SECOND FLOOR PLAN - LIGHTING  
BID DOCUMENTS  
Date: 08/10/2021  
TreanorHL Project Number: HC0728.2101.00  
MU Project Number: CP210701




S:\071625.000 UMC UMTH Renovate 2W03 Electrical\SWAMP\202-071625.000.dwg 08/05/21 11:54 SFreund  
 BIM 360:R:\0728 MU Teaching Hospital\UMTH\2-West\_Materials\_Swamp.rvt  
 5/27/2021 11:52:04 AM




**ABOVE CEILING TELECOM BOX INSTALLATION DETAIL**  
 SCALE: NO SCALE




**VAV SCHEMATIC**



**OCCUPANCY SENSOR MOUNTING DETAIL**  
 NO SCALE



**PARTIAL ONE LINE**  
 NO SCALE




**PARTIAL SECOND FLOOR PLAN - POWER**  
 SCALE: 1/8" = 1'-0"

**GENERAL POWER NOTES:**


1. PROVIDE ENGRAVED COVERPLATE AT EACH DEVICE INDICATING PANEL NAME AND CIRCUIT NUMBER. REFERENCE SPECIFICATIONS.
2. CONDUIT AND CONDUCTORS SHALL BE ROUTED IN A MANNER TO PROVIDE THE MOST DIRECT PATH TO OUTLET. MINIMIZE CONDUIT ELBOWS WHERE POSSIBLE.
3. DO NOT BUNDLE (TIE WRAP) CONDUCTORS OR USE WIRE PULLING COMPOUND.
4. REFER TO ARCHITECTURAL PLANS FOR ELEVATIONS OF EQUIPMENT IN ALL PACUS.
5. COORDINATE ALL SYSTEMS DEVICE LOCATIONS WITH ARCHITECTURAL PLANS AND ELEVATIONS PRIOR TO ROUGH-IN.
6. ALL TELE/DATA CABLES IN THIS AREA SHALL BE ROUTED TO DATA 2W01.
7. COORDINATE FINAL SECURITY DEVICE LOCATIONS WITH OWNER'S SECURITY TEAM PRIOR TO ROUGH-IN.
8. ALL PENETRATIONS THROUGH OR INTO CONCRETE SHALL BE X-RAYED PRIOR TO WORK.
9. ELECTRICAL PANELBOARD DIRECTORIES SHALL BE RETURNED TO MHC. NEW ELECTRICAL PANELBOARD DIRECTORIES SHALL BE TYPED/WRITTEN AND REPRINTED WITH FINAL ROOM NUMBERS AND SPECIFIC LOAD INFORMATION. EXISTING LOADS SHALL BE INCLUDED IN THE NEW DIRECTORIES WITH FINAL ROOM NUMBERS AND SPECIFIC LOAD INFORMATION AND CAN NOT INDICATED EXISTING LOAD, EXISTING RECEPTACLE, ETC.
10. FURNISH AND INSTALL EXPANSION FITTINGS FOR ALL CONDUITS CROSSING BUILDING EXPANSION JOINT.

**KEYED NOTES**

1. POWER AND DATA OUTLET FOR OFCI MONITOR. VERIFY EXACT MOUNTING LOCATION AT JOB SITE.
2. INSTALL STEEL CASE THREAD POWER SYSTEM WITH NEMA MONUMENT CONNECTOR UNDER CARPET WITH INSIDE WALL MOUNTED OPTION. COORDINATE FINAL LOCATION WITH FURNITURE VENDOR AND ARCHITECT PRIOR TO INSTALLATION.
3. NEW LOCATION OF RELOCATED EXISTING 'VAV' POWER SUPPLY RECONNECT TO EXISTING 120 VOLT BRANCH CIRCUITING EXTEND AS REQUIRED. MATCH EXISTING.
4. FUNCTIONAL DEVICES PSH500A POWER SUPPLY FOR 'VAV' BOX POWER, 'VAV', 'RAV' AND 'EAV' BOXES. OUTPUTS SHALL BE LIMITED TO A MAXIMUM OF 3 BOXES. SEE SCHEMATIC ON THIS SHEET.
5. FURNISH AND INSTALL NEW SPLICE BOX WITH ILSCO NIMBUS SPLICES TO EXTEND EXISTING FEEDER WITH 3Ø600MCM, 1Ø250MCM IN 3 1/2" CONDUIT. VERIFY FEEDER SIZES AND NOTIFY ENGINEER OF DISCREPANCIES.
6. PROVIDE AN 'STI' EZ PATH RATED PATH-WAY ABOVE DOOR. SEE SPECIFICATIONS FOR ADDITIONAL 'STI' EZ PATH REQUIREMENT.
7. FURNISH AND INSTALL 3/4" LIGHT COLOR PAINTED AC GRADE PLYWOOD TO PERIMETER WALLS UP TO 8'-0" AFF. DO NOT PAINT OVER FIRE RATING LABELS.
8. SEE ABOVE CEILING TELECOM BOX INSTALLATION DETAIL ON THIS SHEET.
9. FURNISH AND INSTALL 2"x18" CABLE TRAY.
10. FURNISH AND INSTALL NEW 175A 3P BREAKER IN PANEL 'DP-W2NL'. SPLICE AND EXTEND SERVICE ELEVATOR FEEDER FROM EXISTING SPLICE BOX TO PANEL 'DP-W2NL'. SEE PARTIAL ONE LINE THIS SHEET.
11. DUPLEX RECEPTACLES FOR STACKED MICROWAVE. VERIFY EXACT MOUNTING LOCATION AT JOB SITE.
12. JUNCTION BOX FOR POWER CONNECTION TO SMOKE SHUTTER.
13. FURNISH AND INSTALL NEW CIRCUIT BREAKER SINGLE POLE 20 AMP 'GFCI' TYPE, IN EXISTING PANEL AS INDICATED.
14. MOTORIZED DOOR AND DOOR OPERATOR FURNISHED AND INSTALLED BY G.C., CONNECTED BY E.C.
15. CONNECT TO SPARE 20 AMP SINGLE POLE CIRCUIT BREAKER IN EXISTING PANEL AS INDICATED, UNLESS OTHERWISE NOTED.



**KEY PLAN**



AUSTIN P. STRIEKER  
 STATE LIC. 2014032649

**TREANORHL**  
 1511 Bellvue Ave.  
 Saint Louis, Missouri 63102  
 Office: 616.227.0900  
 Fax: 616.227.4692  
 www.treanorhl.com

**MCCLURE ENGINEERING**  
 1000 Clair Avenue  
 Saint Louis, Missouri 63102  
 T: 314-645-6232  
 www.mcclureeng.com

McClure Engineering  
 Professional Engineering Corporation  
 Missouri State Certificate of Authority #000087

**UNIVERSITY OF MISSOURI TEACHING HOSPITAL**  
**FITOUT SPACE 2W**  
 1 HOSPITAL DRIVE, COLUMBIA, MO 65212




REVISIONS		
NO	DESCRIPTION	DATE
1	RE-ISSUED IN ENTIRETY	08/10/21

**E202**  
 PARTIAL SECOND FLOOR PLAN - POWER  
 BID DOCUMENTS  
 Date: 08/10/2021  
 TreanorHL Project Number: HC0728.2101.00  
 MU Project Number: CP210701

S:\071625.000 UMC UMTH Renovate 2W03 Electrical\SWAMP\E203-071625.000.dwg 08/04/21 11:16 S.Freund

BIM 360:R:\020728 MU Teaching Hospital\UMTH\2-West\_Materials\_Swamp.rvt 5/27/2021 11:52:04 AM



**PARTIAL SECOND FLOOR PLAN - SYSTEMS**  
SCALE: 1/8" = 1'-0"


**GENERAL SYSTEMS NOTES:**

- NEW FIRE ALARM DEVICES TO BE SAME TYPE, MANUFACTURER AND COLOR AS EXISTING. MODIFY EXISTING FIRE ALARM SYSTEM AS REQUIRED FOR ADDITIONAL DEVICES.
- COORDINATE ALL SYSTEMS DEVICE LOCATIONS WITH ARCHITECTURAL PLANS AND ELEVATIONS PRIOR TO ROUGH-IN.
- PROVIDE ENGRAVED LABEL AT EACH DEVICE. REFERENCE SPECIFICATIONS.
- FIRE ALARM WIRING SHALL BE WIRED BACK TO FIRE ALARM POWER SUPPLY IN ELECTRICAL ROOM 2W50A.
- FURNISH AND INSTALL EXPANSION FITTINGS FOR ALL CONDUIT CROSSING BUILDING EXPANSION JOINT.


**KEYED NOTES:**

- INSTALL TWO STEEL CITY #82181T BOXES WITH SINGLE GANG MUD RINGS AND 1" BETWEEN THEM FOR HOMI CABLE ROUTING. MOUNT ONE JUNCTION BOX AT +24" AND ONE BEHIND MONITOR. COORDINATE FINAL ELEVATION AND LOCATION WITH OWNER.
- FINAL LOCATION OF RELOCATED AUDIOVISUAL FIRE ALARM DEVICE.
- FURNISH AND INSTALL 120 VOLT FIRE ALARM RATED RELAY FOR SMOKE SHUTTER. CONNECT TO EXISTING 'FACP' IN ELECTRICAL ROOM 2W50A.
- EXISTING SPEAKER TO BE RELOCATED TO NEW CEILING. EXTEND EXISTING WIRING AS REQUIRED. MATCH EXISTING.
- FURNISH AND INSTALL 120 VOLT FIRE ALARM RATED RELAY TO DISABLE AUTO DOOR. CONNECT TO EXISTING 'FACP' IN ELECTRICAL ROOM 2W50A.
- FURNISH AND INSTALL NEW AUDIOVISUAL FIRE ALARM DEVICE ON TEMPORARY CONSTRUCTION WALL. WHEN TEMPORARY CONSTRUCTION WALL IS REMOVED RELOCATE FIRE ALARM DEVICE. SEE KEYED NOTE #7 THIS SHEET.

**ACCESS CONTROL ROUGH-IN DIAGRAM**  
SCALE: NO SCALE



**NOTES:**  
1. DETAIL IS DIAGRAMMATIC ONLY AND MAY NOT REPRESENT ACTUAL DEVICES/QUANTITY OF DEVICES REQUIRED. COORDINATE ALL REQUIREMENTS WITH ACTUAL DOOR HARDWARE PROVIDED AND ARCHITECTURAL DRAWINGS.  
2. RECESS JUNCTION BOXES, SIZED TO MEET MANUFACTURER REQUIREMENTS IN LOCATIONS SHOWN UNLESS OTHERWISE NOTED. PROVIDE BLANK COVERPLATES FOR UNUSED JUNCTION BOXES.  
3. EACH DOOR REQUIRING ACCESS CONTROL MUST BE PROVIDED WITH ONE (1) 18/6 SHIELDED AND ONE (1) 2/6 SHIELDED CABLE, PULLED TO ACCESS PANEL LOCATION.



**SMOKE DETECTOR REMOTE TEST STATION ENGRAVING**

**NOTE:** PROVIDE DUCT DETECTOR TEST SWITCH FOR EACH DUCT DETECTOR. FOR DUCT DETECTORS ASSOCIATED WITH SMOKE AND FIRE/SMOKE DAMPERS, TEST SWITCH SHALL BE LOCATED ADJACENT TO DAMPER APPROXIMATELY 4' ABOVE CEILING TILE. LOCATION OF TEST SWITCH SHALL BE COORDINATED WITH ALL OTHER ABOVE CEILING UTILITIES AND SHALL BE FULLY ACCESSIBLE. IN AREAS EXPOSED TO STRUCTURE (NO CEILING) MOUNT AT 75' AFF.

**TREANORHL**  
AUSTIN P. STRIEKER  
STATE LIC. 2014032649  
PROFESSIONAL ENGINEER

**MCCLEURE ENGINEERING**  
1000 Clark Avenue  
Saint Louis, Missouri 63102  
T 314-646-6522  
www.mccleure.com

UNIVERSITY OF MISSOURI TEACHING HOSPITAL  
**FITOUT SPACE 2W**  
1 HOSPITAL DRIVE, COLUMBIA, MO 65212



**REVISIONS**

NO	DESCRIPTION	DATE
RE-ISSUED IN ENTIRETY		08/10/21

**E203**


PARTIAL SECOND FLOOR PLAN - SYSTEMS

BID DOCUMENTS

Date: 08/10/2021

TreanorHL Project Number: HC0728.2101.00

MU Project Number: CP210701



**KEY PLAN**