

CODE REVIEW INFORMATION

FACILITY NAME AND ADDRESS:
UNIVERSITY OF MISSOURI PHYSICIANS BUILDING
1020 HTT STREET
COLUMBIA, MO 65212

TYPE OF CONSTRUCTION:
RENOVATION OF EXISTING FACILITY

AUTHORITY HAVING JURISDICTION:
UNIVERSITY OF MISSOURI SYSTEM

CITY, COUNTY, STATE:
CITY OF COLUMBIA
BOONE COUNTY
STATE OF MISSOURI

ARCHITECT:
bcd DESIGN GROUP
12101 W 110th STREET, SUITE 100
OVERLAND PARK, KS 66210

APPLICABLE CODES/REGULATIONS:
2021 INTERNATIONAL BUILDING CODE
2021 INTERNATIONAL PLUMBING CODE
2021 INTERNATIONAL MECHANICAL CODE
2021 EXISTING BUILDING CODE (FOR LEVEL 1 & LEVEL 2 ALTERATION ONLY WITH PRE-APPROVAL FROM THE AHJ)
2021 INTERNATIONAL FIRE CODE
2021 INTERNATIONAL FUEL GAS CODE
2017 ICC A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES
NATIONAL ELECTRIC CODE/NFPA 70 - 2020
NFPA 110 STANDARD FOR EMERGENCY AND STANDBY POWER SYSTEMS - 2019
NFPA 101 LIFE SAFETY CODE - 2012
NFPA 99 STANDARD FOR HEALTH CARE FACILITIES - 2012
NFPA 90A INSTALLATION OF AIR CONDITIONING AND VENTILATING SYSTEMS - 2018
NFPA 75 STANDARD FOR THE FIRE PROTECTION OF INFORMATION TECHNOLOGY EQUIPMENT - 2017
NFPA 72 NATIONAL FIRE ALARM CODE - 2019
NFPA 518 STANDARD FOR FIRE PROTECTION DURING WELDING, CUTTING AND OTHER HOT WORK - 2019
NFPA 65 STANDARD ON FIRE PROTECTION FOR LABORATORIES USING CHEMICAL - 2019
NFPA 20 STANDARD FOR THE INSTALLATION OF STATIONARY FIRE PUMPS FOR FIRE PROTECTION - 2019
NFPA 13 INSTALLATION OF FIRE SPRINKLER SYSTEMS - 2019
ASHRAE 62.1 - VENTILATION FOR ACCEPTABLE INDOOR AIR QUALITY - 2019
ASHRAE 90.1 ENERGY STANDARD FOR BUILDINGS - 2019
ASHRAE 170 - VENTILATION OF HEALTH CARE FACILITIES - 2017
ASME A17.1 - SAFETY CODE FOR ELEVATORS AND ESCALATORS (PER STATE OF MISSOURI) - 2011
AMERICANS WITH DISABILITIES ACT - STANDARD FOR ACCESSIBLE DESIGN 2010
FACILITY GUIDELINES INSTITUTE - 2018


CONSTRUCTION TYPE (EXISTING):
IBC TYPE II-A

ALLOWABLE BUILDING HEIGHT AREA:
UNLIMITED
RENOVATED AREA: 2,972 SF

OCCUPANCY:
GROUP B (EXISTING REMODEL)

FIRE SUPPRESSION:
FULLY SPRINKLED
ACTIVE FIRE SAFETY SYSTEMS:
EXISTING BUILDING IS FULLY SPRINKLED
OCCUPANCY LOAD:
B BUSINESS AREA: 2,972 SF / 100 SF PER PERSON = 29.7
TOTAL OCCUPANT LOAD: 30 OCCUPANTS
EGRESS WIDTH:
30 OCCUPANTS X 2' = 6'
GENERAL BUILDING DATA (EXISTING):
GROUND FLOOR AREA OF WORK: 2,972 SF RENOVATION
STRUCTURAL FIRE PROTECTION:
ITEM: EXISTING:
EXTERIOR BEARING WALLS NA
INTERIOR BEARING WALLS NA
EXTERIOR NON-BEARING WALLS NA
STRUCTURAL FRAME NA
SHAFT ENCLOSURES NA
FLOORS NA
ROOF NA
EXTERIOR OPENINGS NA
STAIRWAY CONSTRUCTION 2 HOUR

CODE LEGEND



STATEMENT OF ARCHITECTURAL SPECIAL INSTRUCTIONS

A. THE ARCHITECTURAL DESIGN FOR THIS PROJECT IS BASED ON COMPLETION OF SPECIAL INSPECTIONS DURING CONSTRUCTION IN ACCORDANCE WITH SECTION 1705 OF THE INTERNATIONAL BUILDING CODE. THE OWNER SHALL EMPLOY ONE OR MORE QUALIFIED SPECIAL INSPECTORS TO PROVIDE THE REQUIRED SPECIAL INSPECTIONS.
B. THE SPECIAL INSPECTOR SHALL FURNISH INSPECTION REPORT TO THE BUILDING OFFICIAL, OWNER, ARCHITECT AND ANY OTHER DESIGNATED PERSON.
C. ALL DISCREPANCIES SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE CONTRACTOR FOR CORRECTION. THEN, IF UNCORRECTED, TO THE PROPER DESIGN AUTHORITY OR BUILDING OFFICIAL.
D. THE SPECIAL INSPECTOR SHALL SUBMIT A FINAL SIGNED REPORT STATING THAT THE WORK REQUIRING SPECIAL INSPECTIONS WAS TO THE BEST OF THE INSPECTOR'S KNOWLEDGE, IN CONFORMANCE WITH THE APPROVED PLANS AND SPECIFICATIONS AND THE APPLICABLE WORKMANSHIP PROVISIONS OF THE BUILDING CODE.
E. THE FOLLOWING INSPECTIONS AND TESTS ARE REQUIRED WITH THE FREQUENCY (CONTINUOUS OR PERIODIC) AS DEFINED WITHIN THE REFERENCED SECTION OR STANDARD LISTED BELOW. THE GENERAL CONTRACTOR SHALL PROVIDE NOTIFICATION TO THE INSPECTOR WHEN ITEMS REQUIRING INSPECTION ARE READY TO BE INSPECTED AND PROVIDE ACCESS FOR THOSE INSPECTIONS.
1. FIRE RESISTANT PENETRATIONS & JOINTS PER SECTION 1705.17.

GENERAL CODE NOTES PER MUHC PDCC

1. ALL PENETRATION (NEW OR EXISTING) SHALL BE SEALED AT ALL TIMES, EXCEPT WHEN ACTIVELY WORKING WITH THE PENETRATION. EXISTING UNSEALED PENETRATIONS, ONCE ENCOUNTERED, SHALL BE SEALED IMMEDIATELY WITH THE APPROPRIATE FIRE/SMOKE STOPPING MATERIAL. COORDINATE THE SEALING METHOD, WHETHER TEMPORARY OR PERMANENT, WITH THE OWNER'S REPRESENTATIVE.
2. EXISTING EXITS MUST REMAIN ACCESSIBLE. CLEAR PATHS OF TRAVEL TO EXITS MUST BE MAINTAINED WITHIN THE CONSTRUCTION LIMITS. CONTRACTOR IS TO COORDINATE WITH OWNER'S REPRESENTATIVE TO MAINTAIN PROPER EXIT SIGNAGE THROUGHOUT CONSTRUCTION.
3. EACH SMOKE AND/OR FIRE RATED PARTITION SHALL BE STENCILED WITH 4 INCH LETTERS DIRECTLY ABOVE CEILING TILE SO AS TO IDENTIFY RATED CONSTRUCTION UPON LIFTING OF CEILING TILES. WALLS ARE TO HAVE STENCILED FIRE RATINGS AT EIGHT FOOT INTERVALS HORIZONTALLY.




1 GROUND FLOOR - CODE PLAN
3/32" = 1'-0"

INFECTION CONTROL LEGEND:


INFECTION CONTROL BARRIER | RIGID BARRIER - MODULAR SYSTEM
THE BARRIER SHALL EXTEND FROM THE FLOOR TO THE CEILING AND SHALL BE CONSTRUCTED UTILIZING 3/8" METAL STUDS AND 1/2" OR 3/8" GYPSUM BOARD ON THE CLEAN SIDE OF THE STUDS. THE METAL STUDS SHALL BE PLACED AT NO LESS THAN 16" AND NO MORE THAN 24" O.C. THE SEAMS AND JOINTS ON THE GYPSUM BOARD MUST BE SEALED WITH AN APPROVED TAPE OR WITH JOINT COMPOUND. THE BARRIER SHALL BE ADEQUATELY SEALED AND MAINTAINED AT THE FLOOR AND CEILING CONNECTIONS THROUGHOUT THE PROJECT TO PREVENT THE MIGRATION OF DUST FROM THE WORK AREA INTO ADJACENT OCCUPIED AREAS. AIR FILTRATION EQUIPMENT EXHAUST/VENT HOSE MAY PASS THROUGH THE UPPER PORTION OF THE BARRIER. THE PENETRATION OPENING FOR THE EXHAUST/VENT HOSE SHALL BE ADEQUATELY SEALED AND MAINTAINED THROUGHOUT THE PROJECT. THE BARRIER SHALL BE EQUIPPED WITH A DOOR/FRAME ASSEMBLY. THE ASSEMBLY IS NOT REQUIRED TO BE FIRE-RATED, HOWEVER, MUST BE HINGED SWING-TYPE, A MINIMUM WIDTH OF 36" AND BE SOLID WOOD OR METAL CLAD WITH A METAL FRAME. THE DOOR SHALL BE EQUIPPED WITH A COMMERCIAL GRADE LEVER HANDLE WITH A REMOVABLE KEY CORE. THE HARDWARE MUST BE POSITIVE LATCHING AND ACCEPT A BEST 7-PIN CORE, WHICH WILL BE PROVIDED AND INSTALLED BY UNIVERSITY OF MISSOURI HEALTHCARE. A DOOR SWEEP MAY BE REQUIRED. THE BARRIER DOOR SHALL REMAIN CLOSED AND LOCKED DURING THE WORK PERIOD.
THE BARRIER SHALL ALSO INCLUDE A BARRIER CONSTRUCTED OF 6 OR 10-MIL FIRE-RESISTANT POLYETHYLENE EXTENDING FROM THE CEILING TO DECK DIRECTLY ABOVE THE RIGID BARRIER. IF NECESSARY, NON-COMBUSTIBLE COMPONENTS SHALL BE UTILIZED TO SUPPORT THE POLYETHYLENE. THE BARRIER SHALL BE ADEQUATELY SEALED AT THE DECK AND CEILING CONNECTIONS AND AT ALL PENETRATIONS IN THE BARRIER TO PREVENT THE MIGRATION OF DUST FROM THE WORK AREA INTO ADJACENT AREAS.
OP-5: THE BARRIER SHALL BE CONSTRUCTED OF 6 OR 10-MIL FIRE-RESISTANT POLYETHYLENE EXTENDING FROM THE CEILING TO DECK DIRECTLY ABOVE THE RIGID BARRIER. IF NECESSARY, NON-COMBUSTIBLE COMPONENTS SHALL BE UTILIZED TO SUPPORT THE POLYETHYLENE. THE BARRIER SHALL BE ADEQUATELY SEALED AT THE DECK AND CEILING CONNECTIONS AND AT ALL PENETRATIONS IN THE BARRIER TO PREVENT THE MIGRATION OF DUST FROM THE WORK AREA INTO ADJACENT AREAS.
OP-6: THE BARRIER SHALL BE CONSTRUCTED OF 6 OR 10-MIL FIRE-RESISTANT POLYETHYLENE. BE INSTALLED ON BOTH SIDES OF THE DOOR OPENING, AND COVER THE OPENING COMPLETELY. THE BARRIER SHALL BE ADEQUATELY SEALED AROUND THE PERIMETER OF THE DOOR OPENING AND MAINTAINED THROUGHOUT THE PROJECT TO PREVENT THE MIGRATION OF DUST FROM THE WORK AREA INTO ADJACENT OCCUPIED AREAS. THE DOOR SHALL REMAIN CLOSED THROUGHOUT THE PROJECT AND THERE SHALL BE NO PENETRATIONS IN THE BARRIER.

INFECTION CONTROL PLAN KEYNOTES:


1 FLOOR TO BE PATCHED AND REPAIRED AFTER NORMAL BUSINESS HOURS



2 GROUND FLOOR - INFECTION CONTROL
3/32" = 1'-0"



KEYPLAN
1" = 60'-0"



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201002790

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
University Physicians Medical Building - Ground Floor CHCC Clinic Renovation
University of Missouri, Columbia, Missouri



Issue Date: 08.29.2022
Issue: Date:

Drawn by: CG
bcdg Project #: 12275.27
MU Project #: CP202091

G100
CODE PLAN + IC



bcDESIGN GROUP


12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123

MO Certificate of Authority Number
A-201100729

Project Team:

ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119




KEYPLAN
1" = 60'-0"

FLOOR PLAN LEGEND:



	NEW DOOR		DRAWING NUMBER
	EXISTING DOOR		DENOTES SIMILAR DRAWING
	NEW WALL		CONDITION
	EXISTING WALL		SHEET NUMBER
	CURTAIN TRACK		
	ROOM NAME		
	ROOM NUMBER		
	ELEVATION TAGS		
	BUILDING SECTION TAG		
	ENLARGED DRAWING TAG		
	PLAN KEYNOTE		
	EQUIPMENT TAG		
	DOOR TAG		
	PARTITION WALL TAG		

GENERAL FLOOR PLAN NOTES


1. ALL NEW INTERIOR PARTITIONS ARE TO BE 'AIDN' UNLESS NOTED OTHERWISE, RE COVER
2. ALL INTERIOR DOORS TO BE 3'-8" x 7'-0" x 1-3/4" SOLID CORE WOOD DOORS PER SPEC, UNLESS NOTED OTHERWISE, RE 23/A200 FOR TYPICAL FRAME DETAIL
3. ALL DIMENSIONS ARE TO FACE OF FINISHED WALL, GC TO NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO BEGINNING WORK IN THE AFFECTED AREAS
4. RADIUS OUTSIDE CORNERS OF ALL COUNTERTOPS 1-1/2" TYPICAL
5. DIMENSIONS SHOWN IN BRACKETS ARE CRITICAL AND MUST BE MAINTAINED
6. INSTALL METAL STRAP BLOCKING AT ALL ITEMS SHOWN TO BE MOUNTED TO WALLS, INCLUDING BUT NOT LIMITED TO WALL STOPS, CASEWORK, & GRAB BARS. STRAPS SHALL EXTEND A MINIMUM OF 3 STUDS TYPICAL
7. ALL OFICI ITEMS LOCATIONS ARE TO BE COORDINATED WITH THE OWNER
8. FIELD VERIFY EXISTING INTERIOR WALLS GO TO DECK



3 GROUND FLOOR CONTRACTOR ACCESS



2 FIRST FLOOR CONTRACTOR ACCESS



Project Title:

University Physicians Medical Building - Ground Floor CHCC Clinic Renovation

University of Missouri, Columbia, Missouri



Issue Date: 08.29.2022


Drawn by: Author

bcdg Project #: 12275.291


MU Project #: CP202091

G101


CONTRACTOR ACCESS



5 TYPICAL SLAB REPAIR
1/4" = 1'-0"




3 GROUND FLOOR PLAN - ENLARGED EXAM TYP.
1/4" = 1'-0"



4 GROUND FLOOR PLAN - ENLARGED ECHO TYP.
1/4" = 1'-0"

DEMOLITION PLAN LEGEND



FLOOR/WALL/CEILING NOTES

- FLOOR**
- F1 - REMOVE EXISTING FLOORING, BASE, GUE, ETC. TO SLAB. PATCH, PRIME, AND PREP SUB-FLOOR TO RECEIVE NEW FLOORING AS SCHEDULED.
- F2 - EXISTING FLOOR TO REMAIN
- F3 - SPECIAL CONDITION - REFER TO KEYNOTE
- WALL**
- W1 - REMOVE EXISTING WALL COVERINGS, REMOVE PAINT, ETC. PATCH, PRIME, AND PRIME WALL TO RECEIVE NEW FINISHES AS SCHEDULED.
- W2 - EXISTING WALL TO REMAIN
- W3 - SPECIAL CONDITION - REFER TO KEYNOTE
- CEILING**
- C1 - REMOVE EXISTING CEILING, HANGERS, ETC. TO BOTTOM OF STRUCTURE. EXERCISE EXTREME CAUTION AS TO NOT DISTURB SYSTEMS INTENDED TO REMAIN.
- C2 - EXISTING CEILING TO REMAIN
- C3 - SPECIAL CONDITION - REFER TO KEYNOTE


DEMOLITION KEYNOTES:

- 1 SAW CUT EXISTING CONCRETE SLAB FOR INSTALLATION OF NEW WASTE PIPING SERVING GROUND FLOOR PLUMBING FIXTURE. PATCH CONCRETE FLOOR TO MATCH EXISTING SURROUNDING SURFACES. RE PLUMBING FOR EXACT LOCATIONS. RE: S/A100 FOR INFILL DETAIL
- 2 DEMO CARPET TILE TO EXTENTS SHOWN
- 3 DEMO AND REMOVE CASEWORK INCLUDING BASE CABINETS, COUNTER TOP, AND UPPER CABINETS
- 4 DEMO AND REMOVE PLUMBING FIXTURES. RE: PLUMBING
- 5 LIGHTLY SAND TO PREP WALL FOR NEW PAINT
- 6 RE: RCP FOR DIMENSION OF EXTENT OF NEW CEILING

GENERAL DEMOLITION PLAN NOTES

- CONTRACTOR SHALL CONTACT PLANT OPERATIONS DAILY TO PROVIDE ACTIVITIES AND SHUTDOWN REPORTS. ALL SITE USE SHALL BE COORD. AND APPROVED IN ADVANCE BY OWNER.
- CONTRACTOR IS TO FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO BEGINNING WORK. REPORT ANY DISCREPANCIES TO ARCHITECT IN WRITING PRIOR TO BEGINNING WORK IN THE AFFECTED AREA.
- CONTRACTOR TO VERIFY ALL EXISTING BUILDING SYSTEMS CURRENTLY INSTALLED IN THE CONSTRUCTION AREA. ALL DEVICES TO REMAIN SHALL BE CHECKED AND IN WORKING CONDITION WHEN PROJECT IS COMPLETE.
- CONTRACTOR SHALL EMPLOY REASONABLE MEANS TO CONTAIN DUST, DEBRIS, AND NOISE DUE TO DEMOLITION AND NEW CONSTRUCTION. REFER TO SPEC.
- ALL WALL MOUNTED ITEMS, ETC., SHALL BE REMOVED & REINSTALLED AS INDICATED THROUGHOUT THE DRAWINGS OR TURNED OVER TO THE OWNER FOR SALVAGE U.N.O.
- CONTRACTOR SHALL PATCH TO MATCH SURROUNDING FINISHES. ANY AREAS DAMAGED AS A RESULT OF, OR CAUSED BY, THE WORK INDICATED THROUGHOUT THE CONTRACT DOCUMENTS.
- WHERE REMOVAL OF EXISTING WALL PARTITIONS, EQUIPMENT, ETC., DISRUPTS OR DISTURBS EXISTING ELECTRICAL, MECHANICAL, OR PLUMBING SERVICES TO AREAS NOT DESIGNATED AS CONSTRUCTION AREAS, CONTRACTOR SHALL PROVIDE TEMPORARY CONNECTIONS AS REQUIRED TO ENSURE UNINTERRUPTED SERVICE TO SAID AREAS. NOTE: NO SERVICE IS TO BE SHUT DOWN WITHOUT PRIOR APPROVAL BY OWNER.
- CONTRACTOR IS TO REMOVE COMPLETELY EXISTING CONSTRUCTION AS SHOWN HEREIN, WHICH CONFLICTS WITH THE INTENT OF THE NEW CONSTRUCTION. U.N.O. OWNER WILL BE RESPONSIBLE FOR REMOVING AND STORING ITEMS SUCH AS FURNITURE, PLAQUES, ARTWORK, MOVEABLE EQUIPMENT, ETC.
- REFER TO MEP DRAWINGS FOR ADDITIONAL DEMOLITION WORK. PATCH & MATCH SURROUNDING MATERIALS WHERE ITEMS ARE REMOVED AT WALLS, CEILING AND FLOORS. MAINTAIN FIRE RATINGS WHERE DEMOLISHED ITEMS PENETRATED FIRE RATED WALLS AND FLOORS.
- REMOVE AND REPLACE CEILING TILES AS NECESSARY FOR DEMOLITION AND NEW CONSTRUCTION. REPLACE DAMAGED TILES AS REQUIRED.
- CONTRACTOR TO REMOVE, CLEAN AND STORE ALL PLUMBING FIXTURES SHOWN TO BE REMOVED. ALL FIXTURES TO BE TURNED OVER TO OWNER, U.N.O.

FLOOR PLAN LEGEND



GENERAL FLOOR PLAN NOTES

- ALL NEW INTERIOR PARTITIONS ARE TO BE 'AIDN' UNLESS NOTED OTHERWISE. RE: COVER
- ALL INTERIOR DOORS TO BE 3'-8" x 7'-0" x 1-3/4" SOLID CORE WOOD DOORS PER SPEC. UNLESS NOTED OTHERWISE. RE: S/A100 FOR TYPICAL FRAME DETAIL.
- ALL DIMENSIONS ARE TO FACE OF FINISHED WALL. C/C TO NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO BEGINNING WORK IN THE AFFECTED AREA.
- RADIUS OUTSIDE CORNERS OF ALL COUNTERTOPS 1-1/2" TYPICAL.
- DIMENSIONS SHOWN IN BRACKETS ARE CRITICAL AND MUST BE MAINTAINED.
- INSTALL METAL STRAP BLOCKING AT ALL ITEMS SHOWN TO BE MOUNTED TO WALLS, INCLUDING BUT NOT LIMITED TO WALL STOPS, CASEWORK, & GRAB BARS. STRAPS SHALL EXTEND A MINIMUM OF 3 STUDS TYPICAL.
- ALL CFCI ITEMS LOCATIONS ARE TO BE COORDINATED WITH THE OWNER.
- FIELD VERIFY EXISTING INTERIOR WALLS GO TO DECK.

EQUIPMENT LIST:

E#	ITEM	FURNISHED BY/INSTALLED BY
E01	TELEVISION W/ MOUNTING BRACKET	OFCI, OFCI
E02	NOT USED	
E03	REFRIGERATOR	OFCI
E04	MICROWAVE	OFCI
E05	WORKSTATION: DUAL MONITORS AND KEYBOARD	OFCI
E06	COUNTERTOP PRINTER	OFCI
E07	SHRED-IT	OFCI
E08	NOT USED	
E09	EKG MACHINE	OFCI
E10	LINEN HAMPER W/ LID	OFCI
E11	BOOKSHELF	OFCI
E12	WELCH-ALLYN	OFCI
E13	ERGONOMIC CHAIR	OFCI
E14	SCALE	OFCI
E15	WHEELCHAIR SCALE	OFCI
E16	INFANT SCALE	OFCI
E17	V6 COMPUTER CHARTING STATION	OFCI
E18	CRASH CART	OFCI
E19	TREADMILL	OFCI
E20	TREADMILL COMPUTER	OFCI
E21	MOBILE VITAL MACHINES	OFCI
E22	MOBILE PEDESTALS	OFCI

KEYPLAN


1" = 60'-0"

FLOOR PLAN KEYNOTES:

- SOAP DISPENSER, OFCI
- PAPER TOWEL DISPENSER, OFCI
- MIRROR, CFCI
- DIAPER CHANGING STATION, CFCI
- GRAB BARS 18", CFCI
- FEMININE NAPKIN DISPOSAL, CFCI
- TOILET PAPER DISPENSER, CFCI
- GEL DISPENSER, OFCI
- TRASH GRAMMET
- REFER TO ECHO ROOM 0102H FOR TYPICAL ROOM NOTES, U.N.O. RE: 4/A100
- REFER TO EXAM 0102A FOR TYPICAL ROOM NOTES, U.N.O. RE: 3/A100
- INFILL WALL TO MATCH ADJACENT EXISTING WALL CONSTRUCTION
- EXISTING DOOR TO RECEIVE NEW HARDWARE, RE: SPEC HARDWARE SET #2
- NOT USED
- PUSH FOR HELP, OFCI
- CODE BLUE, OFCI
- NURSE CALL, OFCI
- GRAB BARS 36", CFCI
- GRAB BARS 48", CFCI
- SEMI-RECESSED FIRE EXTINGUISHER CABINET PER SPEC



1 GROUND FLOOR DEMO PLAN
1/8" = 1'-0"



2 GROUND FLOOR PLAN - NOTED
1/8" = 1'-0"



bcDESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123

MO Certificate of Authority Number
A-201103729

Project Team:

ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
University Physicians Medical Building - Ground Floor CHCC Clinic Renovation
University of Missouri, Columbia, Missouri




Issue Date: 08.29.2022
Issue: Date:

Drawn by: CG

bcdg Project #: 12275.27
MU Project #: CP202091

A100

FLOOR PLAN + DEMO PLAN




KEYPLAN
1" = 60'-0"

FLOOR PLAN LEGEND:

TAG	DESCRIPTION	DRAWING NUMBER	CONDITION	SIMILAR DRAWING SHEET NUMBER
	NEW DOOR			
	EXISTING DOOR			
	NEW WALL			
	EXISTING WALL			
	CURTAIN TRACK			
	ROOM NAME			
	ROOM NUMBER			
	ELEVATION TAGS			
	BUILDING SECTION TAG			
	ENLARGED DRAWING TAG			
	PLAN KEYNOTE			
	EQUIPMENT TAG			
	DOOR TAG			
	PARTITION WALL TAG			

GENERAL FLOOR PLAN NOTES

1. ALL NEW INTERIOR PARTITIONS ARE TO BE 'AIDN' UNLESS NOTED OTHERWISE. RE: COVER
2. ALL INTERIOR DOORS TO BE 3'-8" x 7'-0" x 1-3/4" SOLID CORE WOOD DOORS PER SPEC, UNLESS NOTED OTHERWISE. RE: 23/A600 FOR TYPICAL FRAME DETAIL.
3. ALL DIMENSIONS ARE TO FACE OF FINISHED WALL. GC TO NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO BEGINNING WORK IN THE AFFECTED AREAS.
4. RADIUS OUTSIDE CORNERS OF ALL COUNTERTOPS 1-1/2" TYPICAL.
5. DIMENSIONS SHOWN IN BRACKETS ARE CRITICAL AND MUST BE MAINTAINED.
6. INSTALL METAL STRAP BLOCKING AT ALL ITEMS SHOWN TO BE MOUNTED TO WALLS, INCLUDING BUT NOT LIMITED TO WALL STOPS, CASEWORK, & GRAB BARS. STRAPS SHALL EXTEND A MINIMUM OF 3 STUDS, TYPICAL.
7. ALL OFCI ITEMS LOCATIONS ARE TO BE COORDINATED WITH THE OWNER.
8. FIELD VERIFY EXISTING INTERIOR WALLS GO TO DECK.



1 GROUND FLOOR PLAN - DIMENSIONED
1/8" = 1'-0"



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-2011002790

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119


Project Title:
University Physicians Medical Building - Ground Floor CHCC Clinic Renovation
University of Missouri, Columbia, Missouri



Issue Date: 08.29.2022
Issue: Date:

Drawn by: Author
bcdg Project #: 12275.27
MU Project #: CP202091


A101
GROUND FLOOR PLAN - DIMENSIONED
BID SET




4 RCP SOFFIT
1" = 1'-0"

5 RCP SOFFIT AGAINST WALL
1" = 1'-0"

6 RCP SOFFIT NURSE STATION
1" = 1'-0"




3 GROUND FLOOR LVT LAYOUT
1/8" = 1'-0"



1 GROUND FLOOR RCP
1/8" = 1'-0"

REFLECTED CEILING PLAN LEGEND




GENERAL FINISH NOTES

1. WALL FINISHES, AS INDICATED, ARE TO BE FULL HEIGHT (FLOOR TO CEILING) UNLESS NOTED OTHERWISE.
2. CHANGES OF COLOR SHALL OCCUR AT INSIDE CORNERS. DO NOT CHANGE ON AN OUTSIDE CORNER UNLESS OTHERWISE NOTED.
3. THE FOLLOWING ITEMS, EXCEPT WHERE NOTED OTHERWISE, SHALL BE FINISHED TO MATCH ADJACENT COLOR: ELECTRICAL PANELS, AIR GRILLES, LOCKERS, AND ACCESS PANELS.
4. PAINT FINISH ON DRYWALL SURFACES TO BE "SATIN" OR EQUIVALENT FINISH UNLESS NOTED OTHERWISE. SEE SPECIFICATIONS FOR PAINT FINISH ON OTHER SURFACES.
5. ALL SURFACES OF THE SOFFITS (BOTH VERTICAL AND HORIZONTAL PLANES) SHALL BE FINISHED AS NOTED IN THE REFLECTED CEILING PLAN OR ELEVATIONS.
6. PAINT ALL TRIM, CASINGS, DOORS, WINDOWS, AND OTHER WOODWORK TO WALL AND ADJACENT MATERIALS WITH APPROPRIATE PAINTABLE CALK PRIOR TO PAINTING. SAND AND PREP ALL WOODWORK, WINDOWS, DOORS, ETC. PRIOR TO FINISHING FOR A CLEAN, SMOOTH FINISH. ALL INTERIOR CASING SHALL MATCH ADJACENT SURFACES UNLESS NOTED OTHERWISE.
7. PROVIDE APPROPRIATE SCHLUTER BRUSHED BRASS AT ALL TILE TERMINATIONS AND TRANSITIONS. FINISH TO BE SATIN ANOZONIZED.
8. ALL TRANSITION STRIP COLORS TO BE SELECTED BY THE ARCHITECT. CONTRACTOR SHALL BE RESPONSIBLE FOR THE SUPPLY AND INSTALLATION OF ALL TRANSITIONS NECESSARY FOR CHANGES IN FLOOR FINISH.
9. SEE ELEVATIONS AND DETAILS FOR FINISH PLACEMENT. HARDWARE SELECTION NOTED IN THE FINISH SCHEDULE.
10. FLOORING TO REMAIN CLEAN AND PROTECTED UNDER CONSTRUCTION.
11. "N/F" MEANS "NO FINISH REQUIRED".
12. "E/F" MEANS "EXISTING TO REMAIN".
13. "E" MEANS "EXISTING".
14. "C" MEANS "SEALED CONCRETE".
15. DO NOT USE A SECTION OF RUBBER BASE LESS THAN 48" IN LENGTH UNLESS THE WALL ON WHICH THE BASE OCCURS IS LESS THAN 48".
16. FOR ALL CASEWORK, A SET OF SUBMITTALS MUST BE GIVEN TO THE ARCHITECT AND/OR INTERIOR DESIGNER FOR APPROVAL. RECEIVE APPROVAL BEFORE FABRICATION.
17. WHERE TWO OR MORE FLOORING FINISHES ARE CALLED OUT PER ROOM, SEE THE FINISH FLOOR PLAN FOR PATTERN AND CLARIFICATION.
18. RESTROOMS, EXAM ROOMS AND OFFICES ARE ALL CONSIDERED "TYPICAL" - SEE ENLARGED PLANS AND ELEVATIONS FOR FINISHES AND FINISH PLACEMENT FOR THESE ROOMS.
19. WHERE TWO OR MORE WALL FINISHES ARE CALLED OUT PER ROOM, SEE THE FINISH FLOOR PLAN AND/OR ELEVATIONS FOR CLARIFICATION. ACCENT PAINT COLORS ARE SHOWN ON THE FINISH PLAN. ALL OTHER WALLS TO BE PT1.
20. ALL FLOOR FINISH TRANSITIONS ARE TO OCCUR AT THE CENTERLINE OF THE DOOR WHEN THE DOOR IS IN CLOSED POSITION.
21. ALL CORNER GUARDS TO BE CG1. SEE MATERIALS LEGEND.

REFLECTED CEILING PLAN NOTES

1. CONTRACTOR IS TO FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO BEGINNING WORK. REPORT ANY DISCREPANCIES TO ARCHITECT IN WRITING BEFORE BEGINNING WORK IN AFFECTED AREAS.
2. CONTRACTOR SHALL VERIFY ALL EXISTING BUILDING SYSTEMS CURRENTLY INSTALLED IN THE CONSTRUCTION AREA. ALL DEVICES SHALL BE CHECKED AND IN WORKING CONDITION UPON COMPLETION OF THE PROJECT.
3. ALL DIMENSIONS ARE TO FACE OF FINISHED WALL OR FACE OF MASONRY, NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO BEGINNING WORK IN AFFECTED AREAS.
4. "ALIGN" AS USED THROUGHOUT THESE DOCUMENTS IS UNDERSTOOD TO MEAN FINISH SURFACE OF NEW CONSTRUCTION SHALL MEET FINISH SURFACE OF EXISTING CONSTRUCTION IN A NEAT AND SMOOTH MANNER PROVIDING A FLUSH FINISHABLE SURFACE.
5. REFER TO MEP DRAWINGS FOR ADDITIONAL INFORMATION AND WORK, INCLUDING, BUT NOT LIMITED TO, DIFFUSERS, GRILLES, LIGHTS, ETC.
6. ALL CEILING ARE TO 8'-3" ACT. 1" AFF. UNLESS NOTED OTHERWISE.
7. REFER TO MEP DRAWINGS FOR ABOVE CEILING WORK RELATED TO THIS PROJECT. REMOVE TILE AS NEEDED TO INSTALL NEW MEP ITEMS AND PATCH ANY DAMAGED MATERIAL CAUSED FROM NEW INSTALLATION. COORDINATE SCHEDULE W/ BUILDING PRIOR TO START OF WORK.
8. UNLESS NOTED OTHERWISE, SOFFIT PAINT TO MATCH WALL ON WHICH IT OCCURS.
9. REINSTALL CEILING TILES SHOWN TO BE REMOVED FOR INSTALLATION OF NEW ELEC. WORK. REPLACE TILES IF DAMAGED.

FINISH LEGEND:




FINISH KEYNOTES:

1. FLOORING TRANSITION
2. PATCH AND REPAIR FINISHES WITH EXISTING.
3. WALL PROTECTION TO 48" AFF.

MATERIALS LEGEND

- LUXURY VINYL TILE**
- LV1** MANUFACTURER: MANNING COMMERCIAL, COLLECTION: COLOR ANCHOR LVT, PATTERN: STRIKE, COLOR: COTTONTAIL C138, SIZE: 6" X 36", INSTALLATION METHOD: SEE FINISH PLAN FOR PATTERN DIRECTION
 - LV2** MANUFACTURER: MANNING COMMERCIAL, COLLECTION: COLOR ANCHOR LVT, PATTERN: STRIKE, COLOR: BIG WAVE C170, SIZE: 6" X 36", INSTALLATION METHOD: SEE FINISH PLAN FOR PATTERN DIRECTION
 - LV3** MANUFACTURER: MANNING COMMERCIAL, COLLECTION: COLOR ANCHOR LVT, PATTERN: STRIKE, COLOR: HALE THISTLE C121, SIZE: 6" X 36", INSTALLATION METHOD: SEE FINISH PLAN FOR PATTERN DIRECTION
 - LV4** MANUFACTURER: MANNING COMMERCIAL, COLLECTION: COLOR ANCHOR LVT, PATTERN: STRIKE, COLOR: HALE THISTLE SMITH C175, SIZE: 6" X 36", INSTALLATION METHOD: SEE FINISH PLAN FOR PATTERN DIRECTION
- CARPET TILE**
- CP1** SALVAGED EXISTING CARPET TILE REUSED
- SHEET VINYL**
- SV1** MANUFACTURER: MANNING COMMERCIAL, COLLECTION: REALITIES II, COLOR: DRUMMOND S63R
 - SV2** MANUFACTURER: MANNING COMMERCIAL, COLLECTION: ASSURANCE III, COLOR: MARL 1634S
- FLOORING TRANSITIONS**
- FT1** 2.5MM LVT TO 2.03MM SHEET VINYL, MANUFACTURER: TARKETT, PROFILE: 880 TO 890, COLOR: 280 SHORELINE, PRODUCT NUMBER: C1249V1, FLOOR FLOORING AS NECESSARY FOR A SMOOTH TRANSITION, CONTACT: TAYLOR GROSSENMERPER | 913.558.8531 | TAYLOR.GROSSENMERPER@TARKETT.COM
 - B1** MANUFACTURER: JOHNSONITE - TARKETT, STYLE: TIGHTLOCK, WALLBASE: HIGHEAT-4375, COLOR: AS EITHER ONE, PRODUCT NUMBER: TD-09-H4375, CONTACT: TAYLOR GROSSENMERPER | 913.558.8531 | TAYLOR.GROSSENMERPER@TARKETT.COM
 - B2** MANUFACTURER: JOHNSONITE - TARKETT, STYLE REVEAL, WALLBASE: HIGHEAT-4375, COLOR: AS EITHER ONE, PRODUCT NUMBER: MW-09-H425, CONTACT: TAYLOR GROSSENMERPER | 913.558.8531 | TAYLOR.GROSSENMERPER@TARKETT.COM
- SOILD SURFACE**
- SS1** MANUFACTURER: WILSONART, COLOR: MYSTIQUE 9200CS, CONTACT: MANDY BRIDGES | 913.484.2891 | MANDY.BRIDGES@VIRGINATILE.COM
- LAMINATE**
- L1** MANUFACTURER: FORMICA, COLOR: SORREL CHERRY 8556, FINISH: ARTISAN, CONTACT: BROOKE CORCORAN | 913.213.8825 | BROOKE.CORCORAN@FORMICA.COM
 - L2** MANUFACTURER: WILSONART, COLOR: SHEER MESH 4876, FINISH: FINE VELVET, CONTACT: MANDY BRIDGES | 913.484.2891 | MANDY.BRIDGES@VIRGINATILE.COM
- WALLCOVERING**
- WC1** MANUFACTURER: DESIGNTEK, PATTERN: ASKEL WALL 6439-901, COLOR: CONFETTI, WIDTH: 50", REPEAT: VERTICAL DESIGN, CLASS: TYPE II, CONTACT: KATHY ANDERSON | 913.707.3839 | KANDERSON@DESIGNTEK.COM
- PRIVACY CURTAINS**
- CC** MANUFACTURER: ENVIOL TEXTILE, PATTERN: FISSON CHIPS, COLOR: BLUE NILE, CLASS: TYPE II, CONTACT: KATHY ANDERSON | 913.707.3839 | KANDERSON@DESIGNTEK.COM
- FINISH PLAN MATERIALS**
- LV2
 - LV3
 - LV4
- ARCHITECTURAL FINISH**
- AF1** MANUFACTURER: FORM. MATERIAL: VARIA RESIN, FRONT PATTERN: WAVE FRONT, COLOR: HERON, BACK PATTERN: SANDSTONE F01, BACK COLOR: AVALANCHE D01, GRAISE: 58", FIRE RATING: CLASS B, CONTACT: BRAD ANTISDE | 515.708.3182 | BRAD.ANTISDE@FORM.COM
- WALL PROTECTION**
- CG1** MANUFACTURER: CS ACRYOVYN, MATERIAL: 2" SSM SERIES CORNER GUARD, COLOR: 848 PINECE, INSTALL FULL HEIGHT, CONTACT: RICK STINGLEY | 816.536.0229 | RICK.SB.CLOUTMAN@NSDINGLEY.COM



2 GROUND FLOOR FINISH PLAN
1/8" = 1'-0"



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-20100290

Project Title:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
University Physicians Medical Building - Ground Floor CHCC Clinic Renovation
 University of Missouri, Columbia, Missouri




Issue Date: 08.29.2022
Issue: Date:




Drawn by: CG
bcgd Project #: 12275.27
MU Project #: CP202091

A200
RCP + FINISH PLAN


NO.	FRAME TYPE	OPENING			DOOR LABEL	GLAZING TYPE	MATERIAL	FRAME DETAILS				ASSEMBLY RATING	HARDWARE SET	COMMENTS
		WIDTH	HEIGHT	THICKNESS				HEAD	JAMB	SILL	FRAME LABEL			
GROUND FLOOR RCP														
0101	S	4'-0"	7'-0"	1 3/4"	FG	WD	HM	24/A600	24/A600				6	
0102	S	3'-8"	7'-0"	1 3/4"	FG	WD	HM	24/A600	24/A600				5	
0102B	S	3'-8"	7'-0"	1 3/4"	F	WD	HM	24/A600	24/A600				3	
0102C	S	3'-8"	7'-0"	1 3/4"	F	WD	HM	24/A600	24/A600				3	
0102J	S	3'-8"	7'-0"	1 3/4"	F	WD	HM	24/A600	24/A600				3	
0102L	S	3'-8"	7'-0"	1 3/4"	F	WD	HM	24/A600	24/A600				3	
0102M	S	3'-8"	7'-0"	1 3/4"	F	WD	HM	24/A600	24/A600				3	
0102N	S	3'-8"	7'-0"	1 3/4"	F	WD	HM	24/A600	24/A600				4	
0103	S	3'-8"	7'-0"	1 3/4"	F	WD	HM	24/A600	24/A600				1	



25 DOOR TYPES 1/4" = 1'-0"
26 FRAME TYPES 1/4" = 1'-0"
27 DOOR DTL - HEAD/JAMB SIM. 3" = 1'-0"




23 CORRIDOR - N 1/4" = 1'-0"




24 CORRIDOR - N2 1/4" = 1'-0"


- ### GENERAL INTERIOR ELEVATION NOTES
- PROVIDE F.T. WOOD BLOCKING AS REQUIRED FOR EQUIPMENT. COORDINATE SIZE AND LOCATION WITH OWNER.
 - 1 1/2" RADIUS ON ALL OUTSIDE CORNERS OF COUNTERTOPS & MICROWAVE SHELVES, TYP.
 - ALL EXPOSED ENDS OF CABINETS TO BE FINISHED, TYP.
 - ALL UNDERSIDE OF ALL UPPER CABINETS TO BE FINISHED, TYP.
 - ALL SHELVES EQUAL TO OR GREATER THAN 3/4" SHALL BE 1" THICK.
 - ALL FULL HEIGHT CABINET DOORS SHALL BE 1" W/ BALANCED BACKING SHEET, TYP.
 - ALL ELECTRICAL, MECHANICAL AND PLUMBING ITEMS ARE FOR REFERENCE AND LOCATION ONLY. REFER TO MEP DRAWINGS FOR SIZES, TYPES, AND EXACT QUANTITIES.
 - DIMENSIONS FOR MEP ITEMS ARE TO CENTERLINE OF COVERPLATE OR CENTER OF OPERABLE MECHANISM, TYP.
 - ALL EDGES OF PLAM COUNTERTOPS TO BE A PVC EDGE UNLESS OTHERWISE NOTED.
 - ALL END PANELS OF CASEWORK ARE TO BE FINISHED, TYP.
 - PROVIDE UNDER COUNTER SUPPORTS EVERY 3'-0" O.C., MIN.
 - PROVIDE METAL SUPPORT BRACKETS @ 30" O.C. MAX. UNDER UNSUPPORTED PLASTIC LAMINATE COUNTERTOPS. COLOR: SHEER MESH.
 - PROVIDE 1/2" GAP BETWEEN BACK OF COUNTERTOPS AND WALL AT EACH MOUNTING HEIGHTS.
 - REFER TO INSTALLATION GUIDELINES/COVER FOR TYPICAL INSTALLATION GUIDELINES & MOUNTING HEIGHTS.
 - G.C. TO COORDINATE WITH OWNER FINAL LOCATIONS OF ALL CARD READERS (CR).
 - ALL BASE CABINETS THAT ARE NOTED TO BE 25" DP. ON ELEVATIONS SHALL BE 24" FROM WALL TO FRONT OF CABINET DOOR, 25" TO EDGE OF COUNTERTOP, TYP.
 - CORNER GUARD. O/C, INSTALLATION WILL NEED TO BE IN SEQUENCE WITH THE WALL. BASE. G.C. TO COORDINATE WITH OWNER.
 - UPPER CASEWORK TO HAVE FILLER PANEL TO CEILING. FIELD VERIFY DIMENSIONS.
- ### EQUIPMENT LIST:
- | ES# | ITEM | FURNISHED BY/INSTALLED BY |
|-----|---|---------------------------|
| E01 | TELEVISION W/ MOUNTING BRACKET | OFCI, OFCI |
| E02 | NOT USED | OFCI |
| E03 | REFRIGERATOR | OFCI |
| E04 | MICROWAVE | OFCI |
| E05 | WORKSTATION: DUAL MONITORS AND KEYBOARD | OFCI |
| E06 | COUNTERTOP PRINTER | OFCI |
| E07 | SHRED-IT | OFCI |
| E08 | NOT USED | OFCI |
| E09 | EQ MACHINE | OFCI |
| E10 | LINE HAMMER W/ LID | OFCI |
| E11 | ROCKERSHIELD | OFCI |
| E12 | WELCH ALLYN | OFCI |
| E13 | ERGONOMIC CHAIR | OFCI |
| E14 | INFANT SCALE | OFCI |
| E15 | WHEEL CHAIR SCALE | OFCI |
| E16 | INFANT SCALE | OFCI |
| E17 | V6 COMPUTER CHARTING STATION | OFCI |
| E18 | CRASH CART | OFCI |
| E19 | TREADMILL | OFCI |
| E20 | TREADMILL COMPUTER | OFCI |
| E21 | MOBILE VITAL MACHINES | OFCI |
| E22 | MOBILE PEDESTALS | OFCI |




16 TREADMILL - W 1/4" = 1'-0"




17 TOILET ROOM - W 1/4" = 1'-0"




18 TOILET ROOM - N 1/4" = 1'-0"




19 SOILED - E 1/4" = 1'-0"




20 TYPICAL ECHO ROOM - N 1/4" = 1'-0"




21 STAFF LOUNGE - E 1/4" = 1'-0"




22 CORRIDOR - S 1/4" = 1'-0"




8 NURSE STATION - E 1/4" = 1'-0"




9 SOILED HOLDING ALCOVE - S 1/4" = 1'-0"




10 CLEAN/EQUIP. STOR. - E 1/4" = 1'-0"




11 CLEAN/EQUIP. STOR. - S 1/4" = 1'-0"




12 EXAM 0102D - W 1/4" = 1'-0"




13 VITALS - W 1/4" = 1'-0"




14 EXAM 0102H - W 1/4" = 1'-0"




15 TREADMILL - N 1/4" = 1'-0"




1 RECEPTION/CHECK-IN - W 1/4" = 1'-0"




2 RECEPTION/CHECK-IN - S 1/4" = 1'-0"




3 RECEPTION/CHECK-IN - E 1/4" = 1'-0"




4 CHECK-IN - W 1/4" = 1'-0"



5 RECEPTION/CHECK-IN - N 1/4" = 1'-0"



6 CHECK-OUT - S 1/4" = 1'-0"



7 NURSE STATION - W 1/4" = 1'-0"





12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119


Project Title:
University Physicians Medical Building - Ground Floor CHCC Clinic Renovation
University of Missouri, Columbia, Missouri




Issue Date: 08.29.2022
Issue #: CP202091
Drawn by: CG
bcdg Project #: 12275.27
MU Project #: CP202091
A600
INTERIOR ELEVATIONS +
OPENING SCHEDULE
BID SET




9 CASEWORK SECTION
1" = 1'-0"




10 CASEWORK SECTION
1" = 1'-0"




11 CASEWORK SECTION
1" = 1'-0"




12 CASEWORK SECTION
1" = 1'-0"




1 CASEWORK SECTION
1" = 1'-0"




2 CASEWORK SECTION
1" = 1'-0"




3 CASEWORK SECTION
1" = 1'-0"




4 CASEWORK SECTION
1" = 1'-0"




5 CASEWORK SECTION
1" = 1'-0"



6 CASEWORK SECTION
1" = 1'-0"



7 CASEWORK SECTION
1" = 1'-0"




8 CASEWORK SECTION
1" = 1'-0"




Issue Date: 08.29.2022
 Issue: Date:
 Drawn by: CG
 bcdg Project #: 12275.27
 MU Project #: CP202091


GENERAL SYMBOLS



DUCT SYSTEM SYMBOLS



PIPE LINE SYMBOLS



PIPE SYSTEM ABBREVIATIONS

Table listing abbreviations for pipe systems such as BD (Blow Down), CA (Compressed Air), CD (Condensate), and CW (Cold Water).

EQUIPMENT DESIGNATION

Table listing equipment designations including AC (Air Curtain), ACC (Air Cooled Condenser), ACU (Air Conditioning Unit), and AHU (Air Handling Unit).

GENERAL ABBREVIATIONS


Table listing general abbreviations such as A (Air or Amp), ACC (Accessories), AD (Access Door), and AF (Above Finished Floor).

GENERAL ABBREVIATIONS, CONTINUED

Continuation of general abbreviations including IPLV (Integrated Part Load Value), ISP (Internal Static Pressure), JS (Joist Space), and KW (Kilowatts).

GENERAL NOTES:

- List of 17 general notes detailing construction requirements, including compliance with local codes, seismic protection, and coordination with other trades.



12101 W 110th Street, Suite 100 Overland Park, KS 66210 913.232.2123

Project Team: ROSS & BARUZZINI, INC. 6 SOUTH OLD ORCHARD | ST. LOUIS, MO 63119

Project Title: UPMB Ground Floor Renovation 1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author MU Project #: 12275.27 CP202091

M000 MECHANICAL SYMBOLS & ABBREVIATIONS

EXISTING AHU DESCRIPTION AND COMPONENTS

THE EXISTING HVAC SYSTEM IS SET UP FOR A STANDARD MEDICAL OFFICE BUILDING. VARIABLE AIRFLOW AIR HANDLING UNITS ARE LOCATED IN THE BASEMENT MECHANICAL ROOM WITHIN THE BUILDING. AHU-1 FEEDS THE WEST HALF OF THE BUILDING AND AHU-2 FEEDS THE EAST HALF OF THE BUILDING. WE WILL FOCUS ON AHU-1 SINCE IT SERVES THE RENOVATION AREA, BUT BOTH UNITS ARE ESSENTIALLY IDENTICAL. THE AIR HANDLING UNITS CONSIST OF THE FOLLOWING COMPONENTS:

- REMOTE RETURN FAN - SUSPENDED WITHIN THE MECHANICAL ROOM (40,000 CFM, 3" TSP, 40HP, 480V/3PH)
- MIXING SECTION
- AIR BLENDER
- PRE-FILTER (MERV 8)
- SUPPLY FAN (45,000 CFM, 9" TSP, 100 HP, 480V/3PH)
- BLOW THROUGH COOLING COIL - CAMPUS CHILLED WATER (1512 MBH, 250 GPM, 18 FT. HEAD PRESSURE)
- DISCHARGE SECTION
- REMOTE, DUCT MOUNTED, STEAM DISPERSION HUMIDIFIER

SUPPLY AIR IS DUCTED FROM THE AIR HANDLING UNIT AND IS DISTRIBUTED TO MULTIPLE SPACES ON MULTIPLE FLOORS. VAV BOXES WITH HOT WATER REHEAT COILS MODULATE AIRFLOW TO EACH ZONE AND PROVIDE HEATING AT THE ZONE LEVEL FOR TEMPERATURE CONTROL. ALL AIR THAT IS NOT EXHAUSTED IS RETURNED BACK TO THE MAIN UNIT THROUGH THE CEILING RETURN AIR PLENUM.



IMAGE 1



IMAGE 2



IMAGE 3





IMAGE 4

GENERAL NOTES



1. REFER TO SHEET M000 FOR GENERAL NOTES.

KEYED NOTES

1. REMOVE EXISTING AIR DEVICES AND DUCTWORK TO POINT SHOWN.
2. REMOVE EXISTING NON-DUCTED RETURN GRILLE.
3. REMOVE EXISTING RETURN AIR TRANSFER DUCT ABOVE CEILING.
4. CAP EXISTING DUCTWORK AIRTIGHT WITH SHEETMETAL. INSULATE CAP WITH 1-1/2" THICK FOIL FACED DUCT WRAP INSULATION IF DUCT IS SUPPLY DUCT. PROVIDE PROPER VAPOR BARRIER WHERE NEW INSULATION BUTTS EXISTING.
5. PROVIDE TEMPORARY CAP IN EXISTING DUCTWORK UNTIL NEW DUCTWORK IS INSTALLED. EXISTING SYSTEM SERVES MULTIPLE FLOORS AND MUST REMAIN OPERATIONAL AT ALL TIMES.
6. EXISTING WALL MOUNTED DDC THERMOSTAT TO REMAIN.
7. EXISTING WALL MOUNTED DDC THERMOSTAT TO BE REMOVED AND RELOCATED. CONTACT OWNER BEFORE DEMOLITION BEGINS. EXISTING THERMOSTATS TO BE REMOVED BY OWNER. FC BUS SHALL REMAIN INTACT DURING CONSTRUCTION AND ANY EXISTING CONTROL WIRES THAT ARE TOO SHORT SHALL BE RE-PULLED, NOT SPliced. REFER TO SHEET M100 FOR NEW WORK. ASSOCIATED WITH EXISTING DDC THERMOSTAT. PATCH EXISTING WALL IF EXISTING THERMOSTAT IS REMOVED FROM AN EXISTING WALL THAT IS TO REMAIN.
8. EXISTING RETURN AIR TRANSFER DUCT ABOVE CEILING TO REMAIN.
9. ENGAGE OWNER'S REPRESENTATIVE TO CONTACT HOSPITAL OR UNIVERSITY OF MISSOURI ENERGY MANAGEMENT TO CLOSE AIR TERMINAL UNIT DAMPER PRIOR TO STARTING DEMOLITION WORK. EXISTING SYSTEM SERVES MULTIPLE FLOORS AND MUST REMAIN OPERATIONAL AT ALL TIMES.
10. EXISTING OPEN-ENDED RETURN AIR DUCT ABOVE CEILING TO REMAIN.
11. REMOVE EXISTING SUPPLY DUCTWORK. EXISTING FIRE DAMPER AND EXISTING SUPPLY SIDEWALL AIR DEVICE SERVING EXISTING TELECOM ROOM. EXISTING OPENING TO BE RE-USED AND MODIFIED AS NEEDED FOR NEW SIDE WALL AIR DEVICE. REFER TO IMAGE 3 ON THIS SHEET. REFER TO SHEET M100 FOR NEW WORK.
12. EXISTING 16x10 SIDEWALL RETURN AND EXISTING FIRE DAMPER TO BE REMOVED. EXISTING OPENING TO BE RE-USED AND MODIFIED AS NEEDED TO SERVE NEW RETURN SIDE WALL AIR DEVICE. REFER TO IMAGE 4 ON THIS SHEET. REFER TO SHEET M100 FOR NEW WORK.
13. EXISTING VAV DDC POWER SUPPLY UNIT ON WALL TO REMAIN.
14. CLOSE EXISTING SHUT-OFF VALVES PRIOR TO STARTING ANY DEMOLITION. EXISTING VALVES SERVE ONE AIR TERMINAL UNIT. REFER TO IMAGE 2 ON THIS SHEET.
15. CLOSE EXISTING SHUT-OFF VALVES PRIOR TO STARTING ANY DEMOLITION. EXISTING VALVES SERVE ONE AIR TERMINAL UNIT. REFER TO IMAGE 1 ON THIS SHEET.



1 MECHANICAL - GROUND FLOOR PLAN - DEMOLITION



KEYPLAN



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201102790

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author
bcdg Project #: 12275.27
MU Project #: CP202091

MD100
MECHANICAL - GROUND FLOOR - DEMOLITION



bcDESIGNGROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123

MO Certificate of Authority Number
A-201102720

Project Team:

ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

GENERAL NOTES

- REFER TO SHEET M000 FOR GENERAL NOTES.

KEYED NOTES

- NEW LOCATION OF EXISTING WALL MOUNTED DDC THERMOSTAT. CONNECT TO EXISTING ASSOCIATED VAV BOX NOTED ON PLANS. IF EXISTING CONTROL WIRING IS NOT LONG ENOUGH, PROVIDE NEW. SPLICING OF CONTROL WIRING IS PROHIBITED. PATCH WALL TO MATCH EXISTING FINISH. INSTALL AN ADHESIVE LABEL ON THERMOSTAT WITH AIR TERMINAL UNIT LOCATION FROM THERMOSTAT.
- INSTALL NEW OWNER FURNISHED WALL MOUNTED DDC THERMOSTAT ON NEW WALL. INSTALL AN ADHESIVE LABEL ON THERMOSTAT WITH CORRESPONDING AIR TERMINAL UNIT TAG AND AIR TERMINAL UNIT LOCATION FROM THERMOSTAT. LETTERS SHALL BE A MINIMUM 1/8" HIGH. COORDINATE LABEL TYPE AND LETTERING HEIGHT WITH OWNER'S REPRESENTATIVE.
- EXISTING WALL MOUNTED DDC THERMOSTAT TO REMAIN.
- NEW NON-DUCTED RETURN GRILLES TO HAVE A 10"x10" LINED SOUND BOOT PER DETAIL 7 ON SHEET M-500. DUCT SIZE NOTED ON PLAN IS SHEETMETAL SIZE.
- RETURN AIR TRANSFER DUCT WITH 1" DUCT LINER. DUCT SIZE NOTED ON PLAN IS SHEETMETAL SIZE.
- EXISTING RETURN AIR TRANSFER DUCT ABOVE CEILING TO REMAIN.
- PRIOR TO CONNECTING TO EXISTING EXPOSED 3/4" HEATING HOT WATER PIPING, CLOSE EXISTING SHUT-OFF VALVES IN EXISTING NORTH CORRIDOR. EXISTING HEATING HOT WATER SYSTEM MUST REMAIN OPERATIONAL AT ALL TIMES.
- CONNECT NEW BRANCH DUCT TO BOTTOM OF EXISTING SUPPLY MAIN.
- CONNECT TO EXISTING OPEN-ENDED RETURN AIR DUCT ABOVE CEILING AND EXTEND AS SHOWN. BALANCE FOR 4195 CFM.
- EXISTING VAV DDC POWER SUPPLY ON WALL.

EXISTING AHU DESCRIPTION AND COMPONENTS

THE EXISTING HVAC SYSTEM IS SET UP FOR A STANDARD MEDICAL OFFICE BUILDING. VARIABLE AIRFLOW AIR HANDLING UNITS ARE LOCATED IN THE BASEMENT MECHANICAL ROOM WITHIN THE BUILDING. AHU-1 FEEDS THE WEST HALF OF THE BUILDING AND AHU-2 FEEDS THE EAST HALF OF THE BUILDING. WE WILL FOCUS ON AHU-1 SINCE IT SERVES THE RENOVATION AREA, BUT BOTH UNITS ARE ESSENTIALLY IDENTICAL. THE AIR HANDLING UNITS CONSIST OF THE FOLLOWING COMPONENTS:

- REMOTE RETURN FAN - SUSPENDED WITHIN THE MECHANICAL ROOM (40,000 CFM, 3" TSP, 40HP, 480V/3PH)
- MIXING SECTION
- AIR BLENDER
- PRE-FILTER (MERV 8)
- SUPPLY FAN (45,000 CFM, 9" TSP, 100 HP, 480V/3PH)
- BLOW THROUGH COILING COIL - CAMPUS CHILLED WATER (1512 MBH, 250 GPM, 18 FT. HEAD PRESSURE)
- DISCHARGE SECTION
- REMOTE, DUCT MOUNTED, STEAM DISPERSION HUMIDIFIER


SUPPLY AIR IS DUCTED FROM THE AIR HANDLING UNIT AND IS DISTRIBUTED TO MULTIPLE SPACES ON MULTIPLE FLOORS. VAV BOXES WITH HOT WATER REHEAT COILS MODULATE AIRFLOW TO EACH ZONE AND PROVIDE HEATING AT THE ZONE LEVEL FOR TEMPERATURE CONTROL. ALL AIR THAT IS NOT EXHAUSTED IS RETURNED BACK TO THE MAIN UNIT THROUGH THE CEILING RETURN AIR PLENUM.



IMAGE 1




IMAGE 2



MECHANICAL - GROUND FLOOR PLAN - NEW WORK

Scale: 8' 4' 0' 8'



KEYPLAN

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212




Issue Date: 08.29.2022


Drawn by: Author

bcgd Project #: 12275.27
MU Project #: CP202091


M100
MECHANICAL - GROUND FLOOR - NEW WORK



4 RETURN AIR TRANSFER BOOT
NTS




3 TYPICAL DUCTWORK DETAIL
1/4\" = 1'-0"




NOTES:
 1. BRANCH PIPES SHALL TAP THE TOP OF THE MAINS.
 2. STRAINER/DRAIN VALVE SHALL BE LOWER THAN COIL CONNECTION. IF FIELD CONDITIONS DO NOT ALLOW PROVIDE ADDITIONAL DRAIN VALVE AT LOW POINT TO FACILITATE DRAINING SYSTEM.

2 2-WAY TERMINAL UNIT COIL DETAIL
NTS




NOTES:
 1. SUSPEND FROM STRUCTURE IN ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS. HANGERS & BRACING SHALL NOT OBSTRUCT ACCESS PANELS AND/OR SERVICE SPACE. DO NOT OBSTRUCT ACCESS PANELS AND/OR SERVICE SPACE. REFER TO MANUFACTURERS RECOMMENDED UNIT INSTALLATION MANUAL.
 2. INSTALL TERMINAL UNIT PLUMB AND LEVEL, WITH SERVICE SPACE FOR CONTROLS. SERVICE AREA MUST BE MAINTAINED CLEAR OF ALL OBSTRUCTIONS. CONTRACTOR SHALL COORDINATE SERVICE AREA WITH ALL DISCIPLINES AND CONSTRUCTION CONDITIONS. DO NOT INSTALL AIR TERMINAL UNIT WITH ACCESS AREA BLOCKED AND/OR OBSTRUCTED.
 3. WHERE POSSIBLE, PROVIDE 3'-0\"/>


1 AIR TERMINAL UNIT WITH HOT WATER REHEAT INSTALLATION
NTS



7 RETURN GRILLE SOUND BOOT
NTS



6 FLEXIBLE DUCT CONNECTION TO AIR OUTLET/INLET
NTS




5 45 DEGREE BRANCH TAKE-OFF DETAIL
NTS

AIR DEVICE SCHEDULE														
MARK		MFR.	MODEL	TYPE	LOCATION	SERVICE	NECK SIZE (IN)	FACE SIZE (IN x IN)	MATERIAL	FINISH	MAX TPD (IN WC)	MAX NOISE (NC)	MAX CFM @ LISTED CONDITIONS	NOTES
S	1	TITUS	OMNI	SQUARE PLAQUE	CEILING	SUPPLY AIR	6	24x24	STEEL	WHITE	0.1	30	130	1, 2
S	2	TITUS	OMNI	SQUARE PLAQUE	CEILING	SUPPLY AIR	8	24x24	STEEL	WHITE	0.1	30	280	1, 2
S	3	TITUS	301RL	LOUVERED FACE	WALL	SUPPLY AIR	24x14	28x16	STEEL	WHITE	0.1	30	1285	1, 2
R	1	TITUS	PAR	PERFORATED FACE	CEILING	RETURN AIR	10x10	24x24	STEEL	WHITE	0.1	30	200	1, 2
R	2	TITUS	350RL	LOUVERED FACE	WALL	RETURN AIR	24x12	28x14	STEEL	WHITE	0.1	30	1200	1, 2
E	1	TITUS	PAR	PERFORATED FACE	CEILING	EXHAUST AIR	6	24x24	STEEL	WHITE	0.1	30	130	1, 2

AIR TERMINAL UNIT SCHEDULE																								
NOTES: 1. MAX TOTAL PRESSURE DROP SHALL INCLUDE BOX AND REHEAT COIL (WHERE APPLICABLE). 2. PROVIDE THE NUMBER OF COIL ROWS AS REQUIRED TO MEET SCHEDULED PERFORMANCE AND STILL FALL WITHIN REHEAT COIL PRESSURE DROP LIMITATION. 3. DESIGN SUPPLY AIR TEMPERATURE LIMITS THE TEMPERATURE TO 15°F ABOVE THE SPACE SETPOINT OF 72°F TO MAXIMIZE THE VENTILATION EFFECTIVENESS NOTED IN ASHRAE 62.1 - VENTILATION FOR ACCEPTABLE INDOOR AIR QUALITY. 4. PROVIDE WITH BOTTOM ACCESS DOOR PER THE SPECIFICATIONS. 5. EXISTING AIR TERMINAL UNIT 6. HOT WATER REHEAT WATER FLOW (GPM) IS NOT REQUIRED TO BE REBALANCED. 7. AIRFLOWS ARE BASED ON TESTING, ADJUSTING, AND BALANCING REPORT FOR PROJECT #CP171063 DATED: JULY 26, 2019. 8. COOLING ONLY AIR TERMINAL UNIT.																								
MARK	ID	#	EXISTING/NEW	MFR.	MODEL	TYPE	ROUND DUCT INLET SIZE (IN)	PRIMARY AIRFLOW (CFM)			DESIGN INLET STATIC PRESSURE (IN WC)	(1) MAX PRESSURE DROP (IN WC)	OUTLET DUCT SIZE WxD (IN)	AUXILIARY HOT WATER HEATING COIL			MAX NC LEVEL @ MAX CFM			NOTES				
								COOLING MAX	COOLING/HEATING MIN.	UNOCCUPIED AIRFLOW (CFM)				EAT (°F)	LAT (°F) (3)	EWT/LWT (°F)	FLOW (GPM)	MAX WPD (FT HD) (FT HD)	MAX APD (IN WC) (IN WC)		CONTROL VALVE	DISCHARGE	RADIATED	
VAV	1-003	EXISTING	CARNES	AVWD	SINGLE DUCT PRESSURE INDEPENDENT	12	240	120	60	-	-	16x15	120	-	-	180/140	-	-	-	2-WAY	-	-	5, 6	
VAV	1-004	EXISTING	CARNES	AVWD	SINGLE DUCT PRESSURE INDEPENDENT	12	320	160	80	-	-	16x15	160	-	-	180/140	-	-	-	2-WAY	-	-	5, 6	
VAV	1-005	EXISTING	CARNES	AVWD	SINGLE DUCT PRESSURE INDEPENDENT	12	100	50	25	-	-	16x15	50	-	-	180/140	-	-	-	2-WAY	-	-	5, 6	
VAV	1-008	EXISTING	TITUS	DESV	SINGLE DUCT PRESSURE INDEPENDENT	8	240	120	60	-	-	12x10	120	-	-	180/140	-	-	-	2-WAY	-	-	5, 6	
VAV	1-009	EXISTING	TITUS	DESV	SINGLE DUCT PRESSURE INDEPENDENT	8	650	325	165	-	-	12x10	325	-	-	180/140	-	-	-	2-WAY	-	-	5, 6	
VAV	1-010	EXISTING	CARNES	AVWD	SINGLE DUCT PRESSURE INDEPENDENT	10	900	450	225	-	-	14x12 1/2	450	-	-	180/140	-	-	-	2-WAY	-	-	5, 6, 7	
VAV	1-011	EXISTING	CARNES	AVWD	SINGLE DUCT PRESSURE INDEPENDENT	10	770	455	225	-	-	14x12 1/2	455	-	-	180/140	-	-	-	2-WAY	-	-	5, 6, 7	
VAV	1-012	EXISTING	CARNES	AVWD	SINGLE DUCT PRESSURE INDEPENDENT	12	1300	650	325	-	-	16x15	650	-	-	180/140	-	-	-	2-WAY	-	-	5, 6, 7	
VAV	1-013	NEW	TITUS	DESV	SINGLE DUCT PRESSURE INDEPENDENT	6	100	50	25	1.2	0.5	12x8	50	1.7	55	87	180/140	0.5	5.0	0.25	2-WAY	30	30	2, 4
VAV	1-014	NEW	TITUS	DESV	SINGLE DUCT PRESSURE INDEPENDENT	6	100	50	25	1.2	0.5	12x8	50	1.7	55	87	180/140	0.5	5.0	0.25	2-WAY	30	30	2, 4
VAV	1-015	NEW	TITUS	DESV	SINGLE DUCT PRESSURE INDEPENDENT	6	100	50	25	1.2	0.5	12x8	50	1.7	55	87	180/140	0.5	5.0	0.25	2-WAY	30	30	2, 4
VAV	1-016	NEW	TITUS	DESV	SINGLE DUCT PRESSURE INDEPENDENT	14	1200	1200	1200	1.2	0.5	20x15 1/2	-	-	-	-	-	-	-	2-WAY	30	30	4, 8	


AIR CHANGE RATE SCHEDULE																
ROOM #	ROOM NAME	AREA (SF)	CEILING HEIGHT (FT)	ROOM VOLUME (CU. FT.)	SUPPLY AIR				OUTSIDE AIR				EXHAUST AIR			
					ASHRAE 170-2017		DESIGN		ASHRAE 170-2017		DESIGN		ASHRAE 170-2017		DESIGN	
					AC/ HOUR	SA CFM	SA CFM	AC/ HOUR	AC/ HOUR	OA CFM	OA CFM	AC/ HOUR	AC/ HOUR	EA CFM	EA CFM	AC/ HOUR
0102A	EXAM	104	8'-3"	853	4	57	60	4.2	2	28	28	2	0	0	0	0
0102B	EXAM	102	8'-3"	837	4	56	60	4.3	2	28	28	2	0	0	0	0
0102C	EXAM	102	8'-3"	837	4	56	60	4.3	2	28	28	2	0	0	0	0
0102D	EXAM	127	8'-3"	1042	4	70	70	4.0	2	35	35	2	0	0	0	0
0102E	TREADMILL/EXAM	281	8'-3"	2305	4	155	155	4.0	2	77	77	2	0	0	0	0
0102F	ECHO	150	8'-3"	1230	4	82	100	4.9	2	41	41	2	0	0	0	0
0102G	ECHO	150	8'-3"	1230	4	82	100	4.9	2	41	41	2	0	0	0	0
0102H	ECHO	150	8'-3"	1230	4	82	100	4.9	2	41	41	2	0	0	0	0
0102L	CLEAN EQUIP STORAGE	89	8'-3"	730	4	49	50	4.1	2	25	25	2	0	0	0	0
0102M	EXAM	128	8'-3"	1050	4	70	70	4	2	35	35	2	0	0	0	0
0102	CORRIDOR	510	8'-3"	4182	0	0	140	2	2	140	140	2	0	0	0	0
0102J	TOILET ROOM	63	8'-3"	517	0	0	0	0	0	0	0	10	87	90	10.4	



NOTES:

1. FC BUS TO BE CONTINUOUS DAISY CHAIN WITHOUT SPLICES. CONNECTIONS CAN ONLY BE MADE AT CONTROLLERS. SEE PLANS FOR QUANTITY AND LOCATIONS OF VMA CONTROLLERS.
2. BREAK BUS BETWEEN TWO EXISTING CONNECTED VAV CONTROLLERS AND REROUTE AS SHOWN. BUS CAN BE REROUTED IN MULTIPLE LOCATIONS TO KEEP OVERALL BUS LENGTH SHORT. COORDINATE FC BUS ROUTING AND OUTAGES WITH OWNERS REP.
3. FC COMMUNICATION BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 3 CONDUCTOR, WITH BLUE OUTER CASING, DESCRIBED AS 22-03 OAS STR PLNM NEON BLU JK DISTRIBUTED BY WINDY CITY WIRE, CONSTRUCTED BY CABLE-TEK, OR APPROVED EQUIVALENT.

C FC BUS SCHEMATIC DIAGRAM
NO SCALE



B VAV BOX CONTROL DIAGRAM WITH REHEAT
NO SCALE

NOTES:

1. VMA TERMINAL INCLUDES CONSTANT VOLUME (CV) UNITS & VARIABLE AIR VOLUME (VAV) UNITS. UNLESS OTHERWISE NOTED, ALL CONTROL WORK SHALL BE BY CONTRACTOR.
2. CAPS FOR VAV DP TEST PORTS MUST BE 1/4" BRASS PLUGS.

KEYED NOTES:

1. CONTROLLER WILL BE FURNISHED BY OWNER, INSTALLED BY CONTRACTOR. CONTROLLER WILL BE JCI MODEL MS-VMA-16XX SERIES. PROGRAMMING WILL BE DONE BY OWNER.
2. NETWORK SENSOR WILL BE FURNISHED BY OWNER & INSTALLED BY CONTRACTOR. NETWORK SENSOR WILL BE JCI NS SERIES.
3. FC COMMUNICATION BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 3 CONDUCTOR, WITH BLUE OUTER CASING, DESCRIBED AS 22-03 OAS STR PLNM NEON BLU JK DISTRIBUTED BY WINDY CITY WIRE CONSTRUCTED BY CABLE-TEK, OR APPROVED EQUIVALENT.
4. INSTALLATION OF OCC SENSOR IS WORK OF DIVISION 26. SEE E-SERIES SHEETS FOR FINAL LOCATIONS. A CONTROL CIRCUIT SHALL BE CONNECTED TO ALL OCC SENSORS AS WORK OF DIVISION 23. A CONTROL SIGNAL SHALL BE RELAYED TO THE VAV TERMINAL UNIT THAT SERVES THAT SPACE. IN LOCATIONS WHERE MULTIPLE OCC SENSORS ARE PRESENT, ALL SENSORS SHALL BE MONITORED AND TRANSMIT A SIGNAL TO THE VAV TERMINAL UNIT WITHIN THAT SPACE. ALL SENSORS SHALL BE WIRED IN PARALLEL.
5. CONTROLLER MUST HAVE A MINIMUM OF 18 INCHES OF ACCESSIBLE CLEARANCE.
6. VAV SUPPLY TEMP SENSOR 1000 OHM PLATINUM RTD LOCATED APPROX. 8 FT. FROM VAV BOX DISCHARGE. PROVIDED, INSTALLED, & WIRED TO CONTROLLER BY CONTRACTOR.
7. FUSE LOCATED WITHIN 2 FT. OF VMA CONTROLLER.
8. LOW VOLTAGE WIRE BY DIVISION 23. SEE ELECTRICAL DRAWINGS FOR SOURCE.
9. VALVE WITH PROPORTIONAL 0-10 VOLT ACTUATOR OR EQUIVALENT.
10. SA BUS WIRE SHALL BE 22 AWG, PLENUM RATED, TWISTED SHIELDED, 4 CONDUCTOR.



bc DESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123


MO Certificate of Authority Number
A-201102790

Project Team:

ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022
Date:

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

M700

TEMPERATURE CONTROLS

PLUMBING SYMBOLS & ABBREVIATIONS	
NOT ALL SYMBOLS ARE USED FOR THIS PROJECT	
	TRAPPED CONNECTION
	STRAINER
	BALANCING VALVE
	CLEANOUT (CO)
	OS & Y GATE VALVE
	TEMPERATURE GAUGE
	THERMOSTATIC MIXING VALVE
	REDUCED PRESSURE BACKFLOW PREVENTER
	HOSE BIBB/WALL HYDRANT
	ACID VENT
	ACID WASTE
	DRAIN PIPING
	DEIONIZED WATER PIPING
	REVERSE OSMOSIS PIPING (RO)
	DOMESTIC COLD WATER PIPING (CW)
	DOMESTIC HOT WATER PIPING (HW)
	DOMESTIC HOT WATER RETURN PIPING (HWR)
	NON-POTABLE WATER PIPING
	PUMP DISCHARGE PIPING
	SANITARY PIPING
	SUBSOIL DRAINAGE PIPING
	STORM PIPING
	OVERFLOW STORM PIPING
	TEMPERED WATER
	VENT PIPING
	EXISTING FIXTURE TO BE REMOVED
	EXISTING FIXTURE
	NEW FIXTURE
	FLEXIBLE CONNECTION
	FLOOR DRAIN/FLOOR SINK (FD/FS)
	CIRCULATION PUMP

COMMON PLUMBING SYMBOLS & ABBREVIATIONS	
NOT ALL SYMBOLS ARE USED FOR THIS PROJECT	
	DIRECTION OF FLOW
	BRANCH CONNECTION, BOTTOM
	BRANCH CONNECTION, TOP
	ELBOW, TURNED DOWN
	ELBOW, TURNED UP
	SHUTOFF VALVE
	CHECK VALVE
	PRESSURE REDUCING VALVE
	PRESSURE GAUGE
	UNION
	PIPING CAP
	EXISTING PIPING TO BE REMOVED
	MATCH LINE
	CONNECTION TO EXISTING
	DETAIL DESIGNATION
	RISER DESIGNATION
	KEYED NOTE
	REVISION NOTE
AFF	ABOVE FINISH FLOOR
AHJ	AUTHORITIES HAVING JURISDICTION
AP	ACCESS PANEL
BOP	BOTTOM OF PIPE
DIA	DIAMETER
DN	DOWN
EX OR EXIST	EXISTING
FFE	FINISHED FLOOR ELEVATION
GPH	GALLONS PER HOUR
GPM	GALLONS PER MINUTE
HP	HORSEPOWER
IE OR INV. ELEV	INVERT ELEVATION
NC	NORMALLY CLOSED
NTS	NOT TO SCALE
PSI	POUNDS PER SQUARE INCH
RPM	REVOLUTIONS PER MINUTE
RI	ROUGH-IN
SOV	SHUTOFF VALVE
TDH	TOTAL DYNAMIC HEAD
VIF	VERIFY IN FIELD

PLUMBING ABBREVIATIONS	
NOT ALL SYMBOLS ARE USED FOR THIS PROJECT	
ADA	AMERICANS WITH DISABILITIES ACT
AP	ACCESS PANEL
BP	BOOSTER PUMP
BT	BATHTUB
BTC	BRANCH TO CONNECTION
BV	BALANCE VALVE
CI	CAST IRON
CO	CLEANOUT
CSS	CLINICAL SERVICE SINK
DCVA	DOUBLE CHECK VALVE ASSEMBLY
DS	DOWNSPOUT
DW	DISHWASHER
DWH	DOMESTIC WATER HEATER
EEW	EMERGENCY EYE WASH
ESEW	EMERGENCY SHOWER & EYE WASH
ESH	EMERGENCY SHOWER
ET	EXPANSION TANK
EWC	ELECTRIC WATER COOLER
FCO	FLOOR CLEAN OUT
GCO	GRADE CLEANOUT
GD	GARBAGE DISPOSAL
HB	HOSE BIBB
HWRP	HOT WATER RETURN PUMP
HWST	HOT WATER STORAGE TANK
IM	ICE MAKER
IW	INDIRECT WASTE
LA	LAVATORY
MB	MOP BASIN
NIC	NOT IN CONTRACT
OB	OUTLET BOX
RD	ROOF DRAIN
RPZ	REDUCED PRESSURE BACKFLOW PREVENTER
S	SANITARY
S/S	STAINLESS STEEL
SH	SHOWER
SK	SINK
SP	SUMP PUMP
SS	SANITARY STACK
SSK	SHOP SINK
SW	SOFT WATER
TMV	THERMOSTATIC MIXING VALVE
UR	URINAL
V	VENT
VB	VACUUM BREAKER
VS	VENT STACK
VTR	VENT THRU ROOF
W	WASTE
WC	WATER CLOSET
WCO	WALL CLEANOUT
WD	WASHER DRAIN
WH	WALL HYDRANT
WHA	WATER HAMMER ARRESTOR
WM	WATER METER
WS	WASTE STACK
WSV	WASTE STACK VENT
YCO	YARD CLEANOUT

- ### PLUMBING GENERAL NOTES
- DUE TO THE LIMITED SPACE AVAILABLE FOR THE INSTALLATION OF ALL THE PLUMBING WORK, COORDINATION BETWEEN ALL OTHER TRADES IS OF UTMOST IMPORTANCE.
 - THIS CONTRACTOR SHALL VISIT THE PROJECT SITE AND VERIFY LOCATIONS, ELEVATIONS AND SIZES OF ALL UTILITIES AT SITE PRIOR TO PROCEEDING WITH WORK. EXISTING SYSTEMS AND STRUCTURE SHALL BE INVESTIGATED FOR BEST POSSIBLE ROUTING OF COLD WATER, HOT WATER, SANITARY WASTE AND VENT, STORM AND MEDICAL LABORATORY GAS PIPING.
 - THESE PLANS ARE DIAGRAMMATIC IN NATURE SINCE THE ONLY AVAILABLE INFORMATION HAS BEEN OBTAINED FROM EXISTING PLANS, SPECIFICATIONS, AND FIELD SURVEYS. THE EXACT LOCATION OF PIPING, FIXTURES AND EQUIPMENT MAY DEVIATE FROM THE LOCATION INDICATED ON THESE DRAWINGS. EXTREME ACCURACY IS NOT GUARANTEED. THIS CONTRACTOR SHALL BE PREPARED TO MAKE ALTERATIONS TO NEW AND/OR EXISTING SERVICES TO FIT JOB CONDITIONS. THIS CONTRACTOR SHALL FURNISH A COMPLETE CODE COMPLYING SYSTEM. THIS CONTRACTOR SHALL REPORT, IN WRITING, ANY DISCREPANCIES WHICH PREVENT THE INSTALLATION OF WORK AS SHOWN.
 - IF THIS CONTRACTOR DOES NOT CLEARLY UNDERSTAND THESE PLANS OR IS NOT COMPLETELY SURE OF THEIR MEANING, THIS CONTRACTOR SHOULD OBTAIN THE ENGINEER'S WRITTEN EXPLANATION AND/OR INTERPRETATION PRIOR TO SUBMITTING BIDS. SINCE THIS CONTRACTOR WILL BE HELD RIGIDLY TO THE INTERPRETATION OF THE ENGINEER.
 - IT IS THE RESPONSIBILITY OF THIS CONTRACTOR TO REPAIR THE EXISTING SURFACES TO REMAIN WHERE THEIR WORK HAS BEEN COMPLETED. REPAIR SHALL INCLUDE, BUT NOT LIMITED TO, ANY EXISTING WALL, CEILING OR FLOOR THAT IS SCHEDULED TO REMAIN. REPAIR, PAINTING, AND PATCHING SHALL BE COMPLETED BY AN APPROPRIATE CONTRACTOR QUALIFIED FOR THIS TYPE OF WORK.
 - THE OWNER SHALL MAINTAIN ALL SALVAGE RIGHTS OF FIXTURES, EQUIPMENT AND MATERIALS REMOVED. HOWEVER, ALL FIXTURES, EQUIPMENT AND MATERIALS NOT CLAIMED BY THE OWNER SHALL BE REMOVED FROM THE PREMISES AND PROPERLY DISPOSED OF BY THE DEMOLITION CONTRACTOR.
 - CEILING REMOVAL, STORAGE AND REPLACEMENT FOR NEW PIPING INSTALLATION SHALL BE BY THE GENERAL CONTRACTOR.
 - IF HAZARDOUS MATERIALS ARE ENCOUNTERED DURING DEMOLITION OPERATIONS, THE CONTRACTOR WILL NOTIFY BUILDING OWNER OF THE HAZARDOUS MATERIAL.
 - TEMPORARY CONNECTION SHALL BE PROVIDED BY RESPECTIVE PLUMBING AND FIRE PROTECTION CONTRACTORS WHEN EXTENDED INTERRUPTIONS OF SERVICES AND UTILITIES SUCH AS WATER, WASTE AND FIRE PROTECTION WHICH SERVE OTHER AREAS ARE NECESSARY.
 - COORDINATE WITH MAINTENANCE PERSONNEL AS TO SOURCE OF UTILITIES AND TEMPORARILY DISCONNECT OR SHUT OFF SERVICES OR UTILITIES AT NEAREST MAIN. TEMPORARY AND ACCESSIBLE ISOLATION VALVES SHALL BE INSTALLED CLOSE TO THIS POINT OF WORK.
 - IT IS ESSENTIAL THAT BUILDING OPERATIONS CONTINUE WITH MINIMAL INTERRUPTIONS. IT IS NECESSARY THAT OPERATION OF EXISTING SYSTEMS BE INTERFACED WITH AS LITTLE DISRUPTION AS POSSIBLE EXCEPT IN AREAS VACATED FOR CONSTRUCTION WORK. WORK WHICH WILL INTERFERE WITH OPERATION OF EXISTING FIRE SUPPRESSION AND PLUMBING SYSTEMS OR WHICH REQUIRE DOWNTIME WILL BE SCHEDULED ONLY AFTER CONSULTATION WITH AND PERMISSION GIVEN BY THE OWNER. ALLOW 10 DAYS PRIOR TO ANTICIPATED INTERRUPTION OF SYSTEMS. WORK MAY BE REQUIRED TO BE PERFORMED OUTSIDE NORMAL WORKING HOURS.
 - ARCHITECTURAL DEMOLITION DRAWINGS AND SPECIFICATIONS SHALL BE READ IN CONJUNCTION WITH THESE DRAWINGS.
 - ALL PIPING HANGERS AND SUPPORTS SHALL BE REMOVED ALONG WITH PIPING BEING REMOVED.
 - THE CONTRACTOR SHALL COORDINATE DEMOLITION WORK WITH PROJECT'S PHASING SCHEDULE PRIOR TO COMMENCEMENT OF ANY WORK.
 - WHEN PLACING NEW PLUMBING FIXTURES, CONTRACTOR SHALL VERIFY LOCATIONS OF PLUMBING VENTS. OFFSET VENTS THAT TERMINATE WITHIN 25 FEET OF HVAC UNITS OUTDOOR AIR INTAKES. CONTRACTOR SHALL FIELD VERIFY PRIOR TO BID WHERE THE INTERFERENCE'S ARE PRICE ACCORDINGLY OR MAKE ALLOWANCES IN BID.
 - USE CAUTION WHEN SAW-CUTTING THROUGH EXISTING CONCRETE FLOOR OR WALL CONSTRUCTION FOR THE INSTALLATION OF PLUMBING SYSTEMS TO AVOID CUTTING REBAR AT EDGE OF OPENING. LEAVE SUFFICIENT REBAR EXPOSED TO TIE NEW REINFORCING REPLACEMENT CONCRETE AND/OR OTHER STRUCTURAL ATTACHMENTS FOR NEW CONSTRUCTION.
 - CONTRACTOR SHALL BE RESPONSIBLE FOR ANY REVISIONS, TRANSITIONS, OFFSETS, ETC., TO AVOID DUCTWORK, PIPING, EQUIPMENT OR STRUCTURE NEW OR EXISTING AND TO MAKE A COMPLETE AND FUNCTIONING SYSTEM.



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201007290

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

P000
PLUMBING SYMBOLS AND ABBREVIATIONS



KEYED NOTES

1. SAW CUT EXISTING CONCRETE SLAB FOR DEMOLITION AND CAPPING OF EXISTING WASTE PIPING SERVING EXISTING SINK. PATCH CONCRETE FLOOR TO MATCH EXISTING SURROUNDING SURFACES.



*NOTE: THIS PLAN IS TO ILLUSTRATE PLUMBING UNDERFLOOR WORK THAT WILL OCCUR BELOW SLAB. THE GROUND FLOOR PLAN SHOWN FOR REFERENCE ONLY. ANY WORK SHOWN ON THIS PLAN TO BE PERFORMED BELOW SLAB.

1 PLUMBING - UNDERFLOOR DEMO PLAN
1/8" = 1'-0"



KEYPLAN



bcDESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123

MO Certificate of Authority Number
A-201103290

Project Team:

ROSS & BARUZZINI, INC.
8 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

PD100


PLUMBING - UNDERFLOOR
DEMOLITION PLAN

KEYED NOTES

- EXISTING SINK AND ALL PIPING TO BE DEMOLISHED BACK TO THEIR MAINS AND CAPPED. EXISTING ICE MAKER CUP SINK AND ALL ASSOCIATED PIPING TO BE DEMOLISHED.
- EXISTING CW/HW SUPPLY LINES ARE CAPPED DEAD LEGS FROM A PREVIOUS PROJECT. THESE SHALL BE DEMOLISHED.



1 PLUMBING - GROUND FLOOR DEMO PLAN
1/8" = 1'-0"



bcDESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123

MO Certificate of Authority Number
A-201103290

Project Team:

ROSS & BARUZZINI, INC.
8 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

PD101
PLUMBING - GROUND FLOOR
DEMOLITION PLAN


KEYED NOTES

1. SAW CUT EXISTING CONCRETE SLAB FOR INSTALLATION OF NEW WASTE PIPING SERVING GROUND FLOOR PLUMBING FIXTURES. PATCH CONCRETE FLOOR TO MATCH EXISTING SURROUNDING SURFACES.



NOTE: THIS PLAN IS TO ILLUSTRATE PLUMBING UNDERFLOOR WORK THAT WILL OCCUR BELOW SLAB. THE GROUND FLOOR PLAN SHOWN FOR REFERENCE ONLY. ANY WORK SHOWN ON THIS PLAN TO BE PERFORMED BELOW SLAB.

1 PLUMBING - UNDERFLOOR PLAN
1/8" = 1'-0"



bcDESIGN GROUP
12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201103729

Project Team:
ROSS & BARUZZINI, INC.
8 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212




Issue Date: 08.29.2022

Drawn by: Author
bcdg Project #: 12275.27
MU Project #: CP202091




P100
PLUMBING - UNDERFLOOR
PLAN

KEYED NOTES

- SEE "CALIBRATED BALANCING VALVE" DETAIL ON SHEET P500 FOR MORE INFORMATION.



PLUMBING - GROUND FLOOR PLAN
1/8" = 1'-0"



bcDESIGN GROUP
12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201103729

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119


Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022
Date:

Drawn by: Author
bcdg Project #: 12275.27
MU Project #: CP202091

P101
PLUMBING - GROUND FLOOR PLAN



1 PLUMBING - SANITARY AND VENT ISOMETRIC



bcDESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123

MO Certificate of Authority Number
A-201103290

Project Team:

ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212




Issue Date: 08.29.2022

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

P400

PLUMBING ISOMETRICS



1 PLUMBING - DOMESTIC WATER ISOMETRIC



bc DESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123

MO Certificate of Authority Number
A-201103290

Project Team:

ROSS & BARUZZINI, INC.
8 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212




Issue Date: 08.29.2022

Drawn by: Author


bcdg Project #: 12275.27
MU Project #: CP202091

P401


PLUMBING ISOMETRICS



1 FLOOR CLEANOUT
NONE




2 INSULATED PIPE HANGER SUPPORT
NONE




SECTION THRU HANGER


REFER TO SPECS FOR INSULATION AND HANGER SUPPORTS.



3 SENSOR OPERATED FAUCET
NONE



4 TRAP TO VENT MAXIMUM DISTANCE
NONE



NOTE:
0.3 GPM TO 0.7 GPM - B&G 1/2\"/>

5 CALIBRATED BALANCING VALVE
NONE

PLUMBING FIXTURE SCHEDULE													
PLAN MARK	DESCRIPTION	MANUFACTURER	MODEL	TRIM	DRAIN / TRAP	SUPPLIES	CARRIER	HOT WATER	COLD WATER	TEMPERED WATER	SANITARY / WASTE	VENT	NOTES
L-1	WALL HUNG LAVATORY	AMERICAN STANDARD	LUCERNE 0355.012	CHICAGO FAUCETS MODEL 116.606.AB.1; 0.5GPM SENSORED FAUCET; BATTERY POWERED.	GRID DRAIN/CHROME PLATED P-TRAP	CHICAGO FAUCET LOOSE KEY ANGLE STOPS AND RISERS	JAY R. SMITH	1/2"	1/2"	-	2"	2"	INSULATE SUPPLY AND WASTE PIPING WITH TRIBURO #102 WHITE INSULATION KIT WITH #105 OFFSET DRAIN INSULATION KIT. 0.5 GPM NON-AERATED OUTLET. PROVIDE WITH ASSE 1070 THERMOSTATIC MIXING VALVE.
SK-1	SINGLE BOWL STAINLESS STEEL SINK (EXAM ROOMS)	ELKAY	DLR191910PD	CHICAGO FAUCETS MODEL 201-AGNBAE38-317AB. 1.5GPM MANUAL FAUCET	GRID DRAIN/CHROME PLATED P-TRAP	CHICAGO FAUCET LOOSE KEY ANGLE STOPS AND RISERS	-	1/2"	1/2"	-	2"	-	PROVIDE WITH ASSE 1070 THERMOSTATIC MIXING VALVE.
SK-2	SINGLE BOWL STAINLESS STEEL SINK (STAFF LOUNGE)	ELKAY	DLR191910PD	SYMMONS S-23-2-W-1.5 MANUAL KITCHEN FAUCET	GRID DRAIN/CHROME PLATED P-TRAP	CHICAGO FAUCET LOOSE KEY ANGLE STOPS AND RISERS	-	1/2"	1/2"	-	2"	-	PROVIDE WITH ASSE 1070 THERMOSTATIC MIXING VALVE.
WC-1	FLOOR MOUNT FLOOR OUTLET WATER CLOSET (ADA)	AMERICAN STANDARD	MADERA FLOWISE 3461.001	SLOAN ROYAL 111 SFSM-1.6 SENSOR FLUSHMETER; BATTERY POWERED.	INTEGRAL	-	-	-	1 1/4"	-	4"	2"	ADA.

DRAIN SCHEDULE						
PLAN MARK	DESCRIPTION	MANUFACTURER	MODEL	BODY	STRAINER	NOTES
FD-1	ROUND FLOOR DRAIN	SILOUX CHIEF	832-35D-NR	CAST IRON	NICKEL-BRONZE	PROVIDE TRAP PRIMER CONNECTION



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-2011002790

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022


Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091


P500
PLUMBING DETAILS AND SCHEDULES

FIRE PROTECTION - FIRE WATCH


- FIRE WATCH BUILDING AND OCCUPANT SAFETY - INTERRUPTION OF FIRE PROTECTION SERVICE**
- DURING THE TIME THAT FIRE PROTECTION RENOVATION WORK IS BEING PERFORMED, AND THE FIRE PROTECTION SYSTEM IS DOWN AND OUT OF COMMISSION, THE FIRE PROTECTION CONTRACTOR SHALL HAVE SUFFICIENT PERSONNEL ON-SITE TO KEEP A "FIRE WATCH" ON THE FACILITY.
- A FIRE PROTECTION WATCH IS IMPLEMENTED TO ENSURE THE FIRE SAFETY OF A BUILDING IN THE EVENT OF ANY ACT, OR SITUATION INSTIGATING AN INCREASED RISK TO PERSONS OR PROPERTY. THE TERM "FIRE WATCH" IS USED TO DESCRIBE A DEDICATED PERSON OR PERSONS WHOSE SOLE RESPONSIBILITY IS TO LOOK FOR FIRES WITHIN AN ESTABLISHED AREA.
- IN THE OPINION OF THE FIRE AND LIFE-SAFETY GROUP (FLS) OR FM GLOBAL (FM), ANY REQUIRED FIRE PROTECTION SYSTEM THAT IS OUT OF SERVICE FOR MORE THAN 4 HOURS AND OCCUPIED IS REQUIRED TO ESTABLISH A FIRE WATCH. FOR THE PERSON OR PERSONS ASSIGNED TO THE FIRE WATCH, THIS MUST BE THEIR ONLY JOB DUTY DURING THE TIME PERIOD OF THE FIRE PROTECTION RENOVATION WORK.
- IN ADDITION, THE BUILDING OWNER IS REQUIRED TO HAVE AN IMPAIRMENT COORDINATOR. THE OUT OF SERVICE EQUIPMENT MUST BE TAGGED OUT OF SERVICE. AN OUT OF SERVICE TAG MUST BE PLACED AT THE FIRE ALARM PANEL, AND THE FIRE DEPARTMENT CONNECTION (REFERENCE INTERNATIONAL FIRE CODE- CHAPTER 9, SECTION 901.7).
- FIRE WATCH PERSONNEL ARE TO KEEP WATCH FOR FIRES IN THE GENERAL AREA OF PERFORMANCE, THE PERSONS PERFORMING THE FIRE WATCH ARE NOT PERMITTED TO PERFORM ANY OTHER DUTIES.
- FIRE WATCH PERSONNEL ARE TO HAVE FIRE EXTINGUISHING EQUIPMENT READILY AVAILABLE AND TO BE TRAINED IN ITS USE.
- THE QUANTITY OF PERSONNEL INVOLVED IN THE FIRE WATCH IS TO BE ADEQUATE SUCH THAT EACH FLOOR, LEVEL, AND ROOM OF THE FIRE AREA IS COVERED.
- IN GENERAL, A FIRE WATCH IS TO FULFILL THE INTENT OF NFPA-72 AS FOLLOWS:
 - NOTIFY OCCUPANTS TO EVACUATE WHEN THERE IS A FIRE IN THE BUILDING.
 - NOTIFY THE CENTRAL MONITORING STATION TO INITIATE EMERGENCY PERSONNEL RESPONSE.
 - ACTIVATE FIRE PROTECTION SYSTEMS IN ORDER TO RELEASE DOOR HOLDERS, CLOSE SMOKE DAMPERS AND SHUT DOWN FANS.
- IF BUILDING OCCUPANTS ASSIST WITH FIRE WATCH DUTIES, THE PROCEDURES FOR CONTACTING EMERGENCY PERSONNEL AND EVACUATING THE BUILDING ARE TO BE DISTRIBUTED TO BUILDING OCCUPANTS. FOR PLANNED OUTAGES, THE PROCEDURES ARE TO BE SENT OUT TO THE BUILDING OWNER FOR DISTRIBUTION.



1 CONCEALED SPRINKLER HEAD



2 RECESSED SPRINKLER HEAD



3 SPRINKLER HEAD LOCATION

FIRE PROTECTION GENERAL NOTES - EXISTING PROJECT

- ALL WORK SHALL BE PERFORMED, INSTALLED, AND TESTED IN COMPLIANCE WITH THE CODES AND AMENDMENTS ADOPTED BY THE INSPECTION AUTHORITY. NOTHING IN THESE PLANS IS TO BE CONSTRUCTED TO PERMIT WORK NOT CONFORMING TO THESE CODES OR OTHERS APPLICABLE TO THIS PROJECT.
 - A. 2021 - IFC
 - B. 2021 - IRC
 - C. IFC 3400.01
 - D. OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA)
 - E. NATIONAL FIRE PROTECTION ASSOCIATION EDITIONS LISTED IN THE IBC OR MOST CURRENT EDITIONS OF THE FOLLOWING:
 - a. NFPA 13
 - b. NFPA 14
 - c. NFPA 20
 - d. NFPA 24
 - e. NFPA 25
 - f. NFPA 99
- THE WORK CONSISTS OF FURNISHING ALL LABOR AND MATERIALS NECESSARY TO INSTALL, COMPLETE AND READY CONTINUOUS OPERATION. THE FIRE PROTECTION SYSTEMS APPARATUS AND EQUIPMENT FOR THIS PROJECT, AS SHOWN ON THE DRAWINGS, PLUS AS REQUIRED BY NFPA 13 AND THE AUTHORITY HAVING JURISDICTION (AHJ).
- THE CONTRACTOR SHALL INCLUDE IN THEIR BID, A FULLY CODE COMPLIANT AND COORDINATED SPRINKLER SYSTEM. SPRINKLER LOCATIONS ARE SHOWN TO ESTABLISH QUANTITY AND DESIRED LOCATION. EXACT QUANTITY OF SPRINKLERS IS THE CONTRACTOR'S RESPONSIBILITY. PROJECT SHALL BE DESIGNED, CONSTRUCTED, AND TESTED PER THE NFPA STANDARDS AND/OR FM GLOBAL REQUIREMENTS.
- THESE DRAWINGS ARE ACCURATE TO THE BEST OF OUR KNOWLEDGE, HOWEVER, LOCATIONS, DEPTHS, ELEVATIONS AND SIZES WERE TAKEN FROM DIFFERENT SOURCES AND ARE SUBJECT TO DEVIATION. THE CONTRACTOR SHALL ASSUME SOME DEVIATIONS AND INCLUDE OFFSETS, ADDITIONAL PIPING, ETC AT THE TIME OF BID.
- ALL SYSTEMS, EQUIPMENT, AND MATERIALS ARE TO BE INSTALLED IN A NEAT WORKMAN LIKE MANNER, WORK NOT DONE SO SHALL BE REMOVED AND REINSTALLED SATISFACTORILY.
- THE FIRE PROTECTION BID IS A DESIGN-BUILD CONTRACT. BEFORE SUBMITTING THE BID, THE CONTRACTOR SHALL VISIT THE SITE AND BECOME THOROUGHLY FAMILIAR WITH ALL EXISTING CONDITIONS AND VERIFY LOCATIONS, ELEVATIONS, AND SIZES OF ALL UTILITIES AT SITE PRIOR TO PROCEEDING WITH WORK. THE CONTRACTOR SHALL BE HELD RESPONSIBLE FOR ANY ASSUMPTIONS, OMISSIONS, OR ERRORS MADE AS A RESULT OF THE FAILURE TO BECOME FULLY FAMILIAR WITH EXISTING CONDITIONS, EXISTING SYSTEMS AND STRUCTURE SHALL BE INVESTIGATED FOR BEST POSSIBLE ROUTING OF FIRE PROTECTION PIPING.
- WHEN PLACING NEW SPRINKLERS AND ROUTING NEW SPRINKLER PIPING, CONTRACTOR SHALL VERIFY LOCATIONS OF POTENTIAL OBSTRUCTIONS FROM MECHANICAL EQUIPMENT AND ARCHITECTURAL FEATURES PRIOR TO BID AND PRICE ACCORDINGLY TO MAKE ALLOWANCES IN BID.
- THE CONTRACTOR SHALL PERFORM A FLOW TEST PRIOR TO DESIGN AND SUBMITTAL OF THE HYDRAULICALLY CALCULATED SYSTEM. THE FLOW TEST SHALL NOT BE MORE THAN 12 MONTHS OLD FROM THE DATE OF CONSTRUCTION.
- AT LEAST ONE HYDRAULIC CALCULATION SHALL BE PROVIDED PER SPRINKLER ZONE BASED ON THE CURRENT FLOW TEST. THE CALCULATION WILL INCLUDE HOSE ALLOWANCES AT THE BASE OF THE RISER PER NFPA 13 REQUIREMENTS BASED ON THE IDENTIFIED HAZARD. THERE WILL BE A 10% SAFETY ALLOWANCE PROVIDED FOR THE SPRINKLER SYSTEM BASED ON THE AVAILABLE PRESSURE AT THE SOURCE AND SYSTEM DEMAND (10% OF THE SUM OF THE SPRINKLER DEMAND PLUS THE SAFETY FACTOR).
- THE CONTRACTOR SHALL SUBMIT ALL DRAWINGS AND CALCULATIONS TO THE FIRE DEPARTMENT, GOVERNING AGENCIES, AND INSURING AGENCY AND RECEIVE APPROVAL PRIOR TO SUBMITTING DESIGN SHOP DRAWINGS.
- SUBMIT ACCURATE AS-BUILT DRAWINGS TO THE ENGINEER AND OWNER.
- IF THIS CONTRACTOR DOES NOT CLEARLY UNDERSTAND THESE PLANS OR IS NOT COMPLETELY SURE OF THEIR MEANING, THIS CONTRACTOR SHOULD OBTAIN THE ENGINEER'S WRITTEN EXPLANATION AND/OR INTERPRETATION PRIOR TO SUBMITTING BIDS, SINCE THIS CONTRACTOR WILL BE HELD RIGIDLY TO THE INTERPRETATION OF THE ENGINEER.
- THESE PLANS ARE DIAGRAMMATIC IN NATURE SINCE THE ONLY AVAILABLE INFORMATION HAS BEEN OBTAINED FROM EXISTING PLANS, SPECIFICATIONS, AND FIELD SURVEYS. THE EXACT LOCATION OF PIPING AND EQUIPMENT MAY DEVIATE FROM THE LOCATION INDICATED BY THESE DRAWINGS. EXTREME ACCURACY IS NOT GUARANTEED. THIS CONTRACTOR SHALL BE PREPARED TO MAKE ALTERATIONS TO NEW AND/OR EXISTING SERVICES TO FIT JOB CONDITIONS. THIS CONTRACTOR SHALL REPORT, IN WRITING, ANY DISCREPANCIES WHICH PREVENT THE INSTALLATION OF WORK AS SHOWN.
- IT IS ASSUMED THAT AREAS OUTSIDE THE SCOPE OF WORK ARE TESTED, MAINTAINED, AND MEET THE CODE REQUIREMENTS WHEN AS INSTALLED, AND THE EXISTING SYSTEM IS ACCEPTED BY THE LOCAL AHJ. WORK PERFORMED WITHIN SCOPE OF WORK WILL PROVIDE A SYSTEM TO MEET THE REQUIREMENTS SET BY THE AHJ LIMITED BY THE BOUNDARY OF WORK.
- THE SPRINKLER CONTRACTOR PRIOR TO TIME OF BID SHALL EVALUATE THE SITE AND VERIFY ALL SPRINKLER PIPING AND EQUIPMENT THAT IS EXISTING TO REMAIN WITHIN OR SERVING THE SCOPE OF WORK, IS IN GOOD WORKING CONDITION.
- FLEXIBLE SPRINKLER HEADS ARE NOT ALLOWED FOR THIS PROJECT.
- FURNISH AND INSTALL TAMPER SWITCHES ON ALL INDICATING VALVES AND FLOW SWITCHES PER NFPA 13 REQUIREMENTS AND PER THE DESIGN DOCUMENTS BY THE CONTRACTOR.
- THE CONTRACTOR SHALL FURNISH DRAIN VALVES AND INSPECTOR'S TEST CONNECTIONS AS REQUIRED BY NFPA 13 REQUIREMENTS AND AT THE DISCRETION OF THE FIRE MARSHAL, ENGINEER OR GOVERNING AGENCY.
- ALL OPENINGS THROUGH FIRE RATED FLOORS, WALLS, OR PARTITIONS SHALL BE FIRE STOPPED WITH UL RATED ASSEMBLIES OF EQUAL OR GREATER FIRE RATING. REFER TO FIRE STOPPING NOTES FOR ADDITIONAL INFORMATION.
- COORDINATE WITH STRUCTURAL ENGINEER WHEN SAW-CUTTING THROUGH CONCRETE FLOOR OR WALL CONSTRUCTION. LEAVE SUFFICIENT REBAR EXPOSED TO THE NEW REINFORCING REPLACEMENT CONCRETE AND/OR OTHER STRUCTURAL ATTACHMENTS FOR NEW CONSTRUCTION.
- VALVES, TAMPER SWITCHES, OR ANY MECHANICAL/ELECTRICAL ITEM SHALL NOT BE LOCATED ABOVE A HARD CEILING, UNLESS PROVIDED WITH EQUIVALENTLY RATED ACCESS AND SIGNAGE MEETING NFPA 13 REQUIREMENTS.
- SPRINKLERS SHALL BE LOCATED IN THE CENTER OF CEILING TILES, COORDINATE FINAL LAYOUT WITH ARCHITECT, AND OTHER DISCIPLINES.
- EXTENDED COVERAGE SPRINKLERS ARE PERMITTED, CONTRACTOR SHALL VERIFY ADDITIONAL PRESSURE REQUIREMENTS IF THIS TYPE IS SELECTED.
- THE SPRINKLER CONTRACTOR SHALL OBTAIN AND UTILIZE THE ARCHITECTURAL REFLECTED CEILING PLAN FOR THE LOCATING OF SPRINKLER HEADS. REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR CEILING DEVICE LOCATIONS AND THE SPECIFICATIONS FOR COORDINATION DRAWING REQUIREMENTS.
- PIPING SHALL BE INSTALLED AT LEAST 12" ABOVE FINISHED CEILING ELEVATION TO ALLOW FOR SUITABLE ACCESS ABOVE CEILING.
- INSTALL NO PIPING IN A LOCATION OR MANNER WHICH WILL ALLOW FREEZING.
- COORDINATE PIPE ROUTING NEAR ELECTRICAL EQUIPMENT PER NFPA 70. PIPING IS NOT TO BE ROUTED ABOVE ELECTRICAL PANELS, TRANSFORMERS, COMPUTER RACKS ETC. FIELD VERIFY AND COORDINATE WITH ELECTRICAL CONTRACTOR ALL EXISTING AND NEW ELECTRICAL LOCATIONS PRIOR TO DESIGN OF THE FIRE PROTECTION PLANS.
- ROUTING OF SPRINKLER MAINS, BRANCHLINES, AND HEADS SHALL BE THOROUGHLY COORDINATED WITH ALL OTHER DISCIPLINES AND BUILDING STRUCTURE PRIOR TO SUBMISSION OF COORDINATED SHOP DRAWINGS. THIS IS OF THE UTMOST IMPORTANCE ESPECIALLY WHERE SPACE IS LIMITED. FIRE PROTECTION CONTRACTOR IS RESPONSIBLE FOR COORDINATING, PREPARING, AND SUBMITTING COORDINATION DRAWINGS FOR APPROVAL/REVIEW.
- ADVISE THE ENGINEERS OF ANY CONFLICTS, ERRORS, OMISSIONS, ETC. AT LEAST 10 DAYS PRIOR TO BID DATE, TO ALLOW CLARIFICATION BY WRITTEN ADDENDUM.
- IF SEISMIC BRACING IS REQUIRED, FIRE PROTECTION CONTRACTOR SHALL FURNISH AND INSTALL ALL END OF BRANCH LINE RESTRAINTS PER NFPA 13.
- WHEN WORK REQUIRES TEMPORARY INTERRUPTIONS OF FIRE PROTECTION SERVICES OR UTILITIES THE FOLLOWING ACTIONS WILL BE TAKEN:
 - A. COORDINATION WITH MAINTENANCE PERSONNEL TO SHUT OFF SERVICES AT NEAREST MAIN.
 - B. PROVIDE TEMPORARY AND ACCESSIBLE ISOLATION VALVES CLOSE TO THE POINT OF WORK.
 - C. ENSURE BUILDING OPERATIONS CONTINUE WITH MINIMAL INTERRUPTIONS AND OPERATION OF EXISTING SYSTEMS BE INTERFERED WITH AS LITTLE DISRUPTION AS POSSIBLE EXCEPT IN VACATED AREAS.
 - D. WORK INTERFERING WITH OPERATION OF DOWNTIME WILL BE SCHEDULED AFTER CONSULTATION WITH AND PERMISSION GIVEN BY OWNER 10 DAYS PRIOR TO ANTICIPATED INTERRUPTION OF SYSTEMS.
 - E. SUCH WORK MAY BE REQUIRED TO BE PERFORMED OUTSIDE OF NORMAL WORKING HOURS.
 - F. REFER TO FIRE WATCH NOTES FOR DISRUPTION OF FIRE SPRINKLER SYSTEMS IN OCCUPIED BUILDINGS WHEN DISRUPTION EXCEEDS 4 HOURS.

COMMON FIRE PROTECTION SYMBOLS & ABBREVIATIONS

NOT ALL SYMBOLS ARE USED FOR THIS PROJECT

	DIRECTION OF FLOW
	BRANCH CONNECTION, BOTTOM
	BRANCH CONNECTION, TOP
	ELBOW, TURNED DOWN
	ELBOW TURNED UP
	SHUTOFF VALVE
	CHECK VALVE
	PRESSURE REDUCING VALVE
	PRESSURE GAUGE
	UNION
	PIPING CAP
	EXISTING PIPING TO BE REMOVED
	MATCH LINE
	CONNECTION TO EXISTING
	DETAIL DESIGNATION
	RISER DESIGNATION
	KEYED NOTE
	REVISION NOTE
	ABOVE FINISH FLOOR
	AUTHORITIES HAVING JURISDICTION
	ACCESS PANEL
	BOTTOM OF PIPE
	DIAMETER
	DOWN
	EXISTING
	FINISHED FLOOR ELEVATION
	GALLONS PER HOUR
	GALLONS PER MINUTE
	HORSEPOWER
	INVERT ELEVATION
	NORMALLY CLOSED
	NOT TO SCALE
	POUNDS PER SQUARE INCH
	REVOLUTIONS PER MINUTE
	ROUGH-IN
	SHUTOFF VALVE
	TOTAL DYNAMIC HEAD
	VERIFY IN FIELD

FIRE PROTECTION SYMBOLS & ABBREVIATIONS

NOT ALL SYMBOLS ARE USED FOR THIS PROJECT

	AIR VENT (AUTOMATIC)
	DOUBLE CHECK VALVE ASSEMBLY
	DRY PIPE VALVE
	ELECTRONIC SUPERVISED INDICATING VALVE
	FIRE DEPARTMENT VALVE (FDV)
	FLOW SWITCH
	PREACTION VALVE
	PRESSURE RELIEF VALVE
	SOLENOID VALVE
	DRAIN LINE
	DRY PIPE
	FIRE MAIN (BULK)
	SPRINKLER MAIN/BRANCH PIPING
	DRIP CONNECTION
	FIRE DEPARTMENT CONNECTION-FREE STANDING
	FIRE DEPARTMENT CONNECTION-WALL MOUNT
	FLUSH TYPE FIRE DEPARTMENT INLET CONNECTION
	FIRE PUMP TEST HEADER-WALL MOUNT
	FIRE PUMP TEST HEADER-FREE STANDING
	EXISTING SPRINKLER HEAD
	EXISTING SPRINKLER HEAD TO BE REMOVED
	SPRINKLER HEAD (SEE SCHEDULE FOR TYPE)
	SIDEWALL SPRINKLER HEAD (SEE SCHEDULE FOR TYPE)
	ACCESS PANEL
	AIR COMPRESSOR
	AUTOMATIC SPRINKLERS
	BACKFLOW PREVENTER
	BRANCH TO CONNECTION
	CAST IRON
	DOUBLE CHECK VALVE ASSEMBLY
	DRY PIPE VALVE
	DRY STANDPIPE PIPING
	DRY STANDPIPE VALVE
	FIRE DEPARTMENT CONNECTION
	FIRE DEPARTMENT VALVE
	FIRE EXTINGUISHER CABINET
	FIRE HOSE CABINET
	FIRE PUMP
	FIRE PUMP CONTROLLER
	FIRE PUMP TEST HEADER
	JOCKEY PUMP
	JOCKEY PUMP CONTROLLER
	NO AUTOMATIC SPRINKLERS
	NOT IN CONTRACT
	POST INDICATOR VALVE
	SUMP PUMP
	TAMPER SWITCH

FIRE STOPPING NOTES

- MATERIALS: USE ONLY FIRE STOP PRODUCTS THAT HAVE BEEN UL 1479, ASTM E-814, OR UL 2079 TESTED FOR SPECIFIC FIRE RATE CONSTRUCTION CONDITIONS CONFORMING TO CONSTRUCTION ASSEMBLY TYPE. PENETRATING ITEM TYPE, ANNULAR SPACE REQUIREMENTS, AND FIRE RATING INVOLVED FOR EACH SEPARATE INSTANCE.
- FOR SINGLE PENETRATIONS: A READY-TO-USE LATEX BASED INTUMESCENT SEALANT IS REQUIRED TO MAINTAIN THE FIRE RATING OF THE ASSEMBLY PENETRATED. THE SEALANT MUST HAVE UL LISTING FOR BOTH SLEEVED AND NON-SLEEVED APPLICATIONS.
- FOR LARGE OPENINGS: CONTAINING MULTIPLE PENETRATIONS (2 OR MORE), A READY-TO-USE FOAM INTUMESCENT BLOCK MATERIAL MUST BE ABLE TO BE REMOVED AND REINSTALLED WITHOUT COMPROMISING FIRE PROTECTION INTEGRITY. COMPLY WITH MANUFACTURER'S RECOMMENDED PROCEDURES AND PRECAUTIONS. DO NOT USE DAMAGED OR EXPIRED MATERIALS.
- MANUFACTURERS: JOHN'S MANVILLE INTERNATIONAL, 3M BRAND, CSD SEALING SYSTEMS, HILTI, CIBA-GEIGY, HEAVY-DUTY/NEALSON. REFER TO DIVISION 7 FOR FURTHER REQUIREMENTS.

FIRE PROTECTION DEMOLITION NOTES

- ALL PIPING HANGERS AND SUPPORTS SHALL BE REMOVED ALONG WITH THE PIPING.
- PROTECT PIPING WHICH IS NOT TO BE REMOVED FROM DAMAGE, DIRT AND DEBRIS.
- ALL FIRE EQUIPMENT AND MATERIALS NOT CLAIMED BY THE OWNER SHALL BE REMOVED FROM THE PREMISES AND PROPERLY DISPOSED OF BY THE DEMOLITION CONTRACTOR.
- THE CONTRACTOR SHALL PLUG OR CAP ALL PIPING OUTLETS NOT INTENDED FOR REUSE.
- CEILING REMOVAL, STORAGE, AND REPLACEMENT WILL BE MADE BY THE CONTRACTOR AND IT IS THE RESPONSIBILITY OF THIS CONTRACTOR TO REPAIR THE EXISTING SURFACES TO REMAIN WHERE THEIR WORK HAS BEEN COMPLETED. REPAIR INCLUDES BUT SHALL NOT BE LIMITED TO: ANY EXISTING WALL, CEILING, OR FLOOR THAT IS SCHEDULED TO REMAIN. REPAIR, PAINTING, AND PATCHING SHALL BE COMPLETED BY AN APPROPRIATE CONTRACTOR QUALIFIED FOR THIS TYPE OF WORK.
- IF HAZARDOUS MATERIALS ARE ENCOUNTERED DURING DEMOLITION OPERATIONS, THE CONTRACTOR WILL NOTIFY BUILDING OWNER OF THE HAZARDOUS MATERIAL.
- ARCHITECTURAL DEMOLITION DRAWINGS AND SPECIFICATIONS SHALL BE READ IN CONJUNCTION WITH THESE DRAWINGS.
- THE CONTRACTOR SHALL COORDINATE DEMOLITION WORK WITH PROJECT'S PHASING SCHEDULE PRIOR TO ANY WORK



bcDESIGN GROUP
12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123
MO Certificate of Authority Number
A-201102792

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212



Issue Date: 08/29/2022

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

FP000
FIRE PROTECTION SYMBOLS
AND ABBREVIATIONS

GENERAL SHEET NOTES

- A. FIRE SPRINKLER SYSTEM OUTAGES SHALL BE LIMITED IN TIME AND APPROVED BY UMHC.
- B. ONLY SCHEDULE 40 PIPING SHALL BE USED. CONTRACTOR SHALL VERIFY EXISTING SPRINKLER PIPING SCHEDULE AND NOTIFY OWNER BEFORE WORK COMMENCES.
- C. ONLY FULLY CONCEALED-TYPE SPRINKLER HEADS SHALL BE USED.
- D. COORDINATE ALL SPRINKLER HEAD LOCATIONS WITH CEILING LAYOUT, NEW ARCHITECTURAL FEATURES, CEILING-MOUNTED DEVICES, AND ACROSS ALL DISCIPLINES.
- E. FLEXIBLE SPRINKLER HEADS ARE NOT ALLOWED FOR THIS PROJECT.
- F. FIRE PROTECTION SHOP DRAWINGS TO BE PROVIDED, SIGNED AND SEALED BY A LICENSE FIRE PROTECTION ENGINEER IN THE STATE OF MISSOURI.
- G. TEMPORARY FIRE SPRINKLER PROTECTION SHALL BE PROVIDED.


KEYED NOTES

- 1. EXISTING SPRINKLER HEAD AND ARM OVER PIPING TO BE DEMOLISHED.
- 2. EXISTING PIPING IS SCHEDULE 10 BLACK STEEL PIPING.



1 FIRE PROTECTION - GRND FLR DEMO PLAN

1/8" = 1'-0"



bcDESIGNGROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123

MO Certificate of Authority Number
A-201100729

Project Team:

ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation

1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

FPD101

FIRE PROTECTION - GROUND FLOOR DEMOLITION PLAN



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201102790


Project Team:
ROSS & BARUZZINI, INC.
8 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

GENERAL SHEET NOTES

- A. FIRE SPRINKLER SYSTEM OUTAGES SHALL BE LIMITED IN TIME AND APPROVED BY UMHC.
- B. ONLY SCHEDULE 40 PIPING SHALL BE USED. CONTRACTOR SHALL VERIFY EXISTING SPRINKLER PIPING SCHEDULE AND NOTIFY OWNER BEFORE WORK COMMENCES.
- C. ONLY FULLY CONCEALED-TYPE SPRINKLER HEADS SHALL BE USED.
- D. COORDINATE ALL SPRINKLER HEAD LOCATIONS WITH CEILING LAYOUT, NEW ARCHITECTURAL FEATURES, CEILING-MOUNTED DEVICES, AND ACROSS ALL DISCIPLINES.
- E. FLEXIBLE SPRINKLER HEADS ARE NOT ALLOWED FOR THIS PROJECT.
- F. FIRE PROTECTION SHOP DRAWINGS TO BE PROVIDED, SIGNED AND SEALED BY A LICENSE FIRE PROTECTION ENGINEER IN THE STATE OF MISSOURI.
- G. TEMPORARY FIRE SPRINKLER PROTECTION SHALL BE PROVIDED.

KEYED NOTES

1. AREA TO BE CONSIDERED LIGHT HAZARD WITH A SPRINKLER DISCHARGE DENSITY OF 0.10 GPM/SQ.FT. FOR THE MOST HYDRAULICALLY REMOTE 1500 SQ.FT. AND A HOSE STREAM OF 100 GPM. CONTRACTOR SHALL PROVIDE A COMPLETE CODE COMPLIANT AUTOMATIC WET PIPE SYSTEM. SPRINKLER SPACING SHALL BE BASED ON LISTED VALUE AND DISTANCES ESTABLISHED BY NFPA AND FM.
2. AREA TO BE CONSIDERED ORDINARY HAZARD, GROUP 1 WITH A SPRINKLER DISCHARGE DENSITY OF 0.15 GPM/SQ.FT. FOR THE MOST HYDRAULICALLY REMOTE 1500 SQ. FT. AND A HOSE STREAM OF 200 GPM. CONTRACTOR SHALL PROVIDE A COMPLETE CODE COMPLIANT AUTOMATIC WET PIPE SYSTEM. SPRINKLER SPACING SHALL BE BASED ON LISTED VALUE AND DISTANCES ESTABLISHED BY NFPA.



1 FIRE PROTECTION - GROUND FLOOR PLAN
1/8" = 1'-0"
8' 4' 0' 8'

Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022
Date:

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

FP101
FIRE PROTECTION - GROUND FLOOR PLAN


ELECTRICAL GENERAL NOTES

- MAKE ALL INSTALLATIONS IN ACCORDANCE WITH THE (AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES (ADAAG)) AND/OR ARCHITECTURAL BARRIERS ACT (ABA).
- MOUNTING HEIGHTS INDICATED WITHIN PLANS AND SCHEDULES ARE DIMENSIONED TO THE CENTER LINE OF THE DEVICE, EQUIPMENT, LUMINAIRE, ETC. UNLESS OTHERWISE NOTED.
- COORDINATE EXACT EQUIPMENT LOCATIONS WITH OTHER TRADES. EQUIPMENT LOCATIONS SHOWN ON ELECTRICAL PLANS ARE DIAGRAMMATICAL ONLY AND MIGHT NOT BE EXACT.
- CIRCUIT IDENTIFICATION NUMBERS BESIDE ELECTRICAL DEVICES AND CONNECTION POINTS ON PLANS CORRESPOND TO AN OVERCURRENT DEVICE IN THE DESIGNATED PANELBOARD. NOTE ALL CIRCUIT NUMBER CHANGES MADE IN THE FIELD AT EACH ELECTRICAL DEVICE AND CONNECTION POINT. ALSO CORRECT THE DIRECTORIES AND DEVICE MARKINGS AT PANELBOARDS, SWITCHBOARDS AND SWITCHGEAR TO ACCURATELY REFLECT THE AS-BUILT CONDITIONS.
- INSTALL EMERGENCY AND EXIT LUMINAIRE WIRING IN A SEPARATE RACEWAY FROM THAT OF ANY NORMAL POWER DEVICE.
- CONCEAL ALL CONDUIT IN WALLS, PARTITIONS, ABOVE CEILINGS, AND IN FLOOR SLABS, ETC. UNLESS OTHERWISE INDICATED ON THE PLANS OR IN THE SPECIFICATIONS. CONDUIT ROUTED IN MECHANICAL ROOMS, ELECTRICAL ROOMS, AND STORAGE ROOMS WITHOUT CEILINGS MAY BE ROUTED EXPOSED.
- COORDINATE VERTICAL CONDUIT ROUTING TO WALL MOUNTED DEVICES TO ENSURE DEVICES LOCATED WITHIN AN 18-INCH HORIZONTAL DIMENSION WILL BE CENTER-ALIGNED VERTICALLY.
- CONCEAL ELECTRICAL CONNECTIONS FOR ELECTRIC WATER COOLERS (EWC) BEHIND WATER COOLER ACCESS PLATE OR DIRECTLY BELOW AND CENTERED ON WALL.
- FIELD COORDINATE ALL ELECTRICAL AND TELECOMMUNICATIONS EQUIPMENT MOUNTING LOCATIONS TO AVOID ENCRoACHMENT OF OPERATION AND ACCESS TO EQUIPMENT FROM OTHER TRADES. COORDINATE THE APPROPRIATE MOUNTING LOCATION WITH THE AFFECTED DISCIPLINES WHEN EQUIPMENT IS SPECIFIED TO BE MOUNTED ONTO THE SURFACE OF ANOTHER DISCIPLINE'S EQUIPMENT.
- REPAIR ALL OPENINGS MADE IN EXISTING WALLS, PARTITIONS, ETC TO ACCOMMODATE WORK OF THIS DISCIPLINE TO MATCH THE SURROUNDING CONDITIONS. USING WORKERS QUALIFIED IN THE APPROPRIATE TRADE. APPROPRIATELY GROUT OR SEAL ALL CONDUITS THROUGH WALLS.
- ALL MATERIALS USED TO SEAL PENETRATIONS OF FIRE RATED WALLS AND FLOORS MUST HAVE BEEN TESTED AND CERTIFIED AS A SYSTEM PER ASTM E814 STANDARDS FOR FIRE TESTS OF THROUGH-PENETRATION FIRESTOPPS.
- INSTALL A PERMANENT DIRECTORY ACCORDING TO THE NATIONAL ELECTRICAL CODE, ARTICLE 230 AT EACH SERVICE ENTRANCE AND POWER SOURCE.
- PERFORM ALL WELDING ACCORDING TO AMERICAN WELDING SOCIETY STANDARDS. FURNISH CERTIFICATES QUALIFYING EACH WELDER TO THE ARCHITECT OR ENGINEER PRIOR TO START OF WORK. THE ARCHITECT OR ENGINEER RESERVES THE RIGHT TO REQUIRE QUALIFYING DEMONSTRATION, AT NO ADDITIONAL EXPENSE, OF ANY WELDERS ASSIGNED TO THE JOB.
- REPLACE OR REINSTALL ALL PORTIONS OF THE BUILDING (CEILING TILES, WALLS, ETC) REMOVED TO ACCOMMODATE THE INSTALLATION OF ANY ELECTRICAL DEVICE, EQUIPMENT, ETC., USING WORKERS QUALIFIED IN THE APPROPRIATE TRADE.
- COORDINATE LUMINAIRE LOCATIONS SUCH THAT LUMINAIRES RUN PARALLEL TO THE FACE OF THE RADIANT AND OVERLAP ALL OVERLAPPING EQUIPMENT IN ALL MECHANICAL AND ELECTRICAL EQUIPMENT AREAS. INSTALL AT PROPER LOCATIONS AND HEIGHTS TO PROPERLY ILLUMINATE ALL GAGES, PANELS, ELECTRICAL EQUIPMENT, CONTROLS, VALVES, ETC. CHAIN HANGING, STEM HANGING, CHANNEL HANGING, ETC. ARE ACCEPTABLE METHODS.

GENERAL DEMOLITION NOTES

- REMOVE, CAP AND RELOCATE EQUIPMENT, OUTLETS, CONDUIT, WIRE, ETC., AS SHOWN AND SPECIFIED ON DRAWINGS, AND AS MAY BECOME NECESSARY BECAUSE OF EXISTING FIELD CONDITIONS. VISIBLY EXAMINE ALL EXISTING WALLS DESIGNATED FOR REMOVAL TO DETERMINE THE CONDUIT AND THE WIRING THAT WILL REQUIRE CAPPING AND REMOVAL, WHETHER OR NOT SUCH CONDITIONS ARE INDICATED ON THE DRAWINGS. FAILURE TO VISIT THE SITE AND TO TAKE ALL EXISTING CONDITIONS INTO ACCOUNT WILL NOT ALLOW FOR CHANGES TO THE SCOPE OF WORK.
- MAINTAIN CIRCUIT CONTINUITY TO ALL EXISTING FIXTURES, EQUIPMENT, OUTLETS, ETC., TO REMAIN IN USE. RECONNECT RACEWAYS AND WIRING FOR EXISTING CIRCUITS WHICH MUST BE REROUTED OR WHICH ARE PARTIALLY ABANDONED TO POWER THE REMAINING OUTLETS ON THE CIRCUIT.
- REMOVE ALL UNUSED WIRING AND CABLES BACK TO THEIR SOURCE. REMOVE ALL UNUSED CONDUIT THAT IS EXPOSED OR ABOVE ACCESSIBLE CEILINGS WHICH IS AFFECTED BY OR IS IN THE AREA OF THE DEMOLITION WORK.
- THE INTENTION OF THE ELECTRICAL DEMOLITION DRAWINGS IS TO DISCONNECT AND REMOVE ALL ELECTRICAL WORK MADE VOID BY THE SCOPE OF THE CONSTRUCTION AND ALTERATION. FIELD VERIFY EXACT MATERIAL QUANTITIES REQUIRED TO BE REMOVED.
- DISCONNECT AND REMOVE ALL EXISTING ELECTRICAL EQUIPMENT, DEVICES, ASSOCIATED RACEWAYS, SUPPORTING HARDWARE, AND WIRING, WHICH HAVE BEEN MADE OBSOLETE BY THE WORK OR IS SHOWN DASHED ON THE ELECTRICAL DEMOLITION DRAWINGS, UNLESS OTHERWISE NOTED. ALTHOUGH AN ATTEMPT HAS BEEN MADE TO INDICATE ALL OF THIS WORK, TOTAL ACCURACY IS NOT GUARANTEED. VISIBLY EXAMINE ALL AREAS AND WALLS AND CEILINGS SCHEDULED FOR REMOVAL TO DETERMINE EXISTING ELECTRICAL ITEMS TO REMAIN.
- WHERE ELECTRICAL EQUIPMENT, CONDUIT, BOXES, AND SUPPORTING HARDWARE ARE REMOVED, PATCH AND FINISH THE SURFACE AS REQUIRED TO MATCH THE EXISTING, USING WORKERS QUALIFIED IN THE APPROPRIATE TRADE.
- WHERE BURIED CONDUITS EXTENDING OUT OF A CONCRETE SLAB BECOME ABANDONED, CUT AND GRIND THE CONDUITS OFF FLUSH WITH TOP OF SLAB AND PLUG WITH NON-SHRINK WATERPROOF GROUT FILL.
- TAKE ALL REMOVED MATERIALS FROM THE PROJECT SITE. EXCEPT FOR THOSE TO BE RELOCATED, STORED, OR TURNED OVER TO THE OWNER.
- ACCEPTANCE OF CONTRACT MEANS INSTALLER ACCEPTS EXISTING CONDITIONS.
- COORDINATE ALL DEMOLITION WORK WITH ALL OTHER TRADES.
- PROVIDE A BLANK COVER OVER THE OUTLET WHERE A FLUSH DEVICE IS BEING REMOVED FROM FLOORS AND WALLS THAT ARE TO REMAIN. MATCH THE COLOR AND MATERIAL TO THE EXISTING REMAINING COVERS IN THE ROOM OR SPACE.
- LEGALLY DISPOSE OF HAZARDOUS MATERIALS AND BALLASTS OR OTHER EQUIPMENT CONTAINING PCBs AND LAMPS CONTAINING MERCURY. COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS.
- UPON COMPLETION OF CONSTRUCTION, PROVIDE RED-LINE PANEL SCHEDULE DEPICTING THE ACTUAL CIRCUITS MODIFIED OR ADDED AS PART OF THIS PROJECT TO UMHC. PROVIDE NEW TYPED PANELBOARD DIRECTORY CARDS WITHIN EACH PANEL ENCLOSURE FOR ALL PANELS MODIFIED AS PART OF THIS PROJECT. FOR NEW LOADS, DESCRIBE THE SPECIFIC LOAD TYPE AND LOCATION IN THE CIRCUIT DESCRIPTION FIELD IN THE DIRECTORY CARDS GIVEN TO UMHC. FOR EXISTING TO REMAIN LOADS, TRANSPROSE THE ACTUAL CIRCUIT DESCRIPTION INFORMATION PROVIDED ON THE EXISTING PANELBOARD DIRECTORY CARD. DO NOT USE "EXISTING LOAD" VERBIAGE IN THE CIRCUIT DESCRIPTION. WHERE ALL LOADS ARE DEMOLISHED FROM A CIRCUIT, CONTRACTOR TO MOVE CIRCUIT BREAKER HANDLE TO THE OFF POSITION AND INDICATE POLE POSITION AS "SPARE" IN THE NEW PANELBOARD DIRECTORY CARD.

DRAWING REFERENCES



ABBREVIATIONS


A.F.F.	: ABOVE FINISHED FLOOR
C	: CONDUIT
E.C.	: ELECTRICAL CONTRACTOR
ER	: EXISTING RELOCATED
ETR	: EXISTING TO REMAIN
EWC	: ELECTRIC WATER COOLER
G.C.	: GENERAL CONTRACTOR
GND	: GROUND
TYP	: TYPICAL
U.O.N.	: UNLESS OTHERWISE NOTED

LINE TYPE LEGEND


(Solid line)	EXISTING TO REMAIN OR NEW WORK BY OTHERS (LIGHT, SOLID LINE)
(Dashed line)	NEW WORK BY THIS CONTRACTOR (DARK, SOLID LINE)
(Dash-dot line)	EXISTING TO BE REMOVED BY THIS CONTRACTOR (DARK, DASHED LINE, DEMOLITION PLANS)
(Long dashed line)	NEW WORK BY THIS CONTRACTOR TO BE INSTALLED UNDERGROUND, OR BELOW FLOOR (DARK, LONG DASHED LINE)

WIRING PLANS


- PROVIDE WIRING REQUIRED BY THE CIRCUITING AND SWITCHING REQUIREMENTS FOR THE PARTICULAR CIRCUITS INVOLVED. TYPICAL 120V HOMERUNS SHALL CONSIST OF #12 AWG CONDUCTORS IN 3/4" CONDUIT MINIMUM UNLESS INDICATED OTHERWISE. NO SHARED NEUTRALS SHALL BE ALLOWED. A MAXIMUM OF NINE CURRENT-CARRYING CONDUCTORS ARE ALLOWED IN A RACEWAY. NEUTRAL CONDUCTORS ARE ALSO CONSIDERED CURRENT-CARRYING CONDUCTORS. FOR CIRCUITS EXCEEDING 75'-0" IN LENGTH, PROVIDE THE NEXT LARGER WIRE SIZE FOR THE CIRCUIT AMPACITY.
- WHERE NUMBER OF CURRENT-CARRYING CONDUCTORS IN A RACEWAY EXCEEDS THREE, THE ALLOWABLE AMPACITY OF EACH CONDUCTOR SHALL BE REDUCED AS SHOWN IN THE ADJUSTMENT FACTOR TABLE IN THE NATIONAL ELECTRIC CODE. LOAD DIVERSITY FACTORS SHALL NOT BE USED IN SIZING CONDUCTORS. NEUTRAL CONDUCTORS SHALL BE COUNTED AS CURRENT-CARRYING CONDUCTORS.



SECURITY ALARM SYSTEMS




POWER EQUIPMENT




WIRING DEVICES, RECEPTACLES - MISC.

- TYPICAL MOUNTING HEIGHT: +18" A.F.F.
- SUBSCRIPT LEGEND:
 - A: ABOVE COUNTER: MOUNT +6" ABOVE BACKSPASH OR WORK SURFACE
 - C: CEILING MOUNT FLUSH WITHIN CEILING TILE OR GYPSUM BOARD
 - CR: COMPUTER RECEPTACLE: PROVIDE LABEL TO READ: "COMPUTER"
 - S: SWITCHED: PROVIDE ONE OUTLET CONTROLLED BY TOGGLE SWITCH
 - U: UNDER COUNTER: WITHIN CABINETRY OR CASEWORK

A SLASH BETWEEN TWO SUBSCRIPTS INDICATES MULTIPLE PARAMETERS (EXAMPLE: A/3 DENOTES ABOVE COUNTER MOUNTING, 3 CABLES.)




ACCESS CONTROL SYSTEMS



REFER TO LOW VOLTAGE RESPONSIBILITY MATRIX ON SHEET E100 FOR MORE INFORMATION.

PUBLIC ADDRESS SYSTEMS



REFER TO LOW VOLTAGE RESPONSIBILITY MATRIX ON SHEET E100 FOR MORE INFORMATION.

LUMINAIRES

- REFER TO LUMINAIRE SCHEDULE FOR LUMINAIRE DESCRIPTIONS.
- "NL" INDICATES UNSWITCHED LUMINAIRE
- "SE" DESIGNATION INDICATES LUMINAIRE IS SWITCHED DURING NORMAL OPERATION, BUT UPON LOSS OF POWER, LUMINAIRE REVERTS TO 100% OUTPUT VIA BATTERY BALLAST, REGARDLESS OF THE ON/OFF STATUS OF THE LOCAL LIGHTING CONTROL DEVICE. EXTEND AN UNSWITCHED PORTION OF THE LIGHTING CIRCUIT SERVING AREA, AHEAD OF ALL LIGHTING CONTACTORS, TO THIS DEVICE.
- SHADING LEGEND (APPLICABLE TO LUMINAIRE SYMBOLS):
 - NO SHADING: NORMAL POWER
 - HALF-SHADING: LIFE SAFETY OR BATTERY BACKUP
 - FULL-SHADING: CRITICAL POWER
- LUMINAIRE DESIGNATION KEY:
 - A: LUMINAIRE TYPE
 - 1: CIRCUIT NUMBER
 - a: CONTROLLING SWITCH


SWITCHES AND LIGHTING CONTROL DEVICES

- TYPICAL MOUNTING HEIGHT: 48" A.F.F. TO CENTER U.O.N.
- WHERE TWO OR MORE SWITCHES ARE SHOWN ADJACENT TO EACH OTHER, PROVIDE A COMMON GANG BOX WITH A SINGLE, SEAMLESS FACEPLATE.
- SUBSCRIPT LEGEND:
 - 2: TWO-POLE SWITCH
 - 3: THREE-WAY SWITCH
 - 4: FOUR-WAY SWITCH
 - K: KEY SWITCH
 - D: DIMMER - COORDINATE REQUIREMENTS FOR LUMINAIRE COMPATIBILITY
 - P: PILOT LIGHT SWITCH
 - C: MOMENTARY CONTACT SWITCH
 - LV: LOW VOLTAGE CONTROL MASTER STATION
 - L: LOW VOLTAGE LOCAL SINGLE/PUSH BUTTON STATION
- A LOWERCASE SUBSCRIPT INDICATES THE SWITCH/LEG THE DEVICE CONTROLS. REFER TO SPECIFICATION SECTION 26 09 23 FOR ADDITIONAL INFORMATION.
 - SWITCH - TYPE AS INDICATED BY SUBSCRIPT
 - CEILING OCCUPANCY DETECTOR : INFRARED SENSOR TYPE.
 - CEILING OCCUPANCY DETECTOR : ULTRASONIC TYPE.
 - CEILING OCCUPANCY DETECTOR : DUAL TECHNOLOGY TYPE.
 - WALL MOUNTED SINGLE SWITCH OCCUPANCY SENSOR [PIR][ULTRASONIC][DUAL TECHNOLOGY] TYPE
 - WALL MOUNTED DUAL SWITCH OCCUPANCY SENSOR [PIR][ULTRASONIC][DUAL TECHNOLOGY] TYPE
 - CEILING PHOTOCELL
 - DIGITAL TIMER

TELECOMMUNICATIONS

- TYPICAL MOUNTING HEIGHT: +18" A.F.F. UNLESS OTHERWISE NOTED. PROVIDE OR 4 11/16" SQUARE BOX WITH SINGLE GANG PLASTER RING (VERTICAL).
 - ALL TELECOMMUNICATION CONDUIT SHALL BE A MINIMUM OF 1-1/4" IN DIAMETER STUBBED TO ACCESSIBLE CORRIDOR CEILING SPACE, UNLESS OTHERWISE NOTED.
 - ALL TELECOMMUNICATION CABLE SHALL BE OWNER PROVIDED WITH A PLENUM RATED JACKET. ALL CABLES RUN EXPOSED IN STRUCTURE ABOVE OR ABOVE CEILINGS SHALL BE SUPPORTED BY J-HOOKS AT EVERY 5'-0" TO NEAREST CABLE TRAYS. PROVIDE INSULATED BUSHINGS ON ALL RACEWAYS.
 - ALL DATA CABLES SHALL BE CAT 6A, YELLOW IN COLOR, AND TERMINATED BY OWNER.
 - REFER TO LOW VOLTAGE RESPONSIBILITY MATRIX ON E100 FOR MORE INFORMATION.
 - SUBSCRIPT LEGEND:
 - A: ABOVE COUNTER - MOUNT +6" ABOVE BACKSPASH OR WORK SURFACE WITH BOX ORIENTED HORIZONTALLY
 - C: CEILING MOUNTED - MOUNT FLUSH WITHIN CEILING TILE OR GYPSUM CEILING
 - W: WALL PHONE - MOUNT +48" A.F.F. OR 6" ABOVE WORK SURFACE. PROVIDE MOUNTING LUGS FOR TELEPHONE
 - WAP: WIRELESS ACCESS POINT DATA OUTLET - INSTALL ONE (1) OWNER FURNISHED CAT 6A CABLE AND 10'-0" OF SLACK CABLE COILED ABOVE ACCESSIBLE CEILING FROM TELECOM ROOM. WIRELESS ACCESS POINTS ARE OWNER FURNISHED, OWNER INSTALLED.
 - #: QUANTITY OF OWNER FURNISHED CAT 6A CABLES TO BE INSTALLED BY CONTRACTOR. WHEN NOT INDICATED, THREE (3) CABLES SHALL BE ASSUMED. CABLES SHALL ORIGINATE FROM TELECOMMUNICATION.
- A SLASH BETWEEN TWO SUBSCRIPTS INDICATES MULTIPLE PARAMETERS (EXAMPLE: A/3 DENOTES ABOVE COUNTER MOUNTING, 3 CABLES.)
-

JUNCTION AND PULL BOXES



NURSE CALL SYSTEMS

- COORDINATE ALL ROUGH-IN LOCATIONS WITH OWNER'S NURSE CALL VENDOR (ALL SYSTEMS) AND ARCHITECTURAL ELEVATIONS PRIOR TO COMMENCING WORK.
- PROVIDE RECESSED ROUGH-IN COMPONENTS CONSISTING OF 4" x 4" x 3.5" DOUBLE GANG BOX WITH SINGLE GANG MUD RING AND ONE (1) 1" CONDUIT STUBBED TO ABOVE CEILING SPACE WITH BUSHING. PROVIDE J-HOOK SUPPORTS ABOVE CEILING BETWEEN DEVICE, CORRIDOR FIRE RATED PATHWAY, AND CABLE TRAY.
- REFER TO LOW VOLTAGE RESPONSIBILITY MATRIX ON SHEET E100 FOR MORE INFORMATION.
 - EMERGENCY PULL CORD STATION : +3f" A.F.F. AT TOILETS, +7f" AT SHOWER STATIONS. CORD LENGTH SHALL EXTEND TO +6" A.F.F.
 - EMERGENCY PUSHBUTTON STATION : +44" A.F.F. U.O.N.
 - CODE BLUE STATION : +44" A.F.F. U.O.N.
 - WALL MOUNTED DOME LIGHT: MOUNT ABOVE DOOR JAMB, CENTERED BETWEEN TOP OF DOOR FRAME AND CEILING

FIRE ALARM SYSTEMS


- REFER TO SPECIFICATIONS SECTION 283111 FOR ADDITIONAL INFORMATION PERTAINING TO THE FIRE ALARM SYSTEM.
- SIGNALING LINE CIRCUITS SHALL BE ROUTED IN A CLASS B CONFIGURATION.
- NOTIFICATION APPLIANCE CIRCUITS SHALL BE ROUTED IN A CLASS B CONFIGURATION.
- FIRE ALARM CIRCUITS SHALL BE ROUTED IN CONDUIT WHERE INACCESSIBLE. WHERE ROUTED ABOVE ACCESSIBLE CEILINGS, FIRE ALARM CIRCUITS SHALL CONSIST OF PLENUM RATED CABLE SUPPORTED EVERY 4'-0" BETWEEN DEVICES.
- FOR VISUAL DEVICES, THE # WITHIN THE SYMBOL CORRESPONDS TO THE CANDELA RATING OF THE DEVICE: 1=15cd, 3=30cd, 5=75cd, 7=110cd.
- WALL MOUNTED NOTIFICATION DEVICES SHALL BE MOUNTED WITH THE TOP OF THE DEVICE +9f" A.F.F. OR 6" BELOW THE CEILING, WHICHEVER IS LOWER.
 - FIRE ALARM MANUAL STATION : +48" A.F.F. TO CENTER LINE
 - WALL MOUNTED SPEAKER
 - WALL MOUNTED SPEAKER WITH STROBE
 - WALL MOUNTED STROBE
 - CEILING MOUNTED SPEAKER WITH STROBE
 - CEILING MOUNTED SPEAKER
 - HEAT DETECTOR : FIXED TEMPERATURE
 - HEAT DETECTOR : RATE OF RISE
 - SMOKE DETECTOR : PHOTOELECTRIC TYPE
 - DUCT MOUNTED SMOKE DETECTOR : PHOTOELECTRIC TYPE
 - SPRINKLER SYSTEM WATER FLOW SWITCH
 - SPRINKLER SYSTEM TAMPER (SUPERVISORY) SWITCH
 - SPRINKLER SYSTEM ELECTRICAL SOLENOID VALVE
 - EXTINGUISHING SYSTEM PRESSURE SWITCH
 - SINGLE STATION SMOKE DETECTOR WITH SOUNDER BASE
 - FIRE ALARM ELECTROMAGNETIC DOOR HOLDER
 - CONTACT IN KITCHEN EXTINGUISHING SYSTEM PANEL FOR CONNECTION INTO FIRE ALARM SYSTEM
 - END OF LINE RESISTOR
 - ADDRESSABLE CONTROL RELAY
 - ADDRESSABLE MONITOR MODULE
 - SMOKE DAMPER



12101 W 110th Street, Suite 100
Overland Park, KS 66201
913.232.2123
MO Certificate of Authority Number
A-201100790


Project Title:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO 63119

Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08/29/2022

Drawn by: Author
bcdg Project #: 12275_27
MU Project #: CP202091




GENERAL NOTES

1. IN AREAS WHERE DEMOLITION WORK IS NOT SCHEDULED, DISCONNECT, REMOVE, AND SALVAGE EXISTING CEILING MOUNTED DEVICES, LUMINAIRES, ETC. AS REQUIRED TO COMPLETE ABOVE CEILING WORK FOR ALL TRADES. UPON COMPLETION OF CONSTRUCTION, REINSTALL EXISTING CEILING MOUNTED DEVICES IN ORIGINAL LOCATIONS. DEVICES SHALL OPERATE AS THEY DID PRIOR TO CONSTRUCTION.
2. CONTRACTOR SHALL FIELD VERIFY AND REMOVE ALL FIRE ALARM DEVICES AND POWER CONNECTIONS ASSOCIATED WITH AHJ SHUTDOWN, FIRE/SMOKE DAMPERS, AND DUCT WORK BEING REMOVED AS PART OF THIS SCOPE. REMOVED DEVICES SHOULD BE REMOVED FROM FIRE ALARM PROGRAMMING. REFER TO MECHANICAL DEMOLITION SHEETS FOR ADDITIONAL INFORMATION.
3. DISCONNECT, REMOVE, AND SALVAGE ALL FIRE ALARM NOTIFICATION DEVICES FOR RE-USE WITH NEW WORK. ALL FIRE ALARM CABLE AND CONDUIT SHALL BE DISCONNECTED AND REMOVED BACK TO SOURCE.
4. RE-SUPPORT ALL EXISTING TO REMAIN ELECTRICAL SYSTEMS (CONDUIT, WIRE, CABLE, ETC.) CURRENTLY SUPPORTED BY WALLS SCHEDULED TO BE DEMOLISHED.

KEYED NOTES

1. DISCONNECT AND REMOVE EXISTING RECEPTACLE DEVICE AND PRESERVE EXISTING BACKBOX AND WIRING FOR RE-USE IN NEW CONSTRUCTION. SEE SHEET E100.


ELECTRICAL DEMOLITION FLOOR PLAN
1/8" = 1'-0"



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201102790

Project Team:
ROSS & BARUZZINI, INC.
8 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119


Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author
bcbg Project #: 12275.27
MU Project #: CP202091

ED100
ELECTRICAL - GROUND FLOOR
- DEMOLITION




- ### GENERAL NOTES
1. IN AREAS WHERE DEMOLITION WORK IS NOT SCHEDULED, DISCONNECT, REMOVE, AND SALVAGE EXISTING CEILING MOUNTED DEVICES, LUMINAIRES, ETC. AS REQUIRED TO COMPLETE ABOVE CEILING WORK FOR ALL TRADES. UPON COMPLETION OF CONSTRUCTION, REINSTALL EXISTING CEILING MOUNTED DEVICES IN ORIGINAL LOCATIONS. DEVICES SHALL OPERATE AS THEY DID PRIOR TO CONSTRUCTION.
 2. CONTRACTOR SHALL FIELD VERIFY AND REMOVE ALL FIRE ALARM DEVICES AND POWER CONNECTIONS ASSOCIATED WITH AHJ SHUTDOWN, FIRE/SMOKE DAMPERS, AND DUCT WORK BEING REMOVED AS PART OF THIS SCOPE. REMOVED DEVICES SHOULD BE REMOVED FROM FIRE ALARM PROGRAMMING. REFER TO MECHANICAL DEMOLITION SHEETS FOR ADDITIONAL INFORMATION.
 3. DISCONNECT, REMOVE, AND SALVAGE ALL FIRE ALARM NOTIFICATION DEVICES FOR RE-USE WITH NEW WORK. ALL FIRE ALARM CABLE AND CONDUIT SHALL BE DISCONNECTED AND REMOVED BACK TO SOURCE.
 4. RE-SUPPORT ALL EXISTING TO REMAIN ELECTRICAL SYSTEMS (CONDUIT, WIRE, CABLE, ETC.) CURRENTLY SUPPORTED BY WALLS SCHEDULED TO BE DEMOLISHED.
 5. LEGALLY DISPOSE OF LIGHTING BALLASTS AND LAMPS CONTAINING MERCURY. COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS.



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201102790

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212




Issue Date: 08.29.2022
Date

Drawn by: Author
bcdg Project #: 12275.27
MU Project #: CP202091

ED101
LIGHTING - GROUND FLOOR -
DEMOLITION

ELECTRICAL DEMOLITION CEILING PLAN
1/8" = 1'-0"





bc DESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210


913.232.2123

MO Certificate of Authority Number
A-201102790

Project Team:

ROSS & BARUZZINI, INC.
8 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022

Drawn by: Author

bcdg Project #: 12275.27
MU Project #: CP202091

E100

ELECTRICAL - GROUND FLOOR
- NEW WORK

BID SET

CONTRACTOR RESPONSIBILITY
OWNER RESPONSIBILITY

LEGEND:
F: FURNISHED
I: INSTALLED

GENERAL LOW VOLTAGE ITEMS	
LOW VOLTAGE RACKS	F, I
RACK CABLE MANAGEMENT	F, I
CONDUIT SLEEVES	F, I
GROUNDING AND BONDING (GROUND BARS, CONDUCTORS, TERMINATIONS, ETC.)	F, I
CABLE PATHWAYS, CABLE TRAY, LADDER TRAY	F, I
LADDER RACK	F, I
FIRESTOPPING FOR LOW VOLTAGE SYSTEMS	F, I
FIRE RATED PATHWAYS	F, I
EQUIPMENT, CABLE, AND OUTLET FACEPLATE LABELING	F, I
CORE DRILLING FLOOR/WALL SLEEVES	F, I
TELECOMMUNICATIONS SYSTEMS	
FIBER SERVICE AND HORIZONTAL DISTRIBUTION FROM HOSPITAL	F, I
FIBER SWITCH AND TERMINATIONS	F, I
EQUIPMENT (SERVERS, SWITCHES, PDU, ETC.)	F, I
TELECOM ROOM LADDER RACK	F, I
PATCH PANELS	F, I
PATCH CABLES	F, I
HORIZONTAL CABLING AND TERMINATIONS	F, I
BACKBOXES AND CONDUITS	F, I
OUTLET FACEPLATES AND TERMINATIONS	F, I
WIRELESS ACCESS POINTS	F, I
COMMUNITY ACCESS TELEVISION SYSTEM (CATV)	
CABLE DISTRIBUTION (BETWEEN TELECOM ROOMS)	F, I
AMPLIFIERS AND SPLITTERS	F, I
EQUIPMENT, HEAD-END ELECTRONICS	F, I
HORIZONTAL CABLING AND TERMINATIONS	F, I
BACKBOXES AND CONDUITS	F, I
OUTLET FACEPLATES AND TERMINATIONS	F, I
ACCESS CONTROL	
HEAD-END EQUIPMENT	F, I
BACKBOXES AND CONDUITS	F, I
DEVICES (CARD READERS, KEYPADS, ETC.)	F, I
INTERCONNECTION WIRING AND TERMINATIONS	F, I
VIDEO SURVEILLANCE	
HEAD-END EQUIPMENT (HARDWARE, SOFTWARE, DISPLAYS, ETC.)	F, I
CAMERAS AND SUPPORTS	F, I
HORIZONTAL CABLING AND TERMINATIONS	F, I
BACKBOXES AND CONDUITS	F, I
NURSE CALL	
HEAD-END EQUIPMENT, UPS, AND PROGRAMMING	F, I
HORIZONTAL CABLING AND TERMINATIONS	F, I
BACKBOXES AND CONDUITS	F, I
DEVICES	F, I
INTERCONNECTION WIRING AND TERMINATIONS TO PERIPHERALS	F, I
PUBLIC ADDRESS SYSTEM	
HEAD-END EQUIPMENT	F, I
HORIZONTAL CABLING AND TERMINATIONS	F, I
BACKBOXES AND CONDUITS	F, I
SPEAKERS	F, I
SOUND MASKING SYSTEM - ALTERNATE #1	
SYSTEM CONTROLLER	F, I
HORIZONTAL CABLING AND TERMINATIONS	F, I
MOUNTING COMPONENTS AND CONDUITS	F, I
SPEAKERS/EMITTERS	F, I

GENERAL NOTES

- REFER TO SHEET E000 FOR ELECTRICAL GENERAL NOTES.
- CIRCUIT NUMBERS ARE FOR REFERENCE AND ARE SHOWN FOR LOADING PURPOSES ONLY. CONTRACTOR TO USE CIRCUITS MADE SPARE FROM DEMOLITION AND AVAILABLE SPARE CIRCUIT BREAKERS IN PANEL NBB AND IF NECESSARY PANEL NBA. CONTRACTOR MAY CONNECT NEW RECEPTACLES TO EXISTING CIRCUITS ALREADY IN ROOMS SO LONG AS THERE ARE NO MORE THAN (6) RECEPTACLES ON A SINGLE CIRCUIT. DEVICES SHOWN ON DEDICATED CIRCUITS TO REMAIN ON DEDICATED CIRCUITS.
- ALL ELECTRICAL CIRCUITS SHOWN ARE CONNECTED TO PANEL NBB UNLESS OTHERWISE NOTED.

KEYED NOTES

- PROVIDE NEW TAMPER RESISTANT RECEPTACLE IN EXISTING DEVICE BOX AND NEW COVER PLATE. CONNECT TO EXISTING WIRING.
- REMOVE (2) 20A-1P CIRCUIT BREAKERS AND PROVIDE (1) NEW 20A-2P CIRCUIT BREAKER FOR TREADMILL. FIELD VERIFY EXACT CIRCUIT NUMBERS BASED ON CIRCUITS MADE SPARE FROM DEMOLITION. MATCH EXISTING MANUFACTURER AND AIC RATING.

- NOTES:
- THE PARTY RESPONSIBLE FOR INSTALLING THE RESPECTIVE EQUIPMENT SHALL ALSO BE RESPONSIBLE FOR CONNECTING, PROGRAMMING AND TESTING THE SYSTEM, UNLESS OTHERWISE SPECIFICALLY NOTED. CONTRACTOR TO COORDINATED TESTING WITH ALL THIRD PARTY VENDORS.
 - ITEMS INDICATED AS FURNISHED AND/OR INSTALLED BY THE OWNER MAY BE PROVIDED BY A THIRD-PARTY VENDOR. CONTRACTOR IS REQUIRED TO COORDINATE ALL INSTALLATIONS.
 - ALL LINE VOLTAGE RECEPTACLE AND HARD-WIRED CONNECTIONS WILL BE PROVIDED BY THE CONTRACTOR.
 - FIRESTOPPING TO BE PROVIDED BY A SINGLE ENTITY. REFER TO DIVISION 07 SPECIFICATIONS FOR REQUIREMENTS.

2 LOW VOLTAGE RESPONSIBILITY MATRIX


NO SCALE



KEYPLAN



1 ELECTRICAL NEW WORK FLOOR PLAN
1/8" = 1'-0"






GENERAL NOTES

- REFER TO SHEET E000 FOR ELECTRICAL GENERAL NOTES.
- IN GENERAL, THE USE OF MC CABLE IS NOT PERMITTED ON THIS PROJECT. THE ONE EXCEPTION TO THAT IS FOR THE VERTICAL DROP AND FINAL CONNECTION TO THE UNDER CABINET LIGHT FIXTURES. CONTRACTOR TO PROVIDE A JUNCTION BOX ABOVE THE CEILING IN PROXIMITY TO THE WALL(S) THE CABINETS ARE MOUNTED ON AND TRANSITION THE VERTICAL DROP TO THE UNDER CABINET LIGHT FIXTURE TO HOSPITAL GRADE MC CABLE, INCLUSIVE OF FINAL TERMINATION. REFER TO DETAIL 1/ES01 FOR TYPICAL WIRING TO UNDERCABINET LIGHTS.

KEYED NOTES

- NEW EMERGENCY LIGHTING INVERTER, MEYERS EMERGENCY POWER SYSTEMS MODEL 6EM-2-S. CONNECT TO SPARE 20A-1P, 277V CIRCUIT BREAKER IN PANEL NB1. PROVIDE NEW EMERGENCY CIRCUIT WIRING TO ALL NEW EXIT SIGNS AND LIGHTING FIXTURES MARKED AS EMERGENCY.


1 ELECTRICAL NEW WORK CEILING PLAN
1/8" = 1'-0"



12101 W 110th Street, Suite 100
Overland Park, KS 66210
913.232.2123
MO Certificate of Authority Number
A-201102790

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119


Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212



Issue Date: 08.29.2022
Date:

Drawn by: Author
bcbg Project #: 12275.27
MU Project #: CP202091

E101
LIGHTING - GROUND FLOOR -
NEW WORK



bc DESIGN GROUP

12101 W 110th Street, Suite 100
Overland Park, KS 66210

913.232.2123
MO Certificate of Authority Number
A-201102792

Project Team:
ROSS & BARUZZINI, INC.
6 SOUTH OLD ORCHARD | ST. LOUIS, MO
63119

LUMINAIRE SCHEDULE

LUMINAIRE SCHEDULE GENERAL NOTES:

- ALL LUMINAIRES SHOWN ON THIS SCHEDULE MAY NOT BE USED ON THE VARIOUS PLANS. ALSO, THE USE OF ONLY CERTAIN NUMERICAL SUBSCRIPTS FOR LUMINAIRE TYPES (e.g. R2, R3, P2, P3, etc.) ON THIS PROJECT DOES NOT NECESSARILY MEAN THAT ON H1 OR A1 IS USED OR MISSING.
- CONTRACTOR IS RESPONSIBLE FOR ALL MISCELLANEOUS HARDWARE, CLIPS, ANGLES, FRAMES, ETC. AS REQUIRED TO MOUNT THE LUMINAIRES IN OR ON THE SURFACES THEY ARE TO BE INSTALLED.
- REFER TO ARCHITECTURAL DOCUMENTS FOR EXACT MOUNTING LOCATIONS OF LUMINAIRES AND CEILING TYPES.
- WHEN INSTALLING LUMINAIRES, THE CONTRACTOR SHALL USE THE LUMINAIRE MANUFACTURER'S MOUNTING HARDWARE AND FOLLOW ALL MANUFACTURER'S INSTALLATION DIRECTIONS.
- ALL RECESSED DOWNLIGHTS SHALL HAVE SELF-FLANGED REFLECTORS U.O.N. AND SHALL BE INSTALLED SO THAT THE BOTTOM OF THE THROAT IS EVEN WITH THE FINISHED CEILING PLANE. THE OVERLAPPING FLANGE MUST THEN FIT FLUSH TO THE CEILING PLANE/THROAT. NO LIGHT LEAK MUST BE VISIBLE. ALL MISCELLANEOUS HARDWARE ABOVE THE CEILING PLANE TO ACCOMPLISH THE ABOVE SHALL BE INCLUDED IN THE BASE BID.
- ALL LUMINAIRES SHALL HAVE A U.L. LABEL.
- IN ALL MECHANICAL ELECTRICAL EQUIPMENT AREAS, CONTRACTOR TO COORDINATE LUMINAIRE LOCATIONS SUCH THAT LIGHT LUMINAIRES RUN PARALLEL TO THE FACE OF THE EQUIPMENT AND OVER AISLES BETWEEN EQUIPMENT. INSTALL AT EXACT LOCATIONS AND AT EXACT HEIGHT TO ILLUMINATE ALL GAGES, PANELS, CONTROLS, VALVES, ETC. CHAIN HANGING, STEM HANGING, UNISTRUT HANGING, ETC. ARE ACCEPTABLE METHODS.
- ALL LUMINAIRES SHALL OPERATE AT 120 OR 277 VOLTS OR OTHER VOLTAGE AS REQUIRED BY THE CIRCUITS AND/OR PANELS TO WHICH THEY ARE CONNECTED.
- WHEN LUMINAIRES ARE INSTALLED IN CONTINUOUS ROWS TWO (2) OR MORE, LUMINAIRES SHALL BE APPROVED FOR USE AS WIREWAY.
- REFER TO SPECIFICATION SECTION 265100 LIGHTING FOR ADDITIONAL INFORMATION CONCERNING LUMINAIRES, FINISHES, BALLASTS, LAMPS, ETC.
- COMPLETE CATALOG NUMBER MAY NOT BE LISTED. ORDER LUMINAIRE BASED ON DESCRIPTION, PARTIAL CATALOG NUMBER AND SPECIFICATIONS. THE FIRST MANUFACTURER LISTED IS THE BASIS-OF-DESIGN.
- WHEN VARYING FROM BASIS-OF-DESIGN LUMINAIRE, PROVIDE A LUMINAIRE UTILIZING ±10% OF THE LED LUMENS INDICATED IN LUMINAIRE SCHEDULE.
- VERIFY COMPATIBILITY OF ALL DIMMING BALLASTS WITH SPECIFIED DIMMING CONTROLS PRIOR TO ORDERING AND PROVIDE APPROPRIATE COMPONENTS TO CREATE A COMPLETE AND FULLY FUNCTIONAL INSTALLATION.

PLAN MARK	DESCRIPTION	MANUFACTURER	REMARKS	COLOR TEMP.	LAMP TYPE	LED LUMENS	DRIVER	WATTAGE
RA	2X2', 3-1/4" TALL, RECESSED LED LUMINAIRE, EXTRUDED ALUMINUM HOUSING WITH INJECTED MOLDED COMPOSITE END PLATES, GRID-LOCK FEATURE, HIGH OPTICAL GRADE ACRYLIC LENS, HIGH REFLECTANCE BAKED WHITE ENAMEL FINISH, DAMP LOCATION LISTED.	METALUX ENCOUNTER 22EN-LD2-34-UNV-L835-CD-1 OR APPROVED EQUAL		3500	LED	3400	DIM	29 W
RB	4" ROUND, 5 1/2" TALL LED DOWNLIGHT, MEDIUM BEAM DISTRIBUTION, SPUN ALUMINUM REFLECTOR, DIE-CAST ALUMINUM 1-1/2" DEEP COLLAR, ALUMINUM HEAT SINK, WHITE POLYMER TRIM RING, SPECULAR CLEAR FINISH.	PORTFOLIO LD4B-20-D010-EU4B-1020-80-35-4LB-M-0-LI OR APPROVED EQUAL		3500	LED	2390	DIM	21 W
UA	18" X .075"H X 4.37" DEEP LOW PROFILE LED UNDERCABINET TASK LIGHT, ALUMINUM HOUSING, WHITE FINISH, LENGTH AS SHOWN ON DRAWINGS, PROVIDE HARDWARE CONNECTION AND ROCKER SWITCH. COORDINATE ACTUAL LENGTH WITH CABINETS PROVIDED.	HALO HU30B3C18P		3500	LED	440	DRIVER	8 W
XA	CEILING MOUNT, DIE CAST AND EXTRUDED ALUMINUM HOUSING WITH BRUSHED ALUMINUM FINISH, HIGH IMPACT ACRYLIC CLEAR PANEL, EDGE LIT WITH RED LETTERS, SINGLE SIDED, DIRECTIONAL CHEVRONS PER PLANS	SURE-LITES EUX6-1-R OR APPROVED EQUAL		NA	LED	NA	DRIVER	1 W

Branch Panel: NB1

Location: Volts: 480Y/277V
Supply From: Phases: 3
Mounting: Surface Wires: 4
Enclosure: Type 1
A.I.C. Rating:
Mains Type:
Mains Rating: 225 A
MCB Rating:

CKT	Circuit Description	Trip	Poles	A	B	C	Poles	Trip	Circuit Description	CKT	
1	EXISTING LOAD: LIGHT 0302, E0200	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: LIGHT 0100, 0004, 0003, 0102	2	
3	EXISTING LOAD: LIGHT C0100	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: LIGHT	4	
5	EXISTING LOAD: LIGHT W 0200	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: LIGHT 0002, 0201	6	
7	LIGHTING: 102, 103	20 A	1	2213..	0 VA			1	20 A EXISTING LOAD: LIGHT 0101, 0201	8	
9	EXISTING LOAD: EXIT	20 A	1			0 VA	0 VA	1	20 A NB1	10	
11	EXISTING LOAD: LIGHT IN TUNNEL	20 A	1				0 VA	0 VA	1	20 A EXISTING LOAD: LIGHT 0010	12
13	EXISTING LOAD: LIGHT IN TUNNEL	20 A	1	0 VA	0 VA			1	20 A SPARE	14	
15	EXISTING LOAD: EM LIGHT IN TUNNEL	20 A	1		0 VA	0 VA		1	20 A SPARE	16	
17	SPARE	20 A	1			0 VA	0 VA	1	20 A SPARE	18	
19	SPARE	20 A	1	0 VA	0 VA			1	20 A SPARE	20	
21	SPARE	20 A	1		0 VA	0 VA		1	20 A SPARE	22	
23	SPARE	20 A	1			0 VA	0 VA	1	20 A SPARE	24	
25	SPARE	20 A	1	0 VA	--			1	-- SPARE	26	
27	SPARE	--	1		--	--		1	-- SPARE	28	
29	SPARE	--	1		--	--		1	-- SPARE	30	
31	SPARE	--	1	--	--	--		1	-- SPARE	32	
33	SPARE	--	1	--	--	--		1	-- SPARE	34	
35	SPARE	--	1		--	--		1	-- SPARE	36	
37	TRANSFORMER AEBA	45 A	3	0 VA	0 VA			3	70 A TRANSFORMER NBA	38	
39					0 VA	0 VA				40	
41						0 VA	0 VA			42	
Total Load:				2213 VA	0 VA	0 VA					
Total Amps:				8 A	0 A	0 A					

Panel Totals		
Total Conn. Load:	2213 VA	
Total Est. Demand:	2213 VA	
Total Conn.:	3 A	
Total Est. Demand:	3 A	

Branch Panel: NBA

Location: Volts: 208Y/120V
Supply From: Phases: 3
Mounting: Surface Wires: 4
Enclosure: Type 1
A.I.C. Rating:
Mains Type:
Mains Rating: 225 A
MCB Rating: 150 A

CKT	Circuit Description	Trip	Poles	A	B	C	Poles	Trip	Circuit Description	CKT	
1	EXISTING LOAD: EXTERIOR LIGHTING	20 A	1	0 VA	0 VA			2	20 A EXISTING LOAD: EXTERIOR LIGHTING	2	
3	SPARE	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: EXTERIOR LIGHTING	4	
5	EXISTING LOAD: COOLING TOWER RECEP...	20 A	1		0 VA	0 VA	0 VA	0 VA	1	20 A EXISTING LOAD: AIR DRYER	6
7	EXISTING LOAD: RECEPT 0302	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT CENTER 0200	8	
9	EXISTING LOAD: RECEPT 0302	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: RECEPT CENTER 0200	10	
11	EXISTING LOAD: SWITCH C0100	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT NE 0200 & 020	12	
13	SPARE	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT 0106	14	
15	EXISTING LOAD: OUTSIDE SIGN	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: RECEPT C0200 & BSMT...	16	
17	EXISTING LOAD: 0002A	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: PLUGMOLD 0002	18	
19	EXISTING LOAD: RECEPT 002	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: PLUGMOLD 0002	20	
21	EXISTING LOAD: RECEPT 002A	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: PLUGMOLD 0002	22	
23	EXISTING LOAD: RECEPT 0002	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: ELEV 1 & 2 - LIGHT. &...	24	
25	SPARE	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: ELEVATOR LIGHTING	26	
27	EXISTING LOAD: WATER COOLER	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: ELEV 3 LIGHT & RECEPT	28	
29	EXISTING LOAD: VAV POWER SUPPLY	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: ELEVATOR CAB LIGHT	30	
31	EXISTING LOAD: X-RAY 100A PANEL	20 A	2	0 VA	250 VA			2	20 A RECEPT TREADMILL 0102E	32	
35	EXISTING LOAD: CHILLED WATER FLOW...	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT 0101C	36	
37	EXISTING LOAD: CHEMICAL STATION	20 A	1	0 VA	0 VA			1	20 A DOOR OPERATORS	38	
39	RECEPT ECHO 0102H & TOILET 0102J	20 A	1		1080..	0 VA		1	20 A EXISTING LOAD: RECEPT 0101B	40	
41	EXISTING LOAD: 30A 125V TELE. ROOM	30 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT 0101E	42	
43	EXISTING LOAD: 30A 125V TELE. ROOM	30 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT 0102, 0101A	44	
45	RECEPT ECHO 0102G	20 A	1		1080..	0 VA		1	20 A EXISTING LOAD: RECEPT 0102	46	
47	EXISTING LOAD: FUME HOOD CABINET	20 A	1			0 VA	0 VA	3	20 A EXISTING LOAD: AIR CURTAIN	48	
49	EXISTING LOAD: RECEPT S WALL 0302	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: AIR CURTAIN	50	
51	EXISTING LOAD: DEDICATED CIRCUIT LAB	20 A	1		0 VA	0 VA		2	20 A EXISTING LOAD: TUNNEL HEATER	52	
53	EXISTING LOAD: JOHNSON CONTROL PANEL	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: TUNNEL HEATER	54	
55	EXISTING LOAD: RECEPT LAB	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT 0101 COMM.	56	
57	EXISTING LOAD: RECEPT LAB	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: RECEPT 0101 COMM.	58	
59	EXISTING LOAD: SECURITY CONTROLS...	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT 0101 COMM.	60	
Total Load:				250 VA	2410 VA	0 VA					
Total Amps:				2 A	20 A	0 A					

Panel Totals		
Total Conn. Load:	2660 VA	
Total Est. Demand:	2660 VA	
Total Conn.:	7 A	
Total Est. Demand:	7 A	


Branch Panel: NBB

Location: Volts: 208Y/120V
Supply From: Phases: 3
Mounting: Surface Wires: 4
Enclosure: Type 1
A.I.C. Rating:
Mains Type:
Mains Rating: 225 A
MCB Rating:

CKT	Circuit Description	Trip	Poles	A	B	C	Poles	Trip	Circuit Description	CKT
1	EXISTING LOAD: RECEPT 0101K	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT 0106, B, C	2
3	EXISTING LOAD: RECEPT 0101H	20 A	1		0 VA	720 VA		1	20 A RECEPT & TV OPEN OFFICE 0106	4
5	EXISTING LOAD: RECEPT 0101G	20 A	1			0 VA	900 VA	1	20 A TV WAITING RM. & RECEPT STAFF LOUNGE	6
7	EXISTING LOAD: RECEPT 0101F	20 A	1	0 VA	1080..			1	20 A RECEPT CHECK-IN 0103	8
9	EXISTING LOAD: RECEPT 0101M	20 A	1		0 VA	720 VA		1	20 A RECEPT NURSE STATION 0102K	10
11	EXISTING LOAD: RECEPT 0101L	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT DEDICATED N...	12
13	RECEP CLEAN/EQUIP STORAGE 0102L	20 A	1	900 VA	540 VA			1	20 A RECEPT EXAM 0102M	14
15	RECEPT EXAM 102A	20 A	1		720 VA	1260..		1	20 A RECEPT EXAM 102B, 102C	16
17	EXISTING LOAD: HOT WATER 0102	20 A	1			0 VA	900 VA	1	20 A RECEPT EXAM 0102D	18
19	EXISTING LOAD: RECEPT FRIDGE 0102	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT JANITORS CLOSET	20
21	RECEPT EXAM 102E	20 A	1		1260..	0 VA		1	20 A EXISTING LOAD: ICE MACHINE	22
23	RECEPTACLE STAFF LOUNGE	20 A	1			180 VA	0 VA	1	20 A EXISTING LOAD: DOOR OPENER (TUNNEL)	24
25	EXISTING LOAD: RECEPT W WALL 0106	20 A	1	0 VA	1080..			1	20 A RECEPT ECHO 0102F	26
27	EXISTING LOAD: RECEPT "X" 0106	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: RECEPT PRINTER 0106A	28
29	EXISTING LOAD: RECEPT "C" 0106	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT 0106A	30
31	EXISTING LOAD: RECEPT "S" 0105	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT S WALL 0106	32
33	EXISTING LOAD: RECEPT PRINTER & 0106	20 A	1		0 VA	0 VA		1	20 A EXISTING LOAD: RECEPT 0106	34
35	EXISTING LOAD: RECEPT 105	20 A	1			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT 0106A	36
37	EXISTING LOAD: COPIER E WALL 0106	20 A	1	0 VA	0 VA			1	20 A EXISTING LOAD: RECEPT E WALL 0106	38
39	EXISTING LOAD: RECEPT LAMINATOR 0208	20 A	2			0 VA	0 VA	1	20 A EXISTING LOAD: RECEPT 0106	40
41	(OFF)					1980 VA		1	20 A EXISTING LOAD: RECEPT N WALL 0106	42
Total Load:				3600 VA	4680 VA	1980 VA				
Total Amps:				32 A	41 A	17 A				

Panel Totals		
Total Conn. Load:	10260 VA	
Total Est. Demand:	10130 VA	
Total Conn.:	28 A	
Total Est. Demand:	28 A	


Project Title:
UPMB Ground Floor Renovation
1020 Hitt St, Columbia, MO 65212




Issue Date: 08.29.2022

Drawn by: Author
bcdbg Project #: 12275.27
MU Project #: CP202091


E500
ELECTRICAL SCHEDULES



1 TYPICAL WIRING TO UNDERCABINET LIGHTS
1/2" = 1'-0"




2 ELECTRICAL DEVICE PLATE LABELING (ENGRAVING)
NO SCALE




- GENERAL NOTES:**
- LUMINAIRES WEIGHING 56 POUNDS OR MORE SHALL BE SUPPORTED DIRECTLY FROM THE STRUCTURE BY APPROVED HANGERS BY THE E.C. IN SUCH CASES, THE HANGER WIRES IN KEYED NOTE 2 MAY BE OMITTED.
 - PENDANT HUNG LUMINAIRES SHALL BE SUPPORTED DIRECTLY FROM THE STRUCTURE ABOVE USING NO. 9 GAUGE WIRE WITHOUT USING THE CEILING SUSPENSION SYSTEM FOR DIRECT SUPPORT.
 - COMPLY TO NOTE 8 IN TABLE 16-0 OF CA BUILDING CODE AND UBC STANDARD 25-2 PART III.
- KEYED NOTES:**
- ATTACH LUMINAIRE TO THE SUSPENDED CEILING TEE WITH DEVICES HAVING A CAPACITY OF 100% OF THE LUMINAIREWEIGHT ACTING IN ANY DIRECTION. USE #10 STS SCREWS WITH HEAD INSIDE LUMINAIRE. TYPICAL FOR ALL LUMINAIRE. PROVIDE MINIMUM OF 2 (ONE AT EACH END).
 - FOR LUMINAIRES WEIGHING MORE THAN 10 POUNDS BUT LESS THAN 56 POUNDS, E.C. TO PROVIDE TWO NO. 12 GAUGE HANGERS CONNECTED FROM THE FIXTURE HOUSING TO THE STRUCTURE ABOVE. THESE WIRES NEED NOT BE TAUT.

4 TYPICAL MOUNTING DETAIL FOR RECESSED LUMINAIRE IN LAY-IN CEILING
NO SCALE



PLAN VIEW - DETAIL A - OUTLET BOXES IN HOLLOW WALL



PLAN VIEW - DETAIL B - OUTLET BOXES IN FIRE RATED HOLLOW WALL

- GENERAL NOTES:**
- COORDINATE LOCATIONS OF FIRE RATE WALLS AND THICKNESS OF ALL WALLS WITH G.C. AND ARCHITECTURAL DRAWINGS.
 - DETAIL A IS APPLICABLE TO ALL HOLLOW WALLS ON THIS PROJECT. DETAIL B IS APPLICABLE TO ALL FIRE RATED HOLLOW WALLS ON THIS PROJECT.
- KEYED NOTES:**
- PLATE OR COVER ON FOR OUTLET, BOX OR WIREWAY.
 - NON-FIRE RATED WALL (DETAIL A): OUTLET, SWITCH, RECEPTACLE, TEL., DATA, ETC. OR OTHER BOX SPECIFIED. FIRE RATED WALL (DETAIL B): SAME AS ABOVE EXCEPT BOX MUST BE STEEL WITH NOMINAL AREA NOT TO EXCEED 16 SQ. IN.
 - RACEWAY AS ALLOWED BY SPECIFICATIONS.
 - METAL STUD (NO HOLES). IF STUDS HAVE HOLES, BOXES MAY BE LESS THAN 24" APART AND FIRE RATED PUTTY PADS USED ON BOTH BOXES.
 - BOXES SHALL BE SET BACK FROM FINISHED SURFACE NO MORE THAN 1/4" IN ACCORD WITH NEC. BOXES SHALL BE SET AND THE WALL SHALL BE REPAIRED AS REQUIRED SO THAT THE SPACE BETWEEN THE WALL AND THE EDGE OF THE BOX SHALL BE NO GREATER THAN 1/8" IN ACCORD WITH NEC. FIRE RATED WALLS MAY HAVE MORE THAN ONE LAYER OF SHEETROCK IN ORDER TO OBTAIN FIRE RATING. COORDINATE WITH G.C. AND ARCHITECTURAL DRAWINGS PRIOR TO SETTING BOXES.
 - TYPICAL 24" STUD SPACING. COORDINATE WITH G.C.
 - BOXES IN OPPOSITE SIDES OF A FIRE RATED HOLLOW WALL SHALL BE SEPARATED BY A MINIMUM OF 24" AND THERE SHALL BE A STUD BETWEEN THE 2 BOXES. SEE KEYED NOTE 4 ON THIS SHEET.

3 OUTLETS IN HOLLOW WALLS-TYPICAL DETAILS
NO SCALE